## Praktiskais darbs PD "Recenzenti"

## Publiskie testi

## 1. Viens recenzents ar vienu pseidonīmu

L 2007 L 3007

```
<u>Ieeja</u>
         I JackSmart 1 7
         L 7
         D 7
         L 7
<u>Izeja</u>
         ok
         JackSmart
         ok
         no
   2. Viens recenzents ar 5 pseidonīmiem
<u>Ieeja</u>
         I JackSmart 5 17 27 37 47 57
         L 17
         L 27
         L 37
         L 47
         L 57
         D 37
         L 17
         L 27
         L 37
         L 47
         L 57
<u>Izeja</u>
         ok
         JackSmart
         JackSmart
         JackSmart
         JackSmart
         JackSmart
         ok
         no
         no
         no
         no
         no
   3. Jauns recenzents pretendē gan uz aktīva, gan uz kādreiz piesaistīta recenzenta pseidonīmu
<u>Ieeja</u>
         I JackSmart1 3 1007 2007 3007
         I TedPumpkinhead 2 1 1007
         L 1
         L 1007
         D 1007
         I JackSmart2 3 1007 2007 3007
         L 1007
```

```
ok
        no
        no
        JackSmart1
        ok
        ok
        JackSmart2
        JackSmart2
        JackSmart2
  4. Recenzentam tiek pieteikti vairāki vienādi pseidonīmi
<u>Ieeja</u>
        I JackSmart 3 7 7 7
        L 7
<u>Izeja</u>
        ok
        JackSmart
   5. Recenzentiem ir daudz pseidonīmu
<u>Ieeja</u>
        I JackSmart 30 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22
        23 24 25 26 27 28 29 30
        I JackSmart100 30 101 102 103 104 105 106 107 108 109 110 111 112 113 114
        115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130
        I JackSmart200 30 201 202 203 204 205 206 207 208 209 210 211 212 213 214
        215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230
        L 1
        L 7
        L 30
        L 31
        L 101
        L 107
        L 130
        L 131
        L 201
        L 207
        L 230
        L 231
<u>Izeja</u>
        ok
        ok
        ok
        JackSmart
        JackSmart
        JackSmart
        no
        JackSmart100
        JackSmart100
        JackSmart100
        JackSmart200
        JackSmart200
        JackSmart200
        no
  6. Pamatpiemērs no uzdevuma formulējuma
```

<u>Izeja</u>

```
<u>Ieeja</u>
         I JackSmart 3 7 1007 1000007
         L 1000007
         I TedPumpkinhead 1 17
         I PeterMeter 1 7
         L 17
         D 17
         L 17
         I JohnCritic 2 1 17
         L 17
         L 1
        L 7
<u>Izeja</u>
         ok
         JackSmart
         ok
         TedPumpkinhead
         ok
         no
         ok
         JohnCritic
         JohnCritic
         JackSmart
   7. Pseidonīmu saraksta papildināšana aktīvam recenzentam
<u>Ieeja</u>
         I JackSmart 2 6 7
         I JackSmart 2 8 9
         L 6
        L 7
         L 8
         L 9
<u>Izeja</u>
         ok
         ok
         JackSmart
         JackSmart
         JackSmart
         JackSmart
   8. Pseidonīmu saraksta papildināšana aktīvam recenzentam, pseidonīmi var atkārtoties, kontrolējam
     pieļaujamo pseidonīmu skaitu 50
<u>Ieeja</u>
         I JackSmart 30 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22
         23 24 25 26 27 28 29 30
         I JackSmart 30 1 2 3 4 5 6 7 8 9 10 31 32 33 34 35 36 37 38 39 40 41 42
         43 44 45 46 47 48 49 50
         L 1
         L 10
         L 20
         L 40
         L 50
         I JackSmart 1 51
         L 51
         L 50
```

```
ok
     ok
     JackSmart
     JackSmart
     JackSmart
     JackSmart
     JackSmart
     no
     no
     JackSmart
9. Pseidonīmi var būt patvaļīgā secībā
     I JackSmart 4 7777777 7 7654321 1234567
     L 1
     L 7
     L 7654321
     L 1234567
     L 7777777
     ok
     no
     JackSmart
```

<u>Izeja</u>

<u>Ieeja</u>

<u>Izeja</u>

JackSmart JackSmart JackSmart