


**SECTION A:**

**QUESTION A1 SCREENSHOT**




The screenshot shows a database client interface with a script editor on the left and a script output window on the right. The script editor contains the following SQL commands:

```
CREATE TABLE OrderDetail_A (  
    OrderID NUMBER(10),  
    ProductID NUMBER(10),  
    Quantity NUMBER,  
    SubTotal NUMBER(12, 2),  
    CONSTRAINT PK_ODA PRIMARY KEY (OrderID, ProductID)  
);  
  
-- 2. Insert 5 rows into OrderDetail_A (Node A)  
INSERT INTO OrderDetail_A (OrderID, ProductID, Quantity, SubTotal) VALUES (101, 1, 2, 20.00); -- Hash key 101  
INSERT INTO OrderDetail_A (OrderID, ProductID, Quantity, SubTotal) VALUES (102, 2, 1, 15.50); -- Hash key 102  
INSERT INTO OrderDetail_A (OrderID, ProductID, Quantity, SubTotal) VALUES (103, 1, 5, 50.00); -- Hash key 103  
INSERT INTO OrderDetail_A (OrderID, ProductID, Quantity, SubTotal) VALUES (104, 3, 1, 8.25); -- Hash key 104  
INSERT INTO OrderDetail_A (OrderID, ProductID, Quantity, SubTotal) VALUES (105, 2, 3, 46.50); -- Hash key 105  
COMMIT;
```

The script output window shows the message: "Commit complete." and "Task completed in 0.259 seconds".

A1: OrderDetail\_A table created in node A



The screenshot shows a database client interface with a script editor on the left and a script output window on the right. The script editor contains the following SQL commands:

```
CREATE TABLE OrderDetail_B (  
    OrderID NUMBER(10),  
    ProductID NUMBER(10),  
    Quantity NUMBER,  
    SubTotal NUMBER(12, 2),  
    CONSTRAINT PK_ODB PRIMARY KEY (OrderID, ProductID)  
);  
  
-- 2. Insert 5 rows into OrderDetail_B (Node B)  
INSERT INTO OrderDetail_B (OrderID, ProductID, Quantity, SubTotal) VALUES (201, 1, 4, 40.00); -- Hash key 201  
INSERT INTO OrderDetail_B (OrderID, ProductID, Quantity, SubTotal) VALUES (202, 3, 2, 16.50); -- Hash key 202  
INSERT INTO OrderDetail_B (OrderID, ProductID, Quantity, SubTotal) VALUES (203, 2, 1, 15.50); -- Hash key 203  
INSERT INTO OrderDetail_B (OrderID, ProductID, Quantity, SubTotal) VALUES (204, 1, 1, 10.00); -- Hash key 204  
INSERT INTO OrderDetail_B (OrderID, ProductID, Quantity, SubTotal) VALUES (205, 3, 3, 24.75); -- Hash key 205  
COMMIT;
```

The script output window shows the message: "Commit complete." and "Task completed in 0.102 seconds".

A1: OrderDetail\_B table created in node B

```
-- Grant SELECT access on OrderDetail_B to Node A for the view
GRANT SELECT ON OrderDetail_B TO S_BranchDB_A;
```

Script Output x

Task completed in 0.169 seconds

Grant succeeded.

A1: Grant to node A from node B succeeded

```
CREATE OR REPLACE VIEW OrderDetail_ALL AS
SELECT OrderID, ProductID, Quantity, SubTotal FROM OrderDetail_A -- Local fragment
UNION ALL
SELECT OrderID, ProductID, Quantity, SubTotal FROM OrderDetail_B@PROJ_LINK; -- Remote fragment
```

Script Output x

Task completed in 0.43 seconds

View ORDERDETAIL\_ALL created.

A1: Created view ORDERDETAIL\_ALL succeeded

```
SELECT
    COUNT(*) AS Fragment_Count,
    SUM(MOD(OrderID, 97)) AS Fragment_Checksum
FROM (
    SELECT OrderID FROM OrderDetail_A
    UNION ALL
    SELECT OrderID FROM OrderDetail_B@PROJ_LINK
);
-- EXPECTED OUTPUT: Fragment_Count = 10, Fragment_Checksum = (101+...+105 + 201+...+205) mod 97

SELECT
    COUNT(*) AS View_Count,
    SUM(MOD(OrderID, 97)) AS View_Checksum
FROM OrderDetail_ALL;
```


Query Result x

All Rows Fetched: 1 in 0.011 seconds

|   | VIEW_COUNT | VIEW_CHECKSUM |
|---|------------|---------------|
| 1 | 10         | 75            |

A1: Validation output

## QUESTION A2 SCREENSHOTS




The screenshot displays the SQL Developer interface. The main window shows a SQL script with the following content:

```
CREATE TABLE OrderInfo (  
  OrderID NUMBER(10) PRIMARY KEY,  
  CustomerID NUMBER,  
  OrderDate DATE  
);  
  
INSERT INTO OrderInfo (OrderID, CustomerID, OrderDate) VALUES (101, 1, DATE '2025-10-01');  
INSERT INTO OrderInfo (OrderID, CustomerID, OrderDate) VALUES (102, 2, DATE '2025-10-02');  
INSERT INTO OrderInfo (OrderID, CustomerID, OrderDate) VALUES (201, 3, DATE '2025-10-03');  
INSERT INTO OrderInfo (OrderID, CustomerID, OrderDate) VALUES (202, 4, DATE '2025-10-04');  
INSERT INTO OrderInfo (OrderID, CustomerID, OrderDate) VALUES (300, 5, DATE '2025-10-05');  
COMMIT;  
  
CREATE TABLE Product (  
  ProductID NUMBER(10) PRIMARY KEY,  
  ProductName VARCHAR2(100),  
  Category VARCHAR2(50)  
);  
  
INSERT INTO Product (ProductID, ProductName, Category) VALUES (1, 'Widget X', 'Electronics');  
INSERT INTO Product (ProductID, ProductName, Category) VALUES (2, 'Widget Y', 'Electronics');  
INSERT INTO Product (ProductID, ProductName, Category) VALUES (3, 'Gadget Z', 'Office');  
INSERT INTO Product (ProductID, ProductName, Category) VALUES (4, 'Tool A', 'Office');  
COMMIT;
```

The Script Output window at the bottom shows the message: "Commit complete." and "Task completed in 0.181 seconds".

A2: OrderInfo table well created in node B



The screenshot displays the SQL Developer interface. The main window shows a SQL script with the following content:

```
-- Create the database link 'PROJ_LINK' to Node B (Reusing link details from original code)  
CREATE DATABASE LINK PROJ_LINK  
CONNECT TO BranchDB_B IDENTIFIED BY "Emm788@enna"  
USING '//localhost:1521/XE';
```

The Script Output window at the bottom shows the message: "Database link PROJ\_LINK created." and "Task completed in 0.131 seconds".

A2: Database link well created



ns

```

SET AUTOTRACE ON STATISTICS
SET TIMING ON

SELECT /*+ GATHER_PLAN_STATISTICS */
  ProductID,
  COUNT(*) AS TotalLines,
  SUM(Quantity) AS TotalQtySold,
  SUM(SubTotal) AS TotalRevenue
FROM
  (SELECT /*+ PARALLEL(ODA, 8) */ OrderID, ProductID, Quantity, SubTotal FROM OrderDetail_A ODA
   UNION ALL
   SELECT OrderID, ProductID, Quantity, SubTotal FROM OrderDetail_B@PROJ_LINK)
GROUP BY ProductID
ORDER BY TotalRevenue DESC;
SET TIMING OFF
SET AUTOTRACE OFF

```

Query Result x

SQL | All Rows Fetched: 3 in 0.026 seconds

| PRODUCTID | TOTALLINES | TOTALQTY SOLD | TOTALREVENUE |
|-----------|------------|---------------|--------------|
| 1         | 1          | 4             | 124          |
| 2         | 2          | 3             | 77.5         |
| 3         | 3          | 3             | 49.5         |

### A3: Parallel Aggregation

ctions

```

EXPLAIN PLAN FOR
SELECT ProductID, COUNT(*), SUM(Quantity), SUM(SubTotal) FROM OrderDetail_ALL GROUP BY ProductID;
SELECT * FROM TABLE(DBMS_XPLAN.DISPLAY);
-- Check for 'REMOTE' operation (for OrderDetail_B) but no 'PX' (Parallel) steps.

--4 Parallel Plan (Using the specific parallel hint)
EXPLAIN PLAN FOR
SELECT /*+ PARALLEL(OrderDetail_A, 8) */ ProductID, COUNT(*), SUM(Quantity), SUM(SubTotal)
FROM (
  SELECT * FROM OrderDetail_A
  UNION ALL
  SELECT * FROM OrderDetail_B@PROJ_LINK
)
GROUP BY ProductID;

```

Script Output x

Task completed in 0.137 seconds

Explained.

### A3: Explain Plan well explained

SELECT \* FROM TABLE(DBMS\_XPLAN.DISPLAY);

Script Output x Query Result x

Connections SQL All Rows Fetched: 26 in 0.281 seconds

PLAN\_TABLE\_OUTPUT

|    |                                                                             |                                                                                 |               |      |       |             |          |        |        |  |
|----|-----------------------------------------------------------------------------|---------------------------------------------------------------------------------|---------------|------|-------|-------------|----------|--------|--------|--|
| 3  | -----                                                                       |                                                                                 |               |      |       |             |          |        |        |  |
| 4  | Id                                                                          | Operation                                                                       | Name          | Rows | Bytes | Cost (%CPU) | Time     | Inst   | IN-OUT |  |
| 5  | -----                                                                       |                                                                                 |               |      |       |             |          |        |        |  |
| 6  | 0                                                                           | SELECT STATEMENT                                                                |               | 3    | 84    | 7 (15)      | 00:00:01 |        |        |  |
| 7  | 1                                                                           | HASH GROUP BY                                                                   |               | 3    | 84    | 7 (15)      | 00:00:01 |        |        |  |
| 8  | 2                                                                           | VIEW                                                                            |               | 10   | 280   | 6 (0)       | 00:00:01 |        |        |  |
| 9  | 3                                                                           | UNION-ALL                                                                       |               |      |       |             |          |        |        |  |
| 10 | 4                                                                           | TABLE ACCESS FULL                                                               | ORDERDETAIL_A | 5    | 50    | 3 (0)       | 00:00:01 |        |        |  |
| 11 | 5                                                                           | REMOTE                                                                          | ORDERDETAIL_B | 5    | 70    | 3 (0)       | 00:00:01 | PROJ_~ | R->S   |  |
| 12 | -----                                                                       |                                                                                 |               |      |       |             |          |        |        |  |
| 13 |                                                                             |                                                                                 |               |      |       |             |          |        |        |  |
| 14 | Remote SQL Information (identified by operation id):                        |                                                                                 |               |      |       |             |          |        |        |  |
| 15 | -----                                                                       |                                                                                 |               |      |       |             |          |        |        |  |
| 16 |                                                                             |                                                                                 |               |      |       |             |          |        |        |  |
| 17 | 5                                                                           | - SELECT "PRODUCTID","QUANTITY","SUBTOTAL" FROM "ORDERDETAIL_B" "ORDERDETAIL_B" |               |      |       |             |          |        |        |  |
| 18 | (accessing 'PROJ_LINK' )                                                    |                                                                                 |               |      |       |             |          |        |        |  |
| 19 |                                                                             |                                                                                 |               |      |       |             |          |        |        |  |
| 20 |                                                                             |                                                                                 |               |      |       |             |          |        |        |  |
| 21 | Hint Report (identified by operation id / Query Block Name / Object Alias): |                                                                                 |               |      |       |             |          |        |        |  |
| 22 | Total hints for statement: 1 (N - Unresolved (1))                           |                                                                                 |               |      |       |             |          |        |        |  |
| 23 | -----                                                                       |                                                                                 |               |      |       |             |          |        |        |  |
| 24 |                                                                             |                                                                                 |               |      |       |             |          |        |        |  |
| 25 | 1                                                                           | - SEL\$1                                                                        |               |      |       |             |          |        |        |  |
| 26 | N - PARALLEL(OrderDetail A..8)                                              |                                                                                 |               |      |       |             |          |        |        |  |

A3: Explained Plan Table

## QUESTION A3 SCREENSHOTS

```
-- 1.Clean up any test rows from A2 if OrderInfo wasn't minimal
DELETE FROM OrderInfo_KGL WHERE OrderID IN (1000, 1001);
DELETE FROM OrderInfo@PROJ_LINK WHERE OrderID IN (1000, 1001);
COMMIT;
```

Script Output x

Task completed in 0.083 seconds

Commit complete.

A3: Transaction on both node committed successful

N.B: Oracle don't support concurrent transaction failure ( see the error below):

```

BEGIN
  -- Insert into local node (Kigali)
  INSERT INTO OrderInfo_KGL (OrderID, CustomerID, OrderDate)
  VALUES (1000, 10, DATE '2025-10-28');
  -- Insert into remote node (Other cities)
  INSERT INTO OrderInfo@PROJ_LINK (OrderID, CustomerID, OrderDate)
  VALUES (1001, 11, DATE '2025-10-28');
  -- Single commit triggers Two-Phase Commit (2PC)
  COMMIT;

```

Script Output x

Task completed in 0.137 seconds

PL/SQL procedure successfully completed.

A4: Inserting into local and remote node successfully completed

```

-- DBMS_OUTPUT.PUT_LINE('Clean 2PC completed successfully');
EXCEPTION
  WHEN OTHERS THEN
    ROLLBACK;
    -- DBMS_OUTPUT.PUT_LINE('2PC failed and rolled back: ' || SQLERRM);
END;
/

```

Script Output x

Task completed in 0.167 seconds

Error starting at line : 128 in command -  
 WHEN OTHERS THEN  
 Error report -  
 Unknown Command

Rollback complete.

Error starting at line : 131 in command -  
 END  
 Error report -  
 Unknown Command

SP2-0044: For a list of known commands enter HELP  
 and to leave enter EXIT.

A4: Roll back completed with error

```

-- Verify committed data (should see both 1000 and 1001)
SELECT 'Local' AS Node, OrderID FROM OrderInfo_KGL WHERE OrderID = 1000
UNION ALL
SELECT 'Remote' AS Node, OrderID FROM OrderInfo@PROJ_LINK WHERE OrderID = 1001;

```

Query Result x

SQL | All Rows Fetched: 3 in 0.022 seconds

|   | NODE   | ORDERID |
|---|--------|---------|
| 1 | Local  | 1000    |
| 2 | Local  | 1000    |
| 3 | Remote | 1001    |

A: Verification of Transaction made before ( succeeded )

```

BEGIN
-- Insert into local node (Kigali)
INSERT INTO OrderInfo_KGL (OrderID, CustomerID, OrderDate)
VALUES (1000, 10, DATE '2025-10-28');
-- Insert into remote node (Other cities)
INSERT INTO OrderInfo@PROJ_LINK (OrderID, CustomerID, OrderDate)
VALUES (1001, 11, DATE '2025-10-28');
-- When COMMIT is hit, the transaction becomes in-doubt (prepared locally, but commit failed remotely)
COMMIT;

```

Script Output x

Task completed in 0.153 seconds

```

INSERT INTO OrderInfo_KGL (OrderID, CustomerID, OrderDate)
*
ERROR at line 3:
ORA-06550: line 3, column 17:
PL/SQL: ORA-00942: table or view does not exist
ORA-06550: line 3, column 5:
PL/SQL: SQL Statement ignored
ORA-06550: line 6, column 5:
PL/SQL: ORA-00942: table or view does not exist
ORA-06550: line 6, column 5:
PL/SQL: SQL Statement ignored
https://docs.oracle.com/error-help/db/ora-06550/
More Details :
https://docs.oracle.com/error-help/db/ora-06550/

```

A4: This was run in remote node and it shows that oracle don't support failure transaction

```

BEGIN
-- Insert into local node (Kigali)
INSERT INTO OrderInfo_KGL (OrderID, CustomerID, OrderDate)
VALUES (1000, 10, DATE '2025-10-28');
-- Insert into remote node (Other cities)
INSERT INTO OrderInfo@PROJ_LINK (OrderID, CustomerID, OrderDate)
VALUES (1001, 11, DATE '2025-10-28');
-- When COMMIT is hit, the transaction becomes in-doubt (prepared locally, but commit failed remotely)
COMMIT;
-- This may fail with ORA-02055/ORA-02063

```

Script Output x

Task completed in 0.102 seconds

PL/SQL procedure successfully completed.

A4: It is again run in local node, and automatically succeeded ( didn't fail)

```

-- 4. Re-verify consistency (as S_BranchDB A)
SELECT 'Local' AS Node, OrderID FROM OrderInfo_KGL WHERE OrderID = 1000
UNION ALL
SELECT 'Remote' AS Node, OrderID FROM OrderInfo@PROJ_LINK WHERE OrderID = 1001;
-- Output should show 0 rows if ROLLBACK FORCE succeeded

```

Query Result x

All Rows Fetched: 4 in 0.007 seconds

| NODE     | ORDERID |
|----------|---------|
| 1 Local  | 1000    |
| 2 Local  | 1000    |
| 3 Local  | 1000    |
| 4 Remote | 1001    |

A4: Consistency Verification output on both node .

## QUESTION A5 SCREENSHOTS

```
-- 1. UPDATE a single remote row and keep the transaction open (no COMMIT)
UPDATE OrderDetail_B@PROJ_LINK
SET SubTotal = SubTotal * 1.1
WHERE OrderID = 201 AND ProductID = 1;
```

Script Output x

Task completed in 0.069 seconds

1 row updated.

A5: Single row well updated

```
UPDATE OrderDetail_B
SET Quantity = Quantity + 1
WHERE OrderID = 201 AND ProductID = 1;
```

Script Output x

ScriptRunner Task

A: WAITER SESSION IN NODE B

```
SELECT
    L.SID AS WAITER_SID,
    S.SERIAL# AS WAITER_SERIAL,
    L.BLOCKING_SESSION AS BLOCKER_SID,
    BS.SERIAL# AS BLOCKER_SERIAL,
    S.EVENT,
    'Contesting Row: 201/1' AS CONTEXT
FROM
    V$SESSION S
JOIN
    V$SESSION BS ON S.BLOCKING_SESSION = BS.SID
JOIN
    V$SESSION_WAIT W ON S.SID = W.SID
JOIN
    V$LOCK L ON S.SID = L.SID
WHERE
    W.EVENT LIKE 'SQL*Net message from dblink%' -- Waiting on a distributed transaction
    OR S.STATE = 'WAITING' AND S.ROW_WAIT_OBJ# IS NOT NULL;

-- 4. Release the lock by committing Session 1
COMMIT;
```

Script Output x

Task completed in 0.265 seconds

Commit complete.

A5: After committing the waiter session automatically runnel well as shown below

```
UPDATE OrderDetail_B  
SET Quantity = Quantity + 1  
WHERE OrderID = 201 AND ProductID = 1;
```

Script Output x

Task completed in 867.723 seconds

1 row updated.

A5: Waiter session now completed

```
SELECT * FROM OrderDetail_B@PROJ_LINK WHERE OrderID = 201 AND ProductID = 1;
```

Query Result x

All Rows Fetched: 1 in 0.072 seconds

| ORDERID | PRODUCTID | QUANTITY | SUBTOTAL |
|---------|-----------|----------|----------|
| 1       | 201       | 1        | 53.24    |

A5: Data verification in local node