

PRACTICAL - 07

Name: Hansika Reddy Gunapati

Rollno: 2520030237

Section: 8

EXPERIMENT – Memory Address Space and /proc/<PID>/maps

Aim:

To write a C program that prints the addresses of **code, global, static, heap, and stack variables**, and analyse the Linux process address-space layout using /proc/<PID>/maps.

Objective:

- To understand the memory layout of a Linux process.
- To identify code, global, static, heap, and stack regions.
- To observe virtual memory mappings using /proc/<PID>/maps.
- To understand how Linux organizes memory for a running process.

Problem Statement:

Write a C program to display the addresses of different types of variables and use /proc/<PID>/maps to study the virtual memory organization of the running process.

Theory:

A Linux process has its own **virtual address space**. Important regions include:

Memory Segment	Purpose
Code/Text	Contains program instructions
Global/Data	Contains initialized global variables
BSS	Contains uninitialized global/static variables
Heap	Used for dynamically allocated memory
Stack	Stores local variables and function information
Shared Libraries	Libraries mapped into the process address space

The `/proc/<PID>/maps` file shows the virtual memory regions currently mapped into a process.

Example:

55a1...-55a1... r-xp ... /program

55a1...-55a1... rw-p ... /program

7f2...-7f2... r-xp ... /libc.so.6

7ffd...-7ffd... rw-p ... [stack]

Here:

- r = Read
- w = Write
- x = Execute
- p = Private mapping

Algorithm:

1. Declare a global variable.
2. Declare a static variable.
3. Create a local stack variable.
4. Create a function to represent the code segment.

5. Allocate memory dynamically using malloc().
6. Print the addresses of all variables.
7. Print the process PID.
8. Keep the program running.
9. Open /proc/<PID>/maps from another terminal.
10. Analyse the virtual memory mappings.
11. identify the stack, heap, program, and shared-library regions.

C Program:

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
int global_var = 10;
static int static_var = 20;
void code_function()
{
    printf("Code address  : %p\n", (void *)code_function);
}int main()
{
    int stack_var = 30;
    int *heap_var;
    heap_var = (int *)malloc(sizeof(int));
    if (heap_var == NULL)
    {
        printf("Memory allocation failed\n");
        return 1;
    }
}
```

```

}
*heap_var = 40;
printf("Linux Process Memory Layout\n");
printf("-----\n");
printf("PID          : %d\n", getpid());
printf("Code address   : %p\n", (void *)code_function);
printf("Global address  : %p\n", (void *)&global_var);
printf("Static address  : %p\n", (void *)&static_var);
printf("Heap address    : %p\n", (void *)heap_var);
printf("Stack address   : %p\n", (void *)&stack_var);
printf("\nProcess is running...\n");
printf("Use another terminal to check /proc/%d/maps\n", getpid());
while (1)
{
    sleep(10);
} free(heap_var);
return 0;
}

```

OUTPUT:

```
simra@simran315:~$ nano memory_layout.c
simra@simran315:~$ gcc memory_layout.c -o memory_layout
simra@simran315:~$ ./memory_layout
Linux Process Memory Layout
-----
PID           : 1123
Code address  : 0x5bd857c661e9
Global address : 0x5bd857c69010
Static address : 0x5bd857c69014
Heap address   : 0x5bd880bcb010
Stack address  : 0x7ffcb61fb0fc

Process is running...
Use another terminal to check /proc/1123/maps
|
```

```
simra@simran315:~$ cat /proc/1123/maps
5bd857c65000-5bd857c66000 r--p 00000000 08:30 42088
/home/simra/memory_layout
5bd857c66000-5bd857c67000 r-xp 00001000 08:30 42088
/home/simra/memory_layout
5bd857c67000-5bd857c68000 r--p 00002000 08:30 42088
/home/simra/memory_layout
5bd857c68000-5bd857c69000 r--p 00002000 08:30 42088
/home/simra/memory_layout
5bd857c69000-5bd857c6a000 rw-p 00003000 08:30 42088
/home/simra/memory_layout
5bd880bcb000-5bd880bec000 rw-p 00000000 00:00 0
[heap]
726ae1c00000-726ae1c28000 r--p 00000000 08:30 13647
/usr/lib/x86_64-linux-gnu/libc.so.6
726ae1c28000-726ae1dc0000 r-xp 00028000 08:30 13647
/usr/lib/x86_64-linux-gnu/libc.so.6
726ae1dc0000-726ae1e0e000 r--p 001c0000 08:30 13647
/usr/lib/x86_64-linux-gnu/libc.so.6
726ae1e0e000-726ae1e12000 r--p 0020d000 08:30 13647
/usr/lib/x86_64-linux-gnu/libc.so.6
726ae1e12000-726ae1e14000 rw-p 00211000 08:30 13647
/usr/lib/x86_64-linux-gnu/libc.so.6
726ae1e14000-726ae1e21000 rw-p 00000000 00:00 0
726ae1ece000-726ae1ed1000 rw-p 00000000 00:00 0
726ae1ed7000-726ae1ed9000 rw-p 00000000 00:00 0
726ae1ed9000-726ae1edd000 r--p 00000000 00:00 0
[vvar]
726ae1eddd000-726ae1edf000 r--p 00000000 00:00 0
[vvar_vclock]
726ae1edf000-726ae1ee1000 r-xp 00000000 00:00 0
[vdso]
726ae1ee1000-726ae1ee2000 r--p 00000000 08:30 13644
/usr/lib/x86_64-linux-gnu/ld-linux-x86-64.so.2
726ae1ee2000-726ae1f11000 r-xp 00001000 08:30 13644
/usr/lib/x86_64-linux-gnu/ld-linux-x86-64.so.2
726ae1f11000-726ae1f1c000 r--p 00030000 08:30 13644
```

```

726ae1f1f000-726ae1f20000 rw-p 00000000 00:00 0
7ffcb61dd000-7ffcb61fe000 rw-p 00000000 00:00 0
[stack]
simra@simran315:~$ pmap 1123
1123:    ./memory_layout
00005bd857c65000      4K r---- memory_layout
00005bd857c66000      4K r-x-- memory_layout
00005bd857c67000      4K r---- memory_layout
00005bd857c68000      4K r---- memory_layout
00005bd857c69000      4K rw--- memory_layout
00005bd880bcb000    132K rw--- [ anon ]
0000726ae1c00000    160K r---- libc.so.6
0000726ae1c28000   1632K r-x-- libc.so.6
0000726ae1dc0000    312K r---- libc.so.6
0000726ae1e0e000     16K r---- libc.so.6
0000726ae1e12000      8K rw--- libc.so.6
0000726ae1e14000     52K rw--- [ anon ]
0000726ae1ece000     12K rw--- [ anon ]
0000726ae1ed7000      8K rw--- [ anon ]
0000726ae1ed9000     16K r---- [ anon ]
0000726ae1edd000      8K r---- [ anon ]
0000726ae1edf000      8K r-x-- [ anon ]
0000726ae1ee1000      4K r---- ld-linux-x86-64.so.2
0000726ae1ee2000   188K r-x-- ld-linux-x86-64.so.2
0000726ae1f11000     44K r---- ld-linux-x86-64.so.2
0000726ae1f1c000      8K r---- ld-linux-x86-64.so.2
0000726ae1f1e000      4K rw--- ld-linux-x86-64.so.2
0000726ae1f1f000      4K rw--- [ anon ]
00007ffcb61dd000   132K rw--- [ stack ]
total                2768K

```

Program Explanation:

Code Segment

```
(void *)code_function
```

This displays the address of a function. Since program instructions are stored in the **code/text segment**, this represents the code region.

Global Segment

```
int global_var = 10;
```

The global variable is stored in the process's global data area.

Static Segment

```
static int static_var = 20;
```

The static variable has static storage duration and is stored in the program's data area.

Heap

```
heap_var = (int *)malloc(sizeof(int));
```

malloc() dynamically allocates memory from the **heap**.

Stack

```
int stack_var = 30;
```

A local variable inside main() is stored on the **stack**.

Analysis:

- The r-xp mapping of the executable corresponds to the **code/text region**.
- The writable executable mapping contains **data/global/static areas**.
- [heap] represents dynamically allocated memory.
- [stack] represents the process stack.
- libc.so.6 represents a **shared library** mapped into the process.
- Each process sees these as **virtual addresses**, which Linux manages through virtual memory.

Test Cases:

Test Case	Command/Action	Expected Result
1	Run program	PID and memory addresses displayed
2	Check code address	Address of function displayed

Test Case	Command/Action	Expected Result
3	Check global/static address	Data-area addresses displayed
4	Check heap address	Dynamically allocated address displayed
5	Check stack address	Local-variable address displayed
6	cat /proc/PID/maps	Virtual memory mappings displayed
7	pmap PID	Process memory map displayed

Observation:

- The program displayed different virtual addresses for code, global, static, heap, and stack variables.
- The heap and stack appeared as separate regions in /proc/PID/maps.
- The executable and shared libraries were also mapped into the process address space.
- /proc/PID/maps provided information about the permissions and ranges of each virtual memory mapping.

Result:

The C program was successfully implemented to display addresses of the **code, global, static, heap, and stack** regions. The /proc/<PID>/maps file was used to analyse the virtual memory organization of the running process.

Conclusion:

The experiment demonstrated how Linux organizes a process into different virtual memory regions. The memory addresses printed by the program, together with /proc/<PID>/maps, helped identify the **code, data, heap, stack, and shared-library mappings**.