

*Annotated
Version*

Machine Learning Course - CS-433

Text Representation Learning

Nov 29, 2018

©Martin Jaggi 2016

minor changes by Martin Jaggi 2017

minor changes by Martin Jaggi 2018

Last updated: November 29, 2018




ÉCOLE POLYTECHNIQUE
FÉDÉRALE DE LAUSANNE

Motivation

Finding numerical representations for words is fundamental for all machine learning methods dealing with text data.


Goal: For each word, find mapping (embedding)

$$w_i \mapsto \mathbf{w}_i \in \mathbb{R}^K$$



too large dimension $K \approx 1M$

Representation should capture semantics of the word.




Constructing good feature representations (= representation learning) benefits all ML applications.

The Co-Occurrence Matrix

A big corpus of un-labeled text can be represented as the **co-occurrence counts**

$n_{ij} := \# \text{contexts where word } w_i \text{ occurs together with word } w_j.$



Needs definition of

- **Context** e.g. document, paragraph, sentence, window
- **Vocabulary**

$$\mathcal{V} := \{w_1, \dots, w_D\}$$

For words $w_d = 1, 2, \dots, D$ and context words $w_n = 1, 2, \dots, N$, the co-occurrence counts n_{ij} form a very sparse $D \times N$ matrix.

In practice:
Can we $D=N$

Learning Word-Representations (Using Matrix Factorization)

Find a factorization of the co-occurrence matrix!

Typically uses log of the actual counts, i.e. $x_{dn} := \log(n_{dn})$.


We will aim to find \mathbf{W}, \mathbf{Z} s.t.

$$\mathbf{X} \approx \mathbf{W}\mathbf{Z}^\top.$$

on observed entries Ω

So for each pair of words (w_d, w_n) , we try to 'explain' their co-occurrence count by a numerical representation of the two words

- in fact by the inner product of the two feature vectors $\mathbf{W}_{d:}, \mathbf{Z}_{n:}$.



$$\min_{\mathbf{W}, \mathbf{Z}} \mathcal{L}(\mathbf{W}, \mathbf{Z}) := \frac{1}{2} \sum_{(d,n) \in \Omega} f_{dn} [x_{dn} - (\mathbf{W}\mathbf{Z}^\top)_{dn}]^2$$

$\log(\text{count of word } d \text{ with word } n)$

weighting

where $\mathbf{W} \in \mathbb{R}^{D \times K}$ and $\mathbf{Z} \in \mathbb{R}^{N \times K}$ are tall matrices, having only $K \ll D, N$ columns.

The set $\Omega \subseteq [D] \times [N]$ collects the indices of non-zeros of the count matrix \mathbf{X} .

Each row of those matrices forms a representation of a word (\mathbf{W}) or a context word (\mathbf{Z}) respectively.

GloVe

2014

This model is called GloVe, and is a variant of word2vec.


Weights f_{dn} : Give “importance” of each entry. Choosing $f_{dn} := 1$ is ok.

GloVe weight function:

$$f_{dn} := \min \{1, (n_{dn}/n_{\max})^\alpha\}, \quad \alpha \in [0; 1] \quad \text{e.g. } \alpha = \frac{3}{4}$$

↑
Count of
d, n appearing
together

↑
tuning
parameter




↑
count


Choosing K

K e.g. 50, 100, 200

Word Analogies



A	B	C	D
Newspapers			
New York	New York Times	Baltimore	Baltimore Sun
San Jose	San Jose Mercury News	Cincinnati	Cincinnati Enquirer
NHL Teams			
Boston	Boston Bruins	Montreal	Montreal Canadiens
Phoenix	Phoenix Coyotes	Nashville	Nashville Predators
NBA Teams			
Detroit	Detroit Pistons	Toronto	Toronto Raptors
Oakland	Golden State Warriors	Memphis	Memphis Grizzlies
Airlines			
Austria	Austrian Airlines	Spain	Spainair
Belgium	Brussels Airlines	Greece	Aegean Airlines
Company executives			
Steve Ballmer	Microsoft	Larry Page	Google
Samuel J. Palmisano	IBM	Werner Vogels	Amazon



Training

- Stochastic Gradient Descent (SGD)
- Alternating Least-Squares (ALS)

Open questions:

- Parallel and distributed training
- Does regularization help?

Alternative: Skip-Gram Model


(Original word2vec)

Uses binary classification (logistic regression objective), to separate **real** word pairs (w_d, w_n) from **fake** word pairs. Same inner product score = matrix factorization.

Given w_d , a context word w_n is


- **real** = appearing together in a context window of size 5
- **fake** = any word $w_{n'}$ sampled randomly: Negative sampling (also: Noise Contrastive Estimation)

Efficient
online
(streaming)
algorithm



Learning Representations of Documents

Supervised: For a supervised task (e.g. predicting the emotion of a tweet), we can use matrix-factorization (below) or convolutional neural networks (see next weeks).



→ SemEval competition for tweet classification.

Unsupervised:

- Adding (fixed, given) word vectors
- Training word vectors such that adding works well
- Direct unsupervised training for sentences (appearing together with context sentences) instead of words

FastText

Matrix factorization to learn document/sentence representations (supervised).

for classification of documents


Given a sentence $s_n = (w_1, w_2, \dots, w_m)$, let $\mathbf{x}_n \in \mathbb{R}^{|\mathcal{V}|}$ be the bag-of-words representation of the sentence.

$$\min_{\mathbf{W}, \mathbf{Z}} \mathcal{L}(\mathbf{W}, \mathbf{Z}) := \sum_{s_n \text{ a sentence}} f(y_n \mathbf{W} \mathbf{Z}^T \mathbf{x}_n)$$

Label



$\mathbf{x}_n \in \mathbb{R}^{|\mathcal{V}|}$



where $\mathbf{W} \in \mathbb{R}^{1 \times K}$, $\mathbf{Z} \in \mathbb{R}^{|\mathcal{V}| \times K}$ are the variables, and the vector $\mathbf{x}_n \in \mathbb{R}^{|\mathcal{V}|}$ represents our n -th training sentence.

Here f is a linear classifier loss function, and $y_n \in \{\pm 1\}$ is the classification label for sentence \mathbf{x}_n .

Logistic regression
or: hinge loss

Further Pointers

1. word2vec:

code: code.google.com/p/word2vec/

paper:

“Distributed representations of words and phrases and their compositionality” - T Mikolov, I Sutskever, K Chen, GS Corrado, J Dean. NIPS 2013

2. GloVe:

code and vectors: nlp.stanford.edu/projects/glove/

paper:

“GloVe: Global Vectors for Word Representation” - Pennington, J., Socher, R., Manning, C. D.. EMNLP 2014

3. FastText

code: github.com/facebookresearch/fastText

papers:

“Bag of Tricks for Efficient Text Classification” - Joulin, A., Grave, E., Bojanowski, P., Mikolov, T. - [EC-ACL](#), 2017.

“Enriching Word Vectors with Subword Information” - Bojanowski, P., Grave, E., Joulin, A., Mikolov, T. - [TACL](#), 2017.

“Unsupervised Learning of Sentence Embeddings using Compositional n-Gram Features” - Pagliardini, M., Gupta, P., Jaggi, M. [NAACL](#) 2018.