

DFIR LAB 5: Network Forensics

Theory:

- **Spoofing:**

Spoofing is a type of cybercriminal activity where someone or something forges the sender's information and pretends to be a legitimate source, business, colleague, or other trusted contact for the purpose of gaining access to personal information, acquiring money, spreading malware, or stealing data.

- **ARP (Address Resolution Protocol) Spoofing:**

An attacker sends fake ARP messages to an Ethernet LAN, which links the attacker's MAC address with the IP address of a legitimate computer or server on the network. This strategy diverts or intercepts traffic meant for that IP.

Q1. How to detect an ARP poisoning attack?

If the table contains two different IP addresses that have the same MAC address, this indicates an ARP attack is taking place.

```
C:\Users\PMG NMR>arp -a

Interface: 192.168.56.1 --- 0x4
  Internet Address      Physical Address      Type
  192.168.56.255        ff-ff-ff-ff-ff-ff    static
  224.0.0.22            01-00-5e-00-00-16    static
  224.0.0.251           01-00-5e-00-00-fb    static
  224.0.0.252           01-00-5e-00-00-fc    static
  239.255.255.250       01-00-5e-7f-ff-fa    static

Interface: 192.168.1.102 --- 0x6
  Internet Address      Physical Address      Type
  192.168.1.1           48-22-54-be-d0-38    dynamic
  192.168.1.255         ff-ff-ff-ff-ff-ff    static
  224.0.0.22            01-00-5e-00-00-16    static
  224.0.0.251           01-00-5e-00-00-fb    static
  224.0.0.252           01-00-5e-00-00-fc    static
  239.255.255.250       01-00-5e-7f-ff-fa    static
  255.255.255.255       ff-ff-ff-ff-ff-ff    static

Interface: 10.5.0.2 --- 0x19
  Internet Address      Physical Address      Type
  10.5.0.2              10-00-00-00-00-00    dynamic
  10.5.255.255          01-00-5e-00-00-00    static
  224.0.0.22            01-00-5e-00-00-16    static
  224.0.0.251           01-00-5e-00-00-fb    static
  224.0.0.252           01-00-5e-00-00-fc    static
  239.255.255.250       01-00-5e-7f-ff-fa    static
```

Q2. How to prevent an ARP poisoning attack?

- Using a Virtual Private Network (VPN)
- Using static ARP
- Using packet filtering
- Running a spoofing attack

- ***Snooping:***

Sniffing is the process of capturing, monitoring, and analysing network traffic. It can be used for legitimate purposes, such as network troubleshooting and security analysis, or malicious activities like password sniffing and man-in-the-middle (MITM) attacks.

- ***DHCP Snooping:***

It is a security technology on a Layer 2 network switch that can prevent unauthorized DHCP servers from accessing your network. It is a protection from the untrusted hosts that want to become DHCP servers. DHCP Snooping works as a protection from man-in-the-middle attacks.

Dynamic Host Configuration Protocol (DHCP) server is a vital role in every organization's network as most end-user devices like PC and laptops are using DHCP to learn the IP addresses automatically.

Marriott 2018 Data Breach Insights

Summary of the Breach

The 2018 Marriott data breach ranks among the most significant cybersecurity incidents ever, compromising the personal information of nearly 500 million customers. The breach stemmed from security weaknesses in Starwood Hotels' network, which Marriott had acquired in 2016. Hackers initially gained access in 2014 and remained undetected for four years. It was finally discovered in September 2018, resulting in regulatory fines, financial setbacks, and severe reputational harm.

Key Events of the Breach

- ***July 2014:*** Attackers infiltrated Starwood's network using a Remote Access Trojan (RAT) and post-exploitation tools, such as Mimikatz.
- ***September 2016:*** Marriott acquired Starwood but failed to conduct a thorough cybersecurity audit.
- ***September 2018:*** The breach was detected when Marriott's security team identified unauthorized access within the guest reservation database.
- ***November 2018:*** Marriott publicly disclosed the breach, which affected approximately 500 million records.
- ***2020:*** Marriott was fined £18.4 million by UK regulators under GDPR for failing to adequately secure personal data.

Mishandling Cybersecurity

- **Weak Access Controls:** The breach originated from attackers gaining access to Starwood's network in 2014.
- **Lack of Encryption:** Sensitive customer data, including passport numbers, was not adequately encrypted.
- **Failure in Monitoring & Logging:** Marriott lacked robust anomaly detection systems, which delayed the detection of the breach.
- **Regulatory Penalties:** Marriott was fined £18.4 million for violating GDPR Article 32 due to its failure to secure personal data.

Network Forensics Analysis

- **Initial Attack Vector:** In 2014, hackers deployed a Remote Access Trojan (RAT) along with the Mimikatz tool, enabling persistent access to the system.
- **Lateral Movement:** The attackers navigated Marriott's network undetected by exploiting misconfigured servers.
- **Exfiltration Methods:** Stolen data was encrypted and transferred to external servers, bypassing security detection systems.
- **Forensic Evidence:** Investigations indicated the involvement of state-sponsored Chinese hackers who utilized cloud-hosting techniques.
- **Network Hardening Solutions:** The breach could have been detected earlier with the implementation of Intrusion Detection Systems (IDS) and Security Information & Event Management (SIEM).

Digital Forensics & Incident Response

- **Delayed Discovery:** The breach was only detected in September 2018, four years after the initial infiltration.
- **Incident Response Failures:** A lack of proactive security audits following the Starwood acquisition contributed to the prolonged undetected breaches.
- **Legal Consequences:** Multiple lawsuits were filed, and both the U.S. and the UK authorities fined Marriott under GDPR.
- **Response Improvement:** An Incident Response Plan (IRP) with rapid containment and forensic triage mechanisms should be implemented.
- **Key Lessons:** It is crucial to prioritise cybersecurity audits during mergers and acquisitions (M&A) to prevent inherited vulnerabilities.

Business & Financial Impact

- **Number of Affected Customers:** Approximately 500 million records were compromised.
- **Financial Losses:** Marriott incurred \$30 million in recovery costs and over \$1 billion in revenue loss due to diminished customer trust.
- **Stock Price Impact:** Marriott's stock dropped by 5% immediately following the breach disclosure.

- **Industry Implications:** The hotel and hospitality sectors now prioritise investments in cybersecurity and compliance with NIST, GDPR, and PCI-DSS regulations.

Conclusion

The Marriott 2018 Data Breach highlights the importance of proactive cybersecurity, network monitoring, and effective incident response. Strengthening access control, encryption, and forensic readiness is crucial for businesses handling sensitive customer data to avoid legal, financial, and reputational damage.

Network Forensics Commands

netstat netstat, or network statistics, is a command-line tool used to display active network connections, listening ports, routing tables, and network protocol statistics in Windows, Linux, and macOS.

- **netstat**: Displays active TCP connections.

```
C:\Users\PMG NMR>netstat
```

Active Connections

Proto	Local Address	Foreign Address	State
TCP	127.0.0.1:49680	kubernetes:49681	ESTABLISHED
TCP	127.0.0.1:49681	kubernetes:49680	ESTABLISHED
TCP	127.0.0.1:49682	kubernetes:49683	ESTABLISHED
TCP	127.0.0.1:49683	kubernetes:49682	ESTABLISHED
TCP	192.168.1.102:50205	40.99.9.50:https	ESTABLISHED
TCP	192.168.1.102:50206	40.99.9.50:https	ESTABLISHED

- **netstat -a**: Shows all active connections and listening ports.

```
C:\Users\PMG NMR>netstat -a
```

Active Connections

Proto	Local Address	Foreign Address	State
TCP	0.0.0.0:135	LAPTOP-PA4BHMAF:0	LISTENING
TCP	0.0.0.0:445	LAPTOP-PA4BHMAF:0	LISTENING
TCP	0.0.0.0:1521	LAPTOP-PA4BHMAF:0	LISTENING
TCP	0.0.0.0:3306	LAPTOP-PA4BHMAF:0	LISTENING
TCP	0.0.0.0:5040	LAPTOP-PA4BHMAF:0	LISTENING
TCP	0.0.0.0:8080	LAPTOP-PA4BHMAF:0	LISTENING
TCP	0.0.0.0:33060	LAPTOP-PA4BHMAF:0	LISTENING
TCP	0.0.0.0:49664	LAPTOP-PA4BHMAF:0	LISTENING
TCP	0.0.0.0:49665	LAPTOP-PA4BHMAF:0	LISTENING
TCP	0.0.0.0:49666	LAPTOP-PA4BHMAF:0	LISTENING
TCP	0.0.0.0:49667	LAPTOP-PA4BHMAF:0	LISTENING
TCP	0.0.0.0:49668	LAPTOP-PA4BHMAF:0	LISTENING
TCP	0.0.0.0:49685	LAPTOP-PA4BHMAF:0	LISTENING
TCP	0.0.0.0:49686	LAPTOP-PA4BHMAF:0	LISTENING
TCP	0.0.0.0:59869	LAPTOP-PA4BHMAF:0	LISTENING
TCP	10.5.0.2:139	LAPTOP-PA4BHMAF:0	LISTENING
TCP	127.0.0.1:9247	LAPTOP-PA4BHMAF:0	LISTENING
TCP	127.0.0.1:24830	LAPTOP-PA4BHMAF:0	LISTENING
TCP	127.0.0.1:27017	LAPTOP-PA4BHMAF:0	LISTENING
TCP	127.0.0.1:44950	LAPTOP-PA4BHMAF:0	LISTENING
TCP	127.0.0.1:44960	LAPTOP-PA4BHMAF:0	LISTENING
TCP	127.0.0.1:45623	LAPTOP-PA4BHMAF:0	LISTENING
TCP	127.0.0.1:49675	LAPTOP-PA4BHMAF:0	LISTENING
TCP	127.0.0.1:49680	kubernetes:49681	ESTABLISHED

netstat -n: Displays connections in numerical form.

```
C:\Users\PMG NMR>netstat -n

Active Connections

    Proto Local Address          Foreign Address         State
    TCP    127.0.0.1:49680        127.0.0.1:49681        ESTABLISHED
    TCP    127.0.0.1:49681        127.0.0.1:49680        ESTABLISHED
    TCP    127.0.0.1:49682        127.0.0.1:49683        ESTABLISHED
    TCP    127.0.0.1:49683        127.0.0.1:49682        ESTABLISHED
    TCP    192.168.1.102:50205    40.99.9.50:443         ESTABLISHED
    TCP    192.168.1.102:50206    40.99.9.50:443         ESTABLISHED
    TCP    192.168.1.102:50275    64.233.170.188:5228    ESTABLISHED
    TCP    192.168.1.102:50293    52.123.164.120:443     ESTABLISHED
    TCP    192.168.1.102:50294    52.123.171.36:443      ESTABLISHED
    TCP    192.168.1.102:50295    52.123.168.140:443     ESTABLISHED
    TCP    192.168.1.102:50296    52.123.164.85:443      ESTABLISHED
    TCP    192.168.1.102:50298    104.215.18.215:443     ESTABLISHED
    TCP    192.168.1.102:50387    57.144.125.33:5222     ESTABLISHED
    TCP    192.168.1.102:50568    52.98.57.162:443       TIME_WAIT
    TCP    192.168.1.102:50744    54.174.133.91:443      ESTABLISHED
    TCP    192.168.1.102:50855    40.99.9.50:443         ESTABLISHED
```

- **netstat -o:** Shows active connections with the corresponding Process ID (PID).

```
C:\Users\PMG NMR>netstat -o

Active Connections

    Proto Local Address          Foreign Address         State      PID
    TCP    127.0.0.1:49680        kubernetes:49681        ESTABLISHED 7652
    TCP    127.0.0.1:49681        kubernetes:49680        ESTABLISHED 7652
    TCP    127.0.0.1:49682        kubernetes:49683        ESTABLISHED 7652
    TCP    127.0.0.1:49683        kubernetes:49682        ESTABLISHED 7652
    TCP    192.168.1.102:50205    40.99.9.50:https        ESTABLISHED 11208
```

- **netstat -p <protocol>:** Filters results by protocol (tcp, udp, etc.).

```
C:\Users\PMG NMR>netstat -p udp

Active Connections

    Proto Local Address          Foreign Address         State

C:\Users\PMG NMR>netstat -p tcp

Active Connections

    Proto Local Address          Foreign Address         State
    TCP    127.0.0.1:49680        kubernetes:49681        ESTABLISHED
    TCP    127.0.0.1:49681        kubernetes:49680        ESTABLISHED
    TCP    127.0.0.1:49682        kubernetes:49683        ESTABLISHED
    TCP    127.0.0.1:49683        kubernetes:49682        ESTABLISHED
```

- **netstat -r**: Displays the system's routing table.

```
C:\Users\PMG NMR>netstat -r
=====
Interface List
10.....WireGuard Tunnel
25.....NordLynx Tunnel
4...0a 00 27 00 00 04 .....VirtualBox Host-Only Ethernet Adapter
14.....OpenVPN Data Channel Offload
18...00 ff 90 11 b0 13 .....TAP-NordVPN Windows Adapter V9
16...bc 17 b8 cd bf 46 .....Microsoft Wi-Fi Direct Virtual Adapter #3
11...be 17 b8 cd bf 45 .....Microsoft Wi-Fi Direct Virtual Adapter #4
6...bc 17 b8 cd bf 45 .....Intel(R) Wi-Fi 6 AX201 160MHz
26...bc 17 b8 cd bf 49 .....Bluetooth Device (Personal Area Network)
1.....Software Loopback Interface 1
=====

IPv4 Route Table
=====
Active Routes:
Network Destination        Netmask          Gateway           Interface        Metric
0.0.0.0                    0.0.0.0          192.168.1.1       192.168.1.102    55
10.5.0.0                   255.255.0.0      On-link           10.5.0.2         261
10.5.0.2                   255.255.255.255  On-link           10.5.0.2         261
10.5.255.255               255.255.255.255  On-link           10.5.0.2         261
127.0.0.0                  255.0.0.0        On-link           127.0.0.1        331
```

- **netstat -e**: Shows Ethernet statistics (sent/received bytes, errors, etc.).

```
C:\Users\PMG NMR>netstat -e
Interface Statistics

                Received                Sent
Bytes           379465490           2326921151
Unicast packets 14873922             7942212
Non-unicast packets 21906             11934
Discards        0                 18792
Errors          0                 18738
Unknown protocols 0
```

- **netstat -b**: Displays the executable associated with each connection (requires admin).

```
C:\Windows\System32>netstat -b
```

Active Connections

Proto	Local Address	Foreign Address	State
TCP	127.0.0.1:49680	kubernetes:49681	ESTABLISHED
[mysqld.exe]			
TCP	127.0.0.1:49681	kubernetes:49680	ESTABLISHED
[mysqld.exe]			
TCP	127.0.0.1:49682	kubernetes:49683	ESTABLISHED
[mysqld.exe]			

netstat -an: Combines -a and -n, showing all connections in numeric form.

```
C:\Windows\System32>netstat -an
```

Active Connections

Proto	Local Address	Foreign Address	State
TCP	0.0.0.0:135	0.0.0.0:0	LISTENING
TCP	0.0.0.0:445	0.0.0.0:0	LISTENING
TCP	0.0.0.0:1521	0.0.0.0:0	LISTENING
TCP	0.0.0.0:3306	0.0.0.0:0	LISTENING
TCP	0.0.0.0:5040	0.0.0.0:0	LISTENING
TCP	0.0.0.0:8080	0.0.0.0:0	LISTENING
TCP	0.0.0.0:33060	0.0.0.0:0	LISTENING
TCP	0.0.0.0:49664	0.0.0.0:0	LISTENING
TCP	0.0.0.0:49665	0.0.0.0:0	LISTENING
TCP	0.0.0.0:49666	0.0.0.0:0	LISTENING
TCP	0.0.0.0:49667	0.0.0.0:0	LISTENING
TCP	0.0.0.0:49668	0.0.0.0:0	LISTENING
TCP	0.0.0.0:49685	0.0.0.0:0	LISTENING
TCP	0.0.0.0:49686	0.0.0.0:0	LISTENING
TCP	0.0.0.0:59869	0.0.0.0:0	LISTENING
TCP	10.5.0.2:139	0.0.0.0:0	LISTENING
TCP	127.0.0.1:9247	0.0.0.0:0	LISTENING
TCP	127.0.0.1:24830	0.0.0.0:0	LISTENING
TCP	127.0.0.1:27017	0.0.0.0:0	LISTENING
TCP	127.0.0.1:44950	0.0.0.0:0	LISTENING
TCP	127.0.0.1:44960	0.0.0.0:0	LISTENING
TCP	127.0.0.1:45623	0.0.0.0:0	LISTENING
TCP	127.0.0.1:49675	0.0.0.0:0	LISTENING
TCP	127.0.0.1:49680	127.0.0.1:49681	ESTABLISHED
TCP	127.0.0.1:49681	127.0.0.1:49680	ESTABLISHED

- **netstat -ano:** Displays all connections with numeric addresses, listening ports, and PIDs.

```
C:\Windows\System32>netstat -ano

Active Connections

Proto Local Address          Foreign Address         State       PID
TCP   0.0.0.0:135             0.0.0.0:0               LISTENING   1628
TCP   0.0.0.0:445             0.0.0.0:0               LISTENING   4
TCP   0.0.0.0:1521            0.0.0.0:0               LISTENING   5480
TCP   0.0.0.0:3306            0.0.0.0:0               LISTENING   7652
TCP   0.0.0.0:5040            0.0.0.0:0               LISTENING   9648
TCP   0.0.0.0:8080            0.0.0.0:0               LISTENING   5480
TCP   0.0.0.0:33060           0.0.0.0:0               LISTENING   7652
TCP   0.0.0.0:49664           0.0.0.0:0               LISTENING   1244
TCP   0.0.0.0:49665           0.0.0.0:0               LISTENING   1140
TCP   0.0.0.0:49666           0.0.0.0:0               LISTENING   2256
TCP   0.0.0.0:49667           0.0.0.0:0               LISTENING   3528
TCP   0.0.0.0:49668           0.0.0.0:0               LISTENING   4704
TCP   0.0.0.0:49685           0.0.0.0:0               LISTENING   1216
TCP   0.0.0.0:49686           0.0.0.0:0               LISTENING   5340
TCP   0.0.0.0:59869           0.0.0.0:0               LISTENING   9508
TCP   10.5.0.2:139            0.0.0.0:0               LISTENING   4
TCP   127.0.0.1:9247           0.0.0.0:0               LISTENING   5056
TCP   127.0.0.1:24830         0.0.0.0:0               LISTENING   5572
TCP   127.0.0.1:27017         0.0.0.0:0               LISTENING   4776
TCP   127.0.0.1:44950         0.0.0.0:0               LISTENING   17268
TCP   127.0.0.1:44960         0.0.0.0:0               LISTENING   17268
TCP   127.0.0.1:45623         0.0.0.0:0               LISTENING   2572
TCP   127.0.0.1:49675         0.0.0.0:0               LISTENING   5480
TCP   127.0.0.1:49680         127.0.0.1:49681        ESTABLISHED 7652
```

nbtstat

nbtstat (NetBIOS over TCP/IP Statistics) is a Windows command-line tool used to troubleshoot NetBIOS name resolution issues. It helps diagnose problems related to NetBIOS-to-IP address mappings and is useful for network troubleshooting.

- **nbtstat -n:** Displays local NetBIOS names registered on the system.

```

C:\Windows\System32>nbtstat -n

Ethernet:
Node IpAddress: [192.168.56.1] Scope Id: []

                NetBIOS Local Name Table

                Name                Type                Status
                -----
LAPTOP-PA4BHMAF<00>  UNIQUE              Registered
WORKGROUP          <00>                GROUP              Registered
LAPTOP-PA4BHMAF<20>  UNIQUE              Registered

OpenVPN Data Channel Offload for NordVPN:
Node IpAddress: [0.0.0.0] Scope Id: []

    No names in cache

Local Area Connection 2:
Node IpAddress: [0.0.0.0] Scope Id: []

    No names in cache

Local Area Connection:
Node IpAddress: [0.0.0.0] Scope Id: []

    No names in cache

Bluetooth Network Connection:
Node IpAddress: [0.0.0.0] Scope Id: []

    No names in cache

Wi-Fi:
Node IpAddress: [192.168.1.102] Scope Id: []

```

nbstat -c: Shows the NetBIOS name cache (recently resolved names).

```
C:\Windows\System32>nbstat -c

Ethernet:
Node IpAddress: [192.168.56.1] Scope Id: []

    No names in cache

OpenVPN Data Channel Offload for NordVPN:
Node IpAddress: [0.0.0.0] Scope Id: []

    No names in cache

Local Area Connection 2:
Node IpAddress: [0.0.0.0] Scope Id: []

    No names in cache

Local Area Connection:
Node IpAddress: [0.0.0.0] Scope Id: []

    No names in cache

Bluetooth Network Connection:
Node IpAddress: [0.0.0.0] Scope Id: []

    No names in cache

Wi-Fi:
Node IpAddress: [192.168.1.102] Scope Id: []
```

- **nbstat -R:** Purges the NetBIOS name cache.

```
C:\Windows\System32>nbstat -R
Successful purge and preload of the NBT Remote Cache Name Table.
```

- **nbstat -RR:** Sends a refresh request to the WINS server.

```
C:\Windows\System32>nbstat -RR
The NetBIOS names registered by this computer have been refreshed.
```

- ***nbstat -a <computername>***: Displays NetBIOS table of a remote computer.

```
C:\Windows\System32>nbtstat -a LAPTOP-PA4BHMAF

Ethernet:
Node IpAddress: [192.168.56.1] Scope Id: []

    Host not found.

OpenVPN Data Channel Offload for NordVPN:
Node IpAddress: [0.0.0.0] Scope Id: []

    Host not found.

Local Area Connection 2:
Node IpAddress: [0.0.0.0] Scope Id: []

    Host not found.

Local Area Connection:
Node IpAddress: [0.0.0.0] Scope Id: []

    Host not found.

Bluetooth Network Connection:
Node IpAddress: [0.0.0.0] Scope Id: []

    Host not found.
```

nbtstat -A <IP address>: Shows NetBIOS table for a remote machine using its IP address.

```
C:\Windows\System32>nbtstat -A 192.168.56.1

Ethernet:
Node IpAddress: [192.168.56.1] Scope Id: []

    Host not found.

OpenVPN Data Channel Offload for NordVPN:
Node IpAddress: [0.0.0.0] Scope Id: []

    Host not found.

Local Area Connection 2:
Node IpAddress: [0.0.0.0] Scope Id: []

    Host not found.

Local Area Connection:
Node IpAddress: [0.0.0.0] Scope Id: []

    Host not found.

Bluetooth Network Connection:
Node IpAddress: [0.0.0.0] Scope Id: []

    Host not found.

Wi-Fi:
Node IpAddress: [192.168.1.102] Scope Id: []
```

- **nbtstat -s**: Displays active NetBIOS sessions.

```

C:\Windows\System32>nbtstat -s

Ethernet:
Node IpAddress: [192.168.56.1] Scope Id: []

    No Connections

OpenVPN Data Channel Offload for NordVPN:
Node IpAddress: [0.0.0.0] Scope Id: []

    No Connections

Local Area Connection 2:
Node IpAddress: [0.0.0.0] Scope Id: []

    No Connections

Local Area Connection:
Node IpAddress: [0.0.0.0] Scope Id: []

    No Connections

Bluetooth Network Connection:
Node IpAddress: [0.0.0.0] Scope Id: []

    No Connections

Wi-Fi:
Node IpAddress: [192.168.1.102] Scope Id: []

```

- **nbtstat -S:** Shows active NetBIOS connections with IPs.

```

C:\Windows\System32>nbtstat -S

Ethernet:
Node IpAddress: [192.168.56.1] Scope Id: []

    No Connections

OpenVPN Data Channel Offload for NordVPN:
Node IpAddress: [0.0.0.0] Scope Id: []

    No Connections

Local Area Connection 2:
Node IpAddress: [0.0.0.0] Scope Id: []

    No Connections

Local Area Connection:
Node IpAddress: [0.0.0.0] Scope Id: []

    No Connections

Bluetooth Network Connection:
Node IpAddress: [0.0.0.0] Scope Id: []

    No Connections

Wi-Fi:
Node IpAddress: [192.168.1.102] Scope Id: []

    No Connections

Local Area Connection* 3:
Node IpAddress: [0.0.0.0] Scope Id: []

```

net session

The net session command is used in Windows to manage and view information about sessions on a computer that acts as a file server. It displays details about users who have connected to shared resources and allows you to close sessions.

- **net session:** Displays all active sessions on the local computer.

```
C:\Windows\System32>net session
There are no entries in the list.
```

- **net session \\<computername>:** Shows session details for a specific remote computer.

```
C:\Windows\System32>net session \\LAPTOP-PA4BHMAF
A session does not exist with that computer name.

More help is available by typing NET HELPMSG 2312.
```

- **net session /delete:** Ends all active sessions on the local computer.

```
C:\Windows\System32>net session /delete
The command completed successfully.
```

- **net session \\<computername> /delete:** Terminates the session of the specified remote computer.

```
C:\Windows\System32>net session \\LAPTOP-PA4BHMAF /delete
A session does not exist with that computer name.

More help is available by typing NET HELPMSG 2312.
```

Differences between netstat, nbtstat, and net session

Aspect	netstat	nbtstat	net session
Purpose	Network Statistics	NetBIOS over TCP/IP Statistics	Manage Network Sessions
Functionality	Displays active network connections, listening ports, and routing tables.	Troubleshoots NetBIOS name resolution, shows NetBIOS cache, and lists active NetBIOS sessions.	Displays and manages user sessions connected to shared resources on a local computer.
Common Usage	Checking open ports, monitoring network traffic, and finding active TCP/UDP connections.	Resolving NetBIOS name conflicts, checking NetBIOS cache, and troubleshooting network browsing issues.	Viewing and terminating remote user connections to shared folders or drives.