

Hashcat Password Cracking [Total Headers : 3]

Hash Modes

Algorithm	Hashcat Mode	Notes
MD5	0	Most basic & fast hash
SHA1	100	Still common, less secure
SHA2-256	1400	More secure than SHA1
SHA2-512	1700	Part of the SHA family
SHA3-224	17300	Keccak-based algorithm
SHA3-256	17400	Used in newer cryptography
SHA3-384	17500	Used in your question
SHA3-512	17600	Very secure, slow
MD4	900	Rare today, used in NTLM
NTLM	1000	MD4 variant used in Windows
bcrypt	3200	Very slow, used in web apps
PBKDF2-HMAC-SHA1	12000	Used in WPA, Office
PBKDF2-HMAC-SHA256	10900	More secure than SHA1 version
WPA-PBKDF2-PMKID+EAPOL	22000	Used for Wi-Fi password cracking

```
9400 | MS Office 2007
9500 | MS Office 2010
9600 | MS Office 2013
25300 | MS Office 2016 - SheetProtection
9700 | MS Office ≤ 2003 $0/$1, MD5 + RC4
9710 | MS Office ≤ 2003 $0/$1, MD5 + RC4, collider #1
9720 | MS Office ≤ 2003 $0/$1, MD5 + RC4, collider #2
9810 | MS Office ≤ 2003 $3, SHA1 + RC4, collider #1
9820 | MS Office ≤ 2003 $3, SHA1 + RC4, collider #2
9800 | MS Office ≤ 2003 $3/$4, SHA1 + RC4
```

```
(kali@kali)-[~]
$ hashid '8968e60ae465a52918e33412b32d19818e18072637d9ce65749c68878716f01a'
Analyzing '8968e60ae465a52918e33412b32d19818e18072637d9ce65749c68878716f01a'
[+] Snefru-256
[+] SHA-256
[+] RIPEMD-256
[+] Haval-256
[+] GOST R 34.11-94
[+] GOST CryptoPro S-Box
[+] SHA3-256
[+] Skein-256
[+] Skein-512(256)
```

Mask Modes

Symbol	Meaning	Example
?d	Digit (0–9)	?d?d?d?d = 4-digit PIN
?l	Lowercase letter (a–z)	?l?l?l = 3 lowercase letters
?u	Uppercase letter (A–Z)	?u?u = 2 uppercase letters
?s	Special char (!, @, #)	?s = 1 special character
?a	All printable ASCII	Combo of everything above
?h	Hex lowercase (0–f)	Used in hex-based hashes
?H	Hex uppercase (0–F)	Uppercase hex format

Common Attack Modes

Mode	Name	Description
0	Dictionary	Tries each word in the wordlist
1	Combination	Joins words from 2 wordlists
3	Brute-force	Tries every character combination
6	Hybrid [Wordlist + Mask]	Wordlist on the left, mask on the right
7	Hybrid [Mask + Wordlist]	Mask on the left, wordlist on the right

Command Layout

hashcat [options] -m <hash-mode> -a <attack-mode> <hash-file> <wordlist> <mask>
hashcat --show .hash.

← Syntax
← Hash Type

sudo apt install wordlists
sudo gunzip /usr/share/wordlists/rockyou.txt.gz
ls -lh /usr/share/wordlists/rockyou.txt

← Install

1. hashcat -m 17600 -a 7 hash.txt ?d?d?d?d rockyou.txt # Is for digit+list
2. hashcat -m 17600 -a 6 --session sha3_session --status
--status-timer 10 --force -o cracked_passwords.txt hash.txt
/usr/share/wordlists/rockyou.txt ?d?d?d?d # Is for list + digit

← Examples

```
bash
hashcat -m 0 -a 0 -r /usr/share/hashcat/rules/best64.rule hashes.txt wordlist.txt
```

This command:

- Uses `rockyou.txt` as the base wordlist.
- Applies the 64 most effective rules from `best64.rule`.
- Tries many variations like:
 - `password` → `Password`, `Password1`, `P@ssword`, `password123`, etc.

```
(root@kali) - [ /home/aditverma400 ]
# hashcat custom_dict.txt -r /usr/share/hashcat/rules/best64.rule --stdout >> custom_dict.txt

(root@kali) - [ /home/aditverma400 ]
# wc -l custom_dict.txt

161382 custom_dict.txt
```

[Options]

Option	Description	Example
hashcat -h	Lists out all hashcat help commands and modes	hashcat -h
-o <output-file>	Specify output file for cracked passwords.	-o cracked_passwords.txt
--session <session-name>	Name the session for saving and resuming later.	--session my_session
--status	Display real-time status (progress, speed, cracked passwords, etc.).	--status
--status-timer <seconds>	Set the interval (in seconds) for status updates.	--status-timer 10
--force	Force Hashcat to run even with warnings or minor issues.	--force
-w <workload-profile>	Set the workload profile (speed/efficiency). Options: 1 (low), 2 (default), 3 (high), 4 (insane).	-w 3

--potfile-path <path>	Specify the location of the potfile (password storage).	--potfile-path /path/to/potfile
--remove	Automatically remove cracked hashes from the hash file after they're cracked.	--remove
-r <rule-file>	Apply a rule file to modify wordlist entries.	-r usr/share/hashcat/rules/best64.rule
--max-combinations <number>	Limit the total number of combinations Hashcat will try in brute-force or hybrid mode.	--max-combinations 1000000
--skip <number>	Skip a specific number of hashes from the hash file before starting the crack.	--skip 1000
--restore	Resume a session that was previously stopped or interrupted.	--restore

--benchmark	Run a benchmark to test the performance of Hashcat on the current hardware.	--benchmark
--stdout	Output the results of the attack to the terminal instead of a file.	--stdout
-u <username>	Specify a username if cracking hashes that involve a user context (e.g., SMB, HTTP).	-u username
--hash-info	Show detailed information about the hash file before starting the crack.	--hash-info
--debug-mode <level>	Enable debugging output for troubleshooting.	--debug-mode 1
-t <attack-time-limit>	Limit the attack to a specific number of seconds.	-t 600 (10 minutes)
-b	Perform benchmark using only the selected algorithm.	-b
--quiet	Suppress output to only show essential information.	--quiet

```

(kali㉿kali)-[~]
$ hashcat -m 17600 -a 1 hash.txt /usr/share/wordlists/rockyou.txt a.txt
#rockyou_word + Wordlist2_word interchanging the sequence of the .txt file
will give Wordlist2_word + rockyou_word

hashcat (v6.2.6) starting

OpenCL API (OpenCL 3.0 PoCL 6.0+debian Linux, None+Asserts, RELOC, LLVM 1
8.1.8, SLEEF, DISTRO, POCL_DEBUG) - Platform #1 [The pocl project]

=====
* Device #1: cpu-skylake-avx512-AMD Ryzen AI 9 HX 370 w/ Radeon 890M, 6924
/13913 MB (2048 MB allocatable), 24MCU

/usr/share/hashcat/OpenCL/m17600_a1-optimized.cl: Pure kernel not found, f
alling back to optimized kernel
Minimum password length supported by kernel: 0
Maximum password length supported by kernel: 31

INFO: All hashes found as potfile and/or empty entries! Use --show to disp
lay them.

Started: Mon Apr 21 20:55:18 2025
Stopped: Mon Apr 21 20:55:18 2025

(kali㉿kali)-[~]
$ hashcat -m 17600 --show hash.txt

d550390367149fbfbf93f554aa4efba0ced10b66b814ed646298360e0293b9e4fe6bc014c9
4cc45b0f2f10aca1617f92db1c3f236dc6f9a1d7d1774393b89807:$HEX[50415353574f52
442132333421643a6e78]

(kali㉿kali)-[~]
$ echo 50415353574f52442132333421643a6e78 | xxd -r -p

PASSWORD!234!d:nx

```

echo 50415353574f52442132333421643a6e78

echo is a shell command that prints text to the terminal.

50415353574f52442132333421643a6e78 is a hexadecimal string representing ASCII characters.

This part outputs the hex string.

| (pipe)

The pipe takes the output from the echo command and passes it as input to the next command (xxd).

xxd -r -p

xxd is a utility for creating hex dumps or reversing them.

-r tells it to reverse the process (hex to ASCII or binary).

-p indicates plain hex format without offsets or formatting.

This part decodes the hex string into its ASCII representation.

1. Hashcat Attack Modes

Hashcat supports **6 core attack modes**, each suited for specific scenarios depending on the available information about the password or system.

1.1 Straight Mode (Attack Mode 0)

Description:

Applies every word from a wordlist (dictionary) directly to the hash.

Scenario:

You have a list of common passwords or leaked credentials.

Example:

```
hashcat -m 0 -a 0 hashes.txt rockyou.txt
```

- -m 0: Hash type MD5
- -a 0: Straight mode
- rockyou.txt: Dictionary of common passwords

1.2 Combination Mode (Attack Mode 1)

Description:

Concatenates two wordlists (wordlist1 + wordlist2) and tries every possible combination.

Scenario:

The password might be composed of two common words like summer + 2020.

Example:

```
hashcat -m 0 -a 1 hashes.txt wordlist1.txt wordlist2.txt
```

1.3 Brute-Force Mode (Attack Mode 3)

Description:

Tries all possible character combinations of a given length or pattern.

Scenario:

You know the password is a 6-digit number or fixed format like Abcd1234.

Example 1: 6-digit PIN

```
hashcat -m 0 -a 3 hashes.txt ?d?d?d?d?d?d
```

Example 2: Alphanumeric

```
hashcat -m 0 -a 3 hashes.txt ?l?l?l?l?d?d?d?d
```

- ?d = digit, ?l = lowercase, ?u = uppercase, ?s = special char

1.4 Hybrid Attack – Wordlist + Mask (Attack Mode 6)

Description:

Appends a mask (like 123) to words in a wordlist.

Scenario:

The password is a common word followed by a birth year (e.g., password1995).

Example:

```
hashcat -m 0 -a 6 hashes.txt rockyou.txt ?d?d?d?d
```

1.5 Hybrid Attack – Mask + Wordlist (Attack Mode 7)

Description:

Prepends a mask to every word in a wordlist.

Scenario:

The password begins with a fixed pattern like 123 followed by a common word (e.g., 123summer).

Example:

```
hashcat -m 0 -a 7 hashes.txt ?d?d?drockyou.txt
```

1.6 Rule-based Attack (Modifier, not a mode)

Description:

Applies transformation rules (e.g., capitalizing, reversing) to words from a dictionary.

Scenario:

Users modify common passwords slightly (e.g., Password → Password1, password!).

Example:

```
hashcat -m 0 -a 0 -r rules/best64.rule hashes.txt rockyou.txt
```

John Hash Extractor

```
git clone https://github.com/openwall/john.git
cd john/run
office2john.py >> Helps extract password hashes from the documents
python3 office2john.py <Document.extension> = Password hash
```

Hydra Usage

https://www.stationx.net/how-to-use-hydra/?utm_source=chatgpt.com : Hydra Usage online

You can use the CLI or GUI