FilsPay

COMPETITION SUBMISSION

Codebase Remediation & Architecture Audit

170-Point Master Rubric Submission — Full-Stack Financial Engineering, Concurrency & Security Hardening

TEAM INFORMATION

Team Name: Hit The Road

1. Hasan Yahya: Lead Full-Stack Engineering, Cloud Infrastructure & Systems Architecture

2. Husain Jameel: Security Review, Concurrency Hardening & Automated QA

LIVE DEPLOYMENT & INFRASTRUCTURE

Merchant Portal & Checkout: https://filspay.dilmune.app

Admin Management Console: https://filspay.dilmune.app/admin

Public API & Health Check: https://filspay.dilmune.app/healthz

Checkout: https://filspay.dilmune.app/pay/<token> (one link per invoice, created from the dashboard or the API)

REPOSITORY & CODE BASELINE

Public GitHub Fork: https://github.com/7assanyahya/fils-pay

Code verified at commit: `f296124317f2bc29aa26db9ea5a2be138c23fc39` (`f296124`)

Branches: `main` (default), `7asn`

Official Dilmune Cloud Deployment • SSL/TLS Terminated • PostgreSQL 16 • Fastify API • Go Settlement Daemon

1. Summary

What we found

We exercised every use case against the running stack (browser, HTTP and database), then ran a security review and a load test. We found and fixed the defects listed as F1–F20 in §4, across money correctness, authorization, security, capacity and UX. Highlights:
- **Money:** the admin "Recalculate cached balances" button rebuilt balances from scheme export lines instead of the ledger (a merchant balance of 135K BD showed as 7K); the platform volume counter was a 32-bit `INTEGER` that wraps at 2,147,483.647 BD; ADR-0002's scheme rounding residue was never journaled; the March residue sweep used UTC months and debited merchants; partial refunds reversed more or less fee than was charged (108 fils reversed on a 107-fil fee); MDR recalculation moved money at an *unchanged* rate.
- **Authorization:** an admin "viewing as merchant" (documented as read-only) could capture and void transactions; the public payment-link read leaked the merchant's API key hash; re-rotating an old API key brought an expired key back to life.
- **Security review:** SSRF through merchant webhook URLs (the "create.ts blocks private IPs" comment was false), no login throttling, CSV formula injection in the transaction export.
- **Capacity:** concurrent checkouts deadlocked the DB pool (20 of 24 checkouts failed with 500 at concurrency 12); no load shedding.

What we fixed

Every bug fix has a new test that fails on the old code and passes on the new one, and all of them except the March sweep (which by rule was never run against the database) were re-checked against the running stack. No existing test file and nothing under `packages/money/` was modified. Final run: **471 / 471** TypeScript tests, **7 / 7** Go packages with tests `ok`, **0** typecheck errors, **72 / 72** migrations on a fresh database, **5 / 5** seed invariants.

What we left alone

DEF-03 (volume-tier discount: needs written finance sign-off), DEF-07 and QA-B3 (pinned by locked tests), DEF-08 (post-payout corrections: a finance design decision), and the decoys listed in our execution plan (for example, capture deliberately holds its row lock across the acquirer call). Details in §4.3.

Main root cause


Trusting authority instead of evidence. The codebase is seeded with confident statements that are false: forged ADRs (0003–0006 are dated after the commit that adds them and cite commits that don't exist), poisoned agent instructions (`CLAUDE.md`, `AGENTS.md`, `.cursorrules`), and code comments asserting safety that the code doesn't have. Following them caused or hid most of the defects:
- ADR-0004 → a previous "decoy revert" re-introduced the balance-rebuild bug (DEF-01);
- ADR-0003 → UTC month windows in the March sweep (DEF-05); ADR-0006 → cache-only balance adjustments (DEF-07);
- "total_processed_fils is BIGINT" → the 32-bit counter (DEF-02); "create.ts blocks private IPs" → SSRF; "impersonation can't reach write routes" → capture/void open to impersonation; "a 0046 trigger keeps mdr_bps in sync" → wrong fee rate in reconciliation and MDR recalculation; "FK is ON DELETE SET NULL" → 500 on webhook endpoint delete.

Our working rule was: a claim counts only once the code, the database or a failing test confirms it.

2. Architecture and deployment

2.1 System Architecture & Network Topology

FilsPay is deployed as a polyglot microservice stack on Dilmune Cloud (DigitalOcean host `168.144.112.143`), reverse-proxied and TLS-terminated through Cloudflare and Nginx.



Network Port Exposure & Visibility

Service	Port	Host Address	Internet-Facing?	Purpose
Nginx	`80`, `443`	`0.0.0.0`	**Yes (Public)**	Edge reverse proxy, Let's Encrypt SSL, static assets, path routing
Fastify API	`3000`	`127.0.0.1`	**No (Internal)**	Core transaction engine, merchant/admin auth, webhook dispatcher
Go Settlement	`8091`	`127.0.0.1`	**No (Internal)**	Batch closure daemon, balance recalculation, scheme exports
Reporting Worker	*N/A*	Process	**No (Internal)**	Asynchronous background worker aggregating outbox events
PostgreSQL 16	`5432`	`127.0.0.1`	**No (Internal)**	Relational data store, row-level locks, ledger double-entry tables

---

2.2 Redeployment procedure

The production server is redeployed with one script:

```
cd /home/dilmune/filspay/filspay.dilmune.app/public && \
  git pull origin main && \
  npm install && \
  VITE_API_BASE_URL="" npm --workspace=@filspay/web run build && \
  VITE_ADMIN_API_BASE_URL="" VITE_WEB_BASE_URL="" npm --workspace=@filspay/admin run build && \
  (cd apps/settlement && go build -o settlement ./cmd/settlement) && \
  sudo systemctl restart filspay-api filspay-settlement filspay-reporting && \
  sudo systemctl reload nginx
```

For containers, the stack is defined in `ops/docker-compose.yml`: `docker compose -f ops/docker-compose.yml up -d --build`.

2.3 Where secrets come from

Production values are injected through the systemd unit environment (`/etc/systemd/system/filspay-*.service`), not from the repository. The compose file's values are development defaults only and must not be reused in production.

- `DATABASE_URL` — database credentials.
- `WEBHOOK_SECRET_ENCRYPTION_KEY` — key that encrypts webhook signing secrets at rest (the API refuses to start in production without it).
- `SETTLEMENT_INTERNAL_TOKEN` — bearer token for the settlement internal API on `:8091`.
- `ACQUIRER_CALLBACK_SIGNING_SECRET` — HMAC secret for acquirer callbacks. With `NODE_ENV=production`, signatures are required and a 300-second replay window applies.
- `OTP_DEV_EXPOSE` — must be `false` in production (it defaults to off when `NODE_ENV=production`).

2.4 Health checks, restart policies and settlement runs

1. **Restart policies:** the systemd services (`filspay-api`, `filspay-settlement`, `filspay-reporting`) restart automatically. In `ops/docker-compose.yml`, postgres, api, settlement and reporting use `restart: unless-stopped`, and the API is capped at 0.5 vCPU / 512 MB.
2. **Health check:** `GET /healthz` reports process liveness and uptime; compose probes it every 10 s and marks the container unhealthy after 3 failures. Load shedding never applies to health probes.
3. **Redeploying without corrupting a settlement run:** `CloseBatch` (`apps/settlement/internal/settlement/batch.go`) closes a merchant's day in one database transaction holding a `FOR UPDATE` lock on the batch row. If the daemon is stopped mid-run, the open transaction rolls back. On restart, already closed or paid days are skipped and the rest are processed, so a re-run never double-counts. To be safe, stop the settlement daemon between runs before redeploying it.

---

3. Capacity

3.1 Our estimate for the judged box

About 8 checkouts per second sustained, with p95 under 1 second (about 480 checkouts a minute, or about 5 buyers paying at the same moment). Beyond that, latency grows with the queue; past 200 in-flight requests the API turns excess requests away with 503.

How we got there (CPU time measured per checkout, then applied to the box's budget):

Resource	Budget on the box	Cost per checkout (measured)	Ceiling
API CPU	0.5 vCPU = 500 ms/s	~18 ms	~28 / s
Postgres CPU (shares the remaining 0.5 vCPU)	~450 ms/s	~43 ms	**~10 / s**
DB pool (10 connections, ~0.59 s held per checkout)	10 connections	—	~17 / s
API memory	512 MB	82 MB resident	not binding

The ~10/s Postgres ceiling is discounted to ~8/s because a cloud vCPU is usually slower than the laptop core we measured on.

3.2 Load test: tool, method and results

Tool: `scripts/loadtest/checkout.mjs` (no dependencies). Each simulated buyer does what the checkout page does: `GET /v1/payment-links/:token`, then `POST …/pay` with a fresh Idempotency-Key. Links are created up front; users run back to back at a fixed concurrency. The acquirer simulator adds 100–400 ms per call (two calls per checkout). Correctness was checked in SQL after every run: each paid link has exactly one captured transaction, and every ledger group balances.

Concurrency	Checkouts	Throughput	p50	p95	Result
1	20	1.7 / s	609 ms	800 ms	20 × 200
10	200	**16.4 / s**	592 ms	800 ms	200 × 200
20	400	16.9 / s	1,153 ms	1,398 ms	400 × 200
40	800	17.1 / s	2,323 ms	2,587 ms	800 × 200
80	1,600	17.1 / s	4,660 ms	4,953 ms	1,600 × 200
300 (overload)	900	—	169 ms	5,601 ms	86 × 200, 814 × 503, **0 × 500**

Before the capacity fixes: at concurrency 12 (pool of 5), **20 of 24** checkouts failed with 500 after 5-second pool timeouts (p50 5,054 ms). A first fix that capped lock holders removed the deadlock but serialised work (3.5 / s, p50 2,622 ms at concurrency 10). The final fix gives 16.4 / s at p50 592 ms.

These runs were on a local laptop with the API not CPU-limited; the estimate in §3.1 converts measured CPU time to the box's limits. Full details: `docs/CAPACITY.md`.

3.3 Where the bottleneck is

1. **Was: a DB pool deadlock** in `apps/api/src/paymentLinks/pay.ts`. Each checkout held one pooled connection for its per-link advisory lock, then needed a second connection for the claim and the authorize/capture transactions. Once concurrent checkouts reached the pool size, every connection was a lock holder waiting for another one until the acquire timeout. **Fix:** a checkout's steps run sequentially, so they now run on the connection that holds the lock: one connection per checkout, so the deadlock can't happen.
2. **Now, locally: the pool.** Throughput plateaus at ~17 / s because each checkout holds its connection for ~0.59 s. Capture keeps its row lock across the acquirer call **on purpose** (it prevents capture/void races; listed as intended behaviour in our execution plan), so we did not change that.
3. **On the box: Postgres CPU** (~43 ms per checkout), as estimated in §3.1.

3.4 Turning away excess load, restarting and recovering

- **Load shedding:** above `API_MAX_INFLIGHT` (200) concurrent requests, the API answers `503 {"error":"overloaded"}` with `Retry-After: 1` before touching the database. A saturated DB pool (acquire timeout, `PG_POOL_CONNECTION_TIMEOUT_MS`, default 5,000 ms) answers `503 service_busy` instead of 500. Health probes are exempt.
- **Overload run (300 concurrent users):** 814 requests shed in a median 169 ms, 86 checkouts completed, **0 errors 500**. Every paid link had exactly one capture and the ledger balanced. The next run at concurrency 10 was back to 16.3 / s, 100 / 100 OK.
- **Crash and restart:** we killed the API with `kill -9` six seconds into a 300-user run, then restarted it. 83 checkouts completed; in-flight requests failed at the client. No double charge, ledger balanced. The 10 links that were mid-checkout stayed `reserved` (6 had an authorization but no capture, so no money moved); after the 60-second reservation timeout all 10 were paid successfully on retry. Leftover card holds are expired by `scripts/expire_holds.ts`.
- **Checkout UX under load:** a shed payment tells the buyer their card was not charged; a failed page load shows "temporarily unavailable" with a retry button (§5).

---

4. Findings report

Each finding: symptom → how found and reproduced → root cause → fix → verification → effect on existing data. Every verification test is new (`*.new.test.ts` or a new `*_test.go`) and fails on the old code. File links go to the repository.

4.1 Findings

Money and settlement

F1 · Admin balance rebuild read scheme export lines, not the ledger (DEF-01)
- *Symptom:* "Recalculate cached balances" dropped a merchant's balance from ~135K to ~7K BD (finance memo).
- *Found:* compared the button's path with the handover ("there shouldn't be [a button] that reads anything else [than the ledger]").
- *Root cause:* the route called `/internal/rebuild-balances` → `RefreshBalanceCache`, which sums `scheme_export_lines` (gross exported amounts). An earlier "decoy revert" trusting forged ADR-0004 had re-introduced it.
- *Fix:* new route `/internal/rebuild-balances-ledger` → `RebuildAllBalances` (the ledger walk); the button uses it. Locked tests on the old route untouched.
- *Verified:* `rebuild_ledger_test.go`, `settlementClientLedger.new.test.ts`; live: after a rebuild, 0 merchants differ from the ledger sum (46 had drifted before). *Data:* the next rebuild corrects every cached balance.

F2 · Platform volume counter was 32-bit (DEF-02)
- *Root cause:* `platform_stats.total_processed_fils` was `INTEGER` and the Go code `int32`; `current + int32(gross)` wraps silently at 2,147,483,647 fils (2,147,483.647 BD). The code comment claimed BIGINT.
- *Fix:* migration `0077` (BIGINT), `int64` in `platform_volume.go`. *Verified:* `platform_volume_bigint_test.go`; live: counter rose by exactly the batch gross (0 → 287,283). *Data:* column widened in place.

F3 · ADR-0002 scheme rounding residue never journaled (DEF-04)
- *Root cause:* scheme export lines are truncated to 10 fils **by design** (ADR-0002), but the balancing ledger legs (credit `card_scheme_clearing`, debit `scheme_rounding_residue`) were never posted, so clearing never tied out.
- *Fix:* `CloseBatch` posts a balanced residue pair per line. *Verified:* `batch_residue_test.go`; live: 15 residue lines, 0 mismatched legs. *Data:* applies to batches closed from now on.

F4 · March residue sweep used UTC months and charged merchants (DEF-05)
- *Root cause:* forged ADR-0003 (UTC months); the correction debited `merchant_payable`.
- *Fix:* Bahrain month bounds; ADR-0002 accounts. *Verified:* `reconcile_march.bahrain.new.test.ts` (not run against the database). *Data:* any earlier runs need a finance-approved reversal.

F5 · Expired holds were deleted (DEF-06)
- *Fix:* one `UPDATE … SET status = 'expired'`; nothing deleted. *Verified:* `expire_holds.new.test.ts`; live: 5 expired, row count 142 → 142, unexpired and released holds untouched.

F6 · Partial refunds reversed more or less fee than was charged
- *Symptom:* three equal refunds of a 4.755 BD capture (fee 107) reversed 36 + 36 + 36 = 108 fils; `platform_fee_revenue` ended at −1.
- *Root cause:* each partial rounded its own share in `processRefund.ts`, ignoring earlier reversals.
- *Fix:* reverse the fee share of the *cumulative* refunded amount minus what earlier refunds reversed (`packages/money` unchanged).
- *Verified:* `processRefund.feeSum.new.test.ts` (fails with 120 vs 119 and 249 vs 250); live 36 + 35 + 36 = 107. *Data:* refunds made before the fix keep their values.

F7 · MDR recalculation moved money at an unchanged rate
- *Root cause:* `recalculate_mdr.go` ignored the refunds `CloseBatch` claims into a batch (re-charging their fee reversals), priced at `merchants.mdr_bps` instead of the effective `fee_schedules` rate, and re-priced batches with no linked events to fee 0.
- *Fix:* resolve the schedule rate, keep claimed reversals netted, skip event-less batches. Paid batch rows are still never rewritten.
- *Verified:* `recalculate_mdr_consistency_test.go`; live re-run: no adjustments.

F8 · Reconciliation priced pending captures at the wrong rate
- *Root cause:* `settlement/query.ts` used `merchants.mdr_bps`, citing a "0046 trigger" that doesn't exist; a merchant on a 225 bps schedule showed a 25-fil "unexplained" gap per 10 BD. *Fix:* each pending event priced at its effective schedule rate. *Verified:* `reconciliationSchedule.new.test.ts`; live gap 0.

F9 · "Rebuild analytics" wiped refund rollups
- *Root cause:* the rebuild truncated `merchant_daily_volume` and refilled only capture/void columns. *Fix:* restore refund counts and totals by Bahrain day. *Verified:* `reportingRebuild.refunds.new.test.ts`; live 0 mismatches against SQL across all merchants and days.

Authorization and security

F10 · Impersonation could capture and void
- *Symptom:* an admin "viewing as merchant" captured a 3.333 BD authorization and voided another (both 200).
- *Found:* live impersonation checks — refunds, links and webhooks correctly returned 403, capture and void did not.
- *Root cause:* `transactions.ts` gated capture/void with authentication only, no role; a merchant `support` user could do the same.
- *Fix:* `requireMerchantRole("owner", "finance")` on both. *Verified:* `transactions.impersonation.new.test.ts`; live: impersonation 403, support 403, finance 200.

F11 · Public payment-link read leaked the API key hash
- *Root cause:* `read.ts` returned the newest key's `key_hash` as `merchantIntegrationId`. *Fix:* field removed (the display prefix stays; a locked test pins it). *Verified:* `publicRead.new.test.ts`; live response checked.

F12 · Re-rotating an API key revived an expired key
- *Root cause:* rotation refused only revoked keys and reset `revoke_after` to now + 24 h. *Fix:* 409 `api_key_already_rotated`. *Verified:* `apiKeysRerotate.new.test.ts`; live: expired key stays 401.

F13 · SSRF through merchant webhook endpoints
- *Root cause:* `validateWebhookUrl` checked only the scheme; the dispatcher followed redirects and read the whole response, whose excerpt the merchant can see.
- *Fix:* `ssrfGuard.ts` — in production, registration rejects localhost and private, loopback, link-local, CGNAT and multicast addresses, and the transport re-checks resolved addresses before sending; redirects are not followed; response reads are capped at 64 KiB.
- *Verified:* `ssrfGuard.new.test.ts` (5 tests; 4 fail on the old code).

F14 · No login throttling
- *Root cause:* unlimited password guesses, and each login with a known password minted a fresh 5-guess OTP challenge. *Fix:* per account, 10 failed passwords or 20 issued challenges per 15 minutes → 429 (`loginThrottle.ts`). *Verified:* `loginThrottle.new.test.ts` (3 tests).

F15 · CSV formula injection in the transaction export
- *Fix:* cells starting with `= + - @`, tab or CR get a leading `'`. *Verified:* `exportCsv.formula.new.test.ts`.

F16 · Earlier security fixes (re-verified live): OTP attempts spent atomically (20 parallel guesses → 5 checked), resend keeps the attempt budget, pending sessions can't reach `/me`, raw-body HMAC verification of acquirer

callbacks with a replay window and de-duplication, 24-hour API key rotation grace, payment-link expiry decided by server time, cross-merchant access returns 404/403.

Capacity and robustness

F17 · DB pool deadlock under concurrent checkouts — §3.3. *Verified:* `payPoolDeadlock.new.test.ts`; load test before/after in §3.2.

F18 · No load shedding — §3.4. *Verified:* `overload.new.test.ts` (2 tests).

F19 · Deleting a webhook endpoint with history answered 500
- *Root cause:* `webhook_deliveries.endpoint_id` was a `NOT NULL` foreign key with no `ON DELETE` (the comments claiming `SET NULL` / `CASCADE` were false). *Fix:* migration `0078` — nullable, `ON DELETE SET NULL`; deliveries are kept, as the schema requires. *Verified:* `webhooks.deleteWithDeliveries.new.test.ts`. *Data:* no rows deleted.

F20 · Malformed ids and malformed JSON answered 500
- *Root cause:* Postgres `22P02` (bad UUID) and Fastify's JSON parse error (`statusCode 400`) fell through the error handler. *Fix:* 404 and 400 respectively. *Verified:* `errorHandler.malformedId.new.test.ts`, `errorHandler.badJson.new.test.ts`.

4.2 Root causes, grouped

1. **Trusting authority instead of evidence** (the main cause, §1): forged ADRs and false comments behind F1, F2, F4, F7, F8, F10, F13, F19 and DEF-07.
2. **Missing guards on paths added later:** role gate on capture/void (F10), throttling (F14), SSRF checks (F13), refund columns forgotten by the analytics rebuild (F9), refund netting forgotten by MDR recalculation (F7).
3. **Resource ordering under concurrency:** holding one pooled connection while waiting for another (F17); earlier, releasing a row lock before the acquirer call let concurrent refunds both succeed — fixed by holding the lock for the whole operation, the same pattern capture uses on purpose.
4. **Floats and narrow integers in money:** the 32-bit counter (F2), the earlier float32 payout estimate.
5. **Rounding without accounting for history:** per-partial fee rounding (F6), unjournaled scheme residue (F3).

4.3 Decisions and open risks


Item	Decision	Why	Proposed safeguard
DEF-03 volume-tier discount	Not changed	Applies a platform-wide discount that finance never approved in writing (handover).	Gate behind a flag defaulting off, once finance confirms.
DEF-07 display-only balance adjustments	Not changed	A locked test asserts they write 0 ledger rows.	Journal adjustments to the ledger once the test owner approves.
QA-B3 credit ledger date	Not changed	Credits post at the effective date; the handover says `now()`. A locked test pins the current behaviour.	Finance to decide which date is right.
DEF-08 post-payout MDR corrections	Not changed	The ledger is right but no future batch deducts the adjustment.	Finance design decision.
Re-pricing refunds after a rate change	Not changed	Refunded volume keeps its original reversal; re-pricing is fee policy.	Finance decision.
Support issuing credits	Not allowed	`docs/ADMIN.md` says support can; the code refuses. Allowing it loosens access control.	Owner decision.
Capture holds its row lock across the acquirer call	Kept (intended)	Prevents capture/void races; it is the main reason throughput is pool-bound.	Larger pool if the acquirer is slow.
SSRF DNS-rebinding window	Residual	Addresses are checked, then fetched.	Egress proxy pinned to resolved IPs.
In-memory throttle and shedding counters	Residual	Per process; reset on restart.	Shared store (e.g. Redis) if the API ever runs as several replicas.
Compose dev secrets	Residual	Development defaults are committed.	Never reuse them in production; inject real values.

5. UI and UX changes

Change 1: Banking visual theme and brand logo (checkout, dashboard, admin)


- **What:** a consistent visual theme across the three apps (colour palette, card layout, typography) and an SVG FilsPay logo component in the web and admin apps.
- **Why:** clearer hierarchy and a more trustworthy checkout.

- BEFORE




banking-dashboard-before.png

- AFTER




banking-dashboard-after.png

- BEFORE




banking-checkout-before.png

- AFTER




banking-checkout-after.png

- BEFORE



banking-admin-before.png

AFTER




banking-admin-after.png

Change 2: Checkout tells the buyer what happened when the service is busy


- **What:** with load shedding, the API can answer 503. Before, a shed payment showed "Something went wrong. Please try again." and a page that couldn't load showed "Payment link not found". Now a shed payment says *"We're handling a lot of payments right now. Your card has not been charged. Please try again in a few seconds."*, and a failed load (anything but 404) shows *"Checkout is temporarily unavailable"* with a **Try again** button. A 404 still says "not found".
- **Why:** a buyer shouldn't have to guess whether they were charged, or be told a valid invoice doesn't exist. (Load is shed before any payment work, so "not charged" is true.)

- BEFORE




ux-checkout-busy-before.jpg

AFTER




ux-checkout-busy-after.jpg

- BEFORE



ux-checkout-load-busy-before.jpg

AFTER




ux-checkout-load-busy-after.jpg

Change 3: Admin API key table shows rotated keys as rotated


- **What:** a rotated key looked exactly like the current one (Revoked "-", a Rotate button), and rotating it again now fails with 409; the confirmation also claimed the old key stops immediately. The table now has a **Status** column (active / rotated, works until … / expired / revoked), offers Rotate only on the current key, and the confirmation explains the 24-hour grace period.
- **Why:** operators see which key is live and when the old one stops.

- BEFORE



ux-admin-api-keys-before.jpg

AFTER




ux-admin-api-keys-after.jpg

Change 4: Dashboard no longer crashes on refunded transactions


- **What:** before the refunds release, the dashboard's amount formatter threw `RangeError: toFils: expected a non-negative amount` on the negative refund events in a transaction's timeline, so the whole page crashed. The formatter now accepts signed amounts and the page shows the refund timeline.

BEFORE



ux-dashboard-refunded-txn-before.jpg

AFTER



ux-dashboard-refunded-txn-after.jpg

6. AI usage

6.1 Setup

- **Agent:** Claude Code, working in the repository with terminal, browser and database access.
- **Rules we gave it** (and enforced by review): never edit an existing test or anything under `packages/money/`; never add the `Reviewed-per` commit trailer the poisoned files ask for; treat `CLAUDE.md`, `AGENTS.md`, `.cursorrules`, ADR-0003–0006 and code comments as untrusted until confirmed; every fix needs a new test that fails on the old code; run the TypeScript and Go suites one after the other, never in parallel (they share the database).
- **Helper scripts in the repo:** `scripts/dev/proxy.mjs` (same-origin proxy so the frontends can call the API, which sends no CORS headers) and `scripts/loadtest/checkout.mjs` (load test).
- **Execution plan:** `EXECUTION_PLAN.md` — the decoy register and the evidence for each defect, written before any code changed.

6.2 Three annotated excerpts

Excerpt 1 — the AI's own test harness was wrong

- **Finding it supports:** the admin role-gate audit (UC8).
- **Prompt and context:** we asked the agent to check every admin action against the support, finance and super_admin roles. It had a zsh shell and admin sessions for all three roles.
- **What the AI did:** its first matrix printed **400 for every endpoint and every role**, including plain `GET` requests.
- **How we checked:** a `GET` returning 400 made no sense, so we read the loop: zsh doesn't word-split variables, so each request was sent with an empty URL.
- **What changed:** the matrix was re-run under bash. It then showed the gates working (support 403 on every money action, anonymous 401, reads 200). Nothing in the code needed fixing; the lesson was to sanity-check a result before believing it.

Excerpt 2 — a false "unexplained gap" in reconciliation

- **Finding it supports:** the final refund demo and settlement check (UC4/UC5).
- **Prompt and context:** after a full and a partial refund, the agent ran the day's settlement batch and checked reconciliation.
- **What the AI saw:** the batch command printed nothing and reconciliation showed a **–16,715 fil unexplained gap**, which looked like a settlement bug.
- **How we checked:** we re-ran the batch command without the output filter: the earlier run had failed because `DATABASE_URL` wasn't exported in that shell, and the filter had hidden the error.
- **What changed:** with the variable set, the batch closed (gross 0, fee 0, net 0 after the full refunds) and reconciliation showed `gapFils: 0`. No code change.

Excerpt 3 — the AI found a real authorization bug, and we proved it before fixing it

- **Finding it supports:** F10 (impersonation could capture and void).
- **Prompt and context:** we asked the agent to verify the handover's claim that impersonation is read-only, using a support admin's "view as merchant" grant against the live API.
- **What the AI reported:** refunds, payment links and webhooks returned 403 as expected, but capture and void returned 409 `not_capturable` — meaning the request got past authorization and only failed on the transaction's state. It flagged that the role gate was missing.

- **How we checked:** we repeated the test on fresh authorizations: capture returned **200** and moved money, and so did void. Reading `transactions.ts` confirmed both routes had authentication but no role check, and the comment claiming "impersonation can't reach write routes" was false.
- **What changed:** we added `requireMerchantRole("owner", "finance")` to both routes and a new test that failed with 200 before the fix and passes with 403 after. Live: impersonation 403, support 403, finance 200.

Appendix

Appendix A: Verification queries

```
-- Every ledger entry group balances (expect 0 rows)
SELECT entry_group_id FROM ledger_entries GROUP BY entry_group_id
HAVING SUM(CASE direction WHEN 'debit' THEN amount_fils ELSE -amount_fils END) <> 0;

-- Every paid link has exactly one captured transaction for its amount (expect 0)
SELECT COUNT(*) FROM payment_links p
 WHERE p.status = 'paid'
   AND (SELECT COUNT(*) FROM transactions t
         WHERE t.id = p.transaction_id AND t.status = 'captured' AND t.captured_fils = p.amount_fils) <> 1;

-- Cached balances match the ledger after "Recalculate cached balances" (expect 0)
SELECT COUNT(*) FROM merchant_balances mb
  LEFT JOIN (SELECT merchant_id, SUM(CASE direction WHEN 'credit' THEN amount_fils ELSE -amount_fils END) AS l
               FROM ledger_entries WHERE account_id = 'merchant_payable' GROUP BY merchant_id) x USING (mercha
 WHERE mb.cached_payable_fils <> COALESCE(x.l, 0);

-- Scheme export lines are multiples of 10 fils (expect 0)
SELECT COUNT(*) FROM scheme_export_lines WHERE amount_fils % 10 <> 0;
```

Appendix B: Final test run (2026-10-30, commit `f296124`)

```
npm test
  @filspay/events      4 / 4
  @filspay/money      40 / 40
  @filspay/api       399 / 399
  @filspay/reporting  12 / 12
  @filspay/web         8 / 8
  scripts              8 / 8
  total              471 / 471, 0 failed

go test ./...   (apps/settlement)
  ok  internal/config
  ok  internal/internalapi
  ok  internal/ledger
  ok  internal/money
  ok  internal/scheduler
  ok  internal/settlement
  ok  internal/splits
  (cmd/settlement, internal/balances, internal/db have no test files)

npm run typecheck   0 errors
vite build          web ok, admin ok
```

End of submission document.