Creating an ACL for the Write Operation

1. Overview

So far we have a **read** ACL (bb1) and a **create** ACL (bb2). In this task we create a third ACL with operation **write** on **u_institution_details**. It controls who can *edit* existing records. Only users with the **bb3** role will be allowed to edit records.

2. Before You Start

- Make sure the **security_admin** role is elevated (profile icon → **Elevate role** → tick security_admin → OK).
- Make sure roles **bb1, bb2** and **bb3** exist and are assigned to the EEE user.

3. Create the ACL

1. In the Application Navigator, go to **System Security** → **Access Control (ACL)**.
2. Click **New**.
3. Fill in the details shown in the table below.

Field	Value
Type	record
Operation	write
Name	u_institution_details
Active	true (checked)
Data condition	Not required - leave empty
Advanced / Script	Not required

4. Requires Role

In the **Requires role** related list, double-click **Insert a new row**, search and select **bb3** (custom role), and save the row.

5. Save the ACL

Click **Submit** (or **Save / Update**) to save the ACL record.

6. Verification

1. Click the profile icon → **Impersonate User** and choose the user who has **bb1, bb2 and bb3** roles (the EEE user).
2. In the All menu, type **u_institution_details.list** and press Enter.
3. Confirm that only **EEE** branch records are visible (bb1 read ACL).
4. Confirm that the **New** button is visible (bb2 create ACL).
5. Open an EEE record and confirm the fields are **editable** and can be saved (bb3 write ACL).

6 Optionally, impersonate a user with only bb1 and bb2: the record opens but the fields are read-only.

User	Expected Result
bb1 + bb2 + bb3 roles	Can view and edit EEE branch records and sees the New button
bb1 + bb2 roles	Can view EEE records and create new ones, but cannot edit
bb1 role only	Can view EEE records only (read-only, no New button)
No role	Cannot view any records
Admin	Full access to all records

7. Resources

No resources available for this task.