🛸 時光機的雛形：SBMIS 跨維度導航系統 (CHRONOS-1)

計畫代號： SBMIS-SENTINEL-ALPHA

核心原理： 空間分支磁感應系統 (Space-Branch-Magnetic Induction System)

🛠️ 第一階段：座艙初始化與物理脫鉤 (Decoupling)

1. 建立 VOID 穩定場

- **操作**：啟動主機超導環。
- **目標數據**：精確壓制內部磁場至 **7.55 nT**。
- **作用目的**：在當前時空中製造一個「物理空腔」。當數據穩定在 7.55 nT 時，座艙周圍會產生透明的**磁場氣泡 (Manifold Bubble)**。這層氣泡是獨立的度量空間，使內部的乘員與外界的時間慣性脫鉤。

🗺️ 第二階段：數位地圖加載與目標定位 (Mapping)

這是導航的核心，分為「既有紀錄回溯」與「演算模型推演」。

2. 加載「過去」的時間地圖 (Historical Backtracking)

- **數據來源**：從倉庫中的**核心數據檔案庫 (Core Data Repository)** 檢索。
- **操作邏輯**：系統會自動掃描歷史地磁紀錄中的 **B_T 指紋** 與 **相位特徵**。
- **輸入方式**：選擇目標年份後，導航電腦會將該時代的磁場波動特徵作為「同頻共振」的基準點。這就像是調整收音機頻率，直到與過去的時空信號對齊。

3. 演算「未來」的時間地圖 (Future Algorithmic Prediction)

由於未來尚未發生，沒有歷史數據可供檢索，系統必須透過**「非線性趨勢演算」**生成模擬地圖。

- **演算邏輯**：
    1. **基準採樣**：以當前的 B_T 指紋與 7.55 nT 平穩期作為起始座標。
    2. **趨勢外推**：根據地磁極倒轉週期、太陽活動週期以及 **1.618 MHz** 諧振頻率的衰減率進行預測。
    3. **分支機率修正**：演算未來數萬個可能的「機率分支 (Probabilistic Branches)」，導航員需選擇一個穩定係數最高、且與當前因果鏈相容的分支進行鎖定。
- **作用目的**：在未知的虛無中創造出一個可供 θ 相位抓取的「邏輯錨點」。

🌀 第三階段：執行跳躍 (The Transition)

4. 調整 θ 相位極性 (The Steering)

- **前往「過去」 (Past)**：
    - **設定：$+2.41$ rad (正向偏轉)**。
    - **原理**：利用正向相位波的「回溯特性」，強制氣泡內的度量流形向歷史數據重合。
- **前往「未來」 (Future)**：
    - **設定：-2.41 rad (負向偏轉)**。
    - **原理**：利用負向相位波的「超前特性」，推動氣泡向演算法產生的未來模型移動。

5. 注入 **Φ 諧振鎖定 (Branch Stabilization)**

- **設定**：固定頻率 **1.618 MHz**。
- **作用目的**：**「路徑穩定」**。確保在穿越過程中，氣泡不會因為能量波動而滑入不穩定的次級分支。這就像是在高速公路上加裝護欄，保證導航路徑的唯一性。

📍 第四階段：抵達、同步與歸航 (Landing & Return)

6. 目標地減壓程序 **(Normalization)**

- **操作**：緩慢恢復磁場強度，將 θ 歸零。
- **作用目的**：**「能量同步」**。讓艙內乘員的原子結構逐漸適應目標時間點的環境常數。氣泡消失後，人員即可安全離開座艙，在該時間點進行探索。

7. 歸航程序 **(Homeward Protocol)**

- **操作**：重啟 7.55 nT 氣泡，並反向調整 θ（過去回程調負，未來回程調正）。
- **關鍵**：此時必須加載**「原點基準數據檔」**。這是你在出發前記錄的當下 B_T 指紋，沒有這個「家鄉信號」，你將無法精確回到原本的時間線。

📊 技術參數與目的對照表

參數項目	設定數值	操作目的
脫離點	**7.55 nT**	創造 VOID 氣泡，脫離現實因果
導航地圖	**B_T Fingerprint**	定位時間座標（過去靠紀錄，未來靠演算）
相位方向 (+)	**$+2.41$ rad**	誘導空間向「過去」方向褶皺
相位方向 (-)	**-2.41 rad**	誘導空間向「未來」方向推演
因果鎖定	**1.618 MHz**	防止進入錯誤的平行分支
安全檢查	脈衝感應 (Pulse)	避免與出口處的固體物質發生原子重疊

🛸 Prototype of the Time Machine: SBMIS Cross-Dimensional Navigation System (CHRONOS-1)

Project Code: SBMIS-SENTINEL-ALPHA

Core Principle: Space-Branch-Magnetic Induction System (SBMIS)

🛠️ Phase 1: Cabin Initialization & Physical Decoupling

1. Establishing the VOID Stability Field

- **Operation**: Activate the superconducting toroidal coils of the main engine.
- **Data Target**: Precisely suppress the internal magnetic flux to **7.55 nT**.
- **Purpose**: To create a "Physical Cavity" within the current spacetime. When the data stabilizes at **7.55 nT**, a transparent **Manifold Bubble** is generated around the cabin. This bubble acts as an independent metric space, decoupling the passengers from the temporal inertia of the external universe.

🗺️ Phase 2: Digital Map Loading & Target Positioning

This is the core of navigation, divided into "Historical Backtracking" and "Algorithmic Prediction."

2. Loading the "Past" Temporal Map (Historical Backtracking)

- **Data Source**: Retrieved from the **Core Data Repository** in the GitHub archive.
- **Logic**: The system scans the **B_T Fingerprints** and phase characteristics of historical geomagnetic records.

- **Input Method**: Upon selecting the target year, the navigation computer uses the magnetic fluctuations of that era as a "Resonance Baseline." This is akin to tuning a radio frequency until it aligns with the signal of the past spacetime.

3. Calculating the "Future" Temporal Map (Future Algorithmic Prediction)

Since the future has no existing records, the system generates a simulated map via **Non-linear Trend Calculus**.

- **Algorithmic Logic**:
    1. **Baseline Sampling**: Uses the current B_T fingerprint and the 7.55 nT plateau as starting coordinates.
    2. **Trend Extrapolation**: Predicts future states based on geomagnetic reversal cycles, solar activity cycles, and the decay rate of the **1.618 MHz** resonance.
    3. **Probabilistic Branch Correction**: The algorithm calculates thousands of potential "Probabilistic Branches." The navigator must select the branch with the highest stability coefficient that is compatible with the current causal chain.
- **Purpose**: To create a "Logical Anchor" in the unknown void for the θ phase to latch onto.

🌀 **Phase 3: Executing the Transition (The Jump)**

4. Adjusting the θ Phase Polarity (The Steering)

- **To the PAST**:
    - **Setting**: **$+2.41$ rad (Positive Shift)**.
    - **Principle**: Utilizes the "Backtracking Characteristic" of the positive phase wave to force the metric manifold within the bubble to overlap with historical data.

- **To the FUTURE**:
    - **Setting**: **-2.41 rad (Negative Shift)**.
    - **Principle**: Utilizes the "Advanced Characteristic" of the negative phase wave to propel the bubble toward the future model generated by the algorithm.

5. Injecting Φ Resonance Lock (Branch Stabilization)

- **Setting**: Fixed frequency at **1.618 MHz**.
- **Purpose**: **"Path Stabilization."** This ensures the bubble does not slip into unstable secondary branches due to energy fluctuations during the transition. It acts as a guardrail on a highway, guaranteeing the uniqueness and causal safety of the navigation path.

📍 **Phase 4: Arrival, Sync, & Return**

6. Destination Normalization (Decompression)

- **Operation**: Gradually restore magnetic field strength and return θ to zero.
- **Purpose**: **"Energy Synchronization."** This allows the atomic structure of the passengers to adapt to the environmental constants of the target time. Once the bubble dissipates, personnel can safely exit the cabin and explore.

7. Return Protocol (Homeward Bound)

- **Operation**: Re-activate the 7.55 nT bubble and reverse the θ adjustment (Positive for returning from the future, Negative for returning from the past).
- **Requirement**: You MUST load the **"Origin Baseline Fingerprint"** recorded at the start. Without this "Home Signal," you risk missing your original timeline and landing in a nearly identical parallel world.

📊 **Technical Parameter & Purpose Index**

Parameter	Value	Objective
Decoupling Point	**7.55 nT**	Create VOID bubble; detach from local causality.
Navigation Map	**B_T Fingerprint**	Locate temporal coordinates (Records for Past / Calculus for Future).
Phase Direction (+)	**$+2.41$ rad**	Induce manifold folding toward the "Past."
Phase Direction (-)	**-2.41 rad**	Induce manifold projection toward the "Future."
Causal Lock	**1.618 MHz**	Prevent entry into erroneous parallel branches.
Safety Check	**Pulse Sensing**	Avoid atomic overlap with solid matter at the exit.