

ATLS 4320: Advanced Mobile Application Development

Week 1: Advanced Swift

Swift 4.2

Swift 4.2 focuses on developer productivity, faster build times, improving run time performance, safety and security, and reducing the need for some boilerplate code. And Swift 4.2 is compatible with 4.1 with a migrator tool to help move projects over to 4.2.

New and advanced Swift

Go into Xcode (swift4)

File | New | Playground

iOS Blank

Name: swift4

Save

Multi-line string literals can be useful. As of Swift 4.1 they have a simple syntax using 3 quotes. The indentation of the closing delimiter determines how much whitespace is stripped from the start of each line.

```
let galaxy = " "
let introString = """
A long time ago in a \(galaxy) far,
far away....
It is a period of civil war.
Rebel spaceships, striking
from a hidden base, have won
their first victory against
the evil Galactic Empire.
```

```
During the battle, Rebel
spies managed to steal secret
plans to the Empire's
ultimate weapon, the DEATH
STAR, an armored space
station with enough power to
destroy an entire planet.
```

```
Pursued by the Empire's
sinister agents, Princess
Leia races home aboard her
starship, custodian of the
stolen plans that can save
her people and restore
freedom to the \(galaxy).....
"""
print(introString)
```

Swift 4.2 adds the toggle() function to Bool, making it really easy to toggle a Boolean.

```
//toggle Boolean
```

```
var response = true
response.toggle()
print(response)
```

Optionals

Let's review one of the unique aspects of Swift -- optionals (end of "The Basics" section). In Swift a variable/constant can only have the value of nil if it's defined as an optional.

- Defining a variable as an optional says it might have a value or it might not
- If it does not have a value it has the value nil
 - Nil is the absence of a value
- Optionals of any type can have the value nil
- A '?' after the type indicates it's an optional
- If you define an optional variable without providing a default value, the variable is automatically set to nil for you

```
var score : Int?
print("Score is \(score)")
(this gives a warning)
score=80
print("score is \(score!)" )
```

If a variable/constant is defined as an optional, you must take that into consideration when you access it. To access the value of an optional you must add an '!'. This is called **forced unwrapping**.

If you force unwrap an optional that is nil your program will crash so you should use an if statement to find out if an optional has a value before unwrapping it.

```
if score != nil {
    print("The score is \(score!)")
    print("The score is ", score!)
}
```

This is so common in Swift that there's a shorthand for it called **optional binding**. You can conditionally unwrap an optional and if it contains a value, assigns it to a variable or constant which has a local scope(only available where it's defined such as in this if statement)

```
if let currentScore = score {
    print("My current score is \(currentScore)")
}
```

The coalescing operator operator (??) unwraps its left operand, if it's not nil, returns its value; otherwise, it returns its second operand.

```
score = nil
let myScore = score ?? 0
print("My score is \(myScore)")
```

Sometimes it's clear that an optional will always have a value, after the first value is set

We can unwrap these optionals without the need to check it each time

These are called **implicitly unwrapped** optionals

```
let newScore : Int! = 95
print("My new score is ", newScore)
```

- Since newScore is given an initial value, and it's a constant, we now it will always have that value and never be nil
- Rather than placing an exclamation mark after the optional's name each time you use it, you place an exclamation mark after the optional's type when you declare it.
- '!' after the type indicates it's an implicitly unwrapped optional
- No "!" is needed to access the optional because it's an implicitly unwrapped optional
- You see this when you make outlet connections from Interface Builder. It's an optional but because you know it exists in the view it is implicitly unwrapped and we know it will never become nil
 - @IBOutlet weak var name: UILabel!

Implicitly unwrapped optionals should not be used when there is a possibility of a variable becoming nil at a later point.

Type Casting

Type casting is a way to check the type of an instance and treat that instance as a different type in its class hierarchy.

Define a base class and 2 subclasses

```
class Pet {
    var name: String
    init(name: String){
        self.name = name
    }
}

class Dog : Pet {
    var breed: String
    init(name: String, breed: String) {
        self.breed=breed
        super.init(name: name)
    }
}

class Fish : Pet {
    var species: String
    init(name: String, species: String) {
        self.species=species
        super.init(name: name)
    }
}
```

Create an array with two Dog instances and 1 Fish instance

```
let myPets=[Dog(name: "Cole", breed: "Black Lab"), Dog(name: "Nikki", breed: "German Shepherd"), Fish(name: "Nemo", species: "Clown Fish")]
```

(option click on myPets to see its type)

The items stored in `myPets` are still `Dog` and `Fish` instances behind the scenes. However, if you iterate over the contents of this array, the items you receive back are typed as `Pet`, and not as `Dog` or `Fish`. To print the number of each type of pet we need to figure out if each item is a `Dog` or `Fish` and not just as a `Pet`. The “`is`” type check operator lets you test whether an instance is of a certain class type

- Returns **true** if it's of that type
- Returns **false** if it's NOT of that type

```
var dogCount = 0
var fishCount = 0

for pet in myPets {
    if pet is Dog {
        dogCount += 1
    }
    else if pet is Fish {
        fishCount += 1
    }
}

print("I have \(dogCount) dogs and \(fishCount) fish")
```

In order to work with them as their native type, you need to check their type, and then downcast them. When you believe an instance refers to the subclass type use the “`as`” type cast operator to try to downcast to the subclass type

- Use the conditional form “`as?`” when you're not sure if the downcast will succeed
 - Returns an optional
 - Returns `nil` if the downcast wasn't possible
- Use the forced form “`as!`” when you are sure the downcast will always succeed
 - Attempts the downcast and force-unwraps the result
 - You will get a runtime error if you try to downcast to an incorrect class type

Casting treats the instance being cast as an instance of the type to which it has been cast

You can only cast an instance as a different superclass or subclass from somewhere else in its own class hierarchy.

Casting does not actually modify the instance or change its value

```
for pet in myPets {
    if let dog = pet as? Dog {
        print("\(dog.name) is a \(dog.breed)")
    } else if let fish = pet as? Fish {
        print("\(fish.name) is a \(fish.species)")
    }
}
```

We use the conditional form of the type cast operator (`as?`) to check the downcast each time through the loop.

`AnyObject` can represent an instance of any class type

- Objective-C does not have typed arrays so the SDK APIs often return an array of `[AnyObject]`
- If you know the type of objects in the array you can use the force form to downcast to that class type

Any can represent an instance of any type at all, including function types and non-class types.

Closures

Closures are blocks of code that can be passed around and used in your code.

- Closures in Swift are similar to blocks in C and Objective-C and anonymous functions in JavaScript

Functions are really just closures with a name

Swift's standard library provides a method called `sorted(by:)`, which sorts an array of values of a known type, based on the output of a sorting closure that you provide. Once it completes the sorting process, the `sorted(by:)` method returns a new array of the same type and size as the old one, with its elements in the correct sorted order. The original array is not modified by the `sorted(by:)` method.

```
let names=["Tom", "Jessie", "Megan", "Angie"]
```

The `sorted(by:)` method accepts a closure that takes two arguments of the same type as the array's contents, and returns a `Bool` value to say whether the first value should appear before or after the second value once the values are sorted. The sorting closure needs to return `true` if the first value should appear *before* the second value, and `false` otherwise.

This example is sorting an array of `String` values, and so the sorting closure needs to be a function of type `(String, String) -> Bool`.

You could write a normal function and pass it to the `sorted(by:)` method.

```
func backwards(s1: String, s2: String) -> Bool {  
    return s1 > s2  
}
```

```
var reversed = names.sorted(by:backwards)
```

Or you can use a closure. This is the same syntax as in the function but it's passed as a closure in `{}`. The start of the closure's body is introduced by the 'in' keyword. This keyword indicates that the definition of the closure's parameters and return type has finished, and the body of the closure is about to begin.

```
reversed = names.sorted(by: {(s1:String, s2: String)->Bool in return s1 >  
s2})  
print(reversed)
```

Because the sorting closure is passed as an argument to a method, Swift can infer the types of its parameters and the type of the value it returns.

Because all of the types can be inferred, the return arrow (`->`) and the parentheses around the names of the parameters can also be omitted:

```
reversed = names.sorted(by: {s1, s2 in return s1 > s2})  
print(reversed)
```

Because the closure's body contains a single expression (`s1 > s2`) that returns a `Bool` value, there is no ambiguity, and the return keyword can be omitted.

```
reversed = names.sorted(by: { s1, s2 in s1 > s2 } )
print(reversed)
```

Swift automatically provides shorthand argument names to inline closures, which can be used to refer to the values of the closure's arguments by the names \$0, \$1, \$2, and so on.

If you use these shorthand argument names within your closure expression, you can omit the closure's argument list from its definition, and the number and type of the shorthand argument names will be inferred from the expected function type. The `in` keyword can also be omitted, because the closure expression is made up entirely of its body:

\$0 and \$1 refer to the closure's first and second String arguments.

```
reversed = names.sorted(by: { $0 > $1 } )
print(reversed)
```

Enumerations

An enumeration defines a type for a group of related values that are fixed and known in advance.

```
enum carType {
    case gas
    case electric
    case hybrid
}

var car = carType.electric
print(car)
```

The type of `car` is inferred when it's initialized with a value of `carType`. When the context is clear, you can omit the enumeration name and use the shortened dot notation.

```
car = .hybrid
print(car)
```

Error Handling

Error handling is the process of responding to and recovering from error conditions in your program. Enums are often used to represent error conditions.

```
enum WebError: Error{
    case Forbidden
    case NotFound
    case RequestTimeout
}
```

There are four ways to handle errors in Swift.

1. Propagate the error from a function to the code that calls that function

A `throw` statement returns an error and immediately transfers program control back to where the function was called. To indicate that a function can throw an error, you write the `throws` keyword in the function's declaration after its parameters. A function marked with `throws` is called a throwing function. Only throwing functions can propagate errors. (added in Swift 2)

```
func webPage(status: Int) throws -> String{
```

```

switch status{
    case 403: throw WebError.Forbidden
    case 404: throw WebError.NotFound
    case 408: throw WebError.RequestTimeout
    default: return "OK"
}
}

```

2. Handle the error as an optional value

Use the try keyword when calling a function that throws an error

You use try? to handle an error by converting it to an optional value. If an error is thrown while evaluating the try? expression, the value of the expression is nil.

```

var status = try? webPage(status: 400)
status = try? webPage(status: 404)

```

If you call a throwing function without “try” you will get an error.

```

var status2 = webPage(status: 400)

```

3. Handle the error using a do-catch statement

Use a do-catch statement to handle errors. If an error is thrown in the do clause, it is sent to the catch clause.

```

do {
    try webPage(status: 404)
} catch WebError.Forbidden {
    print("Forbidden")
} catch WebError.NotFound {
    print("File not found")
} catch WebError.RequestTimeout {
    print("Request time-out")
}

```

4. Assert that the error will not occur.

Sometimes you know a throwing function or method won’t throw an error at runtime. In that case you can write try! before the expression to disable error propagation and wrap the call in a runtime assertion that no error will be thrown. If an error actually is thrown, you’ll get a runtime error.

Early Exit

In Swift 2 a new guard statement was introduced to avoid nested if statements (pyramids of doom)

A guard statement, like an if statement, executes statements depending on the Boolean value of an expression. (end of Control Flow section)

In a guard statement the condition must be true in order for the code after the guard statement to be executed. If it’s false the code inside the else clause is executed.

- Lets you handle false conditions early, keeping the code that handles a violated condition next to the test condition
- Always has an else clause that MUST transfer control out of the code block. You can transfer control with an early exit
 - Continue: used in loops to skip that iteration and go to the next iteration of the loop
 - Break: used in loops or switch statements to exit completely out of the loop or switch and go on to the rest of the function

- Return: exits out of the current scope. In functions this will return control to where the function was called
- Throw: used to throw (return) an error
- The code that is typically run is kept in the main flow and not wrapped in an else block
- Code is more readable and easier to maintain
- Any variables or unwrapped optional in the guard remain in scope after the guard finishes, so you can use them.

```
guard boolean
  else {
    false
    transfer control
  }
true
main body continues
```

```
enum MathError:Error{
  case DivideByZero
}

func divide(number1: Double, number2:Double) throws -> Double{
  guard number2>0 else{
    throw MathError.DivideByZero
  }
  return number1/number2
}

var answer = try? divide(number1: 10, number2: 5)
```

Better to wrap the try in a do/catch statement to catch the error.

```
do {
  try divide(number1: 10, number2: 0)
} catch MathError.DivideByZero {
  print("You can't divide by zero")
}
```