REV	Description	DATE	ВХ
A3	Production release.	10/21/2011 GC	29
A3A	Updated in conjunction with the release of the SRM. Typos and naming changes. No change in design.	11/5/2011	29
\$	Changed supplier for the SD card connector due to availability issue. Created a dual footprint for two differrent parts. SD connector is now reversed, so label down is the new orientation. Changed R76 from a 50 ohm to 49.9 ohm. Smaller package and lower cost. Changed footprint to 40.0. Changed C99 termination to DGND. Added 10K pulldown to fix link speed LED. Changed C7 to a 0805 package in PCB layout.	12/1/2011	၁၅

This schematic is *NOT SUPPORTED* and DOES NOT constitute a reference design. Only "community" support is allowed via resources at BeagleBoard.org/discuss.

THERE IS NO WARRANTY FOR THIS DESIGN, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE DESIGN "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE DESIGN IS WITH YOU. SHOULD THE DESIGN PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

PAGE NO.	SCHEMATIC PAGE
1	COVER PAGE
2	POWER MANAGEMENT
3	PROCESSOR 1 OF 3
4	PROCESSOR 2 OF 3
5	PROCESSOR 3 OF 3
9	LED, CONFIGURATION AND BUTTON
7	MEMORY
8	ETHERNET AND USB HOST
6	USB CONCENTRATOR
10	SERIAL AND JTAG
11	EXP CONN, uSD, AND LDO

NOTE: PCB Revision for this board is Rev C1.





















