

# LogStage: Zero-cost Structural Logging for Scala

Septimal Mind Ltd

*team@7mind.io*

July 24, 2018

# What's wrong with logging frameworks?

- ▶ Do we need structured logs? Yes, obviously,
- ▶ Logging frameworks are convenient for a programmer *xor* for a machine, not for both,
- ▶ Logging frameworks love to break SOLID,
- ▶ Magic rituals required!

## fluentd logging API example

```
1  object Example {  
2    // We love rituals! Is it SOLID, hmm?..  
3    val LOG = FluentLoggerFactory  
4      .getLogger("fluentd.test")  
5  
6    // ...  
7  
8    val data =  
9      new HashMap[String, String] ()  
10     data.put("from", "userA")  
11     data.put("to", "userB")  
12     LOG.log("follow", data)  
13  }
```

## scala-logging API example

```
1  class Example
2    extends LazyLogging { // Let's break SOLID!
3    //...
4
5    // Renders as "Received message from JohnDoe"
6    // Structure lost
7    logger.trace(s"Received message from $user")
8  }
```

## The code...

```
1 | val user = "JohnDoe"  
2 | logger.debug(s"Received a message from $user")
```

... is structured

```
1 Expr(Apply(Select(  
2   Apply(  
3     Select(Select(Ident("scala"), scala.StringContext),  
4       TermName("apply"))  
5     , List(Literal(Constant("Received a message from "))  
6       , Literal(Constant(""))  
7     )  
8   ),  
9   TermName("s")  
10  )  
11 , List(Ident(TermName("user"))))  
12 ))
```

## The code is always structured

- ▶ We have argument names, types and order defined in code,
- ▶ As well we have some static information about the context – file, line, etc,
- ▶ We have static part of our message – interpolation context or *message template*,
- ▶ We may process our string interpolations with a macro, recover structure and pass it to a logger.

# LOGSTAGE

---

First-class logging framework for Scala



## Quick overview

- ▶ Almost no dependencies,
- ▶ Compile-time structure and context extraction,
- ▶ Console and file sinks out of the box, log rotation supported,
- ▶ Asynchronous sink out of the box (single worker thread at the moment),
- ▶ String and JSON rendering out of the box,
- ▶ Automatic structure identifiers for JSON policy,
- ▶ Modular – you may implement your own sink, router, etc,
- ▶ DI-ready, no singletons or classpath scanners,
- ▶ **Method**-level granularity,
- ▶ User-provided logging contexts,
- ▶ Slf4J backend – LogStage is a drop-in replacement for Logback, route your legacy logs,
- ▶ Location hyperlinks for IntelliJ console.

## An example

```
1  class ExampleService(log: IzLogger) {
2      val justAnArg = "example"
3      val justAList = List[Any](10, "green", "bottles")
4
5      log.trace(s"Argument: $justAnArg, another arg: $justAList")
6      log.info(s"Expr: ${Random.nextInt() -> "number"}")
7      log.warn(s"Hidden: ${Random.nextInt() -> "number" -> null}")
8
9      val ctxLogger = logger(
10         "userId" -> "user@google.com"
11         , "company" -> "acme"
12     )
13     val msec = Random.nextInt(1000)
14
15     ctxLogger.info(s"Processing time: $msec")
16 }
```

# Followed by a cute screenshot of course

```
T 2018-07-23T23:07:14.946+01:00[Europe/Dublin] ...leSinkTest:1 (LoggingAsyncSinkTest.scala:20) Argument: ↗  
└ justAnArg=example, another arg: justAList=List(10, green, bottles)  
I 2018-07-23T23:07:15.056+01:00[Europe/Dublin] ...leSinkTest:1 (LoggingAsyncSinkTest.scala:21) Expr: number=1601070974  
W 2018-07-23T23:07:15.062+01:00[Europe/Dublin] ...leSinkTest:1 (LoggingAsyncSinkTest.scala:22) Hidden: -539747744
```

## Something nice for our robots

```
{  
  "just_a_list": [10, "green", "bottles"],  
  "just_an_arg": "example",  
  "@event": {  
    "class": "f48ebb70",  
    "logger": "...logstage.api.routing.ExampleService.start",  
    "file": "LoggingAsyncSinkTest.scala", "line": 20,  
    "thread": { "id": 1, "name": "ScalaTest-run-running-LoggingJson4sTest" },  
    "level": "trace",  
    "timestamp": 1532384023837,  
    "datetime": "2018-07-23T22:13:43.837Z[UTC]"  
  },  
  "@template":  
    "Argument: ${just_an_arg}, another arg: ${just_a_list}",  
  "@message":  
    "Argument: justAnArg=example, another arg: justAList=List(10, green, bottles)"  
}
```

# Status and things to do

LogStage is.

- ▶ ready to use,
- ▶ in real production for 4 months.

Our plans:

- ▶ Declarative router config,
- ▶ Start using log events to collect metrics (keep in mind, we have derived structure identifiers),
- ▶ Cleanups and refactorings.

## Thank you for attention

<https://izumi.7mind.io/logstage/>

We're looking for clients, contributors, adopters and colleagues ;)

About the author:

- ▶ coding for 18 years, 10 years of hands-on commercial engineering experience,
- ▶ has been leading a cluster orchestration team in Yandex, “the Russian Google”,
- ▶ implemented “*Interstellar Spaceship*” – an orchestration solution to manage 50K+ physical machines across 6 datacenters,
- ▶ Owns an Irish R&D company, <https://7mind.io>,
- ▶ Contacts: [team@7mind.io](mailto:team@7mind.io),
- ▶ Github: <https://github.com/pshirshov>