```
v8::internal::anonymous
_namespace{traced-handles.cc}
::ParallelWeakHandlesProcessor
        < Derived >
```

- heap_
- young_blocks_
- num_young_blocks_
- trace_id_
- processed_young_blocks_

+ ParallelWeakHandlesProcessor()
+ Run()
+ heap()
+ trace_id()

< ComputeWeaknessProcessor >   < ClearWeaknessProcessor >

```
v8::internal::anonymous
_namespace{traced-handles.cc}
::ParallelWeakHandlesProcessor
 < ComputeWeaknessProcessor >
```

- heap_
- young_blocks_
- num_young_blocks_
- trace_id_
- processed_young_blocks_

+ ParallelWeakHandlesProcessor()
+ Run()
+ heap()
+ trace_id()

```
v8::internal::anonymous
_namespace{traced-handles.cc}
::ParallelWeakHandlesProcessor
   < ClearWeaknessProcessor >
```

- heap_
- young_blocks_
- num_young_blocks_
- trace_id_
- processed_young_blocks_

+ ParallelWeakHandlesProcessor()
+ Run()
+ heap()
+ trace_id()

```
v8::internal::anonymous
_namespace{traced-handles.cc}
  ::ComputeWeaknessProcessor
```

+ kMainThreadScope
+ kBackgroundThreadScope
+ kStartNote

+ ComputeWeaknessProcessor()
+ ProcessBlock()

```
v8::internal::anonymous
_namespace{traced-handles.cc}
    ::ClearWeaknessProcessor
```

+ kMainThreadScope
+ kBackgroundThreadScope
+ kStartNote
- visitor_
- handler_
- should_reset_handle_

+ ClearWeaknessProcessor()
+ ProcessBlock()