## v8::internal::CodeEventObserver + CodeEventHandler() + ~CodeEventObserver() v8::internal::ProfilerEvents Processor v8::internal::ProfilerCode # symbolizer Observer # code observer # profiles # running # running cond # running mutex - weak code registry # events buffer # ticks from vm buffer # last\_code\_event\_id + ProfilerCodeObserver() # last\_processed\_code + CodeEventHandler() \_event\_id\_ + code entries() # isolate\_ + instruction stream + ~ProfilerEventsProcessor() + weak\_code\_registry() + CodeEventHandler() + GetEstimatedMemoryUsage() + Run() + ClearCodeMap() + StopSynchronously() CodeEventHandlerInternal() + running() - CreateEntriesForRuntimeCall + Enqueue() + AddCurrentStack() + AddDeoptStack() + AddSample() set\_processor() + SetSamplingInterval() - clear processor() # ProfilerEventsProcessor() # ProcessCodeEvent() # ProcessOneSample() v8::internal::SamplingEvents Processor - ticks buffer - sampler - period - use precise sampling - kTickSampleBufferSize - kTickSampleQueueLength + SamplingEventsProcessor() + ~SamplingEventsProcessor() + operator new() + operator delete() + Run() + SetSamplingInterval() + StartTickSample()

+ FinishTickSample()

- ProcessOneSample()

SymbolizeAndAddToProfiles()

+ sampler() + period()

- isolate

- code entries

- code map

processor

map()

Stats()

- LogBuiltins()

processor()