## v8::internal::CallInterface Descriptor - data + CallInterfaceDescriptor() + ~CallInterfaceDescriptor() + CallInterfaceDescriptor() + flags() + tag() + sandboxing\_mode() + HasContextParameter() + AllowVarArgs() + CalleeSaveRegisters() + GetReturnCount() and 13 more.. + ContextRegister() # data() # CheckFloatingPointParameters() # IsValidFloatParameterRegister() # DefaultRegisterArray() # DefaultDoubleRegisterArray() # DefaultReturnRegisterArray() # DefaultReturnDoubleRegister Array() # DefaultJSRegisterArray() v8::internal::StaticCall InterfaceDescriptor < Derived Descriptor > + kReturnCount + kParameterCount + kNoContext + kAllowVarArgs + kNoStackScan + kStackArgumentOrder + kMaxRegisterParams + kRestrictAllocatableRegisters + kCalleeSaveRegisters

+ kCustomMachineTypes + StaticCallInterfaceDescriptor() + registers() + double\_registers()

+ return\_registers()

+ return double registers() + flags()

+ AllowVarArgs()

+ HasContextParameter()

+ GetReturnCount()

+ GetParameterCount()

+ GetRegisterParameterCount() and 6 more...

Initialize()

InitializeTypes()

< ConstructForwardAllArgs WithFeedbackDescriptor >

v8::internal::StaticCall InterfaceDescriptor < Construct ForwardAllArgs WithFeedbackDescriptor >

- + kReturnCount
- + kParameterCount
- + kNoContext
- + kAllowVarArgs
- + kNoStackScan
- + kStackArgumentOrder
- + kMaxRegisterParams
- + kRestrictAllocatableRegisters
- + kCalleeSaveRegisters
- + kCustomMachineTypes
- + StaticCallInterfaceDescriptor()
- + registers()
- + double\_registers()
- + return\_registers()
- + return\_double\_registers()
- + flags()
- + AllowVarArgs()
- + HasContextParameter()
- + GetReturnCount()
- + GetParameterCount()
- + GetRegisterParameterCount()
- and 6 more... - Initialize()
- InitializeTypes()

v8::internal::ConstructForward AllArgs WithFeedbackDescriptor