```
- data
          + CallInterfaceDescriptor()
          + ~CallInterfaceDescriptor()
           + CallInterfaceDescriptor()
           + flags()
           + tag()
           + sandboxing_mode()
           + HasContextParameter()
          + AllowVarArgs()
           + CalleeSaveRegisters()
           + GetReturnCount()
          and 13 more...
           + ContextRegister()
          # data()
          # CheckFloatingPointParameters()
          # IsValidFloatParameterRegister()
          # DefaultRegisterArray()
          # DefaultDoubleRegisterArray()
          # DefaultReturnRegisterArray()
          # DefaultReturnDoubleRegister
          # DefaultJSRegisterArray()
v8::internal::StaticCall
InterfaceDescriptor< Derived
         Descriptor >
+ kReturnCount
+ kParameterCount
+ kNoContext
+ kAllowVarArgs
+ kNoStackScan
+ kStackArgumentOrder
+ kMaxRegisterParams
+ kRestrictAllocatableRegisters
+ kCalleeSaveRegisters
+ kCustomMachineTypes
+ StaticCallInterfaceDescriptor()
+ registers()
+ double_registers()
+ return_registers()
+ return_double_registers()
+ flags()
+ AllowVarArgs()
+ HasContextParameter()
+ GetReturnCount()
+ GetParameterCount()
+ GetRegisterParameterCount()
and 6 more...
Initialize()
- InitializeTypes()
                      < Descriptor >
                     v8::internal::StaticCall
                     InterfaceDescriptor < Descriptor >
                      + kReturnCount
                      + kParameterCount
                      + kNoContext
                      + kAllowVarArgs
                      + kNoStackScan
                      + kStackArgumentOrder
                      + kMaxRegisterParams
                      + kRestrictAllocatableRegisters
                      + kCalleeSaveRegisters
                      + kCustomMachineTypes
                     + StaticCallInterfaceDescriptor()
                      + registers()
                      + double_registers()
                      + return_registers()
                      + return_double_registers()
                      + flags()
                      + AllowVarArgs()
                      + HasContextParameter()
                      + GetReturnCount()
                      + GetParameterCount()
                      + GetRegisterParameterCount()
                     and 6 more...
                      Initialize()
                      InitializeTypes()
                     v8::internal::StaticJSCall
                     InterfaceDescriptor < Descriptor >
                      + kStackArgumentOrder
                      + registers()
                              < Construct_BaselineDescriptor >
  v8::internal::StaticJSCall
  InterfaceDescriptor < Construct
       _BaselineDescriptor >
  + kStackArgumentOrder
  + registers()
                 Д
      v8::internal::Construct
        BaselineDescriptor
```

v8::internal::CallInterface

Descriptor