iterator - isolate - state - return_address_location _resolver klsolateTag + StackFrame() + is_entry() + is_construct_entry() + is_exit() + is_optimized_js() + is unoptimized js() + is_interpreted() + is baseline() + is_maglev() + is_turbofan_js() and 40 more... + TypeToMarker() + MarkerToType() + IsTypeMarker() + IsJavaScript() + unauthenticated_pc() + maybe_unauthenticated_pc() + SetReturnAddressLocation Resolver() + ReadPC() + ResolveReturnAddressLocation() # StackFrame() # GetCallerStackPointer() - ComputeCallerState() - GetCallerState() v8::internal::CommonFrame + context() + position() + GetExpression() + SetExpression() + ComputeExpressionsCount() + GetCallerStackPointer() + Summarize() + cast() # CommonFrame() # HasTaggedOutgoingParams() # ComputeCallerState() # caller_fp() # caller_pc() # IterateExpressions() # IterateTurbofanJSOptimized Frame() # GetExpressionAddress() v8::internal::TypedFrame + unchecked_code() + Iterate() + IterateParamsOfGenericWasm ToJSWrapper() # TypedFrame() v8::internal::ExitFrame + type() + Iterate() + cast() + GetStateForFramePointer() + ComputeStackPointer() + ComputeFrameType() + FillState() # ExitFrame() ComputeCallerState() v8::internal::ApiCallback ExitFrame + type() + GetFunction() + GetFunctionTemplateInfo() + receiver() + GetParameter() + ComputeParametersCount() + GetParameters() + context()

+ IsConstructor()

ApiCallbackExitFrame()

+ Summarize()

+ Print()

+ cast()

target()

set_target()target_slot()

v8::internal::ApiAccessor ExitFrame

ApiAccessorExitFrame()

- property_name_slot()

+ property_name()

+ type()

+ receiver()

+ Summarize()

- receiver_slot()

- holder slot()

+ holder()

+ Print()

+ cast()

v8::internal::BuiltinExit

+ type()

+ Print()

+ function()

+ receiver()

+ GetParameter()

+ GetParameters()

BuiltinExitFrame()

argc slot object()

target_slot_object()new_target_slot_object()

- receiver_slot_object()

+ IsConstructor()

+ Summarize()

Frame

+ ComputeParametersCount()

v8::internal::StackFrame