```
v8::internal::CallInterface
            Descriptor
- data
+ CallInterfaceDescriptor()
+ ~CallInterfaceDescriptor()
+ CallInterfaceDescriptor()
+ flags()
+ tag()
+ sandboxing_mode()
+ HasContextParameter()
+ AllowVarArgs()
+ CalleeSaveRegisters()
+ GetReturnCount()
and 13 more..
+ ContextRegister()
# data()
# CheckFloatingPointParameters()
# IsValidFloatParameterRegister()
# DefaultRegisterArray()
# DefaultDoubleRegisterArray()
# DefaultReturnRegisterArray()
# DefaultReturnDoubleRegister
# DefaultJSRegisterArray()
                      v8::internal::StaticCall
                      InterfaceDescriptor < Derived
                                Descriptor >
                      + kReturnCount
                      + kParameterCount
                      + kNoContext
                      + kAllowVarArgs
                      + kNoStackScan
                      + kStackArgumentOrder
                      + kMaxRegisterParams
                      + kRestrictAllocatableRegisters
                      + kCalleeSaveRegisters
                      + kCustomMachineTypes
                      + StaticCallInterfaceDescriptor()
                      + registers()
                      + double_registers()
                      + return registers()
                      + return double registers()
                      + flags()
                      + AllowVarArgs()
                      + HasContextParameter()
                      + GetReturnCount()
                      + GetParameterCount()
                      + GetRegisterParameterCount()
                      and 6 more...
                      Initialize()
                      InitializeTypes()
                             < TypeConversionDescriptor >
v8::internal::StaticCall
InterfaceDescriptor < TypeConversion
            Descriptor >
+ kReturnCount
+ kParameterCount
+ kNoContext
+ kAllowVarArgs
+ kNoStackScan
+ kStackArgumentOrder
+ kMaxRegisterParams
+ kRestrictAllocatableRegisters
+ kCalleeSaveRegisters
+ kCustomMachineTypes
+ StaticCallInterfaceDescriptor()
+ registers()
+ double_registers()
+ return_registers()
+ return_double_registers()
+ flags()
```

v8::internal::TypeConversion Descriptor + ArgumentRegister() + registers()

+ AllowVarArgs()

and 6 more...
- Initialize()

+ HasContextParameter()+ GetReturnCount()+ GetParameterCount()

+ GetRegisterParameterCount()