```
Descriptor
- data
+ CallInterfaceDescriptor()
+ ~CallInterfaceDescriptor()
+ CallInterfaceDescriptor()
+ flags()
+ tag()
+ sandboxing_mode()
+ HasContextParameter()
+ AllowVarArgs()
+ CalleeSaveRegisters()
+ GetReturnCount()
and 13 more..
+ ContextRegister()
# data()
# CheckFloatingPointParameters()
# IsValidFloatParameterRegister()
# DefaultRegisterArray()
# DefaultDoubleRegisterArray()
# DefaultReturnRegisterArray()
# DefaultReturnDoubleRegister
Array()
# DefaultJSRegisterArray()
                      v8::internal::StaticCall
                      InterfaceDescriptor < Derived
                               Descriptor >
                      + kReturnCount
                      + kParameterCount
                      + kNoContext
                      + kAllowVarArgs
                      + kNoStackScan
                      + kStackArgumentOrder
                      + kMaxRegisterParams
                      + kRestrictAllocatableRegisters
                      + kCalleeSaveRegisters
                      + kCustomMachineTypes
                      + StaticCallInterfaceDescriptor()
                      + registers()
                      + double_registers()
                      + return registers()
                      + return double registers()
                      + flags()
                      + AllowVarArgs()
                      + HasContextParameter()
                      + GetReturnCount()
                      + GetParameterCount()
                      + GetRegisterParameterCount()
                      and 6 more...
                      Initialize()
                      InitializeTypes()
                            < ApiGetterDescriptor >
 v8::internal::StaticCall
 InterfaceDescriptor< ApiGetter
           Descriptor >
 + kReturnCount
 + kParameterCount
 + kNoContext
 + kAllowVarArgs
 + kNoStackScan
 + kStackArgumentOrder
 + kMaxRegisterParams
 + kRestrictAllocatableRegisters
```

v8::internal::CallInterface

- + kCalleeSaveRegisters
- + kCustomMachineTypes
- + StaticCallInterfaceDescriptor()
- + registers()
- + double\_registers()
- + return\_registers()
- + return\_double\_registers()
- + flags() + AllowVarArgs()
- + HasContextParameter()
- + GetReturnCount() + GetParameterCount()
- + GetRegisterParameterCount() and 6 more...
- Initialize()
- InitializeTypes()

## v8::internal::ApiGetterDescriptor

- + DEFINE\_PARAMETER\_TYPES()
- + HolderRegister()
- + CallbackRegister()
- + registers()