

Standardizing-Marine-Biological-Data

Standardizing Marine Biological Data Working Group

2021-11-05

Contents

| | |
|---|-----------|
| Preface | 5 |
| 1 Introduction | 7 |
| 1.1 Data Structures | 7 |
| 1.2 Ontologies | 7 |
| 1.3 Controlled Vocabularies | 8 |
| 1.4 Technologies | 10 |
| 1.5 Notes on Integrating OBIS, Darwin Core as it relates to OOS's . | 10 |
| 1.6 Metadata | 10 |
| 1.7 Data QC | 10 |
| 2 Applications | 13 |
| 2.1 Salmon Ocean Ecology Data | 13 |
| 2.2 Hakai Seagrass | 17 |
| 2.3 Aligning Data to Darwin Core - Sampling Event with Measure- ment or Fact | 28 |
| 3 Final Words | 37 |
| 4 Tools | 39 |
| 4.1 R | 39 |
| 4.2 Python | 42 |
| 4.3 Google Sheets | 43 |
| 4.4 Validators | 44 |
| References | 45 |

Preface

Biological data structures, definitions, measurements, and linkages are necessarily as diverse as the systems they represent. This presents a real challenge when integrating data across biological research domains such as ecology, oceanography, fisheries, and climate sciences.

Chapter 1

Introduction

The world of standardizing marine biological data can seem complex for the naive oceanographer, biologist, scientist, or programmer. Transforming and integrating data is about combining the right standards for your desired interoperability with other data types. For example, interoperating fish biology measurements with climate level variables. There are a few concepts necessary to make this possible such as standard data structures, controlled vocabularies and knowledge representations, along with metadata standards to facilitate data discovery. This will permit the inclusion of more data and broader access to better ecosystem based models. Many scientific domains data handling practices are currently being reshaped in light of recent advances in computing power, technology, and data science.

1.1 Data Structures

The OBIS-ENV Darwin Core Archive Data Structure.

OBIS manual

1.2 Ontologies

An ontology is a classification system for establishing a hierarchically related set of concepts. Concepts are often terms from controlled vocabularies.

From Marine Metadata: # TODO: add link

“Ontologies can include all of the following, but are not required to include them, depending on which perspective from above you adhere to:

Classes (general things, types of things) Instances (individual things) Relationships among things Properties of things Functions, processes, constraints, and rules relating to things”

TODO: Research Unified Modelling Language?

Environment Ontology (EnvO) EnvO is a community ontology for the concise, controlled description of environments.

1.3 Controlled Vocabularies

There are a number of controlled vocabularies that are used to describe parameters commonly used in specific research domains. This allows for greater interoperability of data sets within the domain, and ideally between domains. Here, we strive to document a number of relevant examples.

- Climate and Format (CF) Standard Names The purpose of the `standard_name` attribute is to provide a succinct and distinguishing description of a variable, in a way that encourages interoperability. These terms are typically for physical observations, however, there have been advancements in aligning biological taxa into the CF standard names (see here).
- NERC Vocabulary Server The NVS gives access to standardised and hierarchically-organized vocabularies.
 - Device categories using the SeaDataNet device categories
 - Device make/model using the SeaVoX Device Catalogue
 - Platform categories using SeaVoX Platform Categories
 - Platform instances using the ICES Platform Codes
 - Unit of measure
- GCMD Keywords (NASA)
- Geographic Domain/Features of Interest
- GeoLink base ontology was part of the EarthCube GeoLink Project

Note: To describe a measurement or fact of a biological specimen that conforms to Darwin Core standards, it’s necessary to use the ‘Biological entity described elsewhere’ method rather than taxon specific.

1.3.1 Taxonomy

- The World Registry of Marine Species (WoRMS) The aim of a World Register of Marine Species (WoRMS) is to provide an authoritative and comprehensive list of names of marine organisms, including information on synonymy. While the highest priority goes to valid names, other names in use are included so that this register can serve as a guide to interpret taxonomic literature.

1.3.2 Resources

1.3.3 Oceanography

Biological and Chemical Oceanography Data Management Office

Marine metadata interoperability vocab resources

1.3.4 Biology

BioPortal Ecosystem Ontology

1.3.5 NERC Search Interfaces

- SeaDataNet Common Vocab Search Interface:
- SeaDataNet Common Vocabularies:
- SeaDataNet Vocab Library
- Measurement Types in OBIS

1.3.6 Geosciences

UDUNITS are more common unit measurements in geosciences

1.3.7 Eco/EnvO

Environment Ontology including genomics.

1.3.8 Wild Cards

Question: Not sure use case for this.

P01 Biological Entity Parameter Code Builder

1.4 Technologies

1.4.1 ERDDAP

ERDDAP can be thought of as a data server. It provides ‘easier access to scientific data’ by providing a consistent interface that aggregates many disparate data sources. It does this by providing translation services between many common file types for gridded arrays (‘net CDF’ files) and tabular data (spreadsheets). Data access is also made easier because it unifies different types of data servers and access protocols. Here is a basic erddap installation that walks you through how to load a data set.

1.5 Notes on Integrating OBIS, Darwin Core as it relates to OOS’s

1.6 Metadata

OBIS uses the GBIF EML profile (version 1.1). In case data providers use ISO19115/ISO19139, there is a mapping available here: <http://rs.gbif.org/schema/eml-gbif-profile/1.1/eml2iso19139.xsl> This will be important for integrating OBIS datasets to other CIOOS and IOOS metadata profiles.

1.7 Data QC

There are a number of tools available to check the quality of data or check your data format against the expected standard.

OBIS Datatools shows some great R packages for this.

1.7.1 Compliance Checking

LifeWatch Belgium provides a number of tools to check your data against. Specifically you can test OBIS data format and see a map of your sample locations to check if they are on land. See <http://www.lifewatch.be/data-services/>

There’s also the GBIF data validator which allows anyone with a GBIF-relevant dataset to receive a report on the syntactical correctness and the validity of the content contained within the dataset.

1.7.2 Semantic Web and Darwin Core

Lessons learned from adapting the Darwin Core vocabulary standard for use in RDF

1.7.3 Resource Description Framework

Darwin Core Resource Description Framework Guide

Chapter 2

Applications

Some applications are demonstrated in this chapter.

2.1 Salmon Ocean Ecology Data

2.1.1 Intro

One of the goals of the Hakai Institute and the Canadian Integrated Ocean Observing System (CIOOS) is to facilitate Open Science and FAIR (findable, accessible, interoperable, reusable) ecological and oceanographic data. In a concerted effort to adopt or establish how best to do that, several Hakai and CIOOS staff attended an International Ocean Observing System (IOOS) Code Sprint in Ann Arbor, Michigan between October 7–11, 2019, to discuss how to implement FAIR data principles for biological data collected in the marine environment.

The Darwin Core is a highly structured data format that standardizes data table relations, vocabularies, and defines field names. The Darwin Core defines three table types: **event**, **occurrence**, and **measurementOrFact**. This intuitively captures the way most ecologists conduct their research. Typically, a survey (event) is conducted and measurements, counts, or observations (collectively measurementOrFacts) are made regarding a specific habitat or species (occurrence).

In the following script I demonstrate how I go about converting a subset of the data collected from the Hakai Institute Juvenile Salmon Program and discuss challenges, solutions, pros and cons, and when and what’s worthwhile to convert to Darwin Core.

The conversion of a dataset to Darwin Core is much easier if your data are already tidy (normalized) in which you represent your data in separate tables

that reflect the hierarchical and related nature of your observations. If your data are not already in a consistent and structured format, the conversion would likely be very arduous and not intuitive.

2.1.2 event

The first step is to consider what you will define as an event in your data set. I defined the capture of fish using a purse seine net as the **event**. Therefore, each row in the **event** table is one deployment of a seine net and is assigned a unique **eventID**.

My process for conversion was to make a new table called **event** and map the standard Darwin Core column names to pre-existing columns that serve the same purpose in my original **seine_data** table and populate the other required fields.

```
event <- tibble(eventID = survey_seines$seine_id,
               eventDate = date(survey_seines$survey_date),
               decimalLatitude = survey_seines$lat,
               decimalLongitude = survey_seines$long,
               geodeticDatum = "EPSG:4326 WGS84",
               minimumDepthInMeters = 0,
               maximumDepthInMeters = 9, # seine depth is 9 m
               samplingProtocol = "http://dx.doi.org/10.21966/1.566666" # This is the
            )

write_csv(event, here::here("datasets", "hakai_salmon_data", "event.csv"))
```

2.1.3 occurrence

Next you'll want to determine what constitutes an occurrence for your data set. Because each event captures fish, I consider each fish to be an occurrence. Therefore, the unit of observation (each row) in the occurrence table is a fish. To link each occurrence to an event you need to include the **eventID** column for every occurrence so that you know what seine (event) each fish (occurrence) came from. You must also provide a globally unique identifier for each occurrence. I already have a locally unique identifier for each fish in the original **fish_data** table called **ufn**. To make it globally unique I pre-pend the organization and research program metadata to the **ufn** column.

```
#TODO: Include bycatch data as well

## make table long first
seines_total_long <- survey_seines %>%
```

```

select(seine_id, so_total, pi_total, cu_total, co_total, he_total, ck_total) %>%
pivot_longer(-seine_id, names_to = "scientificName", values_to = "n")

seines_total_long$scientificName <- recode(seines_total_long$scientificName, so_total = "Oncorhynchus nerka")

seines_taken_long <- survey_seines %>%
  select(seine_id, so_taken, pi_taken, cu_taken, co_taken, he_taken, ck_taken) %>%
  pivot_longer(-seine_id, names_to = "scientificName", values_to = "n_taken")

seines_taken_long$scientificName <- recode(seines_taken_long$scientificName, so_taken = "Oncorhynchus nerka")

## remove records that have already been assigned an ID
seines_long <- full_join(seines_total_long, seines_taken_long, by = c("seine_id", "scientificName"))
drop_na() %>%
  mutate(n_not_taken = n - n_taken) %>% #so_total includes the number taken so I subtract n_taken
  select(-n_taken, -n) %>%
  filter(n_not_taken > 0)

all_fish_caught <-
  seines_long[rep(seq.int(1, nrow(seines_long)), seines_long$n_not_taken), 1:3] %>%
  select(-n_not_taken) %>%
  mutate(prefix = "hakai-jsp-",
         suffix = 1:nrow(.),
         occurrenceID = paste0(prefix, suffix)
  ) %>%
  select(-prefix, -suffix)

#

# Change species names to full Scientific names
latin <- fct_recode(fish_data$species, "Oncorhynchus nerka" = "SO", "Oncorhynchus gorbuscha" = "P")
as.character()

fish_retained_data <- fish_data %>%
  mutate(scientificName = latin) %>%
  select(-species) %>%
  mutate(prefix = "hakai-jsp-",
         occurrenceID = paste0(prefix, ufn)) %>%
  select(-semsp_id, -prefix, -ufn, -fork_length_field, -fork_length, -weight, -weight_field)

occurrence <- bind_rows(all_fish_caught, fish_retained_data) %>%
  mutate(basisOfRecord = "HumanObservation",
         occurrenceStatus = "present") %>%
  rename(eventID = seine_id)

```

For each occurrence of the six different fish species that I caught I need to match the species name that I provide with the official `scientificName` that is part of the World Register of Marine Species database <http://www.marinespecies.org/>

```
# I went directly to the WoRMS website (http://www.marinespecies.org/) to download the
species_matched <- readxl::read_excel(here::here("datasets", "hakai_salmon_data", "raw",
occurrence <- left_join(occurrence, species_matched, by = c("scientificName" = "Scienti
  select(occurrenceID, basisOfRecord, scientificName, eventID, occurrenceStatus = occur
write_csv(occurrence, here::here("datasets", "hakai_salmon_data", "occurrence.csv"))
```

2.1.4 measurementOrFact

To convert all your measurements or facts from your normal format to Darwin Core you essentially need to put all your measurements into one column called `measurementType` and a corresponding column called `MeasurementValue`. This standardizes the column names are in the `measurementOrFact` table. There are a number of predefined `measurementTypes` listed on the NERC database that should be used where possible. I found it difficult to navigate this page to find the correct `measurementType`.

Here I convert length, and weight measurements that relate to an event and an occurrence and call those `measurementTypes` as `length` and `weight`.

```
fish_data$weight <- coalesce(fish_data$weight, fish_data$weight_field)
fish_data$fork_length <- coalesce(fish_data$fork_length, fish_data$fork_length_field)

fish_length <- fish_data %>%
  mutate(occurrenceID = paste0("hakai-jsp-", ufn)) %>%
  select(occurrenceID, eventID = seine_id, fork_length, weight) %>%
  mutate(measurementType = "fork length", measurementValue = fork_length) %>%
  select(eventID, occurrenceID, measurementType, measurementValue) %>%
  mutate(measurementUnit = "millimeters",
    measurementUnitID = "http://vocab.nerc.ac.uk/collection/P06/current/UXMM/")

fish_weight <- fish_data %>%
  mutate(occurrenceID = paste0("hakai-jsp-", ufn)) %>%
  select(occurrenceID, eventID = seine_id, fork_length, weight) %>%
  mutate(measurementType = "mass", measurementValue = weight) %>%
  select(eventID, occurrenceID, measurementType, measurementValue) %>%
  mutate(measurementUnit = "grams",
    measurementUnitID = "http://vocab.nerc.ac.uk/collection/P06/current/UGRM/")
```



```

measurementOrFact <- bind_rows(fish_length, fish_weight) %>%
  drop_na(measurementValue)

rm(fish_length, fish_weight)

write_csv(measurementOrFact, here::here("datasets", "hakai_salmon_data", "measurementOrFact.csv"))

```

2.2 Hakai Seagrass

2.2.1 Setup

This section clears the workspace, checks the working directory, and installs packages (if required) and loads packages, and loads necessary datasets

```

library("knitr")
# Knitr global chunk options
opts_chunk$set(message = FALSE,
                warning = FALSE,
                error   = FALSE)

```

2.2.1.1 Load Data

First load the seagrass density survey data, set variable classes, and have a quick look

```

# Load density data
seagrassDensity <-
  read.csv("raw_data/seagrass_density_survey.csv",
           colClass = "character") %>%
  mutate(date           = ymd(date),
         depth          = as.numeric(depth),
         transect_dist  = factor(transect_dist),
         collected_start = ymd_hms(collected_start),
         collected_end   = ymd_hms(collected_end),
         density         = as.numeric(density),
         density_msq     = as.numeric(density_msq),
         canopy_height_cm = as.numeric(canopy_height_cm),
         flowering_shoots = as.numeric(flowering_shoots)) %T>%
  glimpse()

```

```

## Rows: 3,031
## Columns: 22

```

```
## $ X <chr> "1", "2", "3", "4", "5", "6", "7", "8", "9", "10", "1~
## $ organization <chr> "HAKAI", "HAKAI", "HAKAI", "HAKAI", "HAKAI", "HAKAI",~
## $ work_area <chr> "CALVERT", "CALVERT", "CALVERT", "CALVERT", "CALVERT"~
## $ project <chr> "MARINEGEO", "MARINEGEO", "MARINEGEO", "MARINEGEO", "~
## $ survey <chr> "PRUTH_BAY", "PRUTH_BAY", "PRUTH_BAY", "PRUTH_BAY", "~
## $ site_id <chr> "PRUTH_BAY_INTERIOR4", "PRUTH_BAY_INTERIOR4", "PRUTH~
## $ date <date> 2016-05-13, 2016-05-13, 2016-05-13, 2016-05-13, 2016~
## $ sampling_bout <chr> "4", "4", "4", "4", "4", "4", "6", "6", "6", "6"~
## $ dive_supervisor <chr> "Zach", "Zach", "Zach", "Zach", "Zach", "Zach", "Zach~
## $ collector <chr> "Derek", "Derek", "Derek", "Derek", "Derek", "Derek",~
## $ hakai_id <chr> "2016-05-13_PRUTH_BAY_INTERIOR4_0", "2016-05-13_PRUTH~
## $ sample_type <chr> "seagrass_density", "seagrass_density", "seagrass_den~
## $ depth <dbl> 6.0, 6.0, 6.0, 6.0, 5.0, 6.0, 6.0, 9.1, 9.0, 8.9, 9.0~
## $ transect_dist <fct> 0, 5, 10, 15, 20, 25, 30, 10, 15, 20, 25, 30, 0, 5, 1~
## $ collected_start <dtm> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
## $ collected_end <dtm> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
## $ density <dbl> 13, 10, 18, 22, 16, 31, 9, 5, 6, 6, 6, 3, 13, 30, 23,~
## $ density_msq <dbl> 208, 160, 288, 352, 256, 496, 144, 80, 96, 96, 96, 48~
## $ canopy_height_cm <dbl> 60, 63, 80, 54, 55, 50, 63, 85, 80, 90, 95, 75, 60, 6~
## $ flowering_shoots <dbl> NA, NA, NA, NA, NA, NA, NA, 0, 0, 0, 0, 0, NA, NA, NA~
## $ comments <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, N~
## $ quality_log <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, N~
```

Next, load the habitat survey data, and same as above, set variable classes as necessary, and have a quick look.

```
# load habitat data, set variable classes, have a quick look
seagrassHabitat <-
  read.csv("raw_data/seagrass_habitat_survey.csv",
           colClasses = "character") %>%
  mutate(date = ymd(date),
         depth = as.numeric(depth),
         hakai_id = str_pad(hakai_id, 5, pad = "0"),
         transect_dist = factor(transect_dist),
         collected_start = ymd_hms(collected_start),
         collected_end = ymd_hms(collected_end)) %T>%
  glimpse()
```

```
## Rows: 2,052
## Columns: 28
## $ X <chr> "1", "2", "3", "4", "5", "6", "7", "8", "9", "10", "1~
## $ organization <chr> "HAKAI", "HAKAI", "HAKAI", "HAKAI", "HAKAI", "HAKAI",~
## $ work_area <chr> "CALVERT", "CALVERT", "CALVERT", "CALVERT", "CALVERT"~
## $ project <chr> "MARINEGEO", "MARINEGEO", "MARINEGEO", "MARINEGEO", "~
## $ survey <chr> "CHOKED_PASS", "CHOKED_PASS", "CHOKED_PASS", "CHOKED_~
```

```
## $ site_id      <chr> "CHOKED_PASS_INTERIOR6", "CHOKED_PASS_INTERIOR6", "CH~
## $ date         <date> 2017-11-22, 2017-11-22, 2017-11-22, 2017-11-22, 2017~
## $ sampling_bout <chr> "6", "6", "6", "6", "6", "6", "1", "1", "1", "1", "1"~
## $ dive_supervisor <chr> "gillian", "gillian", "gillian", "gillian", "gillian"~
## $ collector     <chr> "zach", "zach", "zach", "zach", "zach", "zach", "kyle~
## $ hakai_id      <chr> "10883", "2017-11-22_CHOKED_PASS_INTERIOR6_5 - 10", "~
## $ sample_type   <chr> "seagrass_habitat", "seagrass_habitat", "seagrass_hab~
## $ depth         <dbl> 9.2, 9.4, 9.3, 9.0, 9.2, 9.2, 3.4, 3.4, 3.4, 3.4, 3.4~
## $ transect_dist <fct> 0 - 5, 10-May, 15-Oct, 15 - 20, 20 - 25, 25 - 30, 0 --
## $ collected_start <dtm> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
## $ collected_end   <dtm> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
## $ bag_uid        <chr> "10883", NA, NA, "11094", NA, "11182", "7119", "7~
## $ bag_number      <chr> "3557", NA, NA, "3520", NA, "903", "800", NA, "318", ~
## $ density_range   <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, N~
## $ substrate       <chr> "sand,shell hash", "sand,shell hash", "sand,shell has~
## $ patchiness      <chr> "< 1", "< 1", "02-Jan", "< 1", "< 1", "< 1", "< 1", "~
## $ adj_habitat_1    <chr> "seagrass", "seagrass", "seagrass", "seagrass", "seag~
## $ adj_habitat_2    <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, N~
## $ sample_collected <chr> "TRUE", "FALSE", "FALSE", "TRUE", "FALSE", "TRUE", "T~
## $ vegetation_1     <chr> NA, NA, NA, NA, NA, NA, "des", NA, "des", NA, NA, NA, ~
## $ vegetation_2     <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, N~
## $ comments         <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, N~
## $ quality_log      <chr> "1: Flowering shoots 0 for entire transects", NA, NA,~
```

Finally, load coordinate data for surveys, and subset necessary variables

```
coordinates <-
  read.csv("raw_data/seagrassCoordinates.csv",
           colClass = c("Point.Name" = "character")) %>%
  select(Point.Name, Decimal.Lat, Decimal.Long) %T>%
  glimpse()
```

```
## Rows: 70
## Columns: 3
## $ Point.Name   <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, N~
## $ Decimal.Lat  <dbl> 52.06200, 52.05200, 51.92270, 51.92500, 51.80900, 51.8090~
## $ Decimal.Long <dbl> -128.4120, -128.4030, -128.4648, -128.4540, -128.2360, -1~
```

2.2.1.2 Merge Datasets

Now all the datasets have been loaded, and briefly formatted, we'll join together the habitat and density surveys, and the coordinates for these.

The seagrass density surveys collect data at discrete points (ie. 5 metres) along the transects, while the habitat surveys collect data over sections (ie. 0 - 5

metres) along the transects. In order to fit these two surveys together, we'll narrow the habitat surveys from a range to a point so the locations will match. Based on how the habitat data is collected, the point the habitat survey is applied to will be the distance at the end of the swath (ie. 10-15m will become 15m). To account for no preceeding distance, the 0m distance will use the 0-5m section of the survey.

First, we'll make the necessary transformations to the habitat dataset.

```
# Reformat seagrassHabitat to merge with seagrassDensity
## replicate 0 - 5m transect dist to match with 0m in density survey;
## rest of habitat bins can map one to one with density (ie. 5 - 10m -> 10m)
seagrass0tmp <-
  seagrassHabitat %>%
  filter(transect_dist %in% c("0 - 5", "0 - 2.5")) %>%
  mutate(transect_dist = factor(0))

## collapse various levels to match with seagrassDensity transect_dist
seagrassHabitat$transect_dist <-
  fct_collapse(seagrassHabitat$transect_dist,
    "5" = c("0 - 5", "2.5 - 7.5"),
    "10" = c("5 - 10", "7.5 - 12.5"),
    "15" = c("10 - 15", "12.5 - 17.5"),
    "20" = c("15 - 20", "17.5 - 22.5"),
    "25" = c("20 - 25", "22.5 - 27.5"),
    "30" = c("25 - 30", "27.5 - 30"))

## merge seagrass0tmp into seagrassHabitat to account for 0m samples,
## set class for date, datetime variables
seagrassHabitatFull <-
  rbind(seagrass0tmp, seagrassHabitat) %>%
  filter(transect_dist != "0 - 2.5") %>% # already captured in seagrass0tmp
  droplevels(.) # remove now unused factor levels
```

With the distances of habitat and density surveys now corresponding, we can now merge these two datasets plus there coordinates together, combine redundant fields, and remove unnecessary fields.

```
# Merge seagrassHabitatFull with seagrassDensity, then coordinates
seagrass <-
  full_join(seagrassHabitatFull, seagrassDensity,
    by = c("organization",
           "work_area",
           "project",
           "survey",
           "site_id",
```

```

      "date",
      "transect_dist")) %>%
# merge hakai_id.x and hakai_id.y into single variable field;
# use combination of date, site_id, transect_dist, and field uid (hakai_id
# when present)
mutate(field_uid = ifelse(sample_collected == TRUE, hakai_id.x, "NA"),
      hakai_id = paste(date, "HAKAI:CALVERT", site_id, transect_dist, sep = ":"),
      # below, aggregate metadata that didn't merge naturally (ie. due to minor
      # differences in watch time or depth gauges)
      dive_supervisor = dive_supervisor.x,
      collected_start = ymd_hms(ifelse(is.na(collected_start.x),
                                       collected_start.y,
                                       collected_start.x)),
      collected_end   = ymd_hms(ifelse(is.na(collected_start.x),
                                       collected_start.y,
                                       collected_start.x)),
      depth_m         = ifelse(is.na(depth.x), depth.y, depth.x),
      sampling_bout    = sampling_bout.x) %>%
left_join(., coordinates, # add coordinates
      by = c("site_id" = "Point.Name")) %>%
select( - c(X.x, X.y, hakai_id.x, hakai_id.y, # remove unnecessary variables
           dive_supervisor.x, dive_supervisor.y,
           collected_start.x, collected_start.y,
           collected_end.x, collected_end.y,
           depth.x, depth.y,
           sampling_bout.x, sampling_bout.y)) %>%
mutate(density_msq = as.character(density_msq),
      canopy_height_cm = as.character(canopy_height_cm),
      flowering_shoots = as.character(flowering_shoots),
      depth_m = as.character(depth_m)) %T>%
glimpse()

```

```

## Rows: 3,743
## Columns: 38
## $ organization    <chr> "HAKAI", "HAKAI", "HAKAI", "HAKAI", "HAKAI", "HAKAI", ~
## $ work_area       <chr> "CALVERT", "CALVERT", "CALVERT", "CALVERT", "CALVERT"~
## $ project         <chr> "MARINEGEO", "MARINEGEO", "MARINEGEO", "MARINEGEO", "~
## $ survey          <chr> "CHOKED_PASS", "CHOKED_PASS", "CHOKED_PASS", "PRUTH_B~
## $ site_id         <chr> "CHOKED_PASS_INTERIOR6", "CHOKED_PASS_EDGE1", "CHOKED~
## $ date            <date> 2017-11-22, 2017-05-19, 2017-05-19, 2017-07-03, 2017~
## $ collector.x     <chr> "zach", "kyle", NA, "tanya", "zach", "zach", "zach", ~
## $ sample_type.x   <chr> "seagrass_habitat", "seagrass_habitat", "seagrass_hab~
## $ transect_dist   <fct> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, ~
## $ bag_uid         <chr> "10883", "7119", "7031", "2352", "10255", "10023", "1~
## $ bag_number      <chr> "3557", "800", "301", "324", "3506", "3555", "3534", ~

```

2.2.2 Convert Data to Darwin Core - Extended Measurement or Fact format

2.2.2.1 Add Event ID and Occurrence ID variables to dataset

As this dataset will be annually updated, rather than using natural keys (i.e. using `package::uuid` to autogenerate) for event and occurrence IDs, here we will use surrogate keys made up of a concatenation of date survey, transect location, observation distance, and sample ID (for `occurrenceID`, when a sample is present).

```

# create and populate eventID variable
## currently only event is used, but additional surveys and abiotic data
## are associated with parent events that may be included at a later date
seagrass$eventID <- seagrass$hakai_id

# create and populate occurrenceID; combine eventID with transect_dist
# and field_uid
## in the event of <NA> field_uid, no sample was collected, but
## measurements and occurrence are still taken; no further subsamples
## are associated with <NA> field_uids
seagrass$occurrenceID <-
  with(seagrass,
    paste(eventID, transect_dist, field_uid, sep = ":"))

```

2.2.2.2 Create Event, Occurrence, and eMoF tables

Now that we've created eventIDs and occurrenceIDs to connect all the variables together, we can begin to create the Event, Occurrence, and extended Measurement or Fact table necessary for DarwinCore compliant datasets

```

# subset seagrass to create event table
seagrassEvent <-
  seagrass %>%
  distinct %>% # some duplicates in data stemming from database conflicts
  select(date,
    Decimal.Lat, Decimal.Long, transect_dist,
    depth_m, eventID) %>%
  rename(eventDate = date,
    decimalLatitude = Decimal.Lat,
    decimalLongitude = Decimal.Long,
    coordinateUncertaintyInMeters = transect_dist,
    minimumDepthInMeters = depth_m,
    maximumDepthInMeters = depth_m) %>%
  mutate(geodeticDatum = "WGS84",
    samplingEffort = "30 metre transect") %T>% glimpse

```

2.2.2.2.1 Event Table

```

## Rows: 3,659
## Columns: 8
## $ eventDate      <date> 2017-11-22, 2017-05-19, 2017-05-19, 201~

```

```
## $ decimalLatitude      <dbl> 51.67482, 51.67882, 51.67493, 51.64532, ~
## $ decimalLongitude     <dbl> -128.1195, -128.1148, -128.1237, -128.11~
## $ coordinateUncertaintyInMeters <fct> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0~
## $ maximumDepthInMeters <chr> "9.2", "3.4", "4.8", "2.4", "5.3", "5.6"~
## $ eventID              <chr> "2017-11-22:HAKAI:CALVERT:CHOKED_PASS_IN~
## $ geodeticDatum         <chr> "WGS84", "WGS84", "WGS84", "WGS84", "WGS~
## $ samplingEffort        <chr> "30 metre transect", "30 metre transect"~
```

```
# save event table to csv
write.csv(seagrassEvent, "processed_data/hakaiSeagrassDwcEvent.csv")
```

```
# subset seagrass to create occurrence table
seagrassOccurrence <-
  seagrass %>%
  distinct %>% # some duplicates in data stemming from database conflicts
  select(eventID, occurrenceID) %>%
  mutate(basisOfRecord = "HumanObservation",
         scientificName = "Zostera subg. Zostera marina",
         occurrenceStatus = "present")

# Taxonomic name matching
# in addition to the above metadata, DarwinCore format requires further
# taxonomic data that can be acquired through the WoRMS register.
## Load taxonomic info, downloaded via WoRMS tool
# zmWorms <-
#   read.delim("raw_data/zmworms_matched.txt",
#             header = TRUE,
#             nrow = 1)

zmWorms <- wm_record(id = 145795)

# join WoRMS name with seagrassOccurrence create above
seagrassOccurrence <-
  full_join(seagrassOccurrence, zmWorms,
            by = c("scientificName" = "scientificname")) %>%
  select(eventID, occurrenceID, basisOfRecord, scientificName, occurrenceStatus, Aphia.
         url, authority, status, unacceptreason, taxonRankID, rank,
         valid_AphiaID, valid_name, valid_authority, parentNameUsageID,
         kingdom, phylum, class, order, family, genus, citation, lsid,
         isMarine, match_type, modified) %T>%
  glimpse
```

2.2.2.2.2 Occurrence Table


```
## Rows: 3,659
## Columns: 27
## $ eventID <chr> "2017-11-22:HAKAI:CALVERT:CHOKED_PASS_INTERIOR6:0", ~
## $ occurrenceID <chr> "2017-11-22:HAKAI:CALVERT:CHOKED_PASS_INTERIOR6:0:0:~
## $ basisOfRecord <chr> "HumanObservation", "HumanObservation", "HumanObserv~
## $ scientificName <chr> "Zostera subg. Zostera marina", "Zostera subg. Zoste~
## $ occurrenceStatus <chr> "present", "present", "present", "present", "present~
## $ AphiaID <int> 145795, 145795, 145795, 145795, 145795, 145795, 1457~
## $ url <chr> "http://www.marinespecies.org/aphia.php?p=taxdetails~
## $ authority <chr> "Linnaeus, 1753", "Linnaeus, 1753", "Linnaeus, 1753"~
## $ status <chr> "accepted", "accepted", "accepted", "accepted", "acc~
## $ unacceptreason <lg1> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
## $ taxonRankID <int> 220, 220, 220, 220, 220, 220, 220, 220, 220, 22~
## $ rank <chr> "Species", "Species", "Species", "Species", "Species", "Species~
## $ valid_AphiaID <int> 145795, 145795, 145795, 145795, 145795, 1457~
## $ valid_name <chr> "Zostera subg. Zostera marina", "Zostera subg. Zoste~
## $ valid_authority <chr> "Linnaeus, 1753", "Linnaeus, 1753", "Linnaeus, 1753"~
## $ parentNameUsageID <int> 370435, 370435, 370435, 370435, 370435, 3704~
## $ kingdom <chr> "Plantae", "Plantae", "Plantae", "Plantae", "Plantae~
## $ phylum <chr> "Tracheophyta", "Tracheophyta", "Tracheophyta", "Tra~
## $ class <chr> "Magnoliopsida", "Magnoliopsida", "Magnoliopsida", "~
## $ order <chr> "Alismatales", "Alismatales", "Alismatales", "Alisma~
## $ family <chr> "Zosteraceae", "Zosteraceae", "Zosteraceae", "Zoster~
## $ genus <chr> "Zostera", "Zostera", "Zostera", "Zostera", "Zostera~
## $ citation <chr> "WoRMS (2021). Zostera subg. Zostera marina Linnaeus~
## $ lsid <chr> "urn:lsid:marinespecies.org:taxname:145795", "urn:ls~
## $ isMarine <int> 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1~
## $ match_type <chr> "exact", "exact", "exact", "exact", "exact", "exact"~
## $ modified <chr> "2008-12-09T10:03:16.140Z", "2008-12-09T10:03:16.140~
```

```
# save occurrence table to csv
write.csv(seagrassOccurrence, "processed_data/hakaiSeagrassDwcOccurrence.csv")
```

```
seagrassMof <-
  seagrass %>%
    # select variables for eMoF table
    select(date,
           eventID, survey, site_id, transect_dist,
           substrate, patchiness, adj_habitat_1, adj_habitat_2,
           vegetation_1, vegetation_2,
           density_msq, canopy_height_cm, flowering_shoots) %>%
    # split substrate into two variables (currently holds two substrate type in same variable)
    separate(substrate, sep = ",", into = c("substrate_1", "substrate_2")) %>%
```

```

# change variables names to match NERC database (or to be more descriptive where non
rename(measurementDeterminedDate = date,
       SubstrateTypeA            = substrate_1,
       SubstrateTypeB            = substrate_2,
       BarePatchLengthWithinSeagrass = patchiness,
       PrimaryAdjacentHabitat      = adj_habitat_1,
       SecondaryAdjacentHabitat    = adj_habitat_2,
       PrimaryAlgaeSp             = vegetation_1,
       SecondaryAlgaeSp           = vegetation_2,
       BedAbund                   = density_msq,
       CanopyHeight               = canopy_height_cm,
       FloweringBedAbund          = flowering_shoots) %>%
# reformat variables into DwC MeasurementOrFact format
# (single values variable, with measurement type, unit, etc. variables)
pivot_longer( - c(measurementDeterminedDate, eventID, survey, site_id, transect_dist,
                  names_to = "measurementType",
                  values_to = "measurementValue",
                  values_ptypes = list(measurementValue = "character"))) %>%
# use measurement type to fill in remainder of variables relating to
# NERC vocabulary and metadata fields
mutate(
  measurementTypeID = case_when(
    measurementType == "BedAbund" ~ "http://vocab.nerc.ac.uk/collection/P01/current/",
    measurementType == "CanopyHeight" ~ "http://vocab.nerc.ac.uk/collection/P01/current/",
    # measurementType == "BarePatchWithinSeagrass" ~ "",
    measurementType == "FloweringBedAbund" ~ "http://vocab.nerc.ac.uk/collection/P01/current/"),
  measurementUnit = case_when(
    measurementType == "BedAbund" ~ "Number per square metre",
    measurementType == "CanopyHeight" ~ "Centimetres",
    measurementType == "BarePatchhhLengthWithinSeagrass" ~ "Metres",
    measurementType == "FloweringBedAbund" ~ "Number per square metre"),
  measurementUnitID = case_when(
    measurementType == "BedAbund" ~ "http://vocab.nerc.ac.uk/collection/P06/current/",
    measurementType == "CanopyHeight" ~ "http://vocab.nerc.ac.uk/collection/P06/current/",
    measurementType == "BarePatchhhLengthWithinSeagrass" ~ "http://vocab.nerc.ac.uk/collection/P06/current/",
    measurementType == "FloweringBedAbund" ~ "http://vocab.nerc.ac.uk/collection/P06/current/"),
  measurementAccuracy = case_when(
    measurementType == "CanopyHeight" ~ 5),
  measurementMethod = case_when(
    measurementType == "BedAbund" ~ "25cmx25cm quadrat count",
    measurementType == "CanopyHeight" ~ "in situ with ruler",
    measurementType == "BarePatchhhLengthWithinSeagrass" ~ "estimated along transect",
    measurementType == "FloweringBedAbund" ~ "25cmx25cm quadrat count"))) %>%
select(eventID, measurementDeterminedDate, measurementType, measurementValue,
       measurementTypeID, measurementUnit, measurementUnitID, measurementAccuracy,

```

```

        measurementMethod) %T>%
# select(!c(survey, site_id, transect_dist)) %T>%
glimpse()

```

2.2.2.2.3 Extended MeasurementOrFact table

```

## Rows: 37,430
## Columns: 9
## $ eventID <chr> "2017-11-22:HAKAI:CALVERT:CHOKED_PASS_INTERI~
## $ measurementDeterminedDate <date> 2017-11-22, 2017-11-22, 2017-11-22, 2017-11-~
## $ measurementType <chr> "SubstrateTypeA", "SubstrateTypeB", "BarePat~
## $ measurementValue <chr> "sand", "shell hash", "< 1", "seagrass", NA,~
## $ measurementTypeID <chr> NA, NA, NA, NA, NA, NA, NA, "http://vocab.ne~
## $ measurementUnit <chr> NA, NA, NA, NA, NA, NA, NA, "Number per squa~
## $ measurementUnitID <chr> NA, NA, NA, NA, NA, NA, NA, "http://vocab.ne~
## $ measurementAccuracy <dbl> NA, NA, NA, NA, NA, NA, NA, 5, NA, NA, N~
## $ measurementMethod <chr> NA, NA, NA, NA, NA, NA, NA, "25cmx25cm quadr~

# save eMoF table to csv
write.csv(seagrassMof, "processed_data/hakaiSeagrassDwcEmof.csv")

```

2.2.3 Session Info

Print session information below in case necessary for future reference

```

# Print Session Info for future reference
sessionInfo()

## R version 4.1.1 (2021-08-10)
## Platform: x86_64-apple-darwin17.0 (64-bit)
## Running under: macOS Catalina 10.15.7
##
## Matrix products: default
## BLAS: /Library/Frameworks/R.framework/Versions/4.1/Resources/lib/libRblas.0.dylib
## LAPACK: /Library/Frameworks/R.framework/Versions/4.1/Resources/lib/libRlapack.dylib
##
## locale:
## [1] en_US.UTF-8/en_US.UTF-8/en_US.UTF-8/C/en_US.UTF-8/en_US.UTF-8
##
## attached base packages:
## [1] stats graphics grDevices utils datasets methods base
##
## other attached packages:

```

```
## [1] worrms_0.4.2      magrittr_2.0.1  knitr_1.36      lubridate_1.8.0
## [5] here_1.0.1        forcats_0.5.1  stringr_1.4.0  dplyr_1.0.7
## [9] purrr_0.3.4       readr_2.0.2    tidyr_1.1.4    tibble_3.1.5
## [13] ggplot2_3.3.5     tidyverse_1.3.1
##
## loaded via a namespace (and not attached):
## [1] Rcpp_1.0.7         assertthat_0.2.1 rprojroot_2.0.2  digest_0.6.28
## [5] utf8_1.2.2         R6_2.5.1         cellranger_1.1.0 backports_1.3.0
## [9] reprex_2.0.1       evaluate_0.14    httr_1.4.2       pillar_1.6.4
## [13] rlang_0.4.12       curl_4.3.2       readxl_1.3.1     rstudioapi_0.13
## [17] jquerylib_0.1.4    rmarkdown_2.11   urltools_1.7.3   triebeard_0.3.0
## [21] bit_4.0.4          munsell_0.5.0    broom_0.7.10     compiler_4.1.1
## [25] modelr_0.1.8       xfun_0.27        pkgconfig_2.0.3  htmltools_0.5.2
## [29] tidyselect_1.1.1   httpcode_0.3.0   bookdown_0.24    fansi_0.5.0
## [33] crayon_1.4.2       tzdb_0.2.0       dbplyr_2.1.1     withr_2.4.2
## [37] crul_1.1.0         grid_4.1.1       jsonlite_1.7.2   gtable_0.3.0
## [41] lifecycle_1.0.1    DBI_1.1.1        scales_1.1.1     cli_3.1.0
## [45] stringi_1.7.5      vroom_1.5.5      fs_1.5.0         xml2_1.3.2
## [49] ellipsis_0.3.2     generics_0.1.1   vctrs_0.3.8      tools_4.1.1
## [53] bit64_4.0.5        glue_1.4.2       hms_1.1.1        parallel_4.1.1
## [57] fastmap_1.1.0      yaml_2.2.1       colorspace_2.0-2 rvest_1.0.2
## [61] haven_2.4.3
```

2.3 Aligning Data to Darwin Core - Sampling Event with Measurement or Fact

Abby Benson
October 8, 2019

2.3.1 General information about this notebook

This notebook was created for the IOOS DMAC Code Sprint Biological Data Session. The data in this notebook were created specifically as an example and meant solely to be illustrative of the process for aligning data to the biological data standard - Darwin Core. These data should not be considered actual occurrences of species and any measurements are also contrived. This notebook is meant to provide a step by step process for taking original data and aligning it to Darwin Core.

```
library(readr)
library(uuid)
library(dplyr)
```

2.3. ALIGNING DATA TO DARWIN CORE - SAMPLING EVENT WITH MEASUREMENT OR FACTS

```
MadeUpDataForBiologicalDataTraining <- read_csv("~/OBIS/Reference Documentation/Presentations/IOU

## Parsed with column specification:
## cols(
##   date = col_character(),
##   lat = col_double(),
##   lon = col_double(),
##   region = col_character(),
##   station = col_double(),
##   transect = col_double(),
##   `scientific name` = col_character(),
##   `percent cover` = col_double(),
##   depth = col_double(),
##   `bottom type` = col_character(),
##   rugosity = col_double(),
##   temperature = col_double()
## )
```

First we need to decide if we will provide an occurrence only version of the data or a sampling event with measurement or facts version of the data. Occurrence only is easier to create. It's only one file to produce. However, several pieces of information will be left out if we choose that option. If we choose to do sampling event with measurement or fact we'll be able to capture all of the data in the file creating a lossless version. Here we decide to use the sampling event option to include as much information as we can. First let's create the eventID and occurrenceID in the original file so that information can be reused for all necessary files down the line.

```
MadeUpDataForBiologicalDataTraining$eventID <- paste(MadeUpDataForBiologicalDataTraining$region,
                                                    MadeUpDataForBiologicalDataTraining$station,
                                                    MadeUpDataForBiologicalDataTraining$transect)
MadeUpDataForBiologicalDataTraining$occurrenceID <- ""
MadeUpDataForBiologicalDataTraining$occurrenceID <- sapply(MadeUpDataForBiologicalDataTraining$occurrenceID,
                                                           function(x) UUIDgenerate(use.time = TRUE))
```

We will need to create three separate files to comply with the sampling event format. We'll start with the event file but we only need to include the columns that are relevant to the event file.

```
event <- MadeUpDataForBiologicalDataTraining[c("date", "lat", "lon", "region", "station",
                                              "transect", "depth", "bottom type", "eventID")]
```

Next we need to rename any columns of data that match directly to Darwin Core. We know this based on our crosswalk spreadsheet CrosswalkToDarwin-Core.csv

```
event$decimalLatitude <- event$lat
event$decimalLongitude <- event$lon
event$minimumDepthInMeters <- event$depth
event$maximumDepthInMeters <- event$depth
event$habitat <- event$`bottom type`
event$island <- event$region
```

Let's see how it looks:

```
head(event, n = 10)
```

```
## # A tibble: 10 x 15
##   date    lat  lon region station transect depth `bottom type` eventID
##   <chr> <dbl> <dbl> <chr>    <dbl>    <dbl> <dbl> <chr>         <chr>
## 1 7/16~ 18.3 -64.8 St. J~    250      1    25 shallow reef~ St. Jo~
## 2 7/16~ 18.3 -64.8 St. J~    250      1    25 shallow reef~ St. Jo~
## 3 7/16~ 18.3 -64.8 St. J~    250      1    25 shallow reef~ St. Jo~
## 4 7/16~ 18.3 -64.8 St. J~    250      1    25 shallow reef~ St. Jo~
## 5 7/16~ 18.3 -64.8 St. J~    250      2    35 complex back~ St. Jo~
## 6 7/16~ 18.3 -64.8 St. J~    250      2    35 complex back~ St. Jo~
## 7 7/16~ 18.3 -64.8 St. J~    250      2    35 complex back~ St. Jo~
## 8 7/16~ 18.3 -64.8 St. J~    250      2    35 complex back~ St. Jo~
## 9 7/16~ 18.3 -64.8 St. J~    250      3    85 deep reef   St. Jo~
## 10 7/16~ 18.3 -64.8 St. J~    250      3    85 deep reef   St. Jo~
## # ... with 6 more variables: decimalLatitude <dbl>,
## #   decimalLongitude <dbl>, minimumDepthInMeters <dbl>,
## #   maximumDepthInMeters <dbl>, habitat <chr>, island <chr>
```

We need to convert the date to ISO format

```
event$eventDate <- as.Date(event$date, format = "%m/%d/%Y")
```

We will also have to add any missing required fields

```
event$basisOfRecord <- "HumanObservation"
event$geodeticDatum <- "EPSG:4326 WGS84"
```

Then we'll remove any columns that we no longer need to clean things up a bit.

```
event$date <- NULL
event$lat <- NULL
event$lon <- NULL
event$region <- NULL
```

2.3. ALIGNING DATA TO DARWIN CORE - SAMPLING EVENT WITH MEASUREMENT OR FACT31

```
event$station <- NULL
event$transect <- NULL
event$depth <- NULL
event$`bottom type` <- NULL
```

We have too many repeating rows of information. We can pare this down using eventID which is a unique identifier for each sampling event in the data- which is six, three transects per site.

```
event <- event[which(!duplicated(event$eventID)),]

head(event, n = 6)
```

```
## # A tibble: 6 x 10
##   eventID decimalLatitude decimalLongitude minimumDepthInM~
##   <chr>          <dbl>          <dbl>          <dbl>
## 1 St. Jo~        18.3          -64.8           25
## 2 St. Jo~        18.3          -64.8           35
## 3 St. Jo~        18.3          -64.8           85
## 4 St. Jo~        18.3          -64.8           28
## 5 St. Jo~        18.3          -64.8           16
## 6 St. Jo~        18.3          -64.8           90
## # ... with 6 more variables: maximumDepthInMeters <dbl>, habitat <chr>,
## #   island <chr>, eventDate <date>, basisOfRecord <chr>,
## #   geodeticDatum <chr>
```

Finally we write out the event file

```
write.csv(event, file="MadeUpData_event.csv", row.names=FALSE, fileEncoding="UTF-8", quote=TRUE)
```

Next we need to create the occurrence file. We start by creating the dataframe.

```
occurrence <- MadeUpDataForBiologicalDataTraining[c("scientific name", "eventID", "occurrenceID",
```

Then we'll rename the columns that align directly with Darwin Core.

```
occurrence$scientificName <- occurrence$`scientific name`
```

Finally we'll add required information that's missing.

```
occurrence$occurrenceStatus <- ifelse (occurrence$`percent cover` == 0, "absent", "present")
```

2.3.2 Taxonomic Name Matching

A requirement for OBIS is that all scientific names match to the World Register of Marine Species (WoRMS) and a scientificNameID is included. A scientificNameID looks like this “urn:lsid:marinespecies.org:taxname:275730” with the last digits after the colon being the WoRMS aphia ID. We’ll need to go out to WoRMS to grab this information. Create a lookup table of unique scientific names

```
lut_worms <- as.data.frame(unique(occurrence_only$scientificName))
lut_worms$scientificName <- as.character(lut_worms$`unique(occurrence_only$scientificName)`)
lut_worms$`unique(occurrence_only$scientificName)` <- NULL
lut_worms$scientificName <- as.character(lut_worms$scientificName)
```

Add the columns that we can grab information from WoRMS including the required scientificNameID.

```
lut_worms$acceptedname <- ""
lut_worms$acceptedID <- ""
lut_worms$scientificNameID <- ""
lut_worms$kingdom <- ""
lut_worms$phylum <- ""
lut_worms$class <- ""
lut_worms$order <- ""
lut_worms$family <- ""
lut_worms$genus <- ""
lut_worms$scientificNameAuthorship <- ""
lut_worms$taxonRank <- ""
```

Taxonomic lookup using the library taxizesoap

```
for (i in 1:nrow(lut_worms)){
  df <- worms_records(scientific = lut_worms$scientificName[i])
  lut_worms[i,]$scientificNameID <- df$lsid[1]
  lut_worms[i,]$acceptedname <- df$valid_name[1]
  lut_worms[i,]$acceptedID <- df$valid_AphiaID[1]
  lut_worms[i,]$kingdom <- df$kingdom[1]
  lut_worms[i,]$phylum <- df$phylum[1]
  lut_worms[i,]$class <- df$class[1]
  lut_worms[i,]$order <- df$order[1]
  lut_worms[i,]$family <- df$family[1]
  lut_worms[i,]$genus <- df$genus[1]
  lut_worms[i,]$scientificNameAuthorship <- df$authority[1]
  lut_worms[i,]$taxonRank <- df$rank[1]
  message(paste("Looking up information for species:", lut_worms[i,]$scientificName))
}
```


2.3. ALIGNING DATA TO DARWIN CORE - SAMPLING EVENT WITH MEASUREMENT OR FACT33

```
## Looking up information for species: Acropora cervicornis
```

```
## Looking up information for species: Madracis auretenra
```

```
## Looking up information for species: Mussa angulosa
```

```
## Looking up information for species: Siderastrea radians
```

Merge the lookup table of unique scientific names back with the occurrence data.

```
occurrence <- merge(occurrence, lut_worms, by = "scientificName")
```

We're going to remove any unnecessary columns to clean up the file

```
occurrence$`scientific name` <- NULL
occurrence$`percent cover` <- NULL
```

Quick look at what we have before we write out the file

```
head(occurrence, n = 10)
```

```
##      scientificName      eventID
## 1  Acropora cervicornis St. John_250_1
## 2  Acropora cervicornis St. John_250_2
## 3  Acropora cervicornis St. John_250_3
## 4  Acropora cervicornis St. John_356_1
## 5  Acropora cervicornis St. John_356_2
## 6  Acropora cervicornis St. John_356_3
## 7   Madracis auretenra St. John_250_1
## 8   Madracis auretenra St. John_250_2
## 9   Madracis auretenra St. John_250_3
## 10  Madracis auretenra St. John_356_1
##      occurrenceID occurrenceStatus
## 1  63be8f7e-ea9a-11e9-8649-49c6324f3a06      absent
## 2  63beb687-ea9a-11e9-8649-49c6324f3a06      absent
## 3  63beb68b-ea9a-11e9-8649-49c6324f3a06      present
## 4  63bedd76-ea9a-11e9-8649-49c6324f3a06      present
## 5  63bedd7a-ea9a-11e9-8649-49c6324f3a06      present
## 6  63bedd7e-ea9a-11e9-8649-49c6324f3a06      present
## 7  63beb684-ea9a-11e9-8649-49c6324f3a06      present
## 8  63beb688-ea9a-11e9-8649-49c6324f3a06      present
## 9  63beb68c-ea9a-11e9-8649-49c6324f3a06      absent
```

```

## 10 63bedd77-ea9a-11e9-8649-49c6324f3a06      present
##          acceptedname acceptedID
## 1  Acropora cervicornis      206989
## 2  Acropora cervicornis      206989
## 3  Acropora cervicornis      206989
## 4  Acropora cervicornis      206989
## 5  Acropora cervicornis      206989
## 6  Acropora cervicornis      206989
## 7   Madracis auretenra      430664
## 8   Madracis auretenra      430664
## 9   Madracis auretenra      430664
## 10  Madracis auretenra      430664
##          scientificNameID kingdom  phylum  class
## 1  urn:lsid:marinespecies.org:taxname:206989 Animalia Cnidaria Anthozoa
## 2  urn:lsid:marinespecies.org:taxname:206989 Animalia Cnidaria Anthozoa
## 3  urn:lsid:marinespecies.org:taxname:206989 Animalia Cnidaria Anthozoa
## 4  urn:lsid:marinespecies.org:taxname:206989 Animalia Cnidaria Anthozoa
## 5  urn:lsid:marinespecies.org:taxname:206989 Animalia Cnidaria Anthozoa
## 6  urn:lsid:marinespecies.org:taxname:206989 Animalia Cnidaria Anthozoa
## 7  urn:lsid:marinespecies.org:taxname:430664 Animalia Cnidaria Anthozoa
## 8  urn:lsid:marinespecies.org:taxname:430664 Animalia Cnidaria Anthozoa
## 9  urn:lsid:marinespecies.org:taxname:430664 Animalia Cnidaria Anthozoa
## 10 urn:lsid:marinespecies.org:taxname:430664 Animalia Cnidaria Anthozoa
##          order          family    genus  scientificNameAuthorship
## 1  Scleractinia    Acroporidae Acropora      (Lamarck, 1816)
## 2  Scleractinia    Acroporidae Acropora      (Lamarck, 1816)
## 3  Scleractinia    Acroporidae Acropora      (Lamarck, 1816)
## 4  Scleractinia    Acroporidae Acropora      (Lamarck, 1816)
## 5  Scleractinia    Acroporidae Acropora      (Lamarck, 1816)
## 6  Scleractinia    Acroporidae Acropora      (Lamarck, 1816)
## 7  Scleractinia Pocilloporidae Madracis Locke, Weil & Coates, 2007
## 8  Scleractinia Pocilloporidae Madracis Locke, Weil & Coates, 2007
## 9  Scleractinia Pocilloporidae Madracis Locke, Weil & Coates, 2007
## 10 Scleractinia Pocilloporidae Madracis Locke, Weil & Coates, 2007
##          taxonRank
## 1  Species
## 2  Species
## 3  Species
## 4  Species
## 5  Species
## 6  Species
## 7  Species
## 8  Species
## 9  Species
## 10 Species

```

2.3. ALIGNING DATA TO DARWIN CORE - SAMPLING EVENT WITH MEASUREMENT OR FACT 35

Write out the file. All done with occurrence!

```
write.csv(occurrence, file="MadeUpData_Occurrence.csv", row.names=FALSE, fileEncoding="UTF-8", qu
```

The last file we need to create is the measurement or fact file. For this we need to combine all of the measurements or facts that we want to include making sure to include IDs from the BODC NERC vocabulary where possible.

```
temperature <- MadeUpDataForBiologicalDataTraining[c("eventID", "temperature", "date")]
temperature$occurrenceID <- ""
temperature$measurementType <- "temperature"
temperature$measurementTypeID <- "http://vocab.nerc.ac.uk/collection/P25/current/WTEMP/"
temperature$measurementValue <- temperature$temperature
temperature$measurementUnit <- "Celsius"
temperature$measurementUnitID <- "http://vocab.nerc.ac.uk/collection/P06/current/UPAA/"
temperature$measurementAccuracy <- 3
temperature$measurementDeterminedDate <- as.Date(temperature$date, format = "%m/%d/%Y")
temperature$measurementMethod <- ""
temperature$temperature <- NULL
temperature$date <- NULL
rugosity <- MadeUpDataForBiologicalDataTraining[c("eventID", "rugosity", "date")]
rugosity$occurrenceID <- ""
rugosity$measurementType <- "rugosity"
rugosity$measurementTypeID <- ""
rugosity$measurementValue <- rugosity$rugosity
rugosity$measurementUnit <- ""
rugosity$measurementUnitID <- ""
rugosity$measurementAccuracy <- ""
rugosity$measurementDeterminedDate <- as.Date(rugosity$date, format = "%m/%d/%Y")
rugosity$measurementMethod <- ""
rugosity$rugosity <- NULL
rugosity$date <- NULL
percentcover <- MadeUpDataForBiologicalDataTraining[c("eventID", "occurrenceID", "percent cover",
percentcover$measurementType <- "Percent Cover"
percentcover$measurementTypeID <- "http://vocab.nerc.ac.uk/collection/P01/current/SDBIOL10/"
percentcover$measurementValue <- percentcover$`percent cover`
percentcover$measurementUnit <- "Percent/100m^2"
percentcover$measurementUnitID <- ""
percentcover$measurementAccuracy <- 5
percentcover$measurementDeterminedDate <- as.Date(percentcover$date, format = "%m/%d/%Y")
percentcover$measurementMethod <- ""
percentcover$`percent cover` <- NULL
percentcover$date <- NULL
measurementOrFact <- rbind(temperature, rugosity, percentcover)
```

```
## Error in match.names(clabs, names(xi)): names do not match previous names
```

Let's check to see what it looks like

```
head(measurementOrFact, n = 50)
```

```
## # A tibble: 50 x 9
##   eventID occurrenceID measurementType measurementType~ measurementValue
##   <chr>    <chr>          <chr>          <chr>                <dbl>
## 1 St. Jo~ ""            temperature    ""                25.2
## 2 St. Jo~ ""            temperature    ""                25.2
## 3 St. Jo~ ""            temperature    ""                25.2
## 4 St. Jo~ ""            temperature    ""                25.2
## 5 St. Jo~ ""            temperature    ""                24.8
## 6 St. Jo~ ""            temperature    ""                24.8
## 7 St. Jo~ ""            temperature    ""                24.8
## 8 St. Jo~ ""            temperature    ""                24.8
## 9 St. Jo~ ""            temperature    ""                23.1
## 10 St. Jo~ ""           temperature    ""                23.1
## # ... with 40 more rows, and 4 more variables: measurementUnit <chr>,
## #   measurementUnitID <chr>, measurementDeterminedDate <date>,
## #   measurementMethod <chr>

write.csv(measurementOrFact, file="MadeUpData_mof.csv", row.names=FALSE, fileEncoding=
```

Chapter 3

Final Words

We have finished a nice book.

Chapter 4

Tools

Below are some of the tools and packages used in workflows. R and Python package “Type” is BIO for packages specifically for biological applications, and GEN for generic packages.

4.1 R

| Package | Type | Description |
|----------|------|--|
| bdveRse | BIO | A family of R packages for biodiversity data. |
| ecocomDP | BIO | Work with the Ecological Community Data Design Pattern. ‘ecocomDP’ is a flexible data model for harmonizing ecological community surveys, in a research question agnostic format, from source data published across repositories, and with methods that keep the derived data up-to-date as the underlying sources change. |

| Package | Type | Description |
|-------------------------|------|--|
| EDIorg/EMLassemblelylin | BIO | For scientists and data managers to create high quality EML metadata for dataset publication. |
| finch | BIO | Parse Darwin Core Files |
| iobis/obistools | BIO | Tools for data enhancement and quality control. |
| robis | BIO | R client for the OBIS API |
| ropensci/EML | BIO | Provides support for the serializing and parsing of all low-level EML concepts |
| taxize | BIO | Interacts with a suite of web ‘APIs’ for taxonomic tasks, such as getting database specific taxonomic identifiers, verifying species names, getting taxonomic hierarchies, fetching downstream and upstream taxonomic names, getting taxonomic synonyms, converting scientific to common names and vice versa, and more. |
| worms | BIO | Client for World Register of Marine Species. Includes functions for each of the API methods, including searching for names by name, date and common names, searching using external identifiers, fetching synonyms, as well as fetching taxonomic children and taxonomic classification. |

| Package | Type | Description |
|-----------|------|--|
| Hmisc | GEN | Contains many functions useful for data analysis, high-level graphics, utility operations, functions for computing sample size and power, simulation, importing and annotating datasets, imputing missing values, advanced table making, variable clustering, character string manipulation, conversion of R objects to LaTeX and html code, and recoding variables. Particularly check out the describe() function. |
| lubridate | GEN | Functions to work with date-times and time-spans: fast and user friendly parsing of date-time data, extraction and updating of components of a date-time (years, months, days, hours, minutes, and seconds), algebraic manipulation on date-time and time-span objects. |
| stringr | GEN | Simple, Consistent Wrappers for Common String Operations |

| Package | Type | Description |
|-----------|------|---|
| tidyverse | GEN | The ‘tidyverse’ is a set of packages that work in harmony because they share common data representations and ‘API’ design. This package is designed to make it easy to install and load multiple ‘tidyverse’ packages in a single step. |
| uuid | GEN | Tools for generating and handling of UUIDs (Universally Unique Identifiers). |

4.2 Python

| Package | Type | Description |
|--------------------|------|--|
| metatype | BIO | A lightweight Python 3 library for generating EML metadata |
| python-dwca-reader | BIO | A simple Python package to read and parse Darwin Core Archive (DwC-A) files, as produced by the GBIF website, the IPT and many other biodiversity informatics tools. |
| pyworms | BIO | Python client for the World Register of Marine Species (WoRMS) REST service. |

| Package | Type | Description |
|---------|------|--|
| numpy | GEN | NumPy (Numerical Python) is an open source Python library that's used in almost every field of science and engineering. It's the universal standard for working with numerical data in Python, and it's at the core of the scientific Python and PyData ecosystems. |
| pandas | GEN | pandas is a fast, powerful, flexible and easy to use open source data analysis and manipulation tool, built on top of the Python programming language. Super helpful when manipulating tabular data! |
| uuid | GEN | This module provides immutable UUID objects (class UUID) and the functions <code>uuid1()</code> , <code>uuid3()</code> , <code>uuid4()</code> , <code>uuid5()</code> for generating version 1, 3, 4, and 5 UUIDs as specified in RFC 4122. Built in – part of the Python standard library. |

4.3 Google Sheets

| Package | Description |
|--|--|
| Google Sheet DarwinCore Archive Assistant add-on | Google Sheet add-on which assists the creation of Darwin Core Archives (DwCA) and publishing to Zenodo. DwCA's are stored into user's Google Drive and can be downloaded for upload into IPT installations or other software which is able to read DwC-archives. |

4.4 Validators

| Name | Description |
|-------------------------------|--|
| Darwin Core Archive Validator | This validator verifies the structural integrity of a Darwin Core Archive. It does not check the data values, such as coordinates, dates or scientific names. |
| GBIF DATA VALIDATOR | The GBIF data validator is a service that allows anyone with a GBIF-relevant dataset to receive a report on the syntactical correctness and the validity of the content contained within the dataset. |
| LifeWatch Belgium | Through this interactive section of the LifeWatch.be portal users can upload their own data using a standard data format, and choose from several web services, models and applications to process the data. |

References

- Allaire, JJ, Yihui Xie, Jonathan McPherson, Javier Luraschi, Kevin Ushey, Aron Atkins, Hadley Wickham, Joe Cheng, Winston Chang, and Richard Iannone. 2021. *Rmarkdown: Dynamic Documents for r*. <https://CRAN.R-project.org/package=rmarkdown>.
- Bache, Stefan Milton, and Hadley Wickham. 2020. *Magrittr: A Forward-Pipe Operator for r*. <https://CRAN.R-project.org/package=magrittr>.
- Barbier, Edward B. 2017. “Marine Ecosystem Services.” *Current Biology*. Cell Press. <https://doi.org/10.1016/j.cub.2017.03.020>.
- Benson, Abigail, Cassandra M. Brooks, Gabrielle Canonico, Emmett Duffy, Frank Muller-Karger, Heidi M. Sosik, Patricia Miloslavich, and Eduardo Klein. 2018. “Integrated Observations and Informatics Improve Understanding of Changing Marine Ecosystems.” *Frontiers in Marine Science*. Frontiers Media S.A. <https://doi.org/10.3389/fmars.2018.00428>.
- Benson, Abigail, Diana LaScala-Gruenewald, Robert McGuinn, Erin Satterthwaite, Stace Beaulieu, Mathew Biddle, Lynn deWitt, et al. 2021. “Biological Observation Data Standardization - a Primer for Data Managers.” ESIP. <https://doi.org/10.6084/m9.figshare.16806712.v1>.
- Benson, Abigail, Tylar Murray, Gabrielle Canonico, Enrique Montes, Frank Muller-Karger, Maria T. Kavanaugh, Joaquin Trinanes, and Lynn M. deWitt. 2021. “Data Management and Interactive Visualizations for the Evolving Marine Biodiversity Observation Network.” *Oceanography*. <https://doi.org/10.5670/oceanog.2021.220>.
- Borer, Elizabeth T., Eric W. Seabloom, Matthew B. Jones, and Mark Schilbauer. 2009. “Some Simple Guidelines for Effective Data Management.” *Bulletin of the Ecological Society of America* 90 (April). <https://doi.org/10.1890/0012-9623-90.2.205>.
- Canonico, Gabrielle, Pier Luigi Buttigieg, Enrique Montes, Frank E. Muller-Karger, Carol Stepien, Dawn Wright, Abigail Benson, et al. 2019. “Global Observational Needs and Resources for Marine Biodiversity.” *Frontiers in Marine Science*. Frontiers Media S.A. <https://doi.org/10.3389/fmars.2019.00367>.
- Chamberlain, Scott. 2020. *Worrms: World Register of Marine Species (WoRMS) Client*. <https://CRAN.R-project.org/package=worms>.
- Crystal-Ornelas, Robert, Charuleka Varadharajan, Ben Bond-Lamberty, Kristin

- Boye, Madison Burrus, Shreyas Cholia, Michael Crow, et al. 2021. “A Guide to Using GitHub for Developing and Versioning Data Standards and Reporting Formats.” *Earth and Space Science*, July, e2021EA001797. <https://doi.org/10.1029/2021EA001797>.
- Davies, Neil, John Deck, Eric C Kansa, Sarah Whitcher Kansa, John Kunze, Christopher Meyer, Thomas Orrell, et al. 2021. “Internet of Samples (iSamples): Toward an Interdisciplinary Cyberinfrastructure for Material Samples.” *GigaScience* 10: 1–5. <https://doi.org/10.1093/gigascience/giab028>.
- Djurhuus, Anni, Collin J. Closek, Ryan P. Kelly, Kathleen J. Pitz, Reiko P. Michisaki, Hilary A. Starks, Kristine R. Walz, et al. 2020. “Environmental DNA Reveals Seasonal Shifts and Potential Interactions in a Marine Community.” *Nature Communications* 11 (December): 1–9. <https://doi.org/10.1038/s41467-019-14105-1>.
- Duffy, J. Emmett, Linda A. Amaral-Zettler, Daphne G. Fautin, Gustav Paulay, Tatiana A. Rynearson, Heidi M. Sosik, and John J. Stachowicz. 2013. “Envisioning a Marine Biodiversity Observation Network.” *BioScience* 63 (May): 350–61. <https://doi.org/10.1525/bio.2013.63.5.8>.
- Fornwall, M, R Gisiner, S E Simmons, H Moustahfid, G Canonico, P Halpin, P Goldstein, et al. 2012. “Expanding Biological Data Standards Development Processes for US IOOS: Visual Line Transect Observing Community for Mammal, Bird, and Turtle Data.” IOOS. <https://www.researchgate.net/publication/255681522>.
- Grolemund, Garrett, and Hadley Wickham. 2011. “Dates and Times Made Easy with lubridate.” *Journal of Statistical Software* 40 (3): 1–25. <https://www.jstatsoft.org/v40/i03/>.
- Hardisty, Alex R., William K. Michener, Donat Agosti, Enrique Alonso García, Lucy Bastin, Lee Belbin, Anne Bowser, et al. 2019. “The Bari Manifesto: An Interoperability Framework for Essential Biodiversity Variables.” *Ecological Informatics* 49 (January): 22–31. <https://doi.org/10.1016/j.ecoinf.2018.11.003>.
- Heberling, J Mason, Joseph T Miller, Daniel Noesgaard, Scott B Weingart C, Dmitry Schigel, and Douglas E Soltis. 2021. “Data Integration Enables Global Biodiversity Synthesis.” *Proceedings of the National Academy of Sciences of the United States of America*. <https://doi.org/10.1073/pnas.2018093118/-/DCSupplemental>.
- Henry, Lionel, and Hadley Wickham. 2020. *Purrr: Functional Programming Tools*. <https://CRAN.R-project.org/package=purrr>.
- Jonathan A. Hare, Mark W. Nelson, Wendy E. Morrison. n.d. “A Vulnerability Assessment of Fish and Invertebrates to Climate Change on the Northeast u.s. Continental Shelf.” *PLoS ONE* 11 (2): e0146756. <https://doi.org/10.1371/journal.pone.0146756>.
- Jones, Matthew B., Mark P. Schildhauer, O. J. Reichman, and Shawn Bowers. 2006. “The New Bioinformatics: Integrating Ecological Data from the Gene to the Biosphere.” *Annual Review of Ecology, Evolution, and Systematics*. <https://doi.org/10.1146/annurev.ecolsys.37.091305.110031>.
- Kavanaugh, Maria T., Matthew J. Oliver, Francisco P. Chavez, Ricardo M.

- Letelier, Frank E. Muller-Karger, and Scott C. Doney. 2016. “Seascapes as a New Vernacular for Pelagic Ocean Monitoring, Management and Conservation.” *ICES Journal of Marine Science* 73 (July): 1839–50. <https://doi.org/10.1093/icesjms/fsw086>.
- Kot, Connie Y., Ei Fujioka, Lucie J. Hazen, Benjamin D. Best, Andrew J. Read, and Patrick N. Halpin. 2010. “Spatio-Temporal Gap Analysis of OBIS-SEAMAP Project Data: Assessment and Way Forward.” *PLoS ONE* 5 (September): 12990. <https://doi.org/10.1371/journal.pone.0012990>.
- Lab, Malin Pinsky. n.d. “OceanAdapt.” *GitHub*. <https://oceanadapt.rutgers.edu/>.
- Lamprecht, Anna-Lena, Leyla Garcia, Mateusz Kuzak, Carlos Martinez, Ricardo Arcila, Eva Martin Del Pico, Victoria Dominguez Del Angel, et al. 2019. “Towards FAIR Principles for Research Software.” Edited by Paul Groth. *Data Science*, 1–23. <https://doi.org/10.3233/DS-190026>.
- Maria Dornelas, Brian McGill, Nicholas J. Gotelli. 2014. “Assemblage Time Series Reveal Biodiversity Change but Not Systematic Loss.” *Science* 344 (6181): 296–99. <https://doi.org/10.1126/science.1248484>.
- McKenna, Megan F., Simone Baumann-Pickering, Annebelle C. M. Kok, William K. Oestreich, Jeffrey D. Adams, Jack Barkowski, Kurt M. Frstrup, et al. 2021. “Advancing the Interpretation of Shallow Water Marine Soundscapes.” *Frontiers in Marine Science* 0 (September): 1426. <https://doi.org/10.3389/FMARS.2021.719258>.
- Miloslavich, Patricia, Nicholas J. Bax, Samantha E. Simmons, Eduardo Klein, Ward Appeltans, Octavio Aburto-Oropeza, Melissa Andersen Garcia, et al. 2018. “Essential Ocean Variables for Global Sustained Observations of Biodiversity and Ecosystem Changes.” *Global Change Biology* 24 (June): 2416–33. <https://doi.org/10.1111/gcb.14108>.
- Montes, Enrique, Anni Djurhuus, Frank E. Muller-Karger, Daniel Otis, Christopher R. Kelble, and Maria T. Kavanaugh. 2020. “Dynamic Satellite Seascapes as a Biogeographic Framework for Understanding Phytoplankton Assemblages in the Florida Keys National Marine Sanctuary, United States.” *Frontiers in Marine Science* 7 (July): 575. <https://doi.org/10.3389/fmars.2020.00575>.
- Moustahfid, Hassan, and Philip Goldstein. 2014. “IOOS Biological Data Services Enrollment Procedures.”
- Moustahfid, Hassan, Jim Potemra, Philip Goldstein, Roy Mendelsohn, and Annette Desrochers. 2011. “Making United States Integrated Ocean Observing System (u.s. IOOS) Inclusive of Marine Biological Resources.” <https://www.researchgate.net/publication/254013004>.
- Müller, Kirill. 2020. *Here: A Simpler Way to Find Your Files*. <https://CRAN.R-project.org/package=here>.
- Müller, Kirill, and Hadley Wickham. 2021. *Tibble: Simple Data Frames*. <https://CRAN.R-project.org/package=tibble>.
- Muller-Karger, Frank E., Erin Hestir, Christiana Ade, Kevin Turpie, Dar A. Roberts, David Siegel, Robert J. Miller, et al. 2018. “Satellite Sensor Requirements for Monitoring Essential Biodiversity Variables of Coastal

- Ecosystems.” *Ecological Applications* 28 (April): 749–60. <https://doi.org/10.1002/eap.1682>.
- Muller-Karger, Frank E., Patricia Miloslavich, Nicholas J. Bax, Samantha Simmons, Mark J. Costello, Isabel Sousa Pinto, Gabrielle Canonico, et al. 2018. “Advancing Marine Biological Observations and Data Requirements of the Complementary Essential Ocean Variables (EOVs) and Essential Biodiversity Variables (EBVs) Frameworks.” *Frontiers in Marine Science*. Frontiers Media S.A. <https://doi.org/10.3389/fmars.2018.00211>.
- Neeley, Aimee, Stace E. Beaulieu, Chris Proctor, Ivona Cetinić, Joe Futrelle, Inia Soto Ramos, Heidi M. Sosik, et al. 2021. “Standards and Practices for Reporting Plankton and Other Particle Observations from Images.” <https://doi.org/10.1575/1912/27377>.
- O’Brien, Margaret, Colin A. Smith, Eric R. Sokol, Corinna Gries, Nina Lany, Sydne Record, and Max C. N. Castorani. 2021. “ecocomDP: A Flexible Data Design Pattern for Ecological Community Survey Data.” *Ecological Informatics* 64 (September): 101374. <https://doi.org/10.1016/J.ECOINF.2021.101374>.
- Pooter, Daphnis De, Ward Appeltans, Nicolas Bailly, Sky Bristol, Klaas Deneudt, Menashè Eliezer, Ei Fujioka, et al. 2017. “Toward a New Data Standard for Combined Marine Biological and Environmental Datasets - Expanding OBIS Beyond Species Occurrences.” *Biodiversity Data Journal* 5 (January): 10989. <https://doi.org/10.3897/BDJ.5.e10989>.
- Provoost, Pieter. n.d. “Iobis/Ebsa.” *GitHub*. <https://github.com/iobis/ebsa>.
- R Core Team. 2021. *R: A Language and Environment for Statistical Computing*. Vienna, Austria: R Foundation for Statistical Computing. <https://www.R-project.org/>.
- Rücknagel, J., P. Vierkant, R. Ulrich, G. Kloska, E. Schnepf, D. Fichtmüller, E. Reuter, et al. 2015. “Metadata Schema for the Description of Research Data Repositories. Version 3.0.” <https://doi.org/10.2312/re3.008>.
- Rule, Adam, Amanda Birmingham, Cristal Zuniga, Ilkay Altintas, Shih-Cheng Huang, Rob Knight, Niema Moshiri, et al. 2019. “Ten Simple Rules for Writing and Sharing Computational Analyses in Jupyter Notebooks.” *PLOS Computational Biology* 15 (July): e1007007. <https://doi.org/10.1371/JOURNAL.PCBI.1007007>.
- Santora, Jarrod A., Elliott L. Hazen, Isaac D. Schroeder, Steven J. Bograd, Keith M. Sakuma, and John C. Field. 2017. “Impacts of Ocean Climate Variability on Biodiversity of Pelagic Forage Species in an Upwelling Ecosystem.” *Marine Ecology Progress Series* 580 (September): 205–20. <https://doi.org/10.3354/meps12278>.
- Schmid, Moritz S, Dominic Daprano, Kyler M Jacobson, Christopher Sullivan, Christian Briseño-Avena, Jessica Y Luo, and Robert K Cowen. 2021. *A Convolutional Neural Network Based High-Throughput Image Classification Pipeline - Code and Documentation to Process Plankton Underwater Imagery Using Local HPC Infrastructure and NSF’s XSEDE*. Zenodo. <https://doi.org/10.5281/ZENODO.4641158>.
- Spinu, Vitalie, Garrett Grolemond, and Hadley Wickham. 2021. *Lubridate*:

- Make Dealing with Dates a Little Easier.* <https://CRAN.R-project.org/package=lubridate>.
- Taylor, Gordon T., Frank E. Muller-Karger, Robert C. Thunell, Mary I. Scranton, Yrene Astor, Ramon Varela, Luis Troccoli Ghinaglia, et al. 2012. “Ecosystem Responses in the Southern Caribbean Sea to Global Climate Change.” *Proceedings of the National Academy of Sciences of the United States of America* 109 (November): 19315–20. <https://doi.org/10.1073/pnas.1207514109>.
- Tittensor, Derek P, Camilo Mora, Walter Jetz, Heike K Lotze, Daniel Ricard, Edward Vanden Berghe, and Boris Worm. 2010. “Global Patterns and Predictors of Marine Biodiversity Across Taxa.” *Nature* 466 (7310): 1098.
- Warren, R., J. Price, E. Graham, N. Forstnerhaeusler, and J. VanDerWal. 2018. “The Projected Effect on Insects, Vertebrates, and Plants of Limiting Global Warming to 1.5°C Rather Than 2°C.” *Science* 360 (May): 791–95. <https://doi.org/10.1126/science.aar3646>.
- Wickham, Hadley. 2016. *Ggplot2: Elegant Graphics for Data Analysis*. Springer-Verlag New York. <https://ggplot2.tidyverse.org>.
- . 2019. *Stringr: Simple, Consistent Wrappers for Common String Operations*. <https://CRAN.R-project.org/package=stringr>.
- . 2021a. *Forcats: Tools for Working with Categorical Variables (Factors)*. <https://CRAN.R-project.org/package=forcats>.
- . 2021b. *Tidyr: Tidy Messy Data*. <https://CRAN.R-project.org/package=tidyr>.
- . 2021c. *Tidyverse: Easily Install and Load the Tidyverse*. <https://CRAN.R-project.org/package=tidyverse>.
- Wickham, Hadley, Mara Averick, Jennifer Bryan, Winston Chang, Lucy D’Agostino McGowan, Romain François, Garrett Grolemond, et al. 2019. “Welcome to the tidyverse.” *Journal of Open Source Software* 4 (43): 1686. <https://doi.org/10.21105/joss.01686>.
- Wickham, Hadley, Winston Chang, Lionel Henry, Thomas Lin Pedersen, Kohske Takahashi, Claus Wilke, Kara Woo, Hiroaki Yutani, and Dewey Dunnington. 2021. *Ggplot2: Create Elegant Data Visualisations Using the Grammar of Graphics*. <https://CRAN.R-project.org/package=ggplot2>.
- Wickham, Hadley, Romain François, Lionel Henry, and Kirill Müller. 2021. *Dplyr: A Grammar of Data Manipulation*. <https://CRAN.R-project.org/package=dplyr>.
- Wickham, Hadley, and Jim Hester. 2021. *Readr: Read Rectangular Text Data*. <https://CRAN.R-project.org/package=readr>.
- Wieczorek, John, David Bloom, Robert Guralnick, Stan Blum, Markus Döring, Renato Giovanni, Tim Robertson, and David Vieglais. 2012. “Darwin Core: An Evolving Community-Developed Biodiversity Data Standard.” *PLoS ONE* 7 (January): 29715. <https://doi.org/10.1371/journal.pone.0029715>.
- Wilkinson, Mark D., Michel Dumontier, IJsbrand Jan Aalbersberg, Gabrielle Appleton, Myles Axton, Arie Baak, Niklas Blomberg, et al. 2016. “The FAIR Guiding Principles for Scientific Data Management and Stewardship.” *Scientific Data* 3 (March): 1–9. <https://doi.org/10.1038/sdata.2016.18>.

- Xie, Yihui. 2014. “Knitr: A Comprehensive Tool for Reproducible Research in R.” In *Implementing Reproducible Computational Research*, edited by Victoria Stodden, Friedrich Leisch, and Roger D. Peng. Chapman; Hall/CRC. <http://www.crcpress.com/product/isbn/9781466561595>.
- . 2015b. *Dynamic Documents with R and Knitr*. 2nd ed. Boca Raton, Florida: Chapman; Hall/CRC. <http://yihui.name/knitr/>.
- . 2015a. *Dynamic Documents with R and Knitr*. 2nd ed. Boca Raton, Florida: Chapman; Hall/CRC. <https://yihui.org/knitr/>.
- . 2016. *Bookdown: Authoring Books and Technical Documents with R Markdown*. Boca Raton, Florida: Chapman; Hall/CRC. <https://bookdown.org/yihui/bookdown>.
- . 2021a. *Bookdown: Authoring Books and Technical Documents with r Markdown*. <https://CRAN.R-project.org/package=bookdown>.
- . 2021b. *Knitr: A General-Purpose Package for Dynamic Report Generation in r*. <https://yihui.org/knitr/>.
- Xie, Yihui, J. J. Allaire, and Garrett Grolemund. 2018. *R Markdown: The Definitive Guide*. Boca Raton, Florida: Chapman; Hall/CRC. <https://bookdown.org/yihui/rmarkdown>.
- Xie, Yihui, Christophe Dervieux, and Emily Riederer. 2020. *R Markdown Cookbook*. Boca Raton, Florida: Chapman; Hall/CRC. <https://bookdown.org/yihui/rmarkdown-cookbook>.