

Lecture Notes for **Neural Networks and Machine Learning**



Neural Style Transfer
Model Optimization



Logistics and Agenda

- Logistics
 - Next Assignment: Style Transfer
 - Next Lecture: “Fast Style Transfer” Student Presentation
- Agenda
 - *A History of Style Transfer (last time)*
 - *Image Optimization Algorithms (last time)*
 - Student Paper Presentation
 - Model Optimization Algorithms (today)
 - One Shot Algorithms (today)
 - Evaluating Style Transfer Performance
 - Extensions in Other Domains





Model Optimization Based Style Transfer



zach lieberman
@zachlieberman



C++ for kids



Paper Presentation

Perceptual Losses for Real-Time Style Transfer and Super-Resolution

Justin Johnson, Alexandre Alahi, Li Fei-Fei
{jcjohns, alahi, feifeili}@cs.stanford.edu

Department of Computer Science, Stanford University

Abstract. We consider image transformation problems, where an input image is transformed into an output image. Recent methods for such




One other thought!

- I hate the term **perceptual loss**!
- It's marketing! Joy!
- ...but not good science verbiage
- ...like the term global warming
 - it can introduce subjective opinion, misunderstanding through misleading labeling
- There is nothing perceptual here, its a neural network
- A better description of the loss:
 - Convolutional Gram Loss?
 - Information Distillation Covariance?
 - Weighted Grammian Norm (WGN Loss)?
- Just don't say "perceptual" in this class (so you don't fail)




Johnson Paper Recap (if needed)

- **Basic Idea:** replace image optimization with single pass, fully convolutional network to perform the transformation
- Loss functions stay identical to Gatys
 - “Content” through activations difference
 - “Style” through Gramian differences
- Instances are normalized along the channel input
- No bias in filters



Specifics of the Architecture

Layer	Activation size
Input	$3 \times 256 \times 256$
$32 \times 9 \times 9$ conv, stride 1	$32 \times 256 \times 256$
$64 \times 3 \times 3$ conv, stride 2	$64 \times 128 \times 128$
$128 \times 3 \times 3$ conv, stride 2	$128 \times 64 \times 64$
Residual block, 128 filters	$128 \times 64 \times 64$
Residual block, 128 filters	$128 \times 64 \times 64$
Residual block, 128 filters	$128 \times 64 \times 64$
Residual block, 128 filters	$128 \times 64 \times 64$
$64 \times 3 \times 3$ conv, stride 1/2	$64 \times 128 \times 128$
$32 \times 3 \times 3$ conv, stride 1/2	$32 \times 256 \times 256$
$3 \times 9 \times 9$ conv, stride 1	$3 \times 256 \times 256$



Methods	Time(s)			Styles/Model
	256×256	512×512	1024×1024	
Gatys et al. [10]	14.32	51.19	200.3	∞
Johnson et al. [47]	0.014	0.045	0.166	1



Johnson Paper Extensions

- Multi-style transfer:

Set of Style Images For each Style Image

$$\mathcal{L}_s(I_{s0}, \dots, I_{sN}, I_{new}) = \sum_{i=0}^N \beta_i \sum_{l \in L_s} \|G_{si}^{(l)} - G_{new}^{(l)}\|^2$$



(a) A Starry Night



(b) 100% / 0%



(c) 75% / 25%



(d) 50% / 50%



(e) 25% / 75%



(f) 0% / 100%



(g) The Scream



(h) The Great Wave



(i) 100% / 0%



(j) 75% / 25%



(k) 50% / 50%



(l) 25% / 75%



(m) 0% / 100%



(n) Rain Princess



Fast Style Paper Extensions


- Color Preservation:
 - Apply style to luminance only
 - Reapply color channels from original image (blurred)
 - $HS\{V_{\text{transform}}\}$






Model Based Optimization Style Transfer

Johnson, *et. al* Fast Style Transfer



Jake Carlson



Justin Ledford



Luke Wood

Follow Along: `LectureNotesMaster/03 LectureStyleTransfer.ipynb`
Training: https://github.com/8000net/StyleTransfer/blob/master/Style_Transfer_Training.ipynb



One Shot Transfer



🔥🔥 Robert Osazuwa Ness 🔥🔥
@osazuwa

...

There is a cognitive bias call "law of the instrument", as in "if all you have is a hammer, everything looks like a nail."

I propose "dogma of the instrument."
It refers to the following reasoning:

"I successfully smashed something with my hammer. It must have been a nail."



The Problem of Training

- One network is only capable of one style transformation
 - Great for trained filters in an app
 - Does not work for generic transfer of one style to another
- How to define a transformation on a content and style image that transfers style into the content?
 - ...without any “per style” training
 - ...but still using the “grammian style losses”
 - ...and allows for infinite customization?
- We need to first cover **whitening** and **coloring** transformations



Aside: Whitening and Coloring

- Signal processing terms applied typically to spectra of signals
- **Whitening** is the process of removing correlation in a signal
 - For a matrix, the whitening transform:
 - ◆ makes covariance nearly diagonal (identity)
 - ◆ using only linear operations
- **Coloring** is the process of adding the observed correlation back into a signal
 - For a matrix, the coloring transform
 - ◆ makes the covariance of signal A as close as possible to signal B (the target)
 - ◆ with only linear operations to A



Aside: Whitening with SVD

- Singular Value Decomposition (SVD) decomposes a matrix into three elements
 - $A = U\Sigma V^T$
 - U is eig-vec of AA^T and V is eig-vec of A^TA
 - where U and V are orthogonal matrices such that
$$UU^T=I \quad \text{and} \quad VV^T=I$$
 - Σ is a diagonal matrix of the singular values
- the matrix $UV^T=A_w$ is a whitened version of the signal A such that
$$A_w A_w^T=I$$
- since the Gram of a layer activation is $A A^T=G$, the whitened signal has $A_w A_w^T = I = G$
 - which would have “no style” according to Gatys



Coloring with SVD

- Suppose we have two activations
 - $A_c = U_c \Sigma_c V_c^T$ and $G_c = A_c A_c^T$
 - $A_s = U_s \Sigma_s V_s^T$ and $G_s = A_s A_s^T$
- We can transfer the Gram matrix of A_s to A_c using coloring
 - To color the matrix:
$$A_{new} = U_s \Sigma_s V_c^T$$
$$A_{new} A_{new}^T = G_s$$
 - But A_{new} is more similar to A_c than A_s
- That is exactly what we want for style transfer!
- *Can also achieve coloring and whitening through the Eigen decomposition, but is less numerically stable*
 - *(but can be faster)*





Whitening and Coloring


What does this all mean?
Developing an intuition...

Follow Along:
`03b WhiteningColoringExample.ipynb`




How to use this for style transfer?

- If we can learn to **reconstruct an image from VGG...**
 - ...we can **whiten content activations**
 - ...then **color with desired style Grammmian**
- The resulting reconstruction should have largely the same content, but style from the colored activations
- ...One transformation network for any style!




Multi-Staged WCT



Why not go the other way?

- Start at earlier layers and apply WCT as we progress through the network
- Paper does not have good explanation, but results are subjectively poorer:



$L > L-1 > L-2 > L-3$



$L-3 > L-2 > L-1 > L$




Removing Style? Only Whitening





One Shot Style Transfer

Li, *et. al* Universal Style Transfer



justinledford



Justin Ledford •

Follow Along: <https://github.com/8000net/universal-style-transfer-keras>



Lecture Notes for **Neural Networks and Machine Learning**

Style Transfer: Model Opt.



Next Time:
Photo Realistic WCT
Reading: None

