

Lecture Notes for **Neural Networks and Machine Learning**



Deep Transfer Learning
and Demo



Logistics and Agenda

- Logistics
 - Welcome back from Snow days... Updated Schedule!
- Agenda
 - Transfer Learning in Deep Learning
 - Transfer Learning Demo
 - Town Hall
- Next Time:
 - Transformers for Text and Vision
- Next Next Time
 - Self-Supervised Learning and Consistency Loss



Last Time, ConceptNet and Transfer Learning

$$X = x_1, x_2, \dots, x_N \in \mathcal{X}$$

$$Y = y_1, y_2, \dots, y_N \in \mathcal{Y}$$

Transfer learning be like

$$\mathcal{D} = \{\mathcal{X}, p(X)\}$$

Domain Feature Space Probability Observation

$$\mathcal{T} = \{\mathcal{Y}, p(Y|X)\}$$

Task Label Space Learned Probability

- Image Pixels
- Sensor Readings
- Natural Language
- *Almost anything that we can represent as a feature*

- Object Classification
- Dolphin/Shark Classification
- Sentiment Analysis
- *Any labeled task for which we might be able to build a classifier*



How to Make a Racist AI without Really Trying





Robyn Speer, 2017

<http://blog.conceptnet.io/posts/2017/how-to-make-a-racist-ai-without-really-trying/>



Lab One Town Hall

Ethical Machine Learning Bias Reduction with Neural Networks



Transfer Learning with Neural Networks

Found in a recent paper:

6 Unrelated Work

This paper is not related to [8, 23, 48, 13, 35] in any way, but we think everyone should read these papers because: (1) they're real good, (2) my friends also need those citations.

7 Related Work



Deep Transfer Learning

- Almost always **Inductive Transfer**
 - (new task , same domain, or domain adaptation)
- Almost always **Feature Representation Transfer**
 - like image pre-training
- All other topics are mostly open research topics that maybe one of you will solve!



(Sun, B., Feng, J., & Saenko, K. (2016). Return of Frustratingly Easy Domain Adaptation)


20



Approaches with Deep Learning


- **Feature Extraction Transfer**

- Most well known: use learned parameters from one task in another task in same domain
- Most useful when labels for target domain are sparse



Defining the Bottleneck

- Frozen training layers before bottleneck:
 - Why waste computations?
 - Computing more than one forward pass on the same data—just save them out
 - *Unless* using augmentation
- In Keras, build multiple models with different entry points



- **Input to Bottleneck**

```
inputs = Input(shape=(IMG_SIZE, IMG_SIZE, 3))
model_base = VGG(include_top=False,
                  input_tensor=inputs, weights="imagenet")
```

- **Bottleneck to Output**

```
bottleneck = Input(shape=model_base.output.shape)
outputs = Dense(NUM_CLASSES)(bottleneck)
model_top = Model(bottleneck, outputs)
```


- **Input to Output**

```
model_total = Model(inputs, outputs)
```



Freezing and Fine-tuning

- Step 1, Freeze base model:
 - No update during back-propagation
 - Only update layers after the bottleneck
 - *Optional: Augment a set of training data*
 - Send training dataset through base model
 - ◆ Save out bottleneck features
 - Train bottleneck features in new task
 - ◆ Typically 5-10 epochs is sufficient, easy to overfit
 - ◆ Larger training step size is okay
- Step 2, Fine-tune, unfreeze a few layers in base model:
 - *Optional: Setup images to use some type of augmentation*
 - Attach newly trained model to pre-trained model
 - Train to your hearts content, use smaller training step size





Bottlenecking on a GPU

Dogs versus Cats



justinledford Justin Ledford

Member of **8000net**



eclarson Eric Larson

Updated for `tf==2.9` in the Main Repository:
[02 Transfer Learning.ipynb](#)

Original Example: <https://github.com/8000net/Transfer-Learning-Dolphins-and-Sharks>



Justin Ledford ·

Another Great Example:
https://keras.io/examples/vision/image_classification_efficientnet_fine_tuning/



Popular Transfer Learning Models

- **Vision:**
 - Conv Architectures:
 - ◆ VGG, Inception, ResNet, Xception, EfficientNet
 - ◆ ViT: Huge ViT
- **Audio:**
 - WaveNet, VGGish
- **Text:**
 - Word Embedding
 - ◆ Glove, Word2Vec, ConceptNet
 - Sentence Embedding
 - ◆ Universal Sentence Encoders (Google)
 - ◆ BERT (Google)
 - ◆ GPT-X
- **From SMU PhD Students in my Research Lab:**
 - VGG for transferring to gaze classification
 - VGG for swapped face detection
 - Domain adaptation for speaker authentication
 - YOLO/DarkNet for surgical instrument detection
 - GLOVE for similar instructions in a maintenance manual
 - BERT for student vocabulary acquisition



Lecture Notes for **Neural Networks and Machine Learning**

Transfer Learning



Next Time:
Transformers
Reading: None

