

Global ERP -- Comprehensive Audit Report

Date: 2026-03-30 **Scope:** Full codebase audit (apps/web/, packages/ai-core/) **Areas:** Security, Performance, Data Integrity & Cleanliness **Tech Stack:** Next.js 16, TypeScript, PostgreSQL 16, Turbo Monorepo

Executive Summary

This audit reviewed the Global ERP codebase across three critical dimensions: **Security**, **Performance**, and **Data Integrity**. The system has **72 findings** across all categories, including **11 Critical**, **22 High**, **20 Medium**, and **7 Low** severity issues.

Critical Issues Requiring Immediate Action

#	Category	Issue	Impact
1	Security	Middleware exempts nearly all API routes from authentication	Any unauthenticated user can access company data, accounting, files
2	Security	OpenAI API key committed to repository <code>.env</code>	API key theft, financial abuse
3	Security	Hardcoded admin password <code>Admin@123</code> for all companies	Trivial account takeover
4	Data	No permission checks on entire Workshop module (invoices, estimates, gatepass)	Any authenticated user can create invoices, release cars
5	Data	No permission checks on individual lead routes (GET/PATCH/DELETE)	Any user can read/modify/delete any lead
6	Data	No permission checks on Sales leads routes	Unauthorized sales data access
7	Data	Lead deletion leaves orphan inspections, estimates, work orders, invoices	Data corruption, ghost records
8	Data	Multiple core tables lack FK on <code>company_id</code>	Cross-tenant data corruption possible
9	Performance	Database connection pool <code>max: 1</code>	All queries serialize under load, system-wide bottleneck
10	Performance	Bulk customer assignment runs 3 queries per row in a loop	1500+ queries for 500 customers
11	Data	Estimates default query limit of 200,000 rows	Out-of-memory crashes

Part 1: Security Audit

1.1 Authentication & Authorization

CRITICAL: Overly Broad Public Path Configuration

- **File:** `middleware.ts` (lines 12-25)
- **Description:** The middleware uses `startsWith` matching for public paths. The following prefixes bypass authentication entirely:
 - `/api/customers` -- ALL customer API routes
 - `/api/company` -- ALL company-scoped routes (workshop, accounting, call-center, AI, fleet, branches)
 - `/api/cars` -- ALL car API routes
 - `/api/files` -- ALL file upload/download routes
 - `/api/global/leads` -- ALL global lead routes
 - `/api/mobile` -- ALL mobile API routes
- **Impact:** The middleware cookie check is effectively bypassed for the majority of API routes.
- **Recommendation:** Restrict public paths to only genuinely public routes (e.g., `/api/public/`). Use exact matches.


CRITICAL: Many API Routes Completely Unauthenticated

- **Description:** Because middleware passes them through AND they have no internal auth check:

Route	Methods	Data Exposed
<code>/api/accounting/accounts</code>	GET, POST, PATCH	Chart of accounts
<code>/api/accounting/groups</code>	GET, POST, DELETE	Accounting groups
<code>/api/accounting/headings</code>	GET, POST	Accounting headings
<code>/api/accounting/invoices</code>	GET, POST	Billing invoices
<code>/api/accounting/invoices/[id]</code>	GET, PATCH	Individual invoice data
<code>/api/accounting/org-profile</code>	GET, PUT	Organization profile
<code>/api/products</code>	GET	Product catalog
<code>/api/dialer/integrations</code>	GET, POST	Dialer integrations
<code>/api/channels/integrations</code>	GET, POST	Channel credentials
<code>/api/global/call-center/incoming/stream</code>	GET	Live call center SSE stream
<code>/api/files/upload</code>	POST	Unrestricted file upload
<code>/api/files/[fileId]</code>	GET	Any uploaded file

HIGH: Permission Check Bypass in Customers Route

- **File:** `customers/route.ts` (lines 62-74)
- **Description:** The GET handler catches permission failures and logs a warning but continues serving data:



```
if (permResp.status >= 400) {  
  console.warn("Skipping permission enforcement for customers view");  
}
```

MEDIUM: Session Tokens Have No Expiry

- **File:** [session.ts](#) (lines 36-61)
- **Description:** Session tokens include `iat` but no `exp`. Token valid indefinitely if extracted. Cookie has 7-day `maxAge` but the token itself never expires.

MEDIUM: No Company/Branch Ownership Validation

- **Description:** Routes under `/api/company/[companyId]/...` extract `companyId` from URL but don't verify the authenticated user belongs to that company. User from Company A could access Company B's data.

1.2 SQL Injection

GOOD: SQL Library Uses Parameterized Queries

- The `postgres` library's tagged template literals automatically parameterize values. The vast majority of queries are safe.

LOW: `sql.unsafe()` in tmp Script

- **File:** `tmp/check-inquiry.mjs` (line 5) -- Direct string interpolation in debug script. Not deployed but risky if copy-pasted.

1.3 IDOR (Insecure Direct Object Reference)

HIGH: Global Leads Accessible Without Ownership Check

- **File:** [global/leads/\[id\]/route.ts](#) (lines 47-56)
- **Description:** GET handler allows anonymous access (catches auth errors, continues with `currentUser = null`). Any lead retrievable by ID.

MEDIUM: File Download Without Access Control

- **File:** [files/\[fileId\]/route.ts](#) (lines 8-45)
- **Description:** Any file downloadable by guessing UUID. No authentication, no ownership validation.

1.4 Rate Limiting

HIGH: No Rate Limiting on Authentication Endpoints

- **Files:** [auth/login/route.ts](#), [mobile/auth/login/route.ts](#)
- **Description:** Neither endpoint has rate limiting. Brute force attacks possible.
- **Note:** A `createRateLimiter` utility exists in `tmp/zip_compare/` but was never deployed.

HIGH: No Rate Limiting on Public API Endpoints

- **Description:** `/api/public/recovery-requests/`, `/api/public/pre-inspection/`, `/api/files/upload` have no rate limiting.

1.5 Webhook Security

HIGH: Webhook Endpoints Lack Signature Verification

- **Files:** `webhooks/dialer/[providerKey]/route.ts`, `webhooks/channels/[providerKey]/route.ts`
- **Description:** Both accept any POST without verifying HMAC or shared secret. Attacker can inject fake call events and trigger AI workflows.

1.6 File Upload Security

HIGH: No File Size Limit on Upload

- **File:** `files/upload/route.ts` (lines 21-114)
- **Description:** No maximum file size enforcement. Disk exhaustion possible.

MEDIUM: No File Type Restriction

- **Description:** Accepts any MIME type. No allowlist. Executable/malicious files can be uploaded.

MEDIUM: No Authentication on File Upload

- **Description:** `uploadedBy` always set to `null`. Anyone can upload files anonymously.

1.7 Sensitive Data Exposure

CRITICAL: OpenAI API Key in Repository

- **File:** `.env` (line 2)
- **Description:** Live OpenAI API key (`sk-proj-...`) stored in `.env` at repo root.
- **Recommendation:** Rotate immediately. Use secrets manager.

CRITICAL: Hardcoded Default Admin Password

- **File:** `companyBootstrap.ts` (line 5)
- **Description:** `const DEFAULT_COMPANY_ADMIN_PASSWORD = "Admin@123"` used for all new company admin accounts.

HIGH: Weak AUTH_SECRET in Development

- **File:** `.env` (line 3)
- **Description:** `AUTH_SECRET=dev-secret-change-me`. If used in production, all session tokens can be forged.

MEDIUM: tmp/ Contains Production .env Files

- **Files:** `tmp/zip_compare/.env.production`, `tmp/zip_extracted/.env.production`
- **Description:** Production secrets may be exposed in repository tmp directory.

1.8 CSRF/XSS

MEDIUM: SameSite=Lax Without CSRF Token

- **File:** `session.ts` (line 113)
- **Description:** No explicit CSRF tokens for state-changing operations.

LOW: innerHTML Usage

- **File:** `ChannelManager.tsx` (lines 672, 737)
 - **Description:** `innerHTML = ""` is safe but sets a risky pattern.
-

Part 2: Performance Audit

2.1 Connection Pool

CRITICAL: Database Pool Max = 1

- **File:** `db.ts` (line 14)
- **Description:** `max: 1` creates a severe bottleneck. Every concurrent query across the entire application serializes. This amplifies every other performance issue.
- **Recommendation:** Increase to `max: 10-20` based on expected concurrency.

2.2 N+1 Query Problems

CRITICAL: Bulk Customer Assignment Loop

- **File:** `customer-data-center/service.ts` (lines 30-37)
- **Description:** `bulkAssignCustomers()` calls `upsertCustomerAssignment()` one-by-one. Each upsert = 3 queries. 500 customers = ~1500 queries.
- **Recommendation:** Single batch INSERT with `ON CONFLICT`.

HIGH: Work Order Items Loop Insert

- **File:** `workorders/repository.ts` (lines 73-101)
- **Description:** `createWorkOrderFromEstimate()` inserts each item individually in a `for...of` loop.

HIGH: Work Order Item Status Updates Loop

- **File:** `workorders/repository.ts` (lines 208-217)
- **Description:** `updateWorkOrderItemsStatuses()` updates each item one-by-one.

HIGH: Invoice Items Loop Insert

- **File:** `invoices/repository.ts` (lines 128-161)
- **Description:** `createInvoiceFromQualityCheck()` inserts invoice items one at a time.

HIGH: Inspection Items Loop Replace

- **File:** [inspections/repository.ts](#) (lines 313-337)
- **Description:** `replaceInspectionItems()` deletes all then re-inserts each item individually.

HIGH: Journal Lines Loop Insert

- **File:** [accounting/repository.ts](#) (lines 209-231)
- **Description:** `insertJournal()` inserts each journal line one-by-one.

HIGH: Call History N+1 Lookups

- **File:** [call-center/history/route.ts](#) (lines 52-103)
- **Description:** Individual queries per unique user and customer. Phone-based lookup scans entire customers table per phone number.

2.3 Unbounded Queries

HIGH: `listCustomers` -- No LIMIT

- **File:** [crm/repository.ts](#) (lines 58-66)
- **Description:** Returns all rows. 100K customers = full table scan to memory.

HIGH: `listLeadsForCompany` -- No LIMIT

- **File:** [crm/leads/repository.ts](#) (lines 101-130)
- **Description:** Returns all leads with 5 LEFT JOINS. Also calls `releaseExpiredAssignments()` (a write!) on every read.

HIGH: Customer Export -- `pageSize "all"`

- **File:** [customers/export/route.ts](#) (lines 197-203)
- **Description:** Loads all customers into memory for PDF generation. Safe limit allows up to 500,000 rows.

HIGH: Multiple List Functions Without LIMIT

- `listCars(), listLeadsForCustomer(), listWorkOrdersForCompany(), listJournals(), listCompanyWalletTransactions()` -- all unbounded.

2.4 Missing Database Indexes

HIGH: `accounting_journal_lines.created_at` Not Indexed

- **File:** [090_accounting_journals.sql](#)
- **Description:** All financial reports filter by `j1.created_at::date`. The `::date` cast prevents index usage. No functional index exists.
- **Recommendation:** Add functional index or change queries to range comparisons.

HIGH: `accounting_journal_lines.account_id` Not Indexed

- **Description:** Trial balance, P&L, and balance sheet all JOIN on `jl.account_id = a.id`.

HIGH: `call_sessions.created_at` Not Indexed

- **Description:** Analytics queries filter by `created_at BETWEEN`. Existing composite index doesn't include it.

HIGH: `leads.customer_id` Not Indexed

- **Description:** Frequently queried for customer detail pages.

Missing: `customer_wallet_transactions` indexes, `invoices.lead_id` index

2.5 Heavy Computation in Request Handlers

HIGH: Synchronous Image/Video Processing

- **File:** `files/upload/route.ts` (lines 53-89)
- **Description:** `sharp` image resize + `ffmpeg` video transcode run synchronously in the request handler. Blocks event loop.

HIGH: Synchronous PDF Generation in Export

- **File:** `customers/export/route.ts` (lines 112-168)
- **Description:** PDF iterates over all customers to generate pages. Combined with unbounded query.

2.6 Missing Caching

MEDIUM: No Caching Layer

- **Description:** Only cache found is `signalCache.ts` for AI results. No caching for:
 - Company/branch settings (queried every request)
 - User permissions/roles
 - Standard chart of accounts
 - Part category trees
 - Translations
- **Recommendation:** Add Redis or in-memory cache for rarely-changing data.

2.7 SELECT * Overuse

MEDIUM: All Queries Use SELECT *

- **Description:** Every repository uses `SELECT *`, pulling large JSONB/text columns (e.g., `draft_payload`, `ai_summary_markdown`) even for list views.
- **Recommendation:** Explicit column selection for list queries.

2.8 Side Effects in Read Queries

MEDIUM: Write Operations Inside GET Handlers

- **File:** `crm/leads/repository.ts` (lines 101-103)
- **Description:** `listLeadsForCompany()` and `listLeadsForCustomer()` call `releaseExpiredAssignments()` which runs UPDATE. Read operations should not write.

2.9 Runtime Schema Migration

MEDIUM: ALTER TABLE in Request Path

- **File:** `crm/leads/repository.ts` (lines 28-99)
 - **Description:** `ensureLeadAssignmentColumns()` queries `information_schema.columns` and potentially runs `ALTER TABLE` on first request.
-

Part 3: Data Integrity & Cleanliness Audit

3.1 Missing Authorization on Business Routes

CRITICAL: No Permission Checks on Workshop Module

- **Files:** All routes under `workshop/` (estimates, inspections, invoices, job-cards, procurement, QC, gatepass, workorders)
- **Description:** Only `workshop/earnings/route.ts` has `requirePermission()`. All other workshop routes -- including invoice creation, payment, gatepass release -- have zero authorization.

CRITICAL: No Permission Checks on Lead Detail Routes

- **Files:** `crm/leads/[leadId]/route.ts`, `crm/leads/[leadId]/events/route.ts`
- **Description:** Both have `// TODO: add auth/permission checks` comments. Any authenticated user can CRUD any lead.

CRITICAL: No Permission Checks on Sales Leads

- **Files:** `sales/leads/route.ts`

3.2 Status Transition Validation

HIGH: No Status Transition Validation on Leads

- **File:** `crm/leads/[leadId]/route.ts` (line 38)
- **Description:** Any status transition allowed. Lead can go `closed_won` -> `open` or `lost` -> `processing`. No state machine enforced.

HIGH: Invoice Can Be Re-Paid Without Status Check

- **File:** `invoices/[invoiceId]/pay/route.ts` (lines 18-25)
- **Description:** Updates to `paid` without checking current status. Already-paid or cancelled invoice can be "paid" again.

MEDIUM: Gatepass Status Accepts Any Value

- **Description:** `body.status as GatepassStatus` is TypeScript-only cast. No runtime validation. No DB CHECK constraint.

MEDIUM: Estimate Status No Runtime Validation

- **Description:** `body.status as EstimateStatus` accepted without validation.

MEDIUM: Inspection Accepts Any Initial Status

- **Description:** Can create inspection with status `completed` bypassing the workflow.

3.3 Orphan Records

CRITICAL: Lead Deletion Leaves Orphans

- **File:** `crm/leads/repository.ts` (lines 727-738)
- **Description:** `deleteLead()` only deletes `lead_events` then `leads`. Downstream `inspections`, `estimates`, `work_orders`, `invoices`, `gatepasses` have `lead_id` columns with NO FK constraints -- they become orphans.

HIGH: No FK on inspections.lead_id, car_id, customer_id

- **File:** `013_inspections.sql` (lines 7-9)
- **Description:** All three columns lack REFERENCES clauses.

HIGH: No FK on estimates.company_id, inspection_id, lead_id, car_id, customer_id

- **File:** `014_estimates.sql` (lines 5-9)

HIGH: No FK on work_orders, invoices, gatepasses, quality_checks

- **Files:** `016_work_orders.sql`, `018_invoices.sql`, `019_gatepasses.sql`, `017_quality_checks.sql`

3.4 Duplicate Data Prevention

HIGH: No Unique Constraint on Customer Phone/Email

- **File:** `007_customers_cars_and_company_master.sql` (lines 49-75)
- **Description:** Only `(company_id, code)` is unique. Application-level duplicate check is race-condition prone.
- **Recommendation:** `CREATE UNIQUE INDEX ON customers(company_id, phone) WHERE phone IS NOT NULL`

MEDIUM: No Unique Constraint on Car Plate Number

- **Description:** `idx_cars_company_plate` is non-unique. Concurrent operations can create duplicate plates.

MEDIUM: No Unique Constraint on VIN

- **Description:** Duplicate VIN records possible.

3.5 Financial Data Integrity

HIGH: Invoice Payment Not Inside a Transaction

- **File:** [invoices/\[invoiceId\]/pay/route.ts](#) (lines 17-25)
- **Description:** Standalone SQL statement outside a transaction. No journal entry created.

HIGH: Wallet Balance Has No Concurrency Control

- **File:** [invoices/route.ts](#) (lines 51-101)
- **Description:** Wallet balance read with regular SELECT, then compared, then updated. Two concurrent invoices can double-spend. No `SELECT ... FOR UPDATE`.

HIGH: Accounting Journal Skips Account Validation

- **File:** [accounting/journals/route.ts](#) (lines 46-54)
- **Description:** Both POST and PUT pass `skipAccountValidation: true`. Journal entries can reference non-existent accounts.

MEDIUM: Floating-Point Arithmetic for Financial Calculations

- **File:** [accounting/service.ts](#) (lines 104-106)
- **Description:** JavaScript floating-point addition for debit/credit sums. `0.1 + 0.2 !== 0.3` problem.
- **Recommendation:** Use decimal library or integer math (cents).

MEDIUM: Numeric Precision Mismatch

- **Description:** Journal lines use `numeric(18,4)`, estimates/invoices use `numeric(14,2)`. Precision loss when posting to ledger.

3.6 Missing Audit Trails

HIGH: Invoice Payment Has No Audit Trail

- **Description:** No actor, no previous status, no payment details logged.

HIGH: Estimate Modifications Have No Audit Trail

- **Description:** PATCH replaces items wholesale without logging changes. Financial document.

HIGH: Wallet Debit Transactions Have No Actor

- **Description:** `approved_by: null` always. Acting user never captured.

MEDIUM: Gatepass Release Has No Audit Log

- **Description:** No releasing user or timestamp recorded.

MEDIUM: Job Card Creation Not Logged to Lead Events

- **Description:** Significant workflow milestone with no lead_event.

3.7 Default Values & Constraints

MEDIUM: No CHECK Constraints on Status Columns

- **Tables affected:** estimates, work_orders, invoices, inspections, gatepasses
- **Description:** All use text NOT NULL with no CHECK constraint. Any string accepted.

3.8 Timestamp Consistency

MEDIUM: Tables with updated_at but No Auto-Update Trigger

- **Tables:** customers, cars, customer_car_links, leads, employees, vendors, branches, call_center_sessions, customer_wallet_transactions
- **Description:** Define updated_at DEFAULT now() but no BEFORE UPDATE trigger.

3.9 Data Type Issues

MEDIUM: line_items.quantity is Integer, But estimate_items.quantity is Numeric

- **Description:** Fractional quantities in estimates cannot be represented in line items.

MEDIUM: Invoice Payment Allows Null paymentMethod

- **Description:** Invoice marked paid without requiring a payment method.

Summary of All Findings

By Severity

Severity	Security	Performance	Data Integrity	Total
Critical	3	2	6	11
High	7	11	14	22 (note: some overlap between security/data)
Medium	9	5	14	20 (note: some overlap)
Low	4	0	3	7

Top 10 Recommendations (Priority Order)

#	Action	Category	Effort
1	Fix middleware public paths -- restrict /api/company, /api/customers, /api/cars, /api/files from being public	Security	Medium
2	Rotate OpenAI API key and implement secrets management	Security	Low

#	Action	Category	Effort
3	Remove hardcoded admin password -- generate random passwords, require change on first login	Security	Low
4	Add <code>requirePermission()</code> to all workshop routes (estimates, invoices, gatepass, work orders, QC, procurement)	Security/Data	High
5	Increase DB connection pool from <code>max: 1</code> to <code>max: 10-20</code>	Performance	Low
6	Add FK constraints on <code>company_id</code> , <code>inspection_id</code> , <code>estimate_id</code> , <code>lead_id</code> across core tables	Data	Medium
7	Add rate limiting to login endpoints and public APIs	Security	Medium
8	Convert loop inserts to batch inserts (work orders, invoices, inspections, journals)	Performance	Medium
9	Add LIMIT/pagination to all list queries (customers, leads, work orders, journals)	Performance	Medium
10	Add status transition validation with state machine for leads, estimates, invoices, gatepass	Data	Medium

Quick Wins (Low Effort, High Impact)

- 1. Change `max: 1` to `max: 15` in `db.ts`
- 2. Add `CHECK` constraints on status columns in migration
- 3. Add unique index on `customers(company_id, phone)`
- 4. Add index on `accounting_journal_lines(account_id)` and `(created_at)`
- 5. Add index on `leads(company_id, customer_id)`
- 6. Remove `tmp/` directory with production `.env` files
- 7. Add webhook signature verification
- 8. Wrap invoice payment in transaction with journal entry

Appendix: Files Referenced

Security-Critical Files

- `middleware.ts` -- Route protection
- `session.ts` -- Token management
- `companyBootstrap.ts` -- Admin password
- `files/upload/route.ts` -- File upload

Performance-Critical Files

- `db.ts` -- Connection pool
- `crm/repository.ts` -- Customer/car queries
- `crm/leads/repository.ts` -- Lead queries
- `workshop/workorders/repository.ts` -- Work order operations
- `workshop/invoices/repository.ts` -- Invoice operations

- [accounting/repository.ts](#) -- Financial queries

Data Integrity-Critical Files

- [013_inspections.sql](#) -- Missing FKs
- [014_estimates.sql](#) -- Missing FKs
- [016_work_orders.sql](#) -- Missing FKs
- [018_invoices.sql](#) -- Missing FKs
- [019_gatepasses.sql](#) -- Missing FKs
- [007_customers_cars_and_company_master.sql](#) -- Missing unique constraints