## ASSIGNMENT ON FOUNDATION ENGINEERING

Name: Sanchit Sanjay Kinholkar

Roll No.: 22CV045 Class: B.E. Civil – A

## Question:

A 450 mm<sup>2</sup> section of concrete pile 15m long is driven in a deep deposit of uniform clay. The laboratory UCS test on undisturbed sample indicates an average value of UCS as 75kN/m<sup>2</sup>. Calculate the ultimate load capacity of soil.

## INPUT

```
# Input values for the calculation
UCS = float(input("Enter the value of UCS of soil: "))
Cu = UCS / 2 # Calculating cohesion
B = float(input("Enter the value of dimension of pile: "))
L = float(input("Enter the length of pile: "))
Alpha = float(input("Enter the value of adhesion factor: "))
Nc = float(input("Enter the value of Nc: "))
# Calculating the base area of
the pile Ab = B * B print("The
Base area of footing is:", Ab)
# Calculating the surface area of the pile As =
4 * B * L print("The value of cohesion of soil
(Cu) is:", Cu)
# Calculating the ultimate end bearing capacity
(Qpu) Qpu = Cu * Nc * Ab print("Qpu (Ultimate
end bearing capacity):", Qpu)
# Calculating the skin friction resistance
(Qf) Qf = Alpha * Cu * As print("Qf (Skin
friction resistance):", Qf)
# Calculating the ultimate load carrying capacity (Qu) Qu = Qpu + Qf
print("The value of ultimate load carrying capacity of pile (Qu) is:", Qu)
```

## OUTPUT

Enter the value of UCS of soil: 75

Enter the value of dimension of pile: 0.45

Enter the length of pile: 15

Enter the value of adhesion factor: 0.8

Enter the value of Nc: 9

The Base area of footing is: 0.2025

The value of cohesion of soil (Cu) is: 37.5

Qpu (Ultimate end bearing capacity): 68.34375

Qf (Skin friction resistance): 810.0

The value of ultimate load carrying capacity of pile (Qu) is: 878.34375