Component

property binding **Template** .component.ts .component.html Metadata properties < > methods event binding

Data Binding

- Mechanism for coordinating between the
 - Template -> DOM
 - Component -> Property
- Data flowing from component to template
- Events generated by user interaction flowing to the component

Data Binding

property binding

{{ value }}

.component.ts

Metadata

properties

methods

[property] = "value"

(event) = "handler"

[(ngModel)] = "property"

Template

.component.html

event binding

Data Binding Summary

Data direction	Syntax	Туре	Example
One-way from data source to view target	{{expression}} [target]="expression" bind-target="expression"	Interpolation Property Attribute Class Style	<pre>{{ dish.name }} [dish]="selectedDish" bind-dish="selectedDish"</pre>
One-way from view target to data source	(target)="statement" on-target="statement"	Event	(click)="onSelect(dish)" on-click="onSelect(dish)"
Two-way	[(target)]="expression" bindon-target="expression"	Two-way	[(ngModel)]="dish.name"

[()] banana in a box

Binding Targets

- Binding targets are the properties that are declared on the left side of the binding declaration ([...], (...), [(...)])
 - Right side of the = are the binding sources ("...")
- Target properties must be explicitly marked as Input or Output properties using decorators:
 - @Input() dish: Dish;
 - @Output() deleteDish= new EventEmitter<Dish>();