

## Characteristics and partitioning:

### Interface:

C1: list1 is null -> TRUE (T), FALSE (F)  
C2: list2 is null -> TRUE (T), FALSE (F)  
C3: list1 is empty (assuming its not null) -> TRUE (T), FALSE (F)  
C4: list2 is empty (assuming its not null) -> TRUE (T), FALSE (F)

### functional:

C5: function throws exc -> TRUE (T), FALSE (F)  
C6: function returns -> null (N), empty list (E), non-empty list (NE)

#### 1. Disjoint check

C1: the partitions are disjoint because one list cannot be both null and non-null at the same time.  
C2: the partitions are disjoint because one list cannot be both null and non-null at the same time.  
C3: the partitions are disjoint because one list cannot be both empty and non-empty at the same time.  
C4: the partitions are disjoint because one list cannot be both empty and non-empty at the same time.  
C5: the partitions are disjoint because one list cannot be both null, empty or non-empty at the same time.

#### 2. Complete check

C1: the partitions are complete because any list is either null or non-null.  
C2: the partitions are complete because any list is either null or non-null.  
C3: the partitions are complete because any list that is not null is either empty or non-empty.  
C4: the partitions are complete because any list that is not null is either empty or non-empty.  
C5: the partitions are complete because any list is either null, empty or non-empty.

#### 3. BCC

|                                                                      | C1 | C2 | C3 | C4 | C5 | C6        |                              |
|----------------------------------------------------------------------|----|----|----|----|----|-----------|------------------------------|
| Base test:                                                           | F  | F  | F  | F  | F  | NE        | (happy path)                 |
| exception is not thrown and returned list is not null                | T  | F  | F  | F  | F  | NE -> -   | NO (bcs list1 is null, but   |
| exception is not thrown and returned list is not null                | F  | T  | F  | F  | F  | NE -> -   | NO (bcs list1 is null, but   |
| returned list is empty)                                              | F  | F  | T  | F  | F  | NE -> E   | YES (list1 is empty,         |
| returned list is empty)                                              | F  | F  | F  | T  | F  | NE -> E   | YES (list2 is empty,         |
| thrown, but both lists need to be null and function returns nothing) | F  | F  | F  | F  | T  | NE -> -   | NO (bcs exception is         |
| base case and last case                                              | F  | F  | F  | F  | F  | N -> E/NE | YES but already satisfied by |
| empty but have no matches, returned list is empty)                   | F  | F  | F  | F  | F  | E         | YES (list1 and list2 are not |

Dobieni testovi: vkupno 8, unikatni 7, feasible 4