


C Programming

Unit I - Introduction

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
1




Learning Objectives

- History of C
- Characteristics of C
- C Program Structure
- Variables, Defining Global Variables
- Printing Out and Inputting Variables
- Constants
- Operators
- Conditionals
- Looping and Iteration
- Arrays and Strings
- Functions
- Storage classes

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
2




Objectives

- History of C
- Characteristics of C
- C Program Structure
- Variables, Defining Global Variables
- Printing Out and Inputting Variables
- Constants & Literals

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
3




History of C

- Developed by Brian Kernighan and Dennis Ritchie of AT&T Bell Labs in 1972
- In 1983 the American National Standards Institute began the standardization process
- In 1989 the International Standards Organization continued the standardization process
- In 1990 a standard was finalized, known simply as "Standard C"

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
4




Features of C

- C can be thought of as a "high level assembler"
- Most popular programming language for writing system software
- Focus on the procedural programming paradigm, with facilities for programming in a structured style
- Low-level unchecked access to computer memory *via the use of pointers*
- *And many more...*

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
5




Writing C Programs

- A programmer uses a **text editor** to create or modify files containing C code.
- Code is also known as **source code**.
- A file containing source code is called a **source file**.
- After a C source file has been created, the programmer must **invoke the C compiler** before the program can be **executed (run)**

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
6




Getting an executable program

- The process of conversion from source code to machine executable code is a multi step process.
- If there are no errors in the source code, the processes called *compilation & linking* produce an **executable file**
- To execute the program, at the prompt, type
`<executable file name>`

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
7




Conversion from .C to executable

1. Preprocessing
2. Compilation
3. Linking

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
8




Stage 1: Preprocessing

Performed by a program called the **preprocessor**

- Modifies the source code (in RAM) according to **preprocessor directives (preprocessor commands)** embedded in the source code
- Strips comments and white space from the code
- The source code as stored on disk is not modified

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal


U1.
9



Stage 2: Compilation

- Performed by a program called the **compiler**.
- Checks for **syntax errors** and **warnings**
- Translates the preprocessor-modified source code into **object code (machine code)**.
- Saves the object code to a disk file (**.obj**)
- If any compiler errors are received, no object code file will be generated.
 - *An object code file will be generated if only warnings, not errors, are received.*


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1.
10




Stage 3: Linking

- Combines the program object code with other object code to produce the executable file.
- The other object code can come from the
 - Run-Time Library
 - other libraries
 - or object files that you have created.
- Saves the executable code (.exe) to a disk file.
- *If any linker errors are received, no executable file is generated.*

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1.
11






Shortcut Keys: turbo C 2.0

Keys	Operation
F9	Compile Only
Ctrl F9	Compile & run
Alt F5	To see Output Screen
F2	Save the File
Alt X	Exit Turbo C
F3	Load File
F6	Switch Window


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1.
13



A Simple C Program

```
/* Filename:   hello.c
Author:      -----
Date written: --/--/----
Description:  This program prints the greeting
              "Hello, World!"
*/
#include <stdio.h>
int main ( void )
{
    printf ( "Hello, World!\n" );
    return 0 ;
}
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1.
14



Structure of a C Program

```
program header comment

preprocessor directives (if any)

int main ( )
{
    statement(s)
    return 0 ;
}
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1.
15

Explanation

tells compiler about standard input and output functions (i.e. printf + others)

main function

"begin"

```
#include <stdio.h>      /* comment */
int main(void)
{
    printf("Hello\n");
    printf("Welcome to the Course!\n");
    return 0;
}
```

flag success to operating system

"end"

```
Hello
Welcome to the Course!
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
16

Tokens

- The smallest element in the C language is the token.
- It may be a single character or a sequence of characters to form a single item.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal


U1.
17

Tokens can be any of:

- Numeric Literals
- Character Literals
- String Literals
- Keywords
- Names (identifiers)
- Punctuation
- Operators

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
18




Numeric Literals

- Numeric literals are an uninterrupted sequence of digits
- May contain
 - A period,
 - A leading + or – sign
 - A scientific format number
 - A character to indicate data type
- Examples:
 - 123
 - 98.6
 - 1000000

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
19




Character Literals

- Singular!
- One character defined character set.
- Surrounded on the single quotation mark.
- Examples:
 - 'A'
 - 'a'
 - '\$'
 - '4'

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
20




String Literals

- A sequence characters surrounded by double quotation marks.
- Considered a single item.
- Examples:
 - "UMBC"
 - "I like ice cream."
 - "123"
 - "CAR"
 - "car"

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
21




Keywords

- Sometimes called reserved words.
- Are defined as a part of the C language.
- Can not be used for anything else!
- Examples:
 - int
 - while
 - for

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
22




Reserved Words (Keywords) in C

• auto	• break	• int	• long
• case	• char	• register	• return
• const	• continue	• short	• signed
• default	• do	• sizeof	• static
• double	• else	• struct	• switch
• enum	• extern	• typedef	• union
• float	• for	• unsigned	• void
• goto	• if	• volatile	• while

All the C keywords are in small case

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
23



Names / Identifiers

- Variables must be declared before use and immediately after “{”
- Can be of anything length,
 - but only the first 31 are significant
 - A very long name is as bad as a very short, un-descriptive name.
- Are case sensitive: *abc* is different from *ABC*
- Must begin with a letter and the rest can be letters, digits, and underscores.
- Cannot be a reserved word.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
24

Which Are Legal Identifiers?

AREA	area_under_the_curve
3D	num45
Last Dance	#values
x_yt3	pi
num\$	%done
lucky***	continue
Float	integer

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
25

Punctuation

- Semicolons, colons, commas, apostrophes, quotation marks, brackets, and parentheses.

• ; : , ' " { } ()

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
26


Operators

There are operators for:

- assignments
- mathematical operations
- relational operations
- Boolean operations
- bitwise operations
- shifting values
- subscripting
- obtaining the size of an object
- obtaining the address of an object
- referencing an object through its address
- choosing between alternate sub-expressions

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
27




Things to remember

- Statements are terminated with semicolons
- Indentation is ignored by the compiler
- C is case sensitive- all keywords and Standard Library functions are lowercase
- Programs are capable of flagging success or error

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
28




Good Programming Practices

- C programming standards and indentation styles are available in the handouts folder.
- You are expected to conform to these standards for all programming projects in this class. (This will be part of your grade for each project / assignment / test)
- Subsequent lectures will include more "Good Programming Practices" slides.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal


U1.
29



Variables and Constants in C

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
30




Topics

- Variables
 - Naming
 - Declaring
 - Using
- The Assignment Statement
- Constants
- Data Input & Output
- Type Conversion

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
31




What Are Variables in C?

- **C Variables** (like algebraic variables) represent some unknown or variable value.
- Every variable is associated with
 - A data-type
 - A name
 - An Address in memory
- The data-type of a variable governs
 - The amount of memory allocated to it
 - The range of data that can be put into it
 - The operations that can be performed on it

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
32



Naming Conventions


- Begin variable names with lowercase letters
- Use **meaningful** names
- Separate "words" within identifiers with underscores or mixed upper and lower case.
- Use all uppercase for **symbolic constants** (used in **#define** preprocessor directives).
- Be consistent!

Note: symbolic constants are not variables, but make the program easier to read.

In addition to the conventions one must follow all the naming rules as discussed in previous sessions.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
33



Declaring Variables


The **declaration statement** includes (apart from other information) the **data type** of the variable.

Examples of variable declarations:

```
int meatballs ;
float area ;
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
34



Declaring Variables

When we declare a variable

- Space is set aside in memory to hold a value of the specified data type
- That space is associated with
 - ✓ the variable name
 - ✓ a unique address

Visualization of the declaration
`int age ;`

It is required to declare variables before using as compiler needs this information
Purpose!!!


age

garbage

FE07 int

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
35



More About Variables

basic *data types* available in C are:

- char**: stores single character
- int**: stores whole numbers
- float**: store floating point numbers
- double**: store floating point numbers with higher precision

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
36

Integer Types in C

C supports different kinds of integers
maxima and minima defined in "limits.h"
Limits depend upon size in bytes which in turn depends upon environment

type	format	minimum	maximum
char	%c	CHAR_MIN	CHAR_MAX
signed char	%c	SCHAR_MIN	SCHAR_MAX
unsigned char	%c	0	UCHAR_MAX
short [int]	%hi	SHRT_MIN	SHRT_MAX
unsigned short	%hu	0	USHRT_MAX
int	%i	INT_MIN	INT_MAX
unsigned int	%u	0	UINT_MAX
long [int]	%li	LONG_MIN	LONG_MAX
unsigned long	%lu	0	ULONG_MAX

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

Integer Example

```
#include <stdio.h>
#include <limits.h>

int main(void)
{
    unsigned long big = ULONG_MAX;
    printf("minimum int = %i, ", INT_MIN);
    printf("maximum int = %i\n", INT_MAX);
    printf("maximum unsigned = %u\n", UINT_MAX);
    printf("maximum long int = %li\n", LONG_MAX);
    printf("maximum unsigned long = %lu\n", big);
    return 0;
}
```

```
minimum int = -32768, maximum int = 32767
maximum unsigned = 65535
maximum long int = 2147483647
maximum unsigned long = 4294967295
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

Integers With Different Bases

It is possible to work in octal (base 8) and hexadecimal (base 16)

```
#include <stdio.h>

int main(void)
{
    int dec = 20, oct = 020, hex = 0x20;
    printf("dec=%d, oct=%d, hex=%d\n", dec, oct, hex);
    printf("dec=%d, oct=%o, hex=%x\n", dec, oct, hex);
    return 0;
}
```

zero puts compiler into octal mode!

zero "x" puts compiler into hexadecimal mode

```
dec=20, oct=16, hex=32
dec=20, oct=20, hex=20
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

The char Data Type

- The **char** data type holds a single character.
char ch;
- Example assignments:


```
char grade, symbol;
grade = 'B';
symbol = '$';
```
- The char is held as a one-byte integer in memory.
- The ASCII code is what is actually stored,
 - so we can use them as characters or integers, depending on our need.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
40

The char Data Type (Contd.)

Use
`scanf ("%c", &ch);`
 to read a single character into the variable ch.

Use
`printf ("%c", ch);`
 to display the value of a character variable.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
41

Character Example

```
#include <stdio.h>
#include <limits.h>

int main(void)
{
    char lower_a = 'a';
    char lower_m = 'm';

    printf("minimum char = %i, ", CHAR_MIN);
    printf("maximum char = %i\n", CHAR_MAX);

    printf("after 'c' comes '%c'\n", lower_a, lower_a + 1);
    printf("uppercase is '%c'\n", lower_m - 'a' + 'A');


    return 0;
}
```

Note: print integer value of character

minimum char = 0, maximum char = 255
 after 'a' comes 'b'
 uppercase is 'M'

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
42



char I/O

```


#include <stdio.h>
int main ( )
{
    char ch ;

    printf ("Enter a character: " ) ;
    scanf ("%c", &ch) ;
    printf ("The value of %c\n.", ch) ;
    return 0 ;
}

```

Input: A
 Output : The value of A is 65.


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1_43



Problems with Reading Characters

- When getting characters, whether using `scanf()` or `getchar()`, **realize that you are reading only one character.**
- But the user types the character he/she wants to enter, followed by ENTER.
- So, the user is actually entering more than one character, *his/her response and the **newline character**.*
- Unless you handle this, **the newline character will remain in the stdin stream** causing problems the next time you want to read a character. *Another call to `scanf()` or `getchar()` will remove it.*

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1_44



Garbage in stdin

While reading integers using `scanf()`,

- The problem with the newline character didn't seem to be there.
- As `scanf()` looks for the next integer **ignoring whitespaces**.
- After reading the integer, the newline is still present in the input stream.
- If the next item read is a character we will get the newline.
- We have to take this into account and remove it.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1_45

Real Types In C

C supports different kinds of reals
maxima and minima are defined in "float.h"

type	format	minimum	maximum
float	%f %e %g	FLT_MIN	FLT_MAX
double	%lf %le %lg	DBL_MIN	DBL_MAX
long double	%Lf %Le %Lg	LDBL_MIN	LDBL_MAX

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1.46

Real Example

```
#include <stdio.h>
#include <float.h>

int main(void)
{
    double f = 3.1416, g = 1.2e-5, h = 5000000000.0;
    printf("f=%lf\tg=%lf\tg=%lf\n", f, g, h);
    printf("f=%le\tg=%le\tg=%le\n", f, g, h);
    printf("f=%lg\tg=%lg\tg=%lg\n", f, g, h);
    printf("f=%7.2lf\tg=%2le\tg=%4lg\n", f, g, h);
    return 0;
}
```

f=3.141600	g=0.000012	h=5000000000.000000
f=3.141600e+00	g=1.200000e-05	h=5.000000e+09
f=3.1416	g=1.2e-05	h=5e+09
f=3.14	g=1.20e-05	h=5e+09

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1.47

Constants

- Constants have types in C
- Numbers containing "." or "e" are double: 3.5, 1e-7, -1.29e15
- For float constants append "F": 3.5F, 1e-7F
- For long double constants append "L": -1.29e15L, 1e-7L
- Numbers without ".", "e" or "F" are int, e.g. 10000, -35 (some compilers switch to long int if the constant would overflow int)
- For long int constants append "L", e.g. 9000000L

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1.48

Warning!

```
#include <stdio.h>

int main(void)
{
    double f = 5000000000.0;
    double g = 5000000000;

    printf("f=%lf\n", f);
    printf("g=%lf\n", g);

    return 0;
}
```

double constant created because of "."

constant is int or long but 2,147,483,647 is the maximum!

```
f=5000000000.000000
g=705032704.000000
```

OVERFLOW

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1_49

Named Constants

Named constants may be created using `const`

```
#include <stdio.h>

int main(void)
{
    const long double pi = 3.141592653590L;
    const int days_in_week = 7;
    const sunday = 0;

    days_in_week = 5;

    return 0;
}
```

creates an integer constant

error!

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1_50

Preprocessor Constants

Named constants may also be created using the Preprocessor

- Needs to be in "search and replace" mode
- Historically these constants consist of capital letters

```
#include <stdio.h>

#define PI 3.141592653590L
#define DAYS_IN_WEEK 7
#define SUNDAY 0

int day = SUNDAY;
long flag = USE_API;
```


search for "PI", replace with 3.1415....

Note: no "=" and no ";"

"PI" is NOT substituted here

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal


U1_51



Notes About Variables

- You must not use a variable until you somehow give it a value.
- You can not assume that the variable will have a value before you give it one.
 - Some compilers do, others do not! This is the source of many errors that are difficult to find.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1.
52



Using Variables: Initialization

Variables may be be given initial values, or **initialized**, when declared. Examples:

```
int length = 7 ;
float diameter = 5.9 ;
char initial = 'A' ;
```

➔

length
7


➔

diameter
5.9

➔

initial
'A'

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1.
53



Using Variables: Initialization (Contd.)

Do not "hide" the initialization


- put initialized variables on a separate line
- a comment is always a good idea

Example:

```
int height ;    /* rectangle height */
int width = 6 ; /* rectangle width  */
int area ;     /* rectangle area   */
```

AVOID int height, width = 6, area ;

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1.
54




Using Variables: Assignment

- **Assignment statement:** assigns values to variables
- Uses the **assignment operator** =
- This operator does not denote equality.
- It assigns the value of the right-hand side of the statement (the **expression**) to the variable on the left-hand side.
- The entity that appears on the left hand side of an assignment statement (Also termed as an *lvalue*) must be modifiable.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1_55



Using Variables: Assignment (Contd.)

Examples:

```
diameter = 5.9 ;
area = length * width ;
```

Note that only single variables may appear on the left-hand side of the assignment operator,


The statement

```
length= width= 10.9;
```

is accepted and assigns a value 10.9 to both the variables named `length` and `width`. *Can you justify why.*

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1_56



Functions

- We saw that it was necessary for us to use some functions to write our first programs.
- Functions are named code blocks that make reusability of code possible.
- These are parts of programs that
 - Perform a well defined task.
 - At times, expect some information in order to complete the task.
 - The information is provided in form of parameters (arguments)
 - Can return a value to convey result / status of execution

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1_57

I/O Example

create two integer variables, "a" and "b"

read two integer numbers into "a" and "b"

write "a", "b" and "a-b" in the format specified

```
#include <stdio.h>

int main(void)
{
    int a, b;

    printf("Enter two numbers: ");
    scanf("%i %i", &a, &b);

    printf("%i - %i = %i\n", a, b, a - b);

    return 0;
}
```

Enter two numbers: 21 17

21 - 17 = 4

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1. 58

Displaying Variables


- A Function that allows us to display formatted data : `printf()`.
- Needs two pieces of information to display things.
 - How to display it
 - What to display
- `printf("%f\n", diameter);`

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1. 59

`printf("%f\n", diameter);`

- The name of the function is "printf".
- Inside the parentheses are two comma separated parameters:
 - Format specifier:** indicates the format in which the output will be produced
 - ✓`%f` => a floating point value
 - ✓`\n` => a new-line character (*escape sequence*)
 - The expression** *diameter* whose value is to be displayed.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1. 60




scanf (“%f”, & meters) ;

- This function is used to
 - read values from the standard input; and
 - Store them in memory.
- The scanf() function also needs two items:
 - The **input specification** “%f”.
 - The **address** of the memory location where the information is to be stored.
- (We can input more than one item at a time if we wish, as long as we specify it correctly.)
- Notice the “&” in front of the variable name.** Can you explain its significance!

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
51




Format Specifiers

- Format specifiers are normal strings with embedded “conversion specifications” which are placeholders for arguments
- Conversion specifications are a ‘%’ and a letter with an optional set of arguments in between the ‘%’ and letter.

Why are these required!!!

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
52



Conversion Specifications

Conversion specifications tell how to translate a data value into a string

Conversion Specifications:	Options:
%d, %i -- signed integer	l -- long
%u -- unsigned integer	.n -- precision of <i>n</i> digits
%f -- floating point number	0 -- fill unused field with 0s
%c -- character	
%s -- string	
%x -- hexadecimal value	
%p -- pointer	

There are many more! Read help, or search on net .

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
53

Escape Sequences			
Seq	Meaning	Example	Output
\n	New line	Hello \n World	Hello World
\t	Tab	Hello World	Hello World
\r	Carriage return	Hello \r Me	Mello
\a	Alert	Hello \a World	Hello [beep] World
\0	Null	Hello \0 World	Hello

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
54

printf quiz!

Figure out the output of the following:

```
printf("%.3f rounded to 2 decimals is %.2f\n",
2.325, 2.325);

printf("%d in hex is: %04x\n", 24, 24);
```

Answers:

2.325 rounded to 2 decimals is 2.33

24 in hex is 0018

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
65

scanf Examples

```
int items_read;

Read an integer:
int num;
items_read = scanf("%d", &num);

Read a character:
char ch;
items_read = scanf("%c", &ch);

Read a string of max length, 79 chars:
char buf[80];
buf[79]='\0'; // Ensure a terminating NULL.
items_read = scanf("%79s", buf);

Read number after pattern of "a:<num>":
int num;
items_read = scanf("a:%d", &num);
```

always check the return value of scanf

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
66

sscanf examples

```
#include <stdio.h>
main()
{
    char Host[64];
    char User[64];
    char Buff[200] = "Hostname=Server1 User=test
        Time=11:15";

                                -----
                                |         /
                                |        /
    sscanf (Buff, "Hostname=%s %s", Host, User);
    printf("Host is %s\n", Host);
    printf("User is %s\n", User);
    exit(0);
}

Host is Server1
User is User=test
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
67

Type Conversion

```
#include <stdio.h>
void main(void)
{
    int i,j = 12;    /* i not initialized, only j */
    float f1,f2 = 1.2;

    i = (int) f2;    /* explicit: i <- 1, 0.2 lost */
    f1 = i;          /* implicit: f1 <- 1.0 */

    f1 = f2 + (float) j; /* explicit:
                           f1 <- 1.2 + 12.0 */
    f1 = f2 + j;      /* implicit: f1 <- 1.2 + 12.0 */
}
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal


U1.

Type Conversion

- The set of implicit conversions is where the “lower” type is *promoted* to the “higher” type, where the “order” of the types is
- **char < short int < int < long int < float < double < long double**
- Moral: stick to explicit conversions - no confusion !

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.




Good Programming Practices

- Place each variable declaration on its own line with a descriptive comment.
- Place a comment before each logical "chunk" of code describing what it does.
- Do not place a comment on the same line as code (with the exception of variable declarations).
- Use spaces around all arithmetic and assignment operators.
- Use blank lines to enhance readability.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
70



Good Programming Practices (Contd.)

- Place a blank line between the last variable declaration and the first executable statement of the program.
- Indent the body of the program 3 to 5 spaces -- *be consistent!*
- Comments should explain why you are doing something, not what you are doing it.


```

• a = a + 1;
• /* add one to a */    /* WRONG */
• /* count new student */ /* RIGHT */
• /*variable name should have been more descriptive*/

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
71




Remaining

Scope and lifetime of variables

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal


U1.
72



Operators in C

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
73




Objectives

- Arithmetic operators
- Cast operator
- Increment and Decrement
- Bitwise operators
- Comparison operators
- Assignment operators
- `sizeof` operator
- Conditional expression operator

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
74



Arithmetic Operators in C

Name	Operator	Example
Addition	+	num1 + num2
Subtraction	-	initial- spent
Multiplication	*	fathoms * 6
Division	/	sum / count
Modulus	%	m % n

% can not be used with reals

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
75

Using Arithmetic Operators

The compiler uses the types of the operands to determine how the calculation should be done

"i" and "j" are ints, integer division is done, 1 is assigned to "k"

Either of "f" and "g" are double, double division is done, 1.25 is assigned to "h"

integer division is still done, despite "h" being double. Value assigned is 1.00000

```

int main(void)
{
    int    i = 5,  j = 4,  k;
    double f = 5.0, g = 4.0, h;

    k = i / j;
    h = f / g;
    h = i / j;

    return 0;
}

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
76

Division

- If both operands of a division expression are integers, you will get an integer answer. *The fractional portion is discarded.*
- Division where at least one operand is a floating point number will produce a floating point answer.
 - What happens? The integer operand is temporarily converted to a floating point, then the division is performed.
- Division by zero is mathematically undefined.
- Division by zero in a program gives a **fatal error**, thus causing your program to terminate execution.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
77

The Cast Operator

The cast operator generates a temporary value with a type equivalent to the caste type.

if either operand is a double, the other is automatically promoted

integer division is done here, the result, 1, is changed to a double, 1.00000

```

int main(void)
{
    int    i = 5, j = 4;
    double f;


    f = (double)i / j;
    f = i / (double)j;
    f = (double)i / (double)j;
    f = (double)(i / j);

    return 0;
}

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
78




Modulus

- The expression **m % n** yields the integer remainder after **m** is divided by **n**.
- Modulus is an integer operation-- both operands **MUST** be integers.
- Examples :

$17 \% 5 = 2$
 $6 \% 3 = 0$
 $9 \% 2 = 1$
 $5 \% 8 = 5$


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1.
79



Precedence

Operator(s)	Precedence & Associativity
()	Evaluated first. If nested , innermost is evaluated first. If on same level, evaluation is left to right.
* / %	Evaluated second. In case of multiple entries, evaluation is left to right.
+ -	Evaluated third. In case of multiple entries, evaluation is left to right.
=	Evaluated last, right to left.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1.
80



Increment and Decrement

C has two special operators for adding and subtracting 1 from a variable

++ increment
-- decrement

These may be either prefix (before the variable) or postfix (after the variable):

"i" becomes 6

"j" becomes 3

"i" becomes 7

```
int i = 5, j = 4;
i++;
--j;
++i;
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1.
81

Prefix and Postfix

The prefix and postfix versions are different when used as a part of an expression.

```
#include <stdio.h>

int main(void)
{
    int i, j = 5;

    i = ++j; ←
    printf("i=%d, j=%d\n", i, j);

    j = 5;
    i = j++; ←
    printf("i=%d, j=%d\n", i, j);

    return 0;
}
```

equivalent to:

1. j++;
2. i = j;

equivalent to:

1. i = j;
2. j++;

i=6, j=6
i=5, j=6

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1. 52

Prefix Vs Postfix

```
int amount, count ;
count = 3 ;
```

amount = 2 * --count ; amount = 2 * count-- ;

- 1 gets subtracted from count first, then amount gets the value of 2 * 2, which is 4.
- So, after executing the last line, amount is 4 and count is 2.

- amount gets the value of 2 * 3, which is 6, and then 1 gets subtracted from count.
- So, after executing the last line, amount is 6 and count is 2.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1. 53

Increment and Decrement

- Increment and decrement operators can only be applied to variables, *not to constants or expressions*
- When written as a single statement `++count;` and `count++;` have the same meaning.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1. 54

A Hand Trace Example

```
int answer, value = 4 ;
```

<u>Code</u>	<u>Value</u>	<u>Answer</u>
	4	garbage
value = value + 1 ;		
value++ ;		
++value ;		
answer = 2 * value++ ;		
answer = ++value / 2 ;		
value-- ;		
--value ;		
answer = --value * 2 ;		
answer = value-- / 3 ;		

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1: 55

Practice

Given

```
int a = 1, b = 2, c = 3 ;
```

What is the value of this expression?

```
++a * b- c-
```

What are the new values of a, b, and c?

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1: 56

More Practice

Given

```
int a = 1, b = 2, c = 3, d = 4 ;
```


What is the value of this expression?

```
++b / c + a * d++
```

What are the new values of a, b, c, and d?

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1: 57



Using Parentheses

One can use parentheses to change the order in which an expression is evaluated.

$a + b * c$

1. Would multiply $b * c$ first,
2. then add a to the result.


If you really want the sum of a and b to be multiplied by c , use parentheses to force the evaluation to be done in the order you want.

$(a + b) * c$

Also use parentheses to clarify a complex expression.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
88



Evaluate and test by execution

Given integer variables a, b, c, d , and e , where
 $a = 1, b = 2, c = 3, d = 4$,
 evaluate the following expressions:

$a + b - c + d$

$a * b / c$


$1 + a * b \% c$

$a + d \% b - c$

$e = b = d + c / b - a$

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
89



Truth in C


- To understand C's comparison operators (less than, greater than, etc.) and the logical operators (and, or, not) it is important to understand how C regards truth
- There is no boolean data type in C, integers are used instead
- The value of 0 (or 0.0) is false
- Any other value, 1, -1, 0.3, -20.8, is true

```
if(32)
    printf("this will always be printed\n");

if(0)
    printf("this will never be printed\n");
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1.
90



Relational Operators


<	less than
>	greater than
<=	less than or equal to
>=	greater than or equal to
==	is equal to
!=	is not equal to

Relational expressions evaluate to the integer values:
 1 (true) on success
 0 (false) on failure

All of these operators are called **binary operators** because they take two expressions as **operands**.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
31




Evaluate and test by execution

int a = 1, b = 2, c = 3 ;

<u>Expression</u>	<u>Value</u>	<u>Expression</u>	<u>Value</u>
a < c		a + b >= c	
b <= c		a + b == c	
c <= a		a != b	
a > b		a + b != c	
b >= c			

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
32



Logical Operators

- At times we need to test multiple conditions in order to make a decision.
- Logical operators** combine simple conditions to make **complex conditions**.
- Result into a 0 (false) or 1 (true)

&&	AND	if (x > 5 && y < 6)
	OR	if (z == 0 x > 10)
!	NOT	if (!(age > 42))

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
33

Example Use of &&

```

if ( age < 1  &&  gender == 'm')
{
    printf ("Infant boy\n") ;
}

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
34

Truth Table for &&

<u>Expression₁</u>	<u>Expression₂</u>	<u>Expression₁ && Expression₂</u>
0	0	0
0	nonzero	0
nonzero	0	0
nonzero	nonzero	1

Exp₁ && Exp₂ && ... && Exp_n will evaluate to 1 (true) only if ALL sub-conditions are true.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
35

Example Use of ||

```

if (grade == 'D' || grade == 'F')
{
    printf ("Must reappear in the next semester!\n") ;
}

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
36

Truth Table for ||

<u>Expression₁</u>	<u>Expression₂</u>	<u>Expression₁ Expression₂</u>
0	0	0
0	nonzero	1
nonzero	0	1
nonzero	nonzero	1

Exp₁ && Exp₂ && ... && Exp_n will evaluate to 1 (true) if only ONE sub-condition is true.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 97

Example Use of !

```

if ( ! (x == 2) ) /* same as (x != 2) */
{
    printf("x is not equal to 2.\n") ;
}

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 98

Truth Table for !

<u>Expression</u>	<u>! Expression</u>
0	1
nonzero	0

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 99

Practice

Given
`int a = 5, b = 7, c = 17 ;`

evaluate each expression as True or False.

- `c / b == 2`
- `c % b <= a % b`
- `b + c / a != c - a`
- `(b < c) && (c == 7)`
- `(c + 1 - b == 0) || (b = 5)`

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 100

Warning!

Remember to use parentheses with conditions, otherwise your program may not mean what you think

in this attempt to say "i not equal to five", "i" is evaluated first. As "i" is 10, i.e. non zero, i.e. true, "i" must be false, i.e. zero. Zero is compared with five

```
int i = 10;
if(!i == 5)
    printf("i is not equal to five\n");
else
    printf("i is equal to five\n");
```

i is equal to five

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 101

Bitwise Operators

C has the following bit operators which may only be applied to integer types:

<code>&</code>	bitwise and
<code> </code>	bitwise inclusive or
<code>^</code>	bitwise exclusive or
<code>~</code>	one's compliment
<code>>></code>	right shift
<code><<</code>	left shift

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 102

Code Snippet:

```
#include <stdio.h>

int main(void)
{
    short a = 0x6eb9;
    short b = 0x5d27;
    unsigned short c = 7097;

    printf("0x%x, ", a & b);
    printf("0x%x, ", a | b);
    printf("0x%x\n", a ^ b);

    printf("%u, ", c << 2);
    printf("%u\n", c >> 1);

    return 0;
}
```

Memory Layout:

Address	Value (Hex)	Value (Binary)
0x6eb9	0110 1110 1011 0001	0x6eb9
0x5d27	0101 1101 0010 0111	0x5d27
0x4c21	0100 1100 0010 0001	0x4c21

Arrows indicate the mapping from the code to the memory layout:

- 0x6eb9 points to the first memory location.
- 0x5d27 points to the second memory location.
- 0x4c21 points to the third memory location.

Shift Operations

If the left operand is an unsigned integer logical shifts are carried out.

If the left operand is a signed integer:

- \ll results in : $\text{left} \times 2^{\text{right}}$
 - ✓ undefined if an overflow occurs
- \gg
 - ✓ implementation-defined
 - ✓ generally the result of the arithmetic shift: $\text{left} / 2^{\text{right}}$.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

Assignment

- Assignment is more flexible than might first appear
- An assigned value is always made available for subsequent use

```
int i, j, k, l, m, n;  
i = j = k = l = m = n = 22;  
printf("%i\n", j = 93);
```

"n = 22" happens first, this makes 22 available for assignment to "m". Assigning 22 to "m" makes 22 available for assignment to "l" etc.

"j" is assigned 93, the 93 is then made available to print for printing

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

Warning!

One of the most frequent mistakes is to confuse test for equality, "=", with assignment, "="

```
#include <stdio.h>

int main(void)
{
    int i = 0;

    if(i = 0)
        printf("i is equal to zero\n");
    else
        printf("somehow i is not zero\n");

    return 0;
}
```

somehow i is not zero

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 166

Other Assignment Operators

There is a family of assignment operators:

+= -= *= /= %=
 &= |= ^=
 <<= >>=

In each of these:

expression1 op= expression2

is equivalent to:

(expression1) = (expression1) op (expression2)

a += 27;

f /= 9.2;

i *= j + 2;

a = a + 27;

f = f / 9.2;

i = i * (j + 2);

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 167

sizeof Operator

C has a mechanism for determining how many bytes a variable occupies

```
#include <stdio.h>

int main(void)
{
    long big;

    printf("\nbig is %u bytes\n", sizeof(big));
    printf("a short is %u bytes\n", sizeof(short));
    printf("a double is %u bytes\n", sizeof(double));

    return 0;
}
```

"big" is 4 bytes
a short is 2 bytes
a double is 8 bytes

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 168

Conditional Expression Operator

- The conditional expression operator provides an in-line if/then/else
- If the first expression is true, the second is evaluated
- If the first expression is false, the third is evaluated

```
int i, j = 100, k = -1;
i = (j > k) ? j : k;
```

```
int i, j = 100, k = -1;
i = (j < k) ? j : k;
```

```
if(j > k)
    i = j;
else
    i = k;
```

```
if(j < k)
    i = j;
else
    i = k;
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
109

Precedence of Operators

- C treats operators with different importance, known as *precedence*
- There are 15 levels
- In general, the unary operators have higher precedence than binary operators
- Parentheses can always be used to improve clarity

```
#include <stdio.h>

int main(void)
{
    int j = 3 * 4 + 48 / 7;

    printf("j = %i\n", j);

    return 0;
}
```

j = 18

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
110

Associativity of Operators

- For two operators of equal precedence (i.e. same importance) a second rule, "associativity", is used
- Associativity is either "left to right" (left operator first) or "right to left" (right operator first)

```
#include <stdio.h>

int main(void)
{
    int i = 6 * 4 / 7;


    printf("i = %d\n", i);

    return 0;
}
```

i = 3

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
111

	Precedence/Associativity Table	
Operator	Associativity	
() [] -> .	left to right	
! ~ ++ -- -+ + (cast) * & sizeof	right to left	
* / %	left to right	
+ -	left to right	
< < >>	left to right	
< <= >= >	left to right	
== !=	left to right	
&	left to right	
	left to right	
^	left to right	
&&	left to right	
	left to right	
?:	right to left	
= += -= *= /= %= etc	right to left	
,	left to right	
<div> <div>+</div> <div>-</div> <div>:</div> <div>unary</div> </div>		

Review

```
#include <stdio.h>

int main(void){
    int i = 0, j, k = 7, m = 5, n;

    j = m += 2;
    printf("j = %d\n", j);

    j = k++ > 7;
    printf("j = %d\n", j);

    j = i == 0 & k;
    printf("j = %d\n", j);

    n = !i > k >> 2;
    printf("n = %d\n", n);

    return 0;
}
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

UT,
113

Practice with Assignment Operators

```
int i = 1, j = 2, k = 3, m = 4 ;
```


Expression Value

$i += j + k$

$j *= k + m + 5$


$k -= m /= j * 2$

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

 Using /= and ++ to Count Digits in an Integer

```
#include <stdio.h>
int main ( )
{
    int num, temp, digits = 0 ;
    temp = num = 4327 ;
    while ( temp > 0 )
    {
        printf ("%d\n", temp) ;
        temp /= 10 ;
        digits++ ;
    }
    printf ("%d digits in %d.\n", digits, num);
    return 0 ;
}
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 115

 Debugging Tips


Trace your code by hand (a **hand trace**), keeping track of the value of each variable.

Insert temporary *printf()* statements so you can see what your program is doing.

- Confirm that the correct value(s) has been read in.
- Check the results of arithmetic computations immediately after they are performed.

Use () wherever possible to avoid confusion


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 116

 Structured Programming

All programs can be written in terms of only three control structures

- The **sequence** structure
 - ✓ Unless otherwise directed, the statements are executed in the order in which they are written.
- The **selection** structure
 - ✓ Used to choose among alternative courses of action.
- The **repetition** structure
 - ✓ Allows an action to be repeated while some condition remains true.


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 117



Good Programming Practice

- It is best not to take the **“big bang” approach** to coding.
- Use an **incremental approach** by writing your code in incomplete, yet working, pieces.
- For example, for your projects,
 - Don't write the whole program at once.
 - Just write enough to display the user prompt on the screen.
 - Get that part working first (compile and run).
 - Next, write the part that gets the value from the user, and then just print it out.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
118




Selection: the **if** statement

```
if ( condition )
{
    statement(s) /* body of the if statement */
}
```

The braces are not required if the body contains only a single statement.

However, they are a good idea and are required by the C Coding Standards.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
119




Examples

```
if ( age >= 18 )
{
    printf("Vote!\n") ;
}

if ( value == 0 )
{
    printf ("The value you entered was zero.\n");
    printf ("Please try again.\n") ;
}
```


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
120



Good Programming Practice

- Always place braces around the body of an if statement.
- Advantages:
 - Easier to read
 - Will not forget to add the braces if you go back and add a second statement to the body
 - Less likely to make a semantic error
- Indent the body of the if statement 3 to 5 spaces -- be consistent!

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1: 121



Warning!!!!!!


A semicolon after the condition forms a "do nothing" statement

```

printf("input an integer: ");
scanf("%i", &j);
if(j > 0);
    printf("a positive number was entered\n");
  
```

input an integer: -6
 a positive number was entered

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1: 122



Selection: the **if-else** statement

```

if ( condition )
{
    statement(s) /* the if clause */
}
else
{
    statement(s) /* the else clause */
}
  
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1: 123

Example

```

if ( age >= 18 )
{
    printf("Vote!\n") ;
}
else
{
    printf("Maybe next time!\n") ;
}

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 124

Nesting ifs

```

if ( condition1 )
{
    if ( condition2 )
    {
    }
}
else
{
    if ( condition3 )
    {
    }
}

```

Tested when condition1 is true

Tested when condition1 is false

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 125

Nesting ifs

else associates with the nearest **if**
Use curly brackets { } to override

```

int i = 100;
if(i > 0)
{
    if(i > 1000)
        printf("i is big\n");
    else
        printf("i is reasonable\n");
}


int i = -20;
if(i > 0) {
    if(i > 1000)
        printf("i is big\n");
} else
    printf("i is negative\n");

```

i is reasonable

i is negative

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 126



Testing Mutually Exclusive Cases


```

if ( condition1 )
{
    statement(s)
}

else if ( condition2 )
{
    statement(s)
}
...      /* more else clauses may be here */
else
{
    statement(s) /* the default case */
}

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
127




Example

```

if ( value == 0 )
{
    printf ( "You entered zero.\n" ) ;
}
else if ( value < 0 )
{
    printf ( "%d is negative.\n", value ) ;
}
else
{
    printf ( "%d is positive.\n", value ) ;
}

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
128



= versus ==

```

int a = 2 ;

if ( a = 1 )      /* semantic (logic) error! */
{
    printf ( "a is one\n" ) ;
}
else if ( a == 2 )
{
    printf ( "a is two\n" ) ;
}
else
{
    printf ( "a is %d\n", a ) ;
}

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
129

A very common error

The statement `if (a = 1)` is syntactically correct,

- so no error message will be produced.
- Some compilers will produce a warning.
- However, a semantic (logic) error will occur.

An assignment expression has a value

- The value being assigned.
- In this case the value being assigned is 1, which is true.

If the value being assigned was 0

- the expression would evaluate to 0,
- which is false.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

Multiple Selection with *if*

```

if (day == 0) {
    printf ("Sunday");
}
if (day == 1) {
    printf ("Monday");
}
if (day == 2) {
    printf ("Tuesday");
}
if (day == 3) {
    printf ("Wednesday");
}
if (day == 4) {
    printf ("Thursday");
}
if (day == 5) {
    printf ("Friday");
}
if (day == 6) {
    printf ("Saturday");
}
if ((day < 0) || (day > 6)) {
    printf("Error - invalid day.\n");
}
    
```

(continued)

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

Multiple Selection with *if-else*


```

if (day == 0) {
    printf ("Sunday");
} else if (day == 1) {
    printf ("Monday");
} else if (day == 2) {
    printf ("Tuesday");
}
...
else if (day == 6) {
    printf ("Saturday");
} else {
    printf ("Error -
    invalid day.\n");
}
    
```

This if-else structure is more efficient than the corresponding if structure for a particular case.

Which one!!!

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal




switch Multi-Selection Structure

```

switch ( integer expression )
{
    case constant1 :
        statement(s)
        break ;
    case constant2 :
        statement(s)
        break ;
    . . .
    default :
        statement(s)
        break ;
}
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
133



More About switch

- Only integral constants may be tested
- If no condition matches, the default is executed
- If no default, nothing is done (not an error)
- The `break` is important


```
float f;
switch(f) {
    case 2:
        ....
}
```

```
i = 3;
switch(i) {
    case 3: printf("i = 3\n");
    case 2: printf("i = 2\n");
    case 1: printf("i = 1\n");
}
```

```
i = 3
i = 2
i = 1
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
134




switch Statement Details

- The `break` causes program control to jump to *the closing brace of the switch structure*.
- Without the `break`, the code flows into the next case.
- The last statement of each case in the switch should almost always be a *break*. **Exceptional case!!!**
- A switch statement does compile without a default case, but always consider using one.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal


U1:
135



switch

<u>Limitations</u>	<u>Advantages</u>
<ul style="list-style-type: none"> • Can be used for Integer / Character values only • Can test for constant values only • Different test cases are not allowed to map to same value. • Not as efficient as <code>if</code> for small number of test cases 	<ul style="list-style-type: none"> • Readability • Maintainability • More efficient than <code>if</code> for large number of test cases. <ul style="list-style-type: none"> ▪ Why!!!


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1: 136



Good Programming Practices

- Include a default case to catch invalid data.
- Inform the user of the type of error that has occurred (e.g., "Error - invalid day.").
- If appropriate, display the invalid value.
- If appropriate, terminate program execution

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1: 137




switch Example

```

switch ( day )
{
    case 0: printf ("Sunday\n") ;
            break ;
    case 1: printf ("Monday\n") ;
            break ;
    .
    .
    .
    case 6: printf ("Saturday\n") ;
            break ;
    default: printf ("Error -- invalid day.\n") ;
             break ;
}
  
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1: 138




Why Use a switch Statement?

- A if-else-if structure is just as efficient as a switch statement.
- However, a switch statement may be easier to read.
- Also, it is easier to add new cases to a switch statement than to a if-else-if structure.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal


U1
139



Iterative Constructs

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
140




Topics

- The while Loop
- Program Versatility
 - Sentinel Values and Priming Reads
- Checking User Input Using a while Loop
- Counter-Controlled (Definite) Repetition
- Event-Controlled (Indefinite) Repetition
- for Loops
- do-while Loops
- Choosing an Appropriate Loop
- break and continue Statements

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal


U1
141



Review: Repetition Structure

- Allows the programmer to specify that an action is to be repeated **while some condition remains true**.
- There are three repetition structures in C: -
 - the **while** loop
 - the **for** loop
 - the **do-while** loop.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
142




The while Repetition Structure

```
while ( condition )
{
    statement(s)
}
```

The braces are not required if the loop body contains only a single statement.

However, they are a good idea and are required by the C Coding Standards.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
143



while Loop

- The simplest C loop is the **while**
- Parentheses must surround the condition
- One statement forms the body of the loop
- Braces must be added if more statements are to be executed

```
int j = 5;
while(j > 0)
    printf("j = %i\n", j--);
```

```
int j=5;
while(j > 0) {
    printf("j = %i\n", j);
    j--;
```

```
j = 5
j = 4
j = 3
j = 2
j = 1
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
144

(Another) Semicolon Warning!

A semicolon placed after the condition forms a body that does nothing

```
int j = 5;
while(j > 0);
printf("j = %i\n", j--);
```

program disappears into an infinite loop

- Sometimes an empty loop body is required

```
int c, j;
while(scanf("%i", &j) != 1)
    while((c = getchar()) != '\n')
        ;
```

placing semicolon on the line below makes the intention obvious

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 145

while, Not Until!

Remember to get the condition the right way around!

user probably intends "until j is equal to zero", however this is NOT the way to write it

```
int j = 5;
printf("start\n");
while(j == 0)
    printf("j = %i\n", j--);
printf("end\n");
```


start
end

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 146

Exercise

- Problem:** Write a program that calculates the average exam grade for a class of 10 students.
- What are the program inputs?
 - the exam grades
- What are the program outputs?
 - the average exam grade

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 147



The Algorithm

```


<total> = 0
<grade_counter> = 1

While (<grade_counter> <= 10)
    Display "Enter a grade: "
    Read <grade>
    <total> = <total> + <grade>
    <grade_counter> = <grade_counter> + 1
End_while
<average> = <total> / 10
Display "Class average is: ", <average>

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
148



The C Code


```

#include <stdio.h>
int main ( )
{
    int counter, grade, total, average ;
    total = 0 ;
    counter = 1 ;
    while ( counter <= 10 )
    {
        printf ("Enter a grade : ") ;
        scanf ("%d", &grade) ;
        total = total + grade ;
        counter = counter + 1 ;
    }
    average = total / 10 ;
    printf ("Class average is: %d\n", average) ;
    return 0 ;
}

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
149




Versatile?

- How versatile is this program?
- It only works with class sizes of 10.
- We would like it to work with any class size.
- A better way :
 - Ask the user how many students are in the class.
 - Use that number in the condition of the while loop and when computing the average.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
150




New Algorithm

```

<total> = 0
<grade_counter> = 1

Display "Enter the number of students: "
Read <num_students>
While (<grade_counter> <= <num_students>)
    Display "Enter a grade: "
    Read <grade>
    <total> = <total> + <grade>
    <grade_counter> = <grade_counter> + 1
End_while
<average> = <total> / <num_students>
Display "Class average is: ", <average>
  
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
151




New C Code

```

#include <stdio.h>
int main ( )
{
    int numStudents, counter, grade, total, average ;
    total = 0 ;
    counter = 1 ;
    printf ("Enter the number of students: ") ;
    scanf ("%d", &numStudents) ;
    while ( counter <= numStudents) {
        printf ("Enter a grade : ") ;
        scanf ("%d", &grade) ;
        total = total + grade ;
        counter = counter + 1 ;
    }
    average = total / numStudents ;
    printf ("Class average is: %d\n", average) ;
    return 0 ;
}
  
```


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
152



Why Bother to Make It Easier?

- Why do we write programs?
 - So the user can perform some task
- The more versatile the program, the more difficult it is to write. BUT it is more useable.
- The more complex the task, the more difficult it is to write. But that is often what a user needs.
- Always consider the user first.


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
153



Using a Sentinel Value

- We could let the user keep entering grades and when he's done enter some special value that signals us that he's done.
- This special signal value is called a **sentinel value**.
- We have to make sure that the value we choose as the sentinel isn't a legal value.
- For example, we can't use 0 as the sentinel in our example as it is a legal value for an exam score.


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1: 154



The Priming Read

- When we use a sentinel value to control a while loop, we have to get the first value from the user before we encounter the loop so that it will be tested and the loop can be entered.
- This is known as a **priming read**.
- We have to give significant thought to the initialization of variables, the sentinel value, and getting into the loop.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1: 155



New Algorithm

```

<total> = 0
<grade_counter> = 1

Display "Enter a grade: "
Read <grade>
While ( <grade> != -1 )
    <total> = <total> + <grade>
    <grade_counter> = <grade_counter> + 1
    Display "Enter another grade: "
    Read <grade>
End_while
<average> = <total> / <grade_counter>
Display "Class average is: ", <average>
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1: 156

New C Code

```

#include <stdio.h>
int main ( )
{
    int counter, grade, total, average ;

    total = 0 ;
    counter = 1 ;
    printf("Enter a grade: ") ;
    scanf("%d", &grade) ;
    while (grade != -1) {
        total = total + grade ;
        counter = counter + 1 ;
        printf("Enter another grade: ") ;
        scanf("%d", &grade) ;
    }
    average = total / counter ;
    printf ("Class average is: %d\n", average) ;
    return 0 ;
}

```

Can use a do-while loop instead
Covered later

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
157

Final "Clean" C Code

```

#include <stdio.h>
int main ( )
{
    int counter ; /* counts number of grades entered */
    int grade ; /* individual grade */
    int total ; /* total of all grades */
    int average ; /* average grade */

    /* Initializations */
    total = 0 ;
    counter = 1 ;
}

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
158

Final "Clean" C Code (Contd.)

```

/* Get grades from user */
/* Compute grade total and number of grades */

printf("Enter a grade: ") ;
scanf("%d", &grade) ;
while (grade != -1) {
    total = total + grade ;
    counter = counter + 1 ;
    printf("Enter another grade: ") ;
    scanf("%d", &grade) ;
}

/* Compute and display the average grade */
average = total / counter ;
printf ("Class average is: %d\n", average) ;

return 0 ;
}

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
159

while Loop to Check User Input

```
#include <stdio.h>
int main ( )
{
    int number ;
    printf ("Enter a positive integer : ") ;
    scanf ("%d", &number) ;
    while ( number <= 0 )
    {
        printf ("\nThat's incorrect. Enter a +ve number.\n");
        scanf ("%d", &number) ;
    }
    printf ("You entered: %d\n", number) ;    return 0 ;}

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
160

**Counter-Controlled Repetition
(Definite Repetition)**

If it is known in advance exactly how many times a loop will execute, it is known as a **counter-controlled loop**.

```
int i = 1 ;
while ( i <= 10 )
{
    printf("i = %d\n", i) ;
    i = i + 1 ;
}

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
161

Counter-Controlled Repetition (Contd.)

Is the following loop a counter controlled loop?

```
while ( x != y )
{
    printf("x = %d", x) ;
    x = x + 2 ;
}

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
162

Event-Controlled Repetition (Indefinite Repetition)

If it is NOT known in advance exactly how many times a loop will execute, it is known as an **event-controlled loop**.

```

sum = 0 ;
printf("Enter an integer value: ") ;
scanf("%d", &value) ;
while ( value != -1) {
    sum = sum + value ;
    printf("Enter another value: ") ;
    scanf("%d", &value) ;
}

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 163

Event-Controlled Repetition (Contd.)

- An event-controlled loop will terminate when some **event** occurs.
- The event may be the occurrence of a sentinel value, as in the previous example.
- There are other types of events that may occur, such as reaching the end of a data file.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 164

The 3 Parts of a Loop

```

#include <stdio.h>
int main ()
{
    int i = 1 ;
    /* count from 1 to 100 */
    while ( i < 101 ) {
        printf ("%d ", i) ;
        i = i + 1 ;
    }
    return 0 ;
}

```

initialization of **loop control variable**

test of loop termination **condition**

modification of loop control variable

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 165

The **for** Loop Repetition Structure

- The **for** loop handles details of the counter-controlled loop "automatically".
- The *initialization* of the the loop control variable, the *termination condition test*, and *control variable modification* are handled within the **for** loop structure.

```
for ( i = 1; i < 101; i = i + 1 )
{
}
      ↑      ↑      ↑
      init test  modif
```

initialization test modification

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 166

Initialize, Test and Modify in for Loop

Just as with a while loop, a for loop

- initializes** the loop control variable **before beginning the first loop iteration**,
- modifies** the loop control variable **at the very end of each iteration of the loop**, and
- performs the **loop termination test before each iteration of the loop**.

The for loop is easier to write and read for counter-controlled loops.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 167

A for Loop That Counts From 0 to 9

```
for ( i = 0; i < 10; i = i + 1 )
{
    printf ( "%d\n", i ) ;
}
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 168

We Can Count Backwards, Too

```
for ( i = 9; i >= 0; i = i - 1 )
{
    printf ("%d\n", i) ;
}
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 169

Count By 2's or 7's or Whatever

```
for ( i = 0; i < 10; i = i + 2 )
{
    printf ("%d\n", i) ;
}
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 170

for Is Not Until Either!

Remember to get the `for` condition the right way around (it is really a *while* condition)

user probably intends "until j is equal to zero", however this is NOT the way to write it either!

```
int j;
printf("start\n");
for (j = 5; j == 0; j--)
    printf("j = %i\n", j);
printf("end\n");
```

start
end

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 171

Stepping With for

Unlike some languages, the `for` loop in C is not restricted to stepping up or down by 1

```
#include <math.h>

int main(void)
{
    double angle;

    for(angle = 0.0; angle < 3.14159; angle += 0.2)
        printf("sine of %.11f is %.21f\n", angle, sin(angle));

    return 0;
}
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 172

Extending the for Loop

The initial and update parts may contain multiple comma separated statements

```
int i, j, k;
for(i = 0, j = 5, k = -1; i < 10; i++, j++, k--)
```

- The initial, condition and update parts may contain no statements at all!

```
for( ; i < 10; i++, j++, k--)
```

`for(; i < 10;)` use of a while loop would be clearer here!

`for(; ;)` creates an infinite loop


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 173

The do-while Repetition Structure

```
do
{
    statement(s)
} while ( condition );
```

The body of a **do-while** is ALWAYS executed at least once. Is this true of a **while** loop? What about a **for** loop?


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 174



Example

```
do
{
    printf ("Enter a positive number: ");
    scanf ("%d", &num) ;
    if ( num <= 0 )
    {
        printf ("\n Try again\n") ;
    }
} while ( num <= 0 ) ;
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1.
175




An Equivalent while Loop

```
printf ("Enter a positive number: ") ;
scanf ("%d", &num) ;
while ( num <= 0 )
{
    printf ("\nTry again\n") ;
    printf ("Enter a positive number: ");
    scanf ("%d", &num) ;
}
```

Notice that using a while loop in this case requires a priming read.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1.
176



An Equivalent for Loop

```
printf ("Enter a positive number: ") ;
scanf ("%d", &num) ;
for ( ; num <= 0; )
{
    printf ("\nNot +ve. Try again\n") ;
    printf ("Enter a positive number: ") ;
    scanf ("%d", &num) ;
}
```

A for loop is a very awkward choice here because the loop is event-controlled.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1.
177

So, Which Type of Loop Should One Use?

- Use a **for** loop for counter-controlled repetition.
- Use a **while** or **do-while** loop for event-controlled repetition.
 - Use a **do-while** loop when the loop must execute at least one time.
 - Use a **while** loop when it is possible that the loop may never execute.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 178

Nested Loops

- Loops may be **nested (embedded)** inside of each other.
- Actually, any control structure (sequence, selection, or repetition) may be nested inside of any other control structure.
- It is common to see nested **for** loops.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 179

Nested for Loops


```

for ( i = 1; i < 5; i = i + 1 ) {
    for ( j = 1; j < 3; j = j + 1 ){
        if ( j % 2 == 0 ){
            printf ("O" );
        }
        else {
            printf ("X" );
        }
    }
    printf ("\n" );
}
  
```

How many times is the "if" statement executed?

What is the output ?

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 180




The **break** Statement

- The **break** statement can be used in **while**, **do while**, and **for** loops to cause premature exit of the loop.

USE IN *MODERATION*.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
181




Example break in a for Loop

```
#include <stdio.h>
int main ( )
{
    int i ;
    for ( i = 1; i < 10; i = i + 1 )
    {
        if ( i == 5 )
        {
            break ;
        }
        printf ("%d ", i) ;
    }
    printf ("\nBroke out of loop at i = %d.\n", i) ;
    return 0 ;
}
```

OUTPUT:
1 2 3 4
Broke out of loop at i = 5.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
182



The **continue** Statement

- The **continue** statement can be used in **while**, **do-while**, and **for** loops.
- It causes the remaining statements in the body of the loop to be skipped for the current iteration of the loop.
- USE IN *MODERATION*.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
183

Example continue in a for Loop

```
#include <stdio.h>
int main ( )
{
    int i ;
    for ( i = 1; i < 10; i = i + 1 )
    {
        if ( i == 5 )
        {
            continue ;
        }
        printf ("%d ", i) ;
    }
    printf ("\nDone.\n") ;
    return 0 ;
}
```

OUTPUT:
1 2 3 4 6 7 8 9
Done.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 154

Arrays

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 155

Need for Arrays

- Many a time a program needs to work upon multiple related data items.
- e.g.
 - Sales data of multiple products
 - Grades of students in a class
 - Salaries of all employees
- Having independent variables for each such data item would make the program clumsy and difficult to manage.
- An array is a means of solving this problem.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 156

What is an array

- An array is a set of variables that have the same data type and share one name.
- Individual data items in an array are stored in contiguous memory locations.
- These data items are differentiated by means of an index (also termed as subscript).
- The index of an element is an indicator of its storage order.
- Arrays are often used when dealing with multiple data items possessing common characteristics.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
157

Visual Representation of an Array

These numbers indicate the value stored in array element

1	3	5	...	9	11	13
0	1	2	...	n-3	n-2	n-1

Numbers denoting the array subscripts or indices

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
158

Working without Arrays

Store and print marks of all the students of a class

```

int m1, m2, m3...
scanf ("%d", &m1);
scanf ("%d", &m2);
...
scanf ("%d", &m3);
  
```

Without array

1. Multiple variables too tedious to manage.
2. Unnecessary repetition of code.
3. Code difficult to maintain.
4. If we simply use a single variable and keep overwriting it n times then data would not be available for future use.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
159

Declaring an Array

<datatype> <identifier> [<size>]

Examples:

```
int Marks [40];
float Sales [10];
char Grades [40];
char Name [30];
```

Character arrays can have two different interpretations:

- **String:** grouped characters, e.g. *name*
- **Individual characters,** e.g. *grades of all students*

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
150

Basics about Arrays

- An array has a fixed number of elements based on its creation
- The elements are numbered from **0** to “**array size – 1**”
- Arrays store many values but have only one identifier
- The array identifier represents the memory location of where the array begins
- The array index represents a logical offset to an area of storage in the array.
- The actual offset address depends on the data type of the array.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
151

Visual Representation

The diagram shows a memory layout for an array. It consists of four cells, each representing an element of the array. The first cell is at memory address 342901 and contains a question mark, with an offset/index of 0. The second cell is at 342903, also with a question mark, and an offset/index of 1. The third cell is at 342905 and contains the value 23, with an offset/index of 2. The fourth cell is at 342907 and contains a question mark, with an offset/index of 3. Labels indicate the 'Address' for each cell, the 'Identifier' (x) for the array, the 'Offset / Array index' for each element, the 'Value' stored in each cell, and the 'Array elements' as a whole.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
152

The array element operator []

- The array element operator is used to reference a specific array element.
- The expression inside the array element, *termed as index*, must resolve to type int.
- The value of the index can be any number, but care should be taken that the index falls within the bounds (**0 – SIZE-1**) of the array.
 - The compiler / runtime environment do not perform this check.**

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

Array example

```
#include <stdio.h>
int main(void)
{
    int x[5];
    x[0]=23;    /* valid */
    x[2.3]=5;   /* invalid: index isn't int */
    return 0;
}
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

Initializing arrays

An array is initialized

- using a code block
- containing comma-delimited values
- The values match in position with the elements in the array.

If there are values in the initialization block, but not enough to fill the array,

- all the elements in the array without values are initialized to 0 in the case of float or int,
- NULL in the case of char

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

Initializing Arrays - II

If there are values in the initialization block,

- an explicit size for the array does not need to be specified
- only an empty array element operator is enough.

C will count the values and size the array for you

What if size is provided and the initialization block contains extra values !!!

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 156

Examples

`int x [5] = { 1,2,3,4,5 }; size 10 bytes`
 ▪ creates array with indices 0-4; element values 1-5

`int x [5] = { 4,3 }; size 10 bytes`
 ▪ creates array with indices 0-4; element values 4,3,0,0,0

`int x [] = { 1,2,3 }; size 6 bytes`
 ▪ creates array with indices 0-2; element values 1,2,3

`char c [4] = { 'M' , 'o' , 'o' }; size 4 bytes`
 ▪ creates array with indices 0-3; element values M o o NULL

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 157

Using Array Elements

Array elements can be used like any variable

read into:

```
printf("Sales for employee 3: ");
scanf("%f",&(Sales[3]));
```

printed:

```
printf("Sales for employee 3
    $%7.2f\n",Sales[3]);
```

used in other expressions:

```
Total = Sales[0] + Sales[1] + Sales[2] + ...;
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 158

Processing All Elements of Array

Process all elements of array A using for:

```
/* Setup steps */
for (I = 0; I < ArraySize; I++)
    process A[I]
/* Clean up steps */
```

Notes

- Initialize I to 0
- Terminate when I reaches ArraySize

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 199

Arrays and Loops

Problem: initialize Sales with zeros

```
Sales[0] = 0.0;
Sales[1] = 0.0;
...
Sales[9] = 0.0;
```

Should be done with a loop:

```
for (I = 0; I < 10; I++)
    Sales[I] = 0.0;
```


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 200

The Array Advantage

```
#include <stdio.h>
int main(void)
{
    int i , x[5] , total = 0 ;
    for ( i = 0 ; i < 5 ; i++ )
    {
        printf( "Enter mark %d" , i );
        scanf ( "%d" , &x[ i ] );
    }
    for ( i = 0 ; i < 5 ; i++ )
        total = total + x[i];

    printf ( "The average is %d" , total / 5 );
    return 0;
}
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 201



Good Programming Practice

Define constant for highest array subscript:

```
#define MAXEMPS 10
```

Use constant in array declaration:


```
float Sales[MAXEMPS];
```

Use constant in loops:

```
for (I = 0; I < MAXEMPS; I++)
    scanf("%f", &(Sales[I]));
```

If MAXEMPS changes, only need to change one location


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
202



Try working on following

- Print Elements of an Array
- Calculate Sum / Average of Elements in an Array
- Find Maximum / Minimum Element of an Array
- Search for a value in an Array
- Sort (arrange in ascending / descending order) the data of an Array

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
203



Related Arrays - I

Consider two arrays that store

- Roll numbers of students
- Marks of students

Respectively.

Write a program to generate the following output:

Roll Number	Marks
100	20
101	45
105	32

Here the processing block will refer to the same index location of the two arrays

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
204

Related Arrays – II

- Suppose now we have 3 arrays for storing marks in three different subjects.
- Write a program to store sum of marks obtained by a student in all subjects in another array.

Roll number	→	101	102	105	112	113
English	→	20	30	32	40	28
Mathematics	→	45	35	36	47	38
Science	→	37	38	33	40	42
Total	→					

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 206

Try the following

Merge the contents of two arrays on another array

- What should be the size of the resultant array

Extract elements at location *a* to location *b* and store the results in another array


- What should be the size of the resultant array
- What if *a* and *b* are entered by user!!!

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 206

Strings

- Another application of Arrays is to store multiple related characters.
- These set of characters are termed as *strings*.
- Strings in C are a series of characters terminated with a NULL ('\0') character.
 - `char Name [30];`
 - `scanf ("%s", Name);`
 - `printf ("%s", Name);`
- Note that the '&' character is missing while scanning the string. *Why!!! How does scanf work in this case?*

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 207



Processing Strings

Each individual element of a string is a *char*


Use a loop that

- Starts processing from the 0th element (*Name[i]*, where *i* is initialized to 0)
- **Processes each subsequent element**
- **Till the element being processed is not equal to '\0'**

Convert a string to upper case

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
208



Limitation & Overcoming

The size of an array, once defined, is a constant.

Can make use of dynamic creation.

Where memory can be requested at runtime according to the requirement of the user.


Restricted to a single data-type

More on dynamic creation & structures will be covered in later sessions.

- Structure for a single set of related variables with different types
- Array of structures for multiple sets.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
209



Selection Sorting

Approach (N is # elements in array):

1. Find smallest value in A and swap with A[0]
2. Find smallest value in A[1] .. A[N-1] and swap with A[1]
3. Find smallest value in A[2] .. A[N-1] and swap with A[2]
4. Continue through A[N-2]

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
210

Selection Sort Example

Original Array 6 4 8 10 1

Swap the smallest with A[0] 1 4 8 10 6

Swap 2nd smallest with A[1] 1 4 8 10 6

Swap 3rd smallest with A[2] 1 4 6 10 8

Swap 4th smallest with A[3] 1 4 6 8 10

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 211

Selection Sort Notes

- If array has N elements, process of finding smallest repeated N-1 times (outer loop)
- Each iteration requires search for smallest value (inner loop)
- After inner loop, two array members are swapped if required
- Can search for largest member to get descending-order sort

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 212

Selection Sort Algorithm

For J is 0 to N-2
 Find smallest value in A[J], A[J+1] .. A[N-1]
 Store subscript of smallest in Index
 Swap A[J] and A[Index]

Find smallest in A[J..N-1]


```

Smallest = A[J];
for (K = J+1; K < N; K++)
  if (A[K] < Smallest)
    Smallest = A[K];

```

But we need location of smallest, not its value to swap, **Change???**

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 213



Binary Search

Example: when looking up name in phone book, don't search start to end


Prerequisite: Sorted Array

Approach:

- Open book in middle
- Determine if name in left or right half
- Open that half to its middle
- Determine if name in left or right of that half
- Continue process until name is found (or not)

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
214




Dimensionality

- The number of subscripts determines the dimensionality of an array
- $x[i]$ refers to an element of a one dimensional array x
- $y[i][j]$ refers to an element of a two dimensional array y
- $z[i][j][k]$ refers to an element of a three dimensional array z
- Etc.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
215




Single v. Multi-dimensional

- So far, we have only looked at single dimensional arrays
- E.g. we can represent one row of data
 - `int numbers[5] = {2,4,6,7,4};`
- A two dimensional array is similar to creating a table of data (also similar to a Microsoft Excel spreadsheet.)
- You can also create 3, 4, 5 dimensional arrays
 - In fact, the ANSI C specification states that compilers must be able to support up to 12 dimensions
- Beyond 2 dimensions, however, things can get confusing. So, we will stick to 2 initially.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
216




Why use 2-D arrays?

2-D arrays are useful for lots of applications

- Anything that you would put in a table fits nicely into a 2-D array
- Track company stock price for 5 different companies over 30 days. (just create a 5 x 30 array.)
- Track homework grades for 5 homework assignments completed by 55 students (just create a 5 x 55 array.)

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
217



Declaring 2D arrays

To declare a 1-D Array, we specify 1 size
data_type array_name [size];


To declare a 2-D Array, we specify 2 sizes
data_type array_name[# of rows][# of columns]

Examples

```
int a[2][3]; /* Creates a 2x3 array of ints */
double b[5][2] /* Creates a 5x2 array of doubles */
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
218



Initializing 2-D arrays

- To initialize a 1-D Array, just place all your data inside of brackets { }
- To initialize a 2-D Array, place your data inside of embedded brackets { {},{} }

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
219

Logical Interpretation

Syntax: **BaseType Name[*IntLit1*][*IntLit2*];**

First
Dimension

		Second Dimension			
		0	1	2	3
0					
1					
2					

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
220

Storage Scheme

- C follows a "Row-Major" storage order
- All the data elements of an array are stored at contiguous locations
- The elements of 0th row are followed by those of 1th and so on...
- Thus, the actual storage order (in memory) for the array depicted in the previous slide would be

--	--	--	--	--	--	--	--	--	--

Row 0
Row 1
Row 2

We would be using the logical interpretation of data storage as it helps in visualizing programming problems more easily.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
221

Initialising a 2D array

int b[2][2] = { {1}, {3, 4}};

This one line will create a 2 x 2 array and initialize the array as follows

Columns →

		0	1
Rows ↓	0	1	0
	1	3	4

Note: In this case, we provide one data element for the first row. After this, all remaining elements in the row are initialized to 0

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
222

2D Array Element Reference

- Syntax: `array_name[expr_row #][expr_col #]`
- Expressions are used for the two dimensions in that order
- Remember that index numbers in C always start at 0
- Values used as subscripts must be legal for each dimension
- Each location referenced can be treated as variable of that type
- Example: `Grades[3][2]` is a character, provided `Grades` is 2-D character array

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

Examples

Assuming we have the following array b:

	0	1
0	1	0
1	3	4

```
printf ("%d", b[0][0]);    /* prints 1 */
printf ("%d", b[1][0]);    /* prints 3 */
printf ("%d", b[1][1]);    /* prints 4 */
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

Processing 2D Arrays


Use nested loops to process 2D array

Type Name[Dim1][Dim2];

Processing Order:

- Row Major
- Column Major

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal




Row Major processing

Process all the elements of x^{th} row
Followed by those of $(x+1)^{\text{th}}$ row

```
for (J = 0; J < Dim1; J++)
    for (K = 0; K < Dim2; K++)
        process Name[J][K];
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
226




Column Major Processing

Process all the elements of x^{th} column
Followed by those of $(x+1)^{\text{th}}$ column

```
for (J = 0; J < Dim2; J++)
    for (K = 0; K < Dim1; K++)
        process Name[K][J];
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
227



Multi-Dimensional Array Declaration

Syntax:

BaseType Name[*IntLit1*][*IntLit2*][*IntLit3*]...;

Provide one constant for each dimension


Can have as many dimensions as desired

Examples:

```
int ThreeDPoints [100][256][256]; /* 3D array */
float TimeVolume [100][256][256][256]; /* 4D array */
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
228




Multi-Dim Array Reference

- To refer to an element of multi-dimensional array use one expression for each dimension
- syntax:
 - ✓ **Name[Expr1][Expr2][Expr3]** /* 3D */
 - ✓ **Name[Expr1][Expr2][Expr3][Expr4]** /* 4D */
 - ✓ etc.
- First expression - first dimension,
- Second expression - second dimension, etc.
- C does not check dimensions

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal


U1
229



Functions

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
230




Topics

- Using Predefined Functions
- Programmer-Defined Functions
- Using Input Parameters
- Function Header Comments

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
231




Review-Structured Programming

A problem solving strategy and a programming methodology that includes the following guidelines:

- The program uses only the sequence, selection, and repetition control structures.
- The flow of control in the program should be as simple as possible.
- The construction of a program embodies top-down design.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
232




Review of Top-Down Design

- Involves repeatedly **decomposing** a problem into smaller problems
- Eventually leads to a collection of small problems or tasks each of which can be easily coded
- The **function** construct in C is used to write code for these small, simple problems.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
233



Functions

- A C program is made up of one or more functions, one of which is `main()`.
- Execution always begins with `main()`, no matter where it is placed in the program.
- *By convention, `main()` is located before all other functions.*
- When program control encounters a function name, the function is **called (invoked)**.
 - **Program control passes to the function.**
 - **The function is executed.**
 - **Control is passed back to the calling function.**

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
234

Sample Function Call

```
#include <stdio.h>

int main ( )
{
    printf ("Hello World!\n");
    return 0;
}
```

printf is the name of a predefined function in the stdio library

this statement is known as a function call

this is a string we are passing as an argument (parameter) to the printf function

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1: 235

Functions (Contd.)

- We have used three predefined functions so far:
 - printf
 - scanf
 - getchar
- Programmers can write their own functions.
- Typically, each *module* in a program's design *hierarchy chart* is implemented as a function.
- C function names follow the same naming rules as C variables.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1: 236

Sample Programmer-Defined Function

```
#include <stdio.h>

void printMessage ( void ) ;

int main ( )
{
    printMessage ( ) ;
    return 0 ;
}

void printMessage ( void )
{
    printf ("Have a nice day!\n") ;
}
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1: 237

Examining printMessage

```
#include <stdio.h>

void printMessage ( void );

int main ( )
{
    printMessage ( );
    return 0 ;
}

void printMessage ( void )
{
    printf ("A message for you:\n\n");
    printf ("Have a nice day!\n");
}
```

Diagram labels:

- `void printMessage (void);` → function prototype / declaration
- `printMessage ();` → function call
- `void printMessage (void)` → function header
- `{ ... }` → function body
- Entire function block → function definition

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 238

The Function Prototype

Inform the compiler that there will be a function defined later that:

returns this type has this name takes these arguments

↓ ↓ ↓

void printMessage (void);

Needed because the function call is made before the definition
The compiler uses it to see if the call is made properly

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 239

The Function Prototype - II

The prototype provides the compiler with important information about the return type and parameters

If the compiler meets a call to an unknown function it "guesses"

- Guess 1: the function returns an int, even if it doesn't
- Guess 2: you have passed the correct number of parameters and made sure they are all of the correct type, even if you haven't

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 240

Prototyping

- When calling a Standard Library function, `#include` the file specified in the help page(s) - this file will contain the prototype.
- When calling one of your own functions, write a prototype yourself.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 241

The Function Call

- Passes program control to the function
- Must match the prototype in name, number of arguments, and types of arguments

```

void printMessage (void) ;
int main ( ) same name no arguments
{
    printMessage ( ) ;
    return 0 ;
}
  
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 242

The Function Definition

Control is passed to the function by the function call. The statements within the function body are then executed.

```

void printMessage ( void )
{
    printf ("A message for you:\n\n") ;
    printf ("Have a nice day!\n") ;
}
  
```

After the statements in the function have completed, control is passed back to the **calling function**, in this case `main()`.

Note that the calling function does not have to be `main()`.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 243

General Function Definition Syntax

```

return_type functionName(parameter1, . . . ,
                          parametern )
{
    variable declaration(s)
    statement(s)
    return statement
}

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 244

Using Input Parameters

```

void printMessage (int counter) ;
int main ( )
{
    int num;
    printf ("Enter an integer: ");
    scanf ("%d", &num) ;
    printMessage (num) ;
    return 0 ;
}
void printMessage (int counter)
{
    int i ;
    for ( i = 0; i < counter; i++ )
        printf ("Have a nice day!\n") ;
}

```

One argument of type int


Matches one formal parameter of type int

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 245

Parameter Passing

- Consider a function **averageTwo** that calculates and returns the average of two integers passed to it as parameters.
- Actual parameters** are the parameters that appear in the function call. `average = averageTwo (value1, value2) ;`
- Formal parameters** are the parameters that appear in the function header. `float averageTwo (int num1, int num2)`
- Actual and formal parameters are matched by position.
- Each formal parameter receives the value of its corresponding actual parameter.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 246




Parameter Passing - II

Corresponding actual and formal parameters

- do not have to have the same name, but they may.
- must be of the same data type, *with some exceptions*.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
247




Local Variables

- Functions only "see" (have access to) their own **local variables**. This includes main().
- Formal parameters are declarations of local variables. The values passed are assigned to those variables.
- Other local variables can be declared within the function body.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
248



The Rules

- A function may accept zero or as many parameters as it needs.
- A function may return either one or no values.
- Variables declared inside a function, unless explicitly passed to another function, are available to that function only.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
249

Writing a Function - Example

this is the TYPE of the value handed back

accept 3 doubles when called

```

int print_table(double start, double end, double step)
{
    double d;
    int    lines = 1;

    printf("Celsius\tFahrenheit\n");
    for(d = start; d <= end; d += step, lines++)
        printf("%.11f\t%.11f\n", d, d * 1.8 + 32);

    return lines;
}

```

this is the ACTUAL value handed back

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
250

Writing Prototypes

- Function header:


```
int print_table(double start, double end, double step)
{
```
- The function prototype may optionally include variable names (which are ignored)
- Thus, the following declarations are treated to be the same:


```
int print_table(double start, double end, double step);
```

```
int print_table(double x, double y, double z);
```

```
int print_table(double, double, double);
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
251

Take Care With Semicolons

The prototype has a semicolon

```
int print_table(double start, double end, double step);
```

- The function header has an open brace


```
int print_table(double start, double end, double step)
{
```
- Don't confuse the compiler by adding a semicolon into the function header!


```
int print_table(double start, double end, double step);
{
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
252

Example Prototypes

```

/* no parameters, int return value */
int get_integer(void);

/* no parameters, double return value */
double get_double(void);

/* no parameters, no return value */
void clear_screen(void);

/* three int parameters, int return value */
int day_of_year(int day, int month, int year);

/* parameter checking DISABLED, double return value */
double test_function();

/* short int parameter, (default) int return value */
transfer(short int s);

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
253

Example Calls

```

int i;
double d;
long l;
short ints = 5;

i = get_integer();
d = get_double();
clear_screen();

i = day_of_year(16, 7, 1969);

d = test_function();
d = test_function(19.7);
d = test_function("hello world");

i = transfer(s);

```

no mention of "void" when calling these functions

the compiler cannot tell which of these (if any) is correct - neither can we without resorting to documentation!

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
254

Attributes of a variable

A variable has the following attributes associated with it:

- Data type
- Name
- Memory Address
- Scope (code blocks where the variable is visible / accessible)
- Lifetime (duration for which the variable is retained in memory)

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
255


Rules of Visibility


```

int main(void)
{
    int i = 5, j, k = 2;
    float f = 2.8F, g;
    d = 3.7;
}

void func(int v)
{
    double d, e = 0.0, f;
    i++; g--;
    f = 0.0;
}

```

 compiler does not know about "d"

 "i" and "g" not available here

func's "f" is used, not main's

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1: 256

Function call mechanism and the Stack

C uses a **stack** to store local variables (i.e. those declared in functions), it is also used when passing parameters to functions

- ❶ The calling function pushes the parameters (*along with other data*).
- ❷ The function is called.
- ❸ The called function picks up the parameters.
- ❹ The called function pushes its local variables.
- ❺ When finished, the called function pops its local variables.
- ❻ Control jumps back to the calling function.
- ❼ The calling function pops the parameters, and handles the return value.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1: 257

Stack Example

```

#include <stdio.h>

double power(int, int);

int main(void) {
    int x = 2;
    double d;

    d = power(x, 5);
    printf("%lf\n", d);

    return 0;
}

double power(int n, int p) {
    double result = n;
    while(--p > 0)
        result *= n;

    return result;
}

```

Variables on the Stack (partial contents)

32.0	power: result
2	power: n
5	power: p
?	main: d
2	main: x

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1: 258

Storage

- C stores local variables on the stack
- **Global variables** may be declared. These are not stack based, but are placed in the data area meant for global/static data.
- Special keywords exist to specify where local variables are stored:
 - `auto` - place on the stack (default)
 - `static` - place in the global/static data area
 - `register` - place in a CPU register
- Data may also be placed on the heap, **detailed discussion will be carried out in a later session**

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 259

Memory Map

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 260

Auto

- Local variables are automatically allocated on entry into, and *automatically de-allocated on exit from*, a function
- These variables are therefore called “automatic”
- Initial value: random
- Initialization: recommended

```

int table(void)
{
    int    lines = 13;
    auto int columns;
  
```

auto keyword redundant

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 261

static

- The `static` keyword instructs the compiler to place a variable into the data segment
- The data segment is *permanent* (static)
- A value left in a `static` in one call to a function will still be there at the next call
- Initial value: 0
- Initialization: unnecessary if zero is acceptable

```
int running_total(void)
{
    static int rows;
    rows++;
}
```

permanently allocated,
but local to this
function

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 262

register

- The `register` keyword tells the compiler to place a variable into a CPU register (you cannot specify which)
- If a register is unavailable the request will be ignored*
- Largely redundant with optimizing compilers
- Initial value: random
- Initialization: recommended

```
void speedy_function(void)
{
    register int i;
    for(i = 0; i < 10000; i++)

```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 263


Global Variables

- Global variables are created by placing the declaration outside all functions
- They are placed in the global/static data area
- Initial value: 0
- Initialization: unnecessary if zero is acceptable
- Avoid using this category of variables. **Why!!!**

```
#include <stdio.h>
double d;
int main(void)
{
    int i;
    return 0;
}
```

variable "d" is global
and available to all
functions defined
below it

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 264



extern

This declaration indicates that

- the actual storage and initial value of a variable, or
- body of a function

is defined elsewhere.

The location is usually in a separate code module


The keyword is optional for a function prototype.

Example:

```
extern int mode;
extern void GlobalFunction (int);
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
265




Parameter passing mechanisms

By value

By reference (address / pointer)

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
266



Call by Value

- When a function is called the parameters are *copied* - "call by value"
- The function is unable to change any variable passed as a parameter
- In the next session we will discuss *pointers* which allow "call by reference"
- We have already had a sneak preview of this mechanism with `scanf`

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
267

Call by Value - Example

```
#include <stdio.h>

void change(int v);

int main(void){
    int var = 5;

    change(var);

    printf("main: var = %i\n", var);

    return 0;
}

void change(int v){
    v *= 100;
    printf("change: v = %i\n", v);
}
```

the function was not able to alter "var"

the function is able to alter "v"

change: v = 500
main: var = 5

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 268

Formatted Example

```
/* *****
** averageTwo - calculates and returns the average of two
** numbers
** Inputs:      num1 - an integer value
**              num2 - an integer value
** Outputs:     the floating point average of num1 and num2
** ***** */

float averageTwo (int num1, int num2)
{
    float average ;    /* average of the two numbers */
    average = (num1 + num2) / 2.0 ;
    return average ;
}
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 269

Using averageTwo

```
#include <stdio.h>

float averageTwo (int num1, int num2) ;

int main ( )
{
    float ave ;
    int value1 = 5, value2 = 8 ;
    ave = averageTwo (value1, value2) ;
    printf ("%d + %d / 2 = %f\n", value1, value2, ave) ;
    return 0 ;
}
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 270

Parameter Passing and Local Variables

```
#include <stdio.h>
float averageTwo (int num1, int num2);
int main ()
{
    float ave;
    int value1 = 5, value2 = 8;

    ave = averageTwo (value1,
                     value2);
    printf ("The average of ");
    printf ("%d and %d is %f\n",
            value1, value2, ave);
    return 0;
}
```

```
float averageTwo (int num1, int num2)
{
    float average;

    average = (num1 + num2) / 2.0;
    return average;
}
```

Copies of value1 and value2

value1 (int) 5, value2 (int) 8, ave (float)
 num1 (int) 5, num2 (int) 8, average (float) 6.5

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 271

Same Name, Still Different Memory Locations

```
#include <stdio.h>
float averageTwo (int num1, int num2);
int main ()
{
    float average;
    int num1 = 5, num2 = 8;

    average = averageTwo (num1,
                          num2);
    printf ("The average of ");
    printf ("%d and %d is %f\n",
            num1, num2, average);
    return 0;
}
```

```
float averageTwo (int num1, int num2)
{
    float average;

    average = (num1 + num2) / 2.0;
    return average;
}
```

Copies of num1 and num2 of main

num1 (int) 5, num2 (int) 8, average (float)
 num1 (int) 5, num2 (int) 8, average (float)

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 272

Local Variables Vs. Other Variables with Same Name

```
#include <stdio.h>
void addOne (int number);


int main ()
{
    int num1 = 5;
    addOne (num1);
    printf ("In main: ");
    printf ("num1 = %d\n", num1);
    return 0;
}
```

```
void addOne (int num1)
{
    num1++;
    printf ("In addOne: ");
    printf ("num1 = %d\n", num1);
}
```

num1
5
int

OUTPUT
In addOne: num1 = 6
In main: num1 = 5


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 273



Solution...

Use Pointers.


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 274



Pointers

- Declaring pointers
- The "&" operator
- The "*" operator
- Initializing pointers
- Type mismatches
- Call by reference
- Pointers to pointers

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 275



Pointers - Why?

Using pointers allows us to:

- Achieve call by reference (i.e. write functions which change their parameters)
- Handle arrays efficiently
- Handle structures (records) efficiently
- Create linked lists, trees, graphs etc.
- Put data onto the heap

Already been using pointers with `scanf`

Care must be taken when using pointers since there are no safety features

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 276

Declaring Pointers

Pointers are declared by using “*”

Declare an integer:

```
int i;
```

Declare a pointer to an integer:

```
int *p;
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
277

Example Pointer Declarations

```
int    *pi;        /* pi is a pointer to an int */
long int *p;        /* p is a pointer to a long int */
float*  pf;         /* pf is a pointer to a float */
char    c, d, *pc;   /* c and d are a char
                    pc is a pointer to char */
double* pd, e, f;    /* pd is pointer to a double
                    e and f are double */
char*   start;       /* start is a pointer to a char */
char*   end;         /* end is a pointer to a char */
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
278

The “&” Operator

- The “&”, “address of” operator, generates the address of a variable
- All variables have addresses except register variables

```
char g = 'z';
int main(void)
{
    char c = 'a';
    char *p;

    p = &c;
    p = &g;

    return 0;
}
```

p

0x1132

→

c

'a'

0x1132

p

0x91A2

→

g

'z'

0x91A2

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
279

Rules

- Pointers may only point to variables of the same type as the pointer has been declared to point to
- A pointer to an int may only point to an int
 - not to char, short int or long int, certainly not to float, double or long double
- A pointer to a double may only point to a double
 - not to float or long double, certainly not to char or any of the integers
- Etc.....

```
int  *p;      /* p is a pointer to an int */
long large = 27L; /* large is a long int,
                  initialized with 27 */

p = &large;   /* ERROR */
```

What if this rule is not followed!!!

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 280

The “*” Operator

The “*”, “points to” (*indirection*) operator, gives the value at the end of a pointer i.e. the value stored at the address pointed to by a pointer

```
#include <stdio.h>
char g = 'z';
int main(void)
{
    char c = 'a';
    char *p;
    p = &c;
    printf("%c\n", *p);
    p = &g;
    printf("%c\n", *p);
    return 0;
}
```

print “what p points to”

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 281

Writing Down Pointers

Not only is it possible to *read* the values at the end of a pointer, as with:

```
char c = 'a';
char *p;
p = &c;
printf("%c\n", *p);
```

- It is also possible to *write* over the value at the end of a pointer:

```
char c = 'a';
char *p;
p = &c;
*p = 'b';
printf("%c\n", *p);
```

make what p points to equal to 'b'

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 282

Initialization Warning!

The following code contains a horrible error: *why*

```
#include <stdio.h>

int main(void)
{
    short i = 13;
    short *p;

    *p = 23;
    printf("%hi\n", *p);

    return 0;
}
```

p
?

i
13
0x1212

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
283

Initialize Pointers!

Pointers are best initialized!
A pointer may be declared and initialized in a single step

```
short i = 13;
short *p = &i;
```

- This does NOT mean "make what p points to equal to the address of i"
- It DOES mean "declare p as a pointer to a short int, make p equal to the address of i"

short *p = &i;

short *p = &i;

✗

short *p = &i;

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
284

NULL

- A special invalid pointer value exists #defined in various header files, called NULL
- What is the significance of assigning a NULL to a pointer!!!

```
#include <stdio.h>

int main(void)
{
    short i = 13;
    short *p = NULL;

    if(p == NULL)
        ...
    else
        ...

    return 0;
}
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
285

A World of Difference!

There is a great deal of difference between:

```
int i = 10, j = 14;
int *p = &i;
int *q = &j;

*p = *q;
```

Diagram 1:

and:

```
int i = 10, j = 14;
int *p = &i;
int *q = &j;

p = q;
```

Diagram 2:

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 266

Fill in the Gaps

```
int main(void)
{
    int i = 10, j = 14, k;
    int *p = &i;
    int *q = &j;

    *p += 1;

    p = &k;

    *p = *q;

    p = q;

    *p = *q;

    return 0;
}
```

Memory Addresses:

- i
- 0x2100
- j
- 0x2104
- k
- 0x1208
- p
- 0x120B
- q
- 0x1210

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 267

Type Mismatch

The compiler will not allow type mismatches when assigning to pointers, or to where pointers point.

A **warning** is generated if such an attempt is made.

```
int i = 10, j = 14;
int *p = &i;
int *q = &j;

p = *q;
*p = q;
```

Diagram:

cannot write 0x15A4 into i

cannot write 14 into p

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 268

Call by Value - Reminder

```
#include <stdio.h>
void change(int v);
int main(void)
{
    int var = 5;
    change(var);
    printf("main: var = %i\n", var);
    return 0;
}
void change(int v)
{
    v *= 100;
    printf("change: v = %i\n", v);
}
```

the function was not able to alter "var"

the function is able to alter "v"

change: v = 500
main: var = 5

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 289

Call by Reference

prototype "forces" us to pass a pointer

```
#include <stdio.h>
void change(int* p);
int main(void)
{
    int var = 5;
    change(&var);
    printf("main: var = %i\n", var);
    return 0;
}
void change(int* p)
{
    *p *= 100;
    printf("change: *p = %i\n", *p);
}
```

main: var
0x1120 5

change: p
0x1124 0x1120

change: *p = 500
main: var = 500

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 290

Pointers to Pointers

C allows pointers to any type
It is possible to declare a pointer to a pointer
Or a pointer to a pointer to a pointer...

```
#include <stdio.h>
int main(void)
{
    int i = 16;
    int *p = &i;
    int **pp;

    pp = &p;
    printf("%i\n", **pp);
    return 0;
}
```

pp is a "pointer to" a "pointer to an int"


16
0x2320 i

0x2320 p 0x2320

0x2324 pp 0x2324

0x2328

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 291



Review

```

int main(void)
{
    int i = 10, j = 7, k;
    int *p = &i;
    int *q = &j;
    int *pp = &p;

    **pp += 1;

    *pp = &k;

    **pp = *q;

    i = *q**pp;

    i = *q/**pp; /* headache? */;

    return 0;
}

```

i

j


k

p

q

pp


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
292



Good Programming Practices *

- Write functions to avoid rewriting of code
- Each function that you define should address a well defined task.
- Remember to provide the **prototypes** of the functions you intend to use.
- Remember to add **function header comments** formatted neatly according to the guidelines provided.
- Avoid use of global variables
- If a function generates multiple results pass parameters by reference


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
293



Recursion...

...a mechanism by which a function calls itself

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
294




Recursive Functions

- *recursive functions*: represent an activity that can be defined in terms of itself
- Common examples
 - *X raised to power Y* is $X * (X \text{ raised to power } Y-1)$
 - *Factorial N* is $N * (Factorial\ N-1)$

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
295



Algorithm Structures

Iterative \Rightarrow execute action in loop


Recursive \Rightarrow reapply action to sub-problem(s)

Problems that can be solved by recursion can always be solved by iteration also.

Recursive solution:
 Might lead to a simpler algorithm
 The algorithm might not be as efficient, though.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
296



Parts of a Recursive Algorithm


A smallest *base case* that is *processed without recursion*.

A general method to reduce a particular case to one (or more) of smaller cases.

Basic Idea: Progress towards; and eventually reduce a problem to the *base case*.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal


U1:
297



Considerations for Recursive Algorithms

- How to define the problem in terms of a smaller problem of the same type?
- Does each recursive call diminish the size of the problem?
- What instance of the problem can serve as the base case?
- As the problem size diminishes, will you reach this base case?

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
298



Example I: X Raised to Power Y

Iterative definition:
 Power (X, Y) = X * X * X * ... X, Y times for any Y > 0.
 Power (X, 0) = 1


Another Recursive solution

• $x^p = x^{p/2} * x^{p/2}$ if p is even

• $x^p = x^{p/2} * x^{p/2} * x$ if p is odd

- Recursive solution:
 1. **Power (X, Y) = X * Power (X, Y-1)**
 2. **Problem diminishing?** yes.
 3. **Base case:** Power (X, 0) = 1; base case does not have a recursive call.
 4. **Can reach base case as problem diminishes?** yes

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
299




Example II: Factorial of N

Iterative definition:
 Factorial(N) = N * (N-1) * (N-2) * ... 1 for any N > 0.
 Factorial(0) = 1

Recursive solution:

- 1. **Factorial (N) = N * Factorial(N-1)**
 2. **Problem diminishing?** yes.
 3. **Base case:** Factorial(0) = 1; base case does not have a recursive call.
 4. **Can reach base case as problem diminishes?** Yes

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
300



Recursive Calls & Stack

Recall that: When a function is called the


1. Return address
2. Function Parameters

Are pushed on the stack

Whenever a recursive call is made a fresh data frame is added onto the stack.


A failure to reach the base case can lead to stack overflow

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
301




Stack Contents : Example

Function Call: Factorial (5);




Function call sequence



Return sequence

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
302



Designing Recursive Algorithms

Find the Key Step

- Look for a general rule to break the problem into simpler parts

Find a Stopping Rule

- A trivial case that can be handled without recursion


Outline the algorithm

- Combine the key step and the stopping rule using if statement

Check Termination

- The calls must lead to the base case irrespective of the initial value for which the recursive algorithm is invoked.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
303



Discuss

⇒ Sum of first n positive integers

⇒ Fibonacci Series

⇒ Recurrence Relations


⇒ Binary Search

⇒ Is Palindrome

⇒ Reversing a string

⇒ Towers of Hanoi


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
304



Function Calls


- We know that function call activity follows the LIFO rule.
- A set of stack frames can be used to represent function calls.
- These stack frames would plot stack contents against time.
- A stack frame showing
 - a particular function stacked upon itself,
 - at a given point of time
- represents a recursive function call.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
305



A Sample Stack Frame

Recursive Function Calls




© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
306

Tree of function calls – an alternative representation

A tree diagram that shows

- The *main* function as the root (level 0); and
- The direct calls made by *main* are shown as nodes at one lower level (level 1)
- Similarly, a function call made by a node *X* at level *L* is shown by a node at level *L+1*

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 307




Recursion Tree


A part of *function-call tree*
Shows only *recursive calls*

As the number of levels in tree increases

- So does the the amount of space needed to implement the recursive function call.
- **Why!!!**

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal U1: 309





Designing Efficient Recursive Algorithms

Find the Key Step

- Look for a general rule to break the problem into simpler parts

Find a Stopping Rule

- A trivial case that can be handled without recursion

Outline the algorithm

- Combine the key step and the stopping rule using if statement

Check Termination

- The calls must lead to the base case irrespective of the initial value for which the recursive algorithm is invoked.


Draw a Recursion Tree

- To check efficiency

← **Important**

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal


U1:
312



The Towers of Hanoi Legend

- Legend has it that priests in a Temple were given a puzzle by Lord Brahma.
- The puzzle consisted of a golden platform with three diamond needles, on which were placed 64 golden disks.
- The priests were to move one disk per day, following a set of rules.
- When they had successfully completed their task, the world would come to an end.


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
313




Towers of Hanoi: The Rules

- When a disk is moved from one peg it must be placed on another.
- Only one disk may be moved at a time, and it must be the top disk on a tower.
- A larger disk may never be placed upon a smaller disk.


© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
314





A single disk tower





© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal
U1:
315
































Move 7

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
329

Simplifying the method (3 disks)

Step 1

- Move the top 2 disks from A to B using C as intermediate

Step 2

- Move the remaining disk from A to C

Step 3

- Move 2 disks from B to C using A as intermediate

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
329


General solution

The key to the solution is to notice that to move any disk, we must first move the smaller disks off of it, thus a recursive definition

- To move 1 disk
 - ✓ Move 1 disk from start tower to destination tower
- To move 2 disks
 - ✓ Move smaller disk from start tower to intermediate tower
 - ✓ Move larger disk from start tower to final tower
 - ✓ Move smaller disk from intermediate tower to final tower

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1
330




General solution - II

To move n disks

- Move n-1 disks from Start to Intermediate using Final
- Move nth disk from Start to Final
- Move n-1 disks from Intermediate to Final using Start

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
331




Algorithm

```

Hanoi (N, Start, Final, Intermediate)
Begin
  if N IS NOT 0
    Hanoi (N-1, Start, Intermediate, Final)
    Move N from Start to Final
    Hanoi (N-1, Intermediate, Final, Start)
End;
  
```

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
332



Find kth smallest array element


- This problem is different from the ones we examined: You cannot predict in advance the size of either the smaller problems or the base case in the recursive solution to the kth smallest-element problem.

Recursive solution:

1. Decide a pivot element in the array P with index Pindex.
2. Partition the array into three parts: elements < P (call it S1), P, and elements > P (call it S2).

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
333



Find Kth smallest... (Contd.)

3. If there are k or more elements in $S1 = A[\text{First} \dots \text{Pindex}-1]$ then $S1$ contains k smallest elements of array $A[\text{First} \dots \text{Last}]$. k th smallest is in $S1$.
4. If there are $k-1$ elements in $S1$, the pivot element is the required element.
5. If there are fewer than $k-1$ elements in $S1$, then k th element is $S2 = A[\text{Pindex}+1 \dots L]$. Since we have eliminated $\text{Pindex}-\text{First}$ elements, now we are looking for $(k - (\text{Pindex} - \text{First} + 1))$ th element in $S2$.

© Bharati Vidyapeeth's Institute of Computer Applications and Management, New Delhi-63, by Shalini Singh Jaspal

U1:
334
