Comparative Summary of Language Identification Research Papers

Ref	Paper Title	Author(s)/Year	Journal Name	Month/Year of Publication	Methodology & Technology	Advantages	Limitations
1	Language Identification for Seamless Multilingual Machine Translation	Arivubrakan et al., 2025	2025 6th Int'l Conf. on Intelligent Communication Technologies and Virtual Mobile Networks (ICICV) – IEEE	June 2025	Classical ML classifiers (KNN, SVM, Random Forest) integrated into an MT pipeline for text-based LID	Improves translation accuracy/fluency (86.88%); handles normal and code-switched multilingual data	Relies on classical ML paradigms; evaluated on limited datasets, scalability to more languages unclear
2	CUFE@NLU of Devanagari Script Languages 2025: Language Identification using fastText	Ibrahim, 2025	Proc. 1st Workshop on Challenges in Processing South Asian Languages (CHiPSAL 2025), co-located with COLING 2025	January 2025	fastText-based classifier for word/script-level LID (CHiPSAL@COLING 2025 shared task)	Near-perfect performance (F1 = 0.9997); ranked 1st in shared task	Narrow scope limited to Devanagari-script languages; generalization to other scripts untested
3	Bilingual Word Level Language Identification for Omotic Languages	Yigezu et al., 2025	arXiv preprint (cs.CL)	September 2025	Hybrid BERT pretrained language model combined with LSTM for word-level bilingual LID	Effective for low-resource Wolaita/Gofa languages; useful for social media moderation	Moderate F1 (0.72); lexical similarity between the two languages makes identification challenging
4	What Language is This? Ask Your Tokenizer	Meister et al., 2026	arXiv preprint (cs.CL)	February 2026	UniLID: UnigramLM tokenization-based approach learning language-conditional unigram distributions over a shared vocabulary	Data/compute efficient; supports incremental addition of new languages; >70% accuracy with 5 samples/language; strong dialect ID gains	Competitive rather than clearly superior on standard high-resource benchmarks; newer method with less real-world validation
5	Efficient language identification in monolingual and multilingual documents	Sobrier, 2026	Journal of High School Science, 10(2)	March 2026	Lightweight term-frequency-based algorithm assigning independent relevance scores per language	F1 up to 98%; low memory use; efficient on standard hardware; detects multiple languages per document	Relevance scores are not calibrated as true proportions; benchmarked mainly against existing libraries
6	Language Identification via Compositional Data Analysis: A Linear-Time Classifier Based on Log-Ratio Geometry	Pogacean & Avram, 2026	Venue unconfirmed – preprint	2026 (month unconfirmed)	Character/bigram frequencies modeled as compositional vectors via centered log-ratio (CLR) transform with Laplace smoothing; linear-time classifier	Deterministic, interpretable, low resource consumption; robust accuracy especially for longer sequences	Evaluated on only six languages; weaker performance for very short text lengths
7	An LSTM Approach to Language Identification Across Indian Languages Using MFCC	Ganur et al., 2025	IEEE conference paper (exact proceedings title unconfirmed)	May 2025	MFCC feature extraction combined with LSTM deep learning model for spoken LID across 10 Indian languages	88% accuracy; addresses scarcity of Indian-language audio datasets	Limited to short (~5 sec) audio clips and only 10 languages; moderate accuracy relative to text-based methods
8	Identifying Open Challenges in Language Identification	van der Goot, 2025	Proc. 63rd Annual Meeting of the Association for Computational Linguistics (ACL 2025), Vol. 1	July 2025	Systematic benchmark testing five popular LID models across input size, training size, domain, scripts, and language families	Comprehensive cross-condition benchmark; practical training guidance; resulting model achieves 94.41% accuracy across 2,034 languages	Cross-domain setups remain the most challenging condition; residual errors persist even in the best model
9	ILID: Native Script Language Identification for Indian Languages	Ingle & Mishra, 2025	arXiv preprint (cs.CL)	July 2025	New 250K-sentence dataset (23 languages) with baseline models built by fine-tuning pretrained transformer models	Outperforms state-of-the-art pretrained transformer baselines; dataset and code publicly released	Shared scripts across Indian languages and noisy/short/code-mixed text remain core challenges
10	DIVERS-Bench: Evaluating Language Identification Across Domain Shifts and Code-Switching	Ojo et al., 2025	arXiv preprint (cs.CL)	September 2025	DIVERS-BENCH evaluation framework across domains (speech, web, social media, stories, code-	Reveals real-world robustness gaps; provides a dedicated code-switching benchmark for	Performance of existing models degrades sharply on noisy/informal input; poor at

Ref	Paper Title	Author(s)/Year	Journal Name	Month/Year of Publication	Methodology & Technology	Advantages	Limitations
					switching) plus new DIVERS-CS benchmark (10 language pairs)	future research	detecting multiple languages within one sentence

Research Gap Analysis

Across the ten reviewed studies, language identification (LID) research has advanced substantially in accuracy and coverage, yet several recurring gaps limit real-world reliability and generalizability:

1. Weak performance on code-switched and mixed-language text

Several papers (Ref. 3, 10) show that current models degrade sharply when languages are mixed within a single sentence or document. Even the strongest classical (Ref. 1) and benchmark-driven (Ref. 8) approaches note that code-switching and cross-domain input remain the hardest conditions to handle accurately.

2. Limited language and script coverage

Many high-performing systems are narrowly scoped — restricted to a single script family (Ref. 2), a handful of related languages (Ref. 3, 6), or a fixed set of ten spoken languages (Ref. 7). This narrow scope raises open questions about how well reported accuracy generalizes to the thousands of languages and scripts used worldwide, a gap explicitly acknowledged even in large-scale benchmarking work (Ref. 8).

3. Under-resourced and low-resource languages remain difficult

Studies focused on low-resource language pairs (Ref. 3) report comparatively low F1 scores due to lexical overlap between closely related languages, indicating that current architectures still struggle where labeled training data is scarce — a persistent gap despite newer sample-efficient methods (Ref. 4).

4. Inconsistent evaluation standards and unverified metrics

Several works rely on relevance or confidence scores that are not calibrated as true probability estimates (Ref. 5), or are benchmarked mainly against existing libraries rather than a common, standardized test suite (Ref. 5, 6). This makes it difficult to compare results consistently across papers.

5. Limited robustness testing across real-world domains

Robustness to noisy, informal, or short-form text (e.g., social media posts, spoken audio clips) is inconsistently tested. Audio-based LID is still constrained to short clips and few languages (Ref. 7), while text-based benchmarks confirm that performance drops sharply outside curated, formal domains (Ref. 8, 10).

6. Scalability and generalization of newer architectures

Newer tokenizer-based and compositional-geometry approaches (Ref. 4, 6) show promising efficiency and interpretability but have only been validated on limited language sets or lack extensive real-world deployment evidence, leaving their scalability to thousands of languages an open question.

Overall, the literature converges on a central gap: no single method yet combines high accuracy, broad language/script coverage, robustness to code-switching and noisy real-world input, and low computational cost. Future work bridging low-resource language modeling, standardized cross-domain benchmarking, and efficient architectures (as initiated in Ref. 4, 8, and 10) represents the most promising direction for closing this gap.

Alignment with UN Sustainable Development Goals (SDGs)

Language identification research supports several United Nations Sustainable Development Goals by enabling more equitable access to digital communication, education, and information across languages:

SDG 4 – Quality Education

Accurate LID underpins multilingual machine translation and educational tools (Ref. 1), helping learners access instructional content in their native language and supporting inclusive, equitable education.

SDG 9 – Industry, Innovation and Infrastructure

Advances in efficient, low-resource LID algorithms (Ref. 4, 5, 6) contribute to resilient, low-cost language-processing infrastructure that can be deployed on limited hardware, fostering innovation in NLP infrastructure for developing regions.

SDG 10 – Reduced Inequalities

Work targeting low-resource and under-represented languages (Ref. 2, 3, 7, 9) directly addresses the digital and linguistic divide, giving speakers of marginalized languages better access to language technology historically built only for high-resource languages.

SDG 16 – Peace, Justice and Strong Institutions

Reliable LID for social media moderation (Ref. 3) and multilingual content monitoring supports safer digital spaces and can assist institutions in identifying harmful or misleading multilingual content.

SDG 17 – Partnerships for the Goals

Open datasets, shared tasks, and publicly released code (Ref. 2, 9, 10) reflect the kind of open scientific collaboration and knowledge-sharing across institutions and countries that SDG 17 encourages.

References

Arivubrakan, S., et al. (2025, June). Language identification for seamless multilingual machine translation. In 2025 6th International Conference on Intelligent Communication Technologies and Virtual Mobile Networks (ICICV). IEEE.

Ibrahim, M. (2025, January). CUFE@NLU of Devanagari script languages 2025: Language identification using fastText. In Proceedings of the 1st Workshop on Challenges in Processing South Asian Languages (CHiPSAL 2025), co-located with COLING 2025.

Yigezu, M. G., et al. (2025, September). Bilingual word level language identification for Omotic languages. arXiv preprint (cs.CL).

Meister, C., et al. (2026, February). What language is this? Ask your tokenizer. arXiv preprint (cs.CL).

Sobrier, L. (2026, March). Efficient language identification in monolingual and multilingual documents. Journal of High School Science, 10(2).

Pogacean, R., & Avram, A.-M. (2026). Language identification via compositional data analysis: A linear-time classifier based on log-ratio geometry. Preprint (venue unconfirmed).

Ganur, S., et al. (2025, May). An LSTM approach to language identification across Indian languages using MFCC. IEEE conference paper (exact proceedings title unconfirmed).

van der Goot, R. (2025, July). Identifying open challenges in language identification. In Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (ACL 2025), Vol. 1.

Ingle, A., & Mishra, P. (2025, July). ILID: Native script language identification for Indian languages. arXiv preprint (cs.CL).

Ojo, J., et al. (2025, September). DIVERS-Bench: Evaluating language identification across domain shifts and code-switching. arXiv preprint (cs.CL).

Note: Reference entries reflect the author, date, title, and venue details available in the source comparison table. Some details (e.g., full author lists, arXiv identifiers, page numbers) were marked as unconfirmed in the source and have been left as such rather than invented, in line with academic citation integrity.