

Internet Engineering Task Force (IETF)

注释请求: 2

STD: 6

过期文档: 0

类别: 标准任务

ISSN: xxxx-xxxx

S. Time

Retired

R. Time

Check Point Software

5月 2021

# 网关服务器协议--GSP/1.0

摘要

此文档状态

版权声明

# 目录

目录.....	2
1. 介绍.....	4
2. 术语.....	4
3. 主题 报文格式.....	4
4. 对时(TIME_SYN).....	4
4.1. 主题.....	4
4.2. 报文格式.....	5
4.3. 示例.....	5
5. 多主站配置(MQTT_CONFIG).....	5
5.1. 主题.....	5
5.2. 报文格式.....	5
5.3. 示例.....	6
6. 点表配置 (POINT_CONFIG).....	7
6.1. 主题.....	7
6.2. 报文格式.....	7
6.3. 示例.....	9
7. 突变(POINT_MUTATION).....	11
7.1. 主题.....	11
7.2. 报文格式.....	11
7.3. 示例.....	11
8. 总招(ALL_CMD).....	12
8.1. 主题.....	12
8.2. 报文格式.....	12
8.3. 示例.....	12
9. 特种设备(SE).....	13
9.1. 主题.....	13
9.2. 报文格式.....	13
9.3. 机械特性示例.....	13
9.4. 局放示例.....	15
9.5. 空间局放示例.....	15
10. Http(HTTP).....	17
10.1. 摘要.....	17
10.2. 主题.....	17
10.3. 报文格式.....	17
10.4. 机器人示例.....	17
10.4.1. 网关数据库配置.....	17
10.4.2. 主站数据库配置.....	18
10.4.3. 计划列表.....	20
10.4.4. 开始计划.....	21

10.4.5. 结束当前计划.....	22
10.4.6. 当前计划的执行情况(主动上报).....	23
10.4.7. 查看巡检结果.....	23
10.4.8. 获取机柜列表.....	25
10.4.9. 获取巡检点列表.....	26
10.4.10. 定点巡检.....	27
10.4.11. 机器人状态(主动上报).....	27
10.4.12. 获取机器人信息.....	28
10.4.13. 机器人模式切换.....	29
10.4.14. 机器人控制接口.....	29
10.4.15. 机器人传感器状态接口(主动上报).....	30
10.4.16. 机器人实时信息(主动上报).....	30

## 1. 介绍

## 2. 术语

## 3. 主题 报文格式

{from}/{to}/{id\_gateway}/{id\_protocol}/{id\_service}/{type\_data}/  
END

字段	type	描述	remarks
from	char	C:client S:server	
to	char	C:client S:server	
id_gateway	uint64	Gateway mac	uniqueness
id_protocol	string		
id_service	uint32	6:client main service 16:server main service	
type_data	string		

## 4. 对时(TIME\_SYN)

### 4.1. 主题

S/C/{id\_gateway}/V1.0/6/TIME\_SYN/END

C/S/{id\_gateway}/V1.0/16/TIME\_SYN/END

## 4.2. 报文格式

字段	type	描述	remarks
DEVICE_ID	uint64	Gateway mac	
TIME			

## 4.3. 示例

```
{  
  "DEVICE_ID":136176923508744,  
  "TIME":"2020-5-11 12:31:11"  
}
```

## 5. 多主站配置(MQTT\_CONFIG)

### 5.1. 主题

S/C/{id\_gateway}/V1.0/6/MQTT\_CONFIG/END

C/S/{id\_gateway}/V1.0/16/MQTT\_CONFIG/END

### 5.2. 报文格式

字段	type	描述	remarks
DEVICE_ID	uint64	Gateway mac	uniqueness
GW_IP	string	Gateway ip	

QOS	uint32		
IP	string	Server ip	
PWD	string	Server service password	
PORT	string	Server service port	
FLAG_TIME_SYN	bool	1:time syn 0:Ignore the server time	
USERNAME	string	Server service username	

### 5.3. 示例

client->server: null

client->server:

```
[
  {
    "DEVICE_ID":136176923508744,
    "GW_IP":"192.168.1.2",
    "QOS":1,
    "IP":"127.0.0.1",
    "PWD":"123456",
    "PORT":"1883",
    "FLAG_TIME_SYN":"1",
    "USERNAME":"admin"
  },
  {
    "DEVICE_ID":13617692350874,
    "GW_IP":"192.168.1.2",
    "QOS":1,
    "IP":"127.0.0.1",
```

```

    "PWD":"123456",
    "PORT":"1883",
    "FLAG_TIME_SYN":"1",
    "USERNAME":"admin"
  },
  {
    "DEVICE_ID":1361769508744,
    "GW_IP":"192.168.1.2",
    "QOS":1,
    "IP":"127.0.0.1",
    "PWD":"123456",
    "PORT":"1883",
    "FLAG_TIME_SYN":"1",
    "USERNAME":"admin"
  }
]

```

## 6. 点表配置 (POINT\_CONFIG)

### 6.1. 主题

C/S/{id\_gateway}/V1.0/16/POINT\_CONFIG/END  
 S/C/{id\_gateway}/V1.0/6/POINT\_CONFIG/END

### 6.2. 报文格式

字段	type	描述	remarks
----	------	----	---------

FRAGMENT_OFFSET	uint13	The offset, in 8-octet units, of the data following this header, relative to the start of the Fragmentable Part of the original packet.	
M_FLAG	bool	1 = more fragments; 0 = last fragment.	
IDENTIFICATION	uint32_t	In order to send a packet that is too large to fit in the MTU of the path to its destination, a source node may divide the packet into fragments and send each fragment as a separate packet, to be reassembled at the receiver. For every packet that is to be fragmented, the source node generates an Identification value. The Identification must be different than that of any other fragmented packet sent recently* with the same Source Address and Destination Address	
DEVICE_ID	uint64_t	Gateway id	uniqueness
PRODUCT_ID	uint32_t	Product id	uniqueness
MFRS_ID	uint32_t	<a href="#">Manufacturers</a> id	
IP	String	Product service ip	
PORT	string	Product service port	
URL	string	Product service url	
VERIFICATION_MODE	string	Verification mode	
SERIAL_PORT	string	Serial port	
BAUD_RATE	string	Baud rate	
STOP_BIT	string	Stop bit	
INTERFACE_ID	uint32_t	Interface id	uniqueness
SEND_COMMAND	string	Send command	
ACCEPT_COMMAND	string	Accept command	
IDENTIFY	uint32_t	Point id	uniqueness
BIT_FLOAT	string	Point no.	



TYPE	string	Point type	
INDEXES	string	indexes	
LIMITS	string	The limit	
MULTIPLE	string	mutiple	

### 6.3. 示例

client->server: null

server->client:

```
{
  "IDENTIFICATION":1,
  "M_FLAG":1,
  "FRAGMENT_OFFSET":1,
  "DATA":{
    "DEVICE_ID":136176923508744,
    "PRODUCTS":[
      {
        "PRODUCT_ID":1,
        "MFRS_ID":5,
        "PARAM_CONTENT":{
          "IP": "",
          "PORT": "",
          "URL": "",
          "VERIFICATION_MODE": "0",
          "DATA_BITS": "8",
          "SERIAL_PORT": "485-1",
          "BAUD_RATE": "9600",
          "STOP_BIT": "1"
        }
      }
    ]
  }
}
```

```

},
"INTERFACE_CONFIG":[
{
  "INTERFACE_ID":1,
  "SEND_COMMAND":"99 09 32 233",
  "ACCEPT_COMMAND":"99 09 32 233",
  "POINT_CONFIG":[
    {
      "IDENTIFY ":1,
      "BIT_FLOAT ":"1.1 ",
      "TYPE":"122",
      "INDEXES":"232-1",
      "LIMITS":"1.3",
      "MULTIPLE":"0.01"
    }
  ]
}
]
}
]
}
}
}

```

## 7. 突变(POINT\_MUTATION)

### 7.1. 主题

S/C/{id\_gateway}/V1.0/6/POINT\_MUTATION/END

C/S/{id\_gateway}/V1.0/16/POINT\_MUTATION/END

### 7.2. 报文格式

字段	type	描述	remarks
DATA -1	uint32	Point id	
DATA -2	Char *	value	
DATA-3	bool	1 = online; 0 = off-line.	
TIME_DEV		Product time	

### 7.3. 示例

```
{  
  "DEVICE_ID": 136176923508744,  
  "DATA": [  
    [1, "1", 0],  
    [12, "1", 1],  
    [3, "1", 0],  
    [4, "0", 1],  
    [5, "1", 1]
```

```

],
"TIME": "2020-5-11 12:31:11",
"TIME_DEV": "2020-5-11 12:31:11"
}

```

## 8. 总招(ALL\_CMD)

### 8.1. 主题

```

S/C/{id_gateway}/V1.0/6/ALL_CMD/END
C/S/{id_gateway}/V1.0/16/ALL_CMD/END

```

### 8.2. 报文格式

DATA 报文格式:

字段	type	描述	remarks
1	uint32	inode	
2	Char *	value	
3	bool	1 = online; 0 = off-line.	

### 8.3. 示例

```

{
  "DEVICE_ID": 136176923508744,
  "DATA": [
    [1, "1", 0],

```

```

[12, "1", 1],
[3, "1", 0],
[4, "0", 1],
[5, "1", 1]
],
"TIME": "2020-5-11 12:31:11"
}

```

## 9. 特种设备(SE)

### 9.1. 主题

S/C/{id\_gateway}/V1.0/6/SE/END  
C/S/{id\_gateway}/V1.0/16/SE/END

### 9.2. 报文格式

字段	type	描述	remarks
DEVICE_ID	uint64	Gateway mac	
POINT_ID	uin32		
DATA_TYPE	uint32	Can be null	
DATA	json		

### 9.3. 机械特性示例

字段	type	描述
----	------	----

REPORT_NUMBER	string	报告编号（站室编号+间隔号+时间 yyyyMMddHHmmss）
SYS_CODE	string	接入编号
DEVICE_CODE	string	间隔号
REPORT_TYPE	string	报告类型（0 - 晨操，1 - 动作）
REPORT_TIME	string	报告时间（yyyy-MM-dd HH:mm:ss）
FRACTURE_MAP	string	断口图谱
STANDARD_MAP	string	标准图谱
CURRENT_MAP	string	本次图谱
MAP_ADDRESS	string	图谱图片地址
ACTION_TYPE	string	动作类型（0 - 分闸，1 - 合闸，2 - 保护跳 3-手动）
ALARM_TYPE	string	是否有报警（0 - 没有报警，1 - 有报警）
CHARACTERISTIC_VALUE	string	特征值
REPORT_VALUE1	string	铁芯启动卡涩
REPORT_VALUE2	string	铁芯启动位置不复归
REPORT_VALUE3	string	铁芯运动卡涩
REPORT_VALUE4	string	铁芯触碰脱扣器位置变化
REPORT_VALUE5	string	脱扣器卡涩
REPORT_VALUE6	string	线圈匝间绝缘
REPORT_VALUE7	string	跳闸类型判定（0 - 机械，1 - 保护，2 - 指令）
REPORT_VALUE8	string	储能机构异常
REPORT_VALUE9	string	控制电压变化
HEALTH_DEGREE	string	健康度

```

{
  "DEVICE_ID": 136176923508744,
  "POINT_ID": 23,
  "DATA_TYPE": 33,
  "DATA": {
    "REPORT_NUMBER": "2",
    "SYS_CODE": "2",
    "DEVICE_CODE": "2",
    "REPORT_TYPE": "2",
    "REPORT_TIME": "2",
    "FRACTURE_MAP ": "0,0,1",
    "STANDARD_MAP": "0,0,1",
    "CURRENT_MAP": "0,0,1",
    "MAP_ADDRESS": "2",
    "ACTION_TYPE": "2",
    "ALARM_TYPE": "2",
    "CHARACTERISTIC_VALUE": "2",
    "REPORT_VALUE1": "2",

```

```

        "REPORT_VALUE2": "2",
        "REPORT_VALUE3": "2",
        "REPORT_VALUE4": "2",
        "REPORT_VALUE5": "2",
        "REPORT_VALUE6": "2",
        "REPORT_VALUE7": "2",
        "REPORT_VALUE8": "2",
        "REPORT_VALUE9": "2",
        "HEALTH_DEGREE": "2"
    },
    "TIME": "2020-5-11 12:31:11"
}

```

## 9.4. 局放示例

字段	数据格式	描述
data	String;string	Angle;discharge capacity

```

{
    "DEVICE_ID": 136176923508744,
    "POINT_ID": 23,
    "DATA_TYPE": 33,
    "DATA": ["3;4", "2;12", "6;32"],
    "TIME": "2020-5-11 12:31:11"
}

```

## 9.5. 空间局放示例

字段	数据格式	描述
AV_DSCH	string	局放均值(mV)
MAX_DSCH	string	局放峰值(mV)
DSCH_CNT	string	放电频次(次/秒)
DSCH_PHASE	string	放电相位(°)
DSCH_ALARM_STATUS	string	局放报警状态

MAX_TEMP	string	最高温度(°C)
MIN_TEMP	string	最低温度(°C)
IR_ALARM_STATUS	string	红外报警状态
CAMERA_IMG	base64(jpg)	可见光图
IR_OV_IMG	base64(png)	红外热图
JF_PRPD_IMG	base64(png)	PRPD 图
JF_PRPS_IMG	base64(png)	PRPS 图
STATUS	int	在线状态突变(0 离线,1 在线)

```

{
  "DEVICE_ID": 136176923508744,
  "POINT_ID": 23,
  "DATA_TYPE": 33,
  "DATA": {
    "AV_DSCH": "2",
    "MAX_DSCH": "2",
    "DSCH_CNT": "2",
    "DSCH_PHASE": "2"
  },
  "TIME": "2020-5-11 12:31:11"
}
{
  "DEVICE_ID": 136176923508744,
  "POINT_ID": 23,
  "DATA_TYPE": 33,
  "DATA": {
    "MAX_TEMP": "2",
    "MIN_TEMP": "2"
  },
  "TIME": "2020-5-11 12:31:11"
}
{
  "DEVICE_ID": 136176923508744,
  "POINT_ID": 23,
  "DATA_TYPE": 33,
  "DATA": "dfsfiyihvxz0fs32d",
  "TIME": "2020-5-11 12:31:11"
}

```



## 10. Http(HTTP)

### 10.1. 摘要

Two method: Trigger mode and Looping mode. if read is not null, it's looping mode.

### 10.2. 主题

S/C/{id\_gateway}/V1.0/10/HTTP/END

C/S/{id\_gateway}/V1.0/16/HTTP/END

### 10.3. 报文格式

字段	type	描述	remarks
DEVICE_ID	uint64	Gateway mac	
PRODUCT_ID	uint32	device id	
INTERFACE_ID	uint32	Interface id	
DATA	json	Subset json	

### 10.4. 机器人示例

#### 10.4.1. 网关数据库配置

Table name	字段 name	描述	示例
device	id	Device id	1
device	id_parent	Software id	10

device	Param0	ip	192.168.0.250
device	param1	port	8080
Interface	id	Interface id	2
interface	id_parent	Device id	1
interface	send	url	/Monitor/hangZhouApi/scheduleList.do
interface	read	Loop second, null is trigger	3

### 10.4.2. 主站数据库配置

```
{
  "IDENTIFICATION": 1,
  "M_FLAG": 1,
  "FRAGMENT_OFFSET": 1,
  "DATA": {
    "DEVICE_ID": 136176923508744,
    "PRODUCTS": [{
      "PRODUCT_ID": 1,
      "MFRS_ID": 5,
      "PARAM_CONTENT": {
        "IP": "192.168.1.250",
        "PORT": "8080",
        "URL": null,
        "VERIFICATION_MODE": null,
        "DATA_BITS": null,
        "SERIAL_PORT": null,
        "BAUD_RATE": null,
        "STOP_BIT": null
      },
    },
    "INTERFACE_CONFIG": [{
      "INTERFACE_ID": 1,
      "SEND_COMMAND": "/Monitor/hangZhouApi/scheduleList.do",
      "ACCEPT_COMMAND": null,
      "POINT_CONFIG": null
    },
    {
      "INTERFACE_ID": 2,
      "SEND_COMMAND": "/Monitor/hangZhouApi/scheduleStart.do",
      "ACCEPT_COMMAND": null,
      "POINT_CONFIG": null
    }
  ]
}
```

```

    },
    {
        "INTERFACE_ID": 3,
        "SEND_COMMAND": "/Monitor/hangZhouApi/scheduleStop.do",
        "ACCEPT_COMMAND": null,
        "POINT_CONFIG": null
    },
    {
        "INTERFACE_ID": 4,
        "SEND_COMMAND":      "/Monitor/hangZhouApi/scheduleStatus.do?",

robotId=7",

        "ACCEPT_COMMAND": "5",
        "POINT_CONFIG": null
    },
    {
        "INTERFACE_ID": 5,
        "SEND_COMMAND": "/Monitor/hangZhouApi/scheduleResult.do",
        "ACCEPT_COMMAND": null,
        "POINT_CONFIG": null
    },
    {
        "INTERFACE_ID": 6,
        "SEND_COMMAND": "/Monitor/hangZhouApi/cabinetList.do",
        "ACCEPT_COMMAND": null,
        "POINT_CONFIG": null
    },
    {
        "INTERFACE_ID": 7,
        "SEND_COMMAND": "/Monitor/hangZhouApi/unitList.do",
        "ACCEPT_COMMAND": null,
        "POINT_CONFIG": null
    },
    {
        "INTERFACE_ID": 8,
        "SEND_COMMAND": "/Monitor/hangZhouApi/superSchedule.do",
        "ACCEPT_COMMAND": null,
        "POINT_CONFIG": null
    },
    {
        "INTERFACE_ID": 9,

robotId=7",

        "SEND_COMMAND":      "/Monitor/hangZhouApi/robotStatus.do?",

        "ACCEPT_COMMAND": "6",
        "POINT_CONFIG": null
    }

```

```

    },
    {
        "INTERFACE_ID": 10,
        "SEND_COMMAND": "/Monitor/hangZhouApi/getRobotIp.do",
        "ACCEPT_COMMAND": null,
        "POINT_CONFIG": null
    },
    {
        "INTERFACE_ID": 11,
        "SEND_COMMAND": "/Monitor/hangZhouApi/symodel.do",
        "ACCEPT_COMMAND": null,
        "POINT_CONFIG": null
    },
    {
        "INTERFACE_ID": 12,
        "SEND_COMMAND": "/Monitor/hangZhouApi/robotApi.do",
        "ACCEPT_COMMAND": null,
        "POINT_CONFIG": null
    },
    {
        "INTERFACE_ID": 13,
        "SEND_COMMAND":      "/Monitor/hangZhouApi/getRobotSensor.do?",
robotId=7",
        "ACCEPT_COMMAND": "60",
        "POINT_CONFIG": null
    },
    {
        "INTERFACE_ID": 14,
        "SEND_COMMAND":      "/Monitor/hangZhouApi/getRobotPos.do?",
robotId=7",
        "ACCEPT_COMMAND": null,
        "POINT_CONFIG": null
    }
    ]
}
}
}
}

```

### 10.4.3. 计划列表

S/C:

```

{

```

```

    "DEVICE_ID": 136176923508744,
    "PRODUCT_ID": 23,
    "DATA": {
        "INTERFACE_ID": 23,
        "DATA": "?robotId=7"
    },
    "TIME": "2020-5-11 12:31:11"
}
C/S:
{
    "DEVICE_ID": 136176923508744,
    "PRODUCT_ID": 23,
    "DATA": {
        "INTERFACE_ID": 23,
        "DATA": [{
            "scheduleId": "75",
            "scheduleName": "视觉阈值"
        },
        {
            "scheduleId": "105",
            "scheduleName": "电流巡视"
        },
        {
            "scheduleId": "106",
            "scheduleName": "局放巡视"
        }
    ]
    },
    "TIME": "2020-5-11 12:31:11"
}

```

#### 10.4.4. 开始计划

```

S/C:
{
    "DEVICE_ID": 136176923508744,
    "PRODUCT_ID": 23,
    "DATA": {
        "INTERFACE_ID": 23,
        "DATA": "?robotId=7&scheduleId=4"
    },
    "TIME": "2020-5-11 12:31:11"
}

```

```

}
C/S:
{
    "DEVICE_ID": 136176923508744,
    "PRODUCT_ID": 23,
    "DATA": {
        "INTERFACE_ID": 23,
        "DATA": {
            "scheduleId": "75",
            "jobId": "3920-201708"
        }
    },
    "TIME": "2020-5-11 12:31:11"
}

```

### 10.4.5. 结束当前计划

```

S/C:
{
    "DEVICE_ID": 136176923508744,
    "PRODUCT_ID": 23,
    "DATA": {
        "INTERFACE_ID": 23,
        "DATA": "?robotId=7"
    },
    "TIME": "2020-5-11 12:31:11"
}
C/S:
{
    "DEVICE_ID": 136176923508744,
    "PRODUCT_ID": 23,
    "DATA": {
        "INTERFACE_ID": 23,
        "DATA": {
            "status": "0"
        }
    },
    "TIME": "2020-5-11 12:31:11"
}

```

#### 10.4.6. 当前计划的执行情况(主动上报)

C/S:

```
{
  "DEVICE_ID": 136176923508744,
  "PRODUCT_ID": 23,
  "DATA": {
    "INTERFACE_ID": 23,
    "DATA": {
      "jobId": "3920-201708",
      "jobStatus": "1",
      "unitCount": "3",
      "unitFinish": "1",
      "result": [{
        "cabinetName": "机柜 1",
        "unitName": "电流巡检点",
        "unitResult": "3A",
        "unitStatus": "已检查"
      }, {
        "cabinetName": "机柜 1",
        "unitName": "电压巡检点",
        "unitResult": "",
        "unitStatus": "检测中"
      }, {
        "cabinetName": "机柜 1",
        "unitName": "二氧化碳巡检点",
        "unitResult": "",
        "unitStatus": "待检"
      }
    ]
  },
  "TIME": "2020-5-11 12:31:11"
}
```

#### 10.4.7. 查看巡检结果

S/C:

```
{
  "DEVICE_ID": 136176923508744,
  "PRODUCT_ID": 23,
```

```

"DATA": {
  "INTERFACE_ID": 23,
  "DATA": "?robotId=7jobId=6"
},
"TIME": "2020-5-11 12:31:11"
}
C/S:
{
  "DEVICE_ID": 136176923508744,
  "PRODUCT_ID": 23,
  "DATA": {
    "INTERFACE_ID": 23,
    "DATA": {
      "scheduleName": "视觉阈值",
      "unitTotal": "4",
      "unitFinish": "3",
      "unitWrong": "2",
      "unitCancel": "1",
      "startTime": "",
      "stopTime": "",
      "conclusion": ["噪声异常", "温度异常"],
      "result": [{
        "unitName": "噪声传感器",
        "unitId": "172",
        "unitType": "噪声",
        "cabinetId": "7",
        "cabinetName": "机柜 1",
        "unitResult": "46dB",
        "unitThreshold": "大于 0",
        "unitStatus": "异常",
        "unitPhoto": "",
        "unitTime": "2018-08-22 09:44:00"
      }, {
        "unitName": "温度传感器",
        "unitId": "173",
        "unitType": "温度",
        "cabinetId": "9",
        "cabinetName": "机柜 3",
        "unitResult": "80°C",
        "unitThreshold": "大于 30",
        "unitStatus": "异常",
        "unitPhoto": "",
        "unitTime": "2018-08-22 09:44:03"
      }, {

```



```

        "unitName": "SATEC96",
        "unitId": "176",
        "unitType": "SATEC96",
        "cabinetId": "8",
        "cabinetName": "机柜 2",
        "unitResult": "",
        "unitThreshold": "大于 10",
        "unitStatus": "已取消",
        "unitPhoto": "",
        "unitTime": "2018-08-22 09:44:05"
    }}
}
},
"TIME": "2020-5-11 12:31:11"
}

```

#### 10.4.8. 获取机柜列表

S/C:

```

{
    "DEVICE_ID": 136176923508744,
    "PRODUCT_ID": 23,
    "DATA": {
        "INTERFACE_ID": 23,
        "DATA": "?robotId=7"
    },
    "TIME": "2020-5-11 12:31:11"
}

```

C/S:

```

{
    "DEVICE_ID": 136176923508744,
    "PRODUCT_ID": 23,
    "DATA": {
        "INTERFACE_ID": 23,
        "DATA": [{
            "cabinetId": "75",
            "cabinetName": "机柜 1"
        }, {
            "cabinetId": "76",
            "cabinetName": "机柜 2"
        }, {
            "cabinetId": "77",

```

```

        "cabinetName": "机柜 3"
    }}
},
"TIME": "2020-5-11 12:31:11"
}

```

### 10.4.9. 获取巡检点列表

```

S/C:
{
    "DEVICE_ID": 136176923508744,
    "PRODUCT_ID": 23,
    "DATA": {
        "INTERFACE_ID": 23,
        "DATA": "?robotId=7"
    },
    "TIME": "2020-5-11 12:31:11"
}

C/S:
{
    "DEVICE_ID": 136176923508744,
    "PRODUCT_ID": 23,
    "DATA": {
        "INTERFACE_ID": 23,
        "DATA": [{
            "cabinetId": "75",
            "cabinetName": "机柜 1",
            "unitId": "15",
            "unitName": "超声波巡检"
        }, {
            "cabinetId": "76",
            "cabinetName": "机柜 2",
            "unitId": "19",
            "unitName": "局放巡检点"
        }, {
            "cabinetId": "77",
            "cabinetName": "机柜 3",
            "unitId": "27",
            "unitName": "温度巡检点"
        }
    ]
},
"TIME": "2020-5-11 12:31:11"

```

```
}
```

#### 10.4.10. 定点巡检

S/C:

```
{  
  "DEVICE_ID": 136176923508744,  
  "PRODUCT_ID": 23,  
  "DATA": {  
    "INTERFACE_ID": 23,  
    "DATA": "?robotId=7&superType=3&superId=1"  
  },  
  "TIME": "2020-5-11 12:31:11"  
}
```

C/S:

```
{  
  "DEVICE_ID": 136176923508744,  
  "PRODUCT_ID": 23,  
  "DATA": {  
    "INTERFACE_ID": 23,  
    "DATA": {  
      "superType": "1",  
      "superId": "15",  
      "jobId": "3920-201708"  
    }  
  },  
  "TIME": "2020-5-11 12:31:11"  
}
```

#### 10.4.11. 机器人状态(主动上报)

C/S:

```
{  
  "DEVICE_ID": 136176923508744,  
  "PRODUCT_ID": 23,  
  "DATA": {  
    "INTERFACE_ID": 23,  
    "DATA": {  
      "robotStatus": "1"  
    }  
  }  
}
```

```

    },
    "TIME": "2020-5-11 12:31:11"
}

```

## 10.4.12. 获取机器人信息

```

S/C:
{
    "DEVICE_ID": 136176923508744,
    "PRODUCT_ID": 23,
    "DATA": {
        "INTERFACE_ID": 23,
        "DATA": null
    },
    "TIME": "2020-5-11 12:31:11"
}

C/S:
{
    "DEVICE_ID": 136176923508744,
    "PRODUCT_ID": 23,
    "DATA": {
        "INTERFACE_ID": 23,
        "DATA": {
            "robot": [{
                "robotId": "1",
                "robotIp": "192.168.1.90",
                "robotName": "10kV 广天开关站",
                "robotPort": "1",
                "robotCameraIp": "192.168.1.90",
                "robotCameraPort": "10kV 广天开关站",
                "robotCameraUsr": "1",
                "robotCameraPwd": "192.168.1.90",
                "robotInfraredIp": "10kV 广天开关站",
                "robotInfraredPort": "192.168.1.90",
                "robotInfraredRtspAddr": "10kV 广天开关站",
                "robotGcsIp": "1",
                "robotGcsPort": "192.168.1.90"
            }]
        }
    },
    "TIME": "2020-5-11 12:31:11"
}

```

### 10.4.13. 机器人模式切换

```
S/C:
{
  "DEVICE_ID": 136176923508744,
  "PRODUCT_ID": 23,
  "DATA": {
    "INTERFACE_ID": 23,
    "DATA": "?robotId=7&cmd=1"
  },
  "TIME": "2020-5-11 12:31:11"
}
```

```
C/S:
{
  "DEVICE_ID": 136176923508744,
  "PRODUCT_ID": 23,
  "DATA": {
    "INTERFACE_ID": 23,
    "DATA": {
      "code ": 200,
      "message": "成功"
    }
  },
  "TIME": "2020-5-11 12:31:11"
}
```

### 10.4.14. 机器人控制接口

```
S/C:
{
  "DEVICE_ID": 136176923508744,
  "PRODUCT_ID": 23,
  "DATA": {
    "INTERFACE_ID": 23,
    "DATA": "?robotId=7&cmd=1"
  },
  "TIME": "2020-5-11 12:31:11"
}
C/S:
```

```
{
  "DEVICE_ID": 136176923508744,
  "PRODUCT_ID": 23,
  "DATA": {
    "INTERFACE_ID": 23,
    "DATA": {
      "code": 200,
      "message": "成功"
    }
  },
  "TIME": "2020-5-11 12:31:11"
}
```

#### 10.4.15. 机器人传感器状态接口(主动上报)

C/S:

```
{
  "DEVICE_ID": 136176923508744,
  "PRODUCT_ID": 23,
  "DATA": {
    "INTERFACE_ID": 23,
    "DATA": {
      "data": {
        "rbtRiseCoder": "1",
        "rbtRiseDriver": "1",
        "rbtSlideDriver": "1",
        "rbtStatusCamera": "1",
        "rbtStatusDischarge": "1",
        "rbtStatusThermal": "1",
        "robotIp": "192.168.0.45"
      }
    }
  },
  "TIME": "2020-5-11 12:31:11"
}
```

#### 10.4.16. 机器人实时信息(主动上报)

```
{
  "DEVICE_ID": 136176923508744,
```

```
"PRODUCT_ID": 23,  
"DATA": {  
  "INTERFACE_ID": 23,  
  "DATA": {  
    "data": {  
      "robotIp": "1",  
      "slide": "1",  
      "rise": "1",  
      "posTime": "1",  
      "speed": "1"  
    }  
  }  
},  
"TIME": "2020-5-11 12:31:11"  
}
```