
Introduction to Linux Ramdump Parser



Qualcomm Technologies, Inc.

80-P7139-5 A

Confidential and Proprietary – Qualcomm Technologies, Inc.

Restricted Distribution: Not to be distributed to anyone who is not an employee of either Qualcomm Technologies, Inc. or its affiliated companies without the express approval of Qualcomm Configuration Management.



Confidential and Proprietary – Qualcomm Technologies, Inc.

Qualcomm
2019-03-13 05:27:18 PDT
zk_sw@wingtech.com

NO PUBLIC DISCLOSURE PERMITTED: Please report postings of this document on public servers or websites to: DocCtrlAgent@qualcomm.com.

Not to be used, copied, reproduced, or modified in whole or in part, nor its contents revealed in any manner to others without the express written permission of Qualcomm Technologies, Inc.

Qualcomm is a trademark of Qualcomm Incorporated, registered in the United States and other countries. Other product and brand names may be trademarks or registered trademarks of their respective owners.

This technical data may be subject to U.S. and international export, re-export, or transfer (“export”) laws. Diversion contrary to U.S. and international law is strictly prohibited.

Qualcomm Technologies, Inc.
5775 Morehouse Drive
San Diego, CA 92121
U.S.A.

© 2016 Qualcomm Technologies, Inc. and/or its affiliated companies. All rights reserved.

Revision History

Revision	Date	Description
A	June 2016	Initial release

Qualcomm
2019-03-13 05:27:18 PDT
zk_sw@wingtech.com

Contents

- Ramdump parser introduction
- Ramdump parser logs
- Ramdump parser commands
- RTB log example
- TRACE32 simulator launcher for Linux
- Debug image (registers/call stack for each core)
- Runqueue analysis
- Every task's kernel stack, running state
- Each core's timer list
- Clock dump
- Workqueue for each core
- IRQ state

Contents (cont.)

- CPR info (Not for all targets)
- Thermal sensor data
- Page type info
- Zone info
- Read-only area comparison
- DDR Cache Compare
- References
- Questions?

Ramdump parser introduction

- What is Linux Ramdump parser?
 - Qualcomm developed open source tools, used to analyze crash dumps from Linux's perspective.
- How to get Ramdump parser?
 - `git clone git://codeaurora.org/quic/la/platform/vendor/qcom-opensource/tools`
- How to run Ramdump parser?
 - Example:
 - `python C:\Tools\linux-ramdump-parser-v2\ramparse.py -v C:\Port_COM3\vmlinux -g C:\D\Tools\aarch64-linux-gnu-gdb.exe -n C:\D\Tools\aarch64-linux-gnu-gcc-nm.exe -j C:\D\Tools\aarch64-linux-gnu-gcc-objdump.exe -e C:\Port_COM3\DDRCS0.bin 0x80000000 0x13ffffff --force-hardware 8996 --64-bit --phys-offset=0x80000000 -x -o C:\Port_COM3\parser`
 - See load.cmm under dump folder to know how to set **-e** and **-phys-offset**.

Ramdump parser logs

- Kconfig
- Kernel log
- RTB log
- An entry to launch TRACE32 simulator
- Cores' final call stack in non-secure world, parsed from debug images
- Runqueue for each core
- Each task's call stack, state, stack base
- Each core's timer list (tv1/2/3/4/5, and hrtimers)
- Clock dumps
- Workqueue
- IRQ state
- CPR information
- Thermal info
- L2 cache dump
- Zone info
- /proc/pagetypeinfo
- Page allocation corruption
- DDR cache compare

Ramdump parser commands

-h, --help	show this help message and exit	--print-cache-dump	Print L2 cache dump
--print-watchdog-time	Print watchdog timing information	--clock-dump	Dump all the clocks in the system
-e, --ram-file	List of ram files (name, start, end)	--cpr3-info	Print CPR3 information
-v UMLINUX, --vmlinux=UMLINUX	vmlinux path	--cpr-info	Print CPR information
-n NM, --nm-path=NM	nm path	--cpu-state	Reads register values of non-panic'ing CPUs
-g GDB, --gdb-path=GDB	gdb path	--ddr-compare	Sanity check the DDR data to find possible corruptions
-j OBJDUMP, --objdump-path=OBJDUMP	objdump path	-w, --check-for-watchdog	Check for an FIQ watchdog
-a AUTODUMP, --auto-dump=AUTODUMP	Auto find ram dumps from the path	--parse-debug-image	Parse the debug image and associated information
-o OUTDIR, --outdir=OUTDIR	Output directory	-d, --dmesg	Print the dmesg
-s, --t32launcher	Create T32 simulator launcher	--print-gpuinfo	print gpu info like ringbuffer, snapshot and pointer addresses
--t32-host-system=HOST	T32 host system (for launcher script generation). Supported choices: "Linux", "Windows". Defaults to the system ramparse.py is running on.	--print-iommu-pg-tables	Print IOMMU page tables
-x, --everything	Output everything (may be slow)	--print-ipc-logging	Print all the IPC information
-f OUTFILE, --output-file=OUTFILE	Name of file to save output	-i, --print-irqs	Print all the irq information
--stdout	Dump to stdout instead of the file	-c, --print-kconfig	Print saved kernel configuration
--phys-offset=PHYS_OFFSET	use custom phys offset	--lpm	Parse LPM Driver info
--kaslr-offset=KASLR_OFFSET	Offset for address space layout randomization	--dump-page-tables	Dumps page tables
--page-offset=PAGE_OFFSET	use custom page offset	--print-pagealloccorruption	print pagealloc corruption information (if available)
--force-hardware=FORCE_HARDWARE	Force the hardware detection	--print-pagetracking	print page tracking information (if available)
--force-version=FORCE_HARDWARE_VERSION	Force the hardware detection to a specific hardware version	--print-pagetypeinfo	Print the pagetypeinfo
--parse-qdss	Parse QDSS (deprecated)	--check-rodata	check rodata in dump against the static image
--64-bit	Parse dumps as 64-bit dumps (default)	-r, --print-rtb	Print RTB (if enabled)
--32-bit	Parse dumps as 32-bit dumps	--print-runqueues	Print the runqueue status
--shell	Run an interactive python interpreter with the ramdump loaded	--slabinfo	print information about slabs
		--slabpoison	check slab poison
		--spm	Parse SPM Driver info
		-t, --print-tasks	Print all the task information
		-T, --print-tasks-timestamps	Print all the task sched stats per core sorted on arrival time
		-p, --check-for-panic	Check if a kernel panic occurred
		--thermal-info	Useful information from thermal data structures
		--timer-list	Print all the linux timers
		--print-vmalloc	print vmalloc information
		--print-vmstats	Print the information similar to /proc/zoneinfo and /proc/vmstat
		-q, --print-workqueues	

RTB log example

```
246882.014895: [0xE2A760F0] LOGK_IRQ 0x000000050 from address 0xFFFFF0C000081524 gic_handle_irq
246882.014905: [0xE2A760F4] LOGK_WRITE 0xFFFFF080000000188 from address 0xFFFFF0C00035CDBC gic_poke_irq
246882.014906: [0xE2A760F8] LOGK_READ 0xFFFFF080000000000 from address 0xFFFFF0C00035CF90 gic_do_wait_for_rwp
246882.015295: [0xE2A760FC] LOGK_IRQ 0x00000001B from address 0xFFFFF0C000081524 gic_handle_irq
246882.015320: [0xE2A76100] LOGK_IRQ 0x0000000D7 from address 0xFFFFF0C000081524 gic_handle_irq
246882.015324: [0xE2A76104] LOGK_WRITE 0xFFFFF080000000198 from address 0xFFFFF0C00035CDBC gic_poke_irq
246882.015326: [0xE2A76108] LOGK_READ 0xFFFFF080000000000 from address 0xFFFFF0C00035CF90 gic_do_wait_for_rwp
246882.015330: [0xE2A7610C] LOGK_READ 0xFFFFF0800277A100 from address 0xFFFFF0C0009FADDC mon_irq_status
246882.015339: [0xE2A76110] LOGK_WRITE 0xFFFFF0800277A280 from address 0xFFFFF0C0009FAC8C mon_disable
246882.015342: [0xE2A76114] LOGK_READ 0xFFFFF0800277A288 from address 0xFFFFF0C0009FB398 mon_get_count
246882.015344: [0xE2A76118] LOGK_READ 0xFFFFF0800277A100 from address 0xFFFFF0C0009FADDC mon_irq_status
246882.015346: [0xE2A7611C] LOGK_WRITE 0xFFFFF0800277A284 from address 0xFFFFF0C0009FB4AC mon_clear.isra.2
246882.015348: [0xE2A76120] LOGK_WRITE 0xFFFFF0800277A108 from address 0xFFFFF0C0009FACE4 mon_irq_clear
246882.015350: [0xE2A76124] LOGK_WRITE 0xFFFFF080028AE108 from address 0xFFFFF0C0009FAD20 mon_irq_clear
246882.015352: [0xE2A76128] LOGK_WRITE 0xFFFFF0800277A280 from address 0xFFFFF0C0009FAD80 mon_enable
246882.015355: [0xE2A7612C] LOGK_WRITE 0xFFFFF080000000118 from address 0xFFFFF0C00035CDBC gic_poke_irq
246882.015357: [0xE2A76130] LOGK_READ 0xFFFFF080000000000 from address 0xFFFFF0C00035CF90 gic_do_wait_for_rwp
246882.015399: [0xE2A76134] LOGK_CTXID 0x0000029C5 from address 0xFFFFF0C00008679C __switch_to
246882.015438: [0xE2A76138] LOGK_CTXID 0x000000008 from address 0xFFFFF0C00008679C __switch_to
246882.015458: [0xE2A7613C] LOGK_CTXID 0x000000000 from address 0xFFFFF0C00008679C __switch_to
246882.015477: [0xE2A76140] LOGK_READ 0xFFFFF080000000104 from address 0xFFFFF0C00035D6A4 gic_set_affinity
246882.015480: [0xE2A76144] LOGK_WRITE 0xFFFFF080000000184 from address 0xFFFFF0C00035CDBC gic_poke_irq
246882.015481: [0xE2A76148] LOGK_READ 0xFFFFF080000000000 from address 0xFFFFF0C00035CF90 gic_do_wait_for_rwp
246882.015482: [0xE2A7614C] LOGK_WRITE 0xFFFFF0800000061F0 from address 0xFFFFF0C00035D74C gic_set_affinity
246882.015484: [0xE2A76150] LOGK_WRITE 0xFFFFF080000000104 from address 0xFFFFF0C00035CDBC gic_poke_irq
246882.015485: [0xE2A76154] LOGK_READ 0xFFFFF080000000000 from address 0xFFFFF0C00035CF90 gic_do_wait_for_rwp
246882.015605: [0xE2A76158] LOGK_IRQ 0x000000000 from address 0xFFFFF0C000081580 gic_handle_irq
246882.015606: [0xE2A7615C] LOGK_IRQ 0x000000050 from address 0xFFFFF0C000081524 gic_handle_irq
246882.015614: [0xE2A76160] LOGK_WRITE 0xFFFFF080000000188 from address 0xFFFFF0C00035CDBC gic_poke_irq
246882.015615: [0xE2A76164] LOGK_READ 0xFFFFF080000000000 from address 0xFFFFF0C00035CF90 gic_do_wait_for_rwp
```

TRACE32 simulator launcher for Linux

```
start C:\T32\bin\windows64\t32MARM64.exe -c ./t32_config.t32, ./t32_startup_script.cmm
```

```
OS=  
ID=T32_1000002  
TMP=C:\TEMP  
SYS=C:\T32  
HELP=C:\T32\pdf  
  
PBI=SIM  
  
SCREEN=  
FONT=SMALL  
HEADER=Trace32-Simulator  
  
PRINTER=WINDOWS  
  
RCL=NETASSIST  
PACKLEN=1024  
PORT=29764
```

```
title "C:\02392677\Port_COM185\parser"  
sys.cpu HYDRA  
sys.up  
data.load.binary C:\02392677\Port_COM185\DDRCS0.bin 0x80000000  
data.load.binary C:\02392677\Port_COM185\DDRCS1.bin 0x100000000  
Register.Set NS 1  
Data.Set SPR:0x30201 %Quad 0x8203c000  
Data.Set SPR:0x30202 %Quad 0x00000032B5193519  
Data.Set SPR:0x30A20 %Quad 0x000000FF440C0400  
Data.Set SPR:0x30A30 %Quad 0x0000000000000000  
Data.Set SPR:0x30100 %Quad 0x00000000004C5D93D  
Register.Set CPSR 0x3C5  
MMU.Delete  
MMU.SCAN PT 0xFFFFFFFF8000000000--0xFFFFFFFFFFFFFFFF  
mmu.on  
mmu.pt.list 0xffffffff8000000000  
data.load.elf C:\02392677\Port_COM185\vmlinux /nocode  
task.config C:\T32\demo\arm64\kernel\linux\linux-3.x\linux3.t32  
menu.reprogram C:\T32\demo\arm64\kernel\linux\linux-3.x\linux.men  
task.dtask  
v.v %ASCII %STRING linux_banner
```

Debug image (registers/call stack for each core)

```
Debug image version: 2.0 Number of table entries 1
-----
Debug image version: 2.0 Entry id: MSM_DUMP_TABLE_APPS Entry type: MSM_DUMP_TYPE_TABLE Number of entries: 30
-----
Parsing debug information for MSM_DUMP_DATA_CPU_CTX. Version: 20 Magic: 42445953 Source:
Parsing CPU0 context start 1720ca180 end 1720ca980
Core 0 PC: handle_IPI+1b4 <ffffffc0000910e4>
Core 0 LR: handle_IPI+1b4 <ffffffc0000910e4>

[<ffffffc0000910e4>] handle_IPI+0x1b4
[<ffffffc000081584>] gic_handle_irq+0x6c
[<ffffffc000084dac>] el1_irq+0x6c
[<ffffffc0000840774>] cpuidle_enter_state+0x6c
[<ffffffc0000840950>] cpuidle_enter+0x18
[<ffffffc0000de264>] cpu_startup_entry+0x284
[<ffffffc000c630f0>] rest_init+0x84
[<ffffffc00133ba34>] start_kernel+0x470
[<80081750>] (No symbol for address 80081750)+0x0

core0 regs:
x0 = 0x0000000000000000
x1 = 0x000000000f03fe03b
x2 = 0x0000000000000007
x3 = 0x0000000000000004
x4 = 0x0000000000000007
x5 = 0x000000000000001d
x6 = 0x0000000000000000
x7 = 0xffffffffffffffff
x8 = 0x78302b6c656e7265
x9 = 0xffffffffffffffff
x10 = 0x0000000000000000
x11 = 0x0000000000000002
x12 = 0xffffffffc0000910dc
x13 = 0x0000000000000000
x14 = 0x0xffffffffffffffff
x15 = 0x0000000000000000
x16 = 0x0000000000000000
x17 = 0x0000000000000000
x18 = 0x00000000000001ff80
x19 = 0x0000000000000000
x20 = 0xffffffffc0013f0248
x21 = 0x0000000000000003
x22 = 0xffffffffc0011de000
x23 = 0xffffffffc0011de000
x24 = 0xffffffffc0013dbd30
x25 = 0x0000000000000000
x26 = 0xffffffffc0013c8f88
x27 = 0xffffffffc0010b3ac8
x28 = 0x0000000000000000
x29 = 0xffffffffc0013dbc90
x30 = 0xffffffffc0000910e4 [handle_IPI+0x1b4]
pc = 0xffffffffc0000910e4 [handle_IPI+0x1b4]
currentEL = 0x0000000000000000
sp_el3 = 0x0000000000000000
elr_el3 = 0xffffffffc0000910e4 [handle_IPI+0x1b4]
spsr_el3 = 0x00000000600001c5
sp_el2 = 0x0000000085970ff0
elr_el2 = 0xffffffffc00008ae04 [__invoke_psci_fn_smc+0x4]
spsr_el2 = 0x00000000200001c5
sp_el1 = 0xffffffffc0013dbc90
elr_el1 = 0xffffffffc000844a7c [lpm_cpuidle_enter+0x620]
spsr_el1 = 0x0000000060000145
sp_el0 = 0x00000007fdb5e2600
dirty_flag = 0x0000000000000000
PStateMisc = 0x0000000000000000
```

Runqueue analysis

===== RUNQUEUE STATE =====

CPU0 8 process is running

|--curr: migration/0(10)

|--idle: swapper/0(0)

|--stop: migration/0(10)

CFS 5 process is pending

|--curr: None(0)

|--next: ksoftirqd/0(3)

|--last: None(0)

|--skip: None(0)

|--pend: ksoftirqd/0(3)

|--pend: kworker/0:1H(274)

|--pend: kworker/0:4(423)

|--pend: kworker/1:0(15)

|--pend: kworker/0:2(288)

RT 2 process is pending

|--pend: msm_watchdog(37)

|--pend: watchdog/0(11)

current callstack is maybe:

<snip>

0xffffffffc16b177bd8:('el1_irq', 108L)

0xffffffffc16b177be8:('save_return_addr', 0L)

0xffffffffc16b177bf8:('walk_stackframe', 48L)

0xffffffffc16b177c40:('cpu_bit_bitmap', 24L)

0xffffffffc16b177c88:('__func__.26497', 0L)

0xffffffffc16b177cb0:('save_return_addr', 0L)

0xffffffffc16b177d00:('walk_stackframe', 40L)

0xffffffffc16b177d10:('walk_stackframe', 48L)

0xffffffffc16b177d38:('return_address', 64L)

0xffffffffc16b177d48:('smpboot_thread_fn', 460L)

0xffffffffc16b177d68:('preempt_count_sub', 212L)

0xffffffffc16b177d98:('preempt_count_sub', 208L)

0xffffffffc16b177da8:('smpboot_thread_fn', 460L)

0xffffffffc16b177dc8:('kthread', 228L)

0xffffffffc16b177de0:('kallsyms_token_index',
25411L)

0xffffffffc16b177df0:('smpboot_thread_fn', 0L)

0xffffffffc16b177e08:('kthread', 200L)

0xffffffffc16b177e18:('ret_from_fork', 16L)

0xffffffffc16b177e20:('kthread', 0L)

Kernel stack and Running state of every task

Process: swapper/0, cpu: 0 pid: 0 start: 0xffffffc0015405b0

```
=====
Task name: swapper/0 pid: 0 cpu: 0
state: 0x0 exit_state: 0x0 stack base: 0xffffffc00152c000
Stack:
[<ffffffc0000867ac>] __switch_to+0x7c
[<ffffffc000d048ac>] __schedule+0x56c
[<ffffffc000d04f4c>] preempt_schedule_irq+0x48
[<ffffffc000084e24>] ell_preempt+0x8
[<ffffffc000d04b68>] schedule+0x74
[<ffffffc000d04ef4>] schedule_preempt_disabled+0x14
[<ffffffc0000dfbd8>] cpu_startup_entry+0x324
[<ffffffc000cf6680>] rest_init+0x84
[<ffffffc0013fa9b4>] start_kernel+0x3f0
[<40081750>] (No symbol for address 40081750)+0x0
```

Each core's timer list

```
-----  
CPU 0(tvvec_base: ffffffff001801480 timer_jiffies: 4294938144 next_timer: 4294937660 active_timers: 8)  
-----
```

+ tv1 Timers (6)

INDEX	TIMER_LIST ADDR	EXPIRES	FUNCTION	DATA / WORK
33	fffffffc169f774c8	4294938145	pm_suspend_timer_fn	0xffffffffc169f77390
36	fffffffc0b4b892f8	4294938148	delayed_work_timer_fn	0xffffffffc0b4b892d8 / ufshcd_gate_work
88	fffffffc17cb86e10	4294938200	delayed_work_timer_fn	0xffffffffc17cb86df0 / vmstat_update
90	fffffffc0b49ec920	4294938202	blk_rq_timed_out_timer	0xffffffffc0b49ec328
90	fffffffc0b49ebf88	4294938202	blk_rq_timed_out_timer	0xffffffffc0b49eb990
90	fffffffc0b45805f8	4294938202	blk_rq_timed_out_timer	0xffffffffc0b4580000

+ tv2 Timers (2)

INDEX	TIMER_LIST ADDR	EXPIRES	FUNCTION	DATA / WORK
16	fffffffc0019eb600	4294938628	delayed_work_timer_fn	0xffffffffc0019eb5e0 / remote_rmi4_delay_work
16	fffffffc0019ebf20	4294938692	delayed_work_timer_fn	0xffffffffc0019ebf00 / remote_rmi4_delay_work

+ No tv3 Timers found

+ No tv4 Timers found

+ No tv5 Timers found

Clock dump

CLOCK NAME	COUNT/PREPARE_COUNT	RATE	CUR_LEVEL	CLOCK STRUCTURE
D mmss_gcc_dbg_clk	0 / 0	0	NULL	v.v (struct clk *)0xffffffffc001aff250
D gpu_gcc_dbg_clk	0 / 0	0	NULL	v.v (struct clk *)0xffffffffc001aff420
D gcc_debug_mux_v2	0 / 0	0	NULL	v.v (struct clk *)0xffffffffc001b043e0
D cpu_dbg_clk	0 / 0	0	NULL	v.v (struct clk *)0xffffffffc001aff338
D gcc_debug_mux	0 / 0	1593600000	NULL	v.v (struct clk *)0xffffffffc001b04530
D audio_ext_ap_clk	0 / 0	0	NULL	v.v (struct clk *)0xffffffffc001b419c8
D audio_ext_pmi_clk	0 / 0	0	NULL	v.v (struct clk *)0xffffffffc001b418e8
D audio_ext_ap_clk2	0 / 0	0	NULL	v.v (struct clk *)0xffffffffc001b41ac0
D gpu_aon_isense_clk	0 / 0	0	NULL	v.v (struct clk *)0xffffffffc001b24ae8
D gpu_mx_clk	0 / 0	0	0	v.v (struct clk *)0xffffffffc001b20480
D gpu_gcc_dbg_clk	0 / 0	19200000	NULL	v.v (struct clk *)0xffffffffc001b20ec8
D pwrcl_pll_main	0 / 0	595200000	NULL	v.v (struct clk *)0xffffffffc001b2e930
D pwrcl_lf_mux	0 / 0	595200000	NULL	v.v (struct clk *)0xffffffffc001b30290
D perfcl_pll_main	0 / 0	403200000	NULL	v.v (struct clk *)0xffffffffc001b2ea58
D perfcl_lf_mux	0 / 0	403200000	NULL	v.v (struct clk *)0xffffffffc001b2fff0
D sys_apcsaux_clk	0 / 0	300000000	NULL	v.v (struct clk *)0xffffffffc001b2f5b0
D cpu_debug_mux	0 / 0	1593600000	NULL	v.v (struct clk *)0xffffffffc001b30698
D mmpl18_postdiv_clk	0 / 0	133000000	NULL	v.v (struct clk *)0xffffffffc001b2d750
D mmpl19_postdiv_clk	0 / 0	624000000	NULL	v.v (struct clk *)0xffffffffc001b2d518
D mmsscc_gpll0_div	0 / 0	0	NULL	v.v (struct clk *)0xffffffffc001b1a470
D mmpl10	0 / 0	800000000	1	v.v (struct clk *)0xffffffffc001b2e1c0
D mmpl10_out_main	0 / 0	800000000	NULL	v.v (struct clk *)0xffffffffc001b2e090
D mmpl11	0 / 0	810000000	1	v.v (struct clk *)0xffffffffc001b1aa28

Note: The clock structures' pointer can be obtained so that the details in TRACE32 simulator can be checked. The current rate can be seen, whether it is enabled (if count = prepar_count !=0).

Workqueue for each core

CPU 0

pool 0

BUSY Workqueue worker: kworker/0:4 current_work: (None)

BUSY Workqueue worker: kworker/0:2 current_work: (None)

IDLE Workqueue worker: kworker/0:3 current_work: (None)

IDLE Workqueue worker: kworker/0:0 current_work: (None)

IDLE Workqueue worker: kworker/0:1 current_work: (None)

Pending entry: push_to_pool

Pending entry: ding entry: battery_age_tsens_poll

Pending entry: rslow_comp_work

Pending entry: update_cycle_count

Pending entry: update_esr_value

Pending entry: power_supply_changed_work

Pending entry: power_supply_changed_work

Pending entry: push_to_pool

pool 1

BUSY Workqueue worker: kworker/0:4 current_work: (None)

BUSY Workqueue worker: kworker/0:2 current_work: (None)

IDLE Workqueue worker: kworker/0:1H current_work: (None)

IDLE Workqueue worker: kworker/0:0H current_work: (None)

Pending entry: cfq_kick_queue

IRQ state

-----begin IrqParse-----

IRQ	CPU0	CPU1	CPU2	CPU3	Name	Chip	IRQ Structure
3	1421	447	1325	1275	arch_timer	GICv3	v.v (struct irq_desc *)0xffffffffc16b00b480
5	0	0	0	0	arch_mem_timer	GICv3	v.v (struct irq_desc *)0xffffffffc16b00b100
6	0	0	0	0	MDSS	GICv3	v.v (struct irq_desc *)0xffffffffc169d68e00
7	0	0	0	0	smp2p	GICv3	v.v (struct irq_desc *)0xffffffffc169d6aa00
8	0	0	0	0	smp2p	GICv3	v.v (struct irq_desc *)0xffffffffc169d69180
9	0	0	0	0	smp2p	GICv3	v.v (struct irq_desc *)0xffffffffc169d6a680
10	0	0	0	0	spdm_bw_hyp	GICv3	v.v (struct irq_desc *)0xffffffffc169d6a300
13	58	0	0	0	i2c-msm-v2-irq	GICv3	v.v (struct irq_desc *)0xffffffffc169d69c00
14	0	0	0	0	sps	GICv3	v.v (struct irq_desc *)0xffffffffc169f7c000
16	507	0	0	0	i2c-msm-v2-irq	GICv3	v.v (struct irq_desc *)0xffffffffc169f7c380
17	6	0	0	0	i2c-msm-v2-irq	GICv3	v.v (struct irq_desc *)0xffffffffc169f7f800
18	0	0	0	0	i2c-msm-v2-irq	GICv3	v.v (struct irq_desc *)0xffffffffc169f7c700
19	22	0	0	0	i2c-msm-v2-irq	GICv3	v.v (struct irq_desc *)0xffffffffc169f7f480
26	0	0	0	0	ngd_slim_irq	GICv3	v.v (struct irq_desc *)0xffffffffc169f7e300
28	0	0	0	0	630000.ufsice	GICv3	v.v (struct irq_desc *)0xffffffffc169f7df80
29	465	0	0	0	ufshcd	GICv3	v.v (struct irq_desc *)0xffffffffc169fcc000
30	0	0	0	0	int_msi	GICv3	v.v (struct irq_desc *)0xffffffffc169fcfb80
37	0	0	0	0	int_pls_err	GICv3	v.v (struct irq_desc *)0xffffffffc169fcce00
38	0	0	0	0	int_aer_legacy	GICv3	v.v (struct irq_desc *)0xffffffffc169fced80
40	0	0	0	0	int_pls_link_down	GICv3	v.v (struct irq_desc *)0xffffffffc169fcea00

CPR information (Not for all targets)

CPR Regulator	apc1_corner						
CPR Enabled	1						
Current Voltage	920000						
speed_bin	0						
cpr_fuse_revision	1						
cpr_fuse_map_match	-1						
num_fuse_corners	3						
num_corners	7						
corner	3						
cpr_fuse_redundant	0						
ro_sel	2						
cpr_fuse_ro_sel	2 2 2						
Corner	1	2	3	4	5	6	7
ceiling_volt	850000	850000	925000	970000	1040000	1080000	1095000
open_loop_volt	850000	850000	925000	970000	1040000	1080000	1095000
last_volt	850000	850000	920000	965000	1025000	1065000	1080000
floor_volt	790000	790000	820000	850000	940000	990000	990000
Target quotient	940	940	1119	1230	1372	1455	1490

Thermal sensor data

Thermal sensor data

TEMPERATURE ENTRIES FOR CPU:0

Temperature reading -	493	TimeStamp -	8469957160
Temperature reading -	503	TimeStamp -	8470442420
Temperature reading -	503	TimeStamp -	8470575650
Temperature reading -	474	TimeStamp -	8166957107
Temperature reading -	470	TimeStamp -	8168471534
Temperature reading -	480	TimeStamp -	8409028566
Temperature reading -	480	TimeStamp -	8413876639
Temperature reading -	477	TimeStamp -	8415337681
Temperature reading -	480	TimeStamp -	8435138462
Temperature reading -	477	TimeStamp -	8448638931

TEMPERATURE ENTRIES FOR CPU:1

Temperature reading -	516	TimeStamp -	8469915806
Temperature reading -	451	TimeStamp -	8126790180
Temperature reading -	454	TimeStamp -	8128299346
Temperature reading -	451	TimeStamp -	8166965492
Temperature reading -	454	TimeStamp -	8168479659
Temperature reading -	503	TimeStamp -	8408967628
Temperature reading -	474	TimeStamp -	8413886951
Temperature reading -	474	TimeStamp -	8415350024
Temperature reading -	464	TimeStamp -	8435150545
Temperature reading -	461	TimeStamp -	8448646952

Page type information

zone DMA	type Unmovable	74	73	65	16	1	1	0	1	2	1	0 = 7 MB 1808 pages
zone DMA	type Reclaimable	75	74	66	17	2	2	1	2	3	2	1 = 15 MB 3855 pages
zone DMA	type Movable	1	0	1	1	1	2	1	1	1	0	0 = 2 MB 541 pages
zone DMA	type CMA	2	1	2	2	2	3	2	2	2	1	1 = 10 MB 2588 pages
zone DMA	type Reserve	320	411	127	37	2	5	0	2	1	0	180 = 730 MB 186970 pages
zone DMA	type Isolate	321	412	128	38	3	6	1	3	2	1	181 = 738 MB 189017 pages
Total pages:		793	971	389	111	11	19	5	11	11	5	363

Approximate total for zone DMA: 1503 MB, 384779 pages

!!! Numbers may not be accurate due to list corruption!

zone Normal	type Unmovable	140	100	88	19	1	0	1	3	2	1	1 = 13 MB 3356 pages
zone Normal	type Reclaimable	141	101	89	20	2	1	2	4	3	2	2 = 21 MB 5403 pages
zone Normal	type Movable	1	1	1	5	0	1	0	0	1	1	0 = 3 MB 847 pages
zone Normal	type CMA	2	2	2	6	1	2	1	1	2	2	1 = 11 MB 2894 pages
zone Normal	type Reserve	952	1758	897	129	22	1	2	1	1	1	191 = 805 MB 206080 pages
zone Normal	type Isolate	953	1759	898	130	23	2	3	2	2	2	192 = 812 MB 208127 pages
Total pages:		2189	3721	1975	309	49	7	9	11	11	9	387

Zone information

Zone DMA		NR_VMSCAN_IMMEDIATE	:	0		
NR_FREE_PAGES	:	692168		NR_WRITEBACK_TEMP	:	0
NR_ALLOC_BATCH	:	277		NR_ISOLATED_ANON	:	0
NR_LRU_BASE	:	2		NR_ISOLATED_FILE	:	0
NR_ACTIVE_ANON	:	316		NR_SHMEM	:	5
NR_INACTIVE_FILE	:	0		NR_DIRTIED	:	0
NR_ACTIVE_FILE	:	74		NR_WRITTEN	:	0
NR_UNEVICTABLE	:	0		NR_PAGES_SCANNED	:	0
NR_MLOCK	:	0		WORKINGSET_REFAULT	:	0
NR_ANON_PAGES	:	317		WORKINGSET_ACTIVATE	:	0
NR_FILE_MAPPED	:	4		WORKINGSET_NODERECLAIM	:	0
NR_FILE_PAGES	:	119		NR_ANON_TRANSPARENT_HUGEPAGES	:	0
NR_FILE_DIRTY	:	0		NR_FREE_CMA_PAGES	:	34243
NR_WRITEBACK	:	0		NR_SWAPCACHE	:	0
NR_SLAB_RECLAIMABLE	:	2010		WMARK_MIN	:	1195
NR_SLAB_UNRECLAIMABLE	:	10488		WMARK_LOW	:	1493
NR_PAGETABLE	:	3		WMARK_HIGH	:	1792
NR_KERNEL_STACK	:	104				
NR_UNSTABLE_NFS	:	0				
NR_BOUNCE	:	0				
NR_VMSCAN_WRITE	:	0				

from DDR:

fffffffc001666800	*31a739c7	*29663186	*29452946	*29452945	*29452925	*29452945	*29452945	*29452945	.9.1.1f)F)E)E)E(%)E)E)E)E)E(%)
fffffffc001666820	*21042125	*10a318e4	*08621082	*08210841	*08210021	*08410841	*08410841	*08420842	%!.....b.A.!...!.A.A.A.B.B.
fffffffc001666840	*08620862	*08620862	*08620862	*08620862	*08620862	*08620862	*10820862	*10821082	b.b.b.b.b.b.b.b.b.b.b.b.b.b.b.b.b.....
fffffffc001666860	*10a310a3	*18c318c3	*18e418c4	*21252104	*29662145	*31a72986	*39e839c7	*4a494229!%E!f).).1.9.9)BIJ
fffffffc001666880	*52ab4a6a	*630c5acb	*6b6e634d	*73af738e	*7bf07bcf	*8c728c71	*9cf49cd3	*42284208	jJ.R.ZcMcnk.s.s.{q.r.....B(B
fffffffc0016668a0	*630c4a49	*52aa52aa	*5aaa5aaa	*5aaa5aaa	*5aaa5aaa	*5aaa62cb	*52695a8a	*4a284a28	IJC.R.R.Z.Z.Z.Z.Z.z.b.Z.ZiR(J(J
fffffffc0016668c0	*52694a48	*5aaa5aaa	*5aaa5aaa	*52695aaa	*630b5aaa	*20e35269	*20e31081	*20e320e3	HJR.Z.Z.Z.Z.ZiR.ZciR.....
fffffffc0016668e0	*20e320e3	*20c320c3	*20e320c3	*20e320e3	*20e320e3	*20e420e4	*290420e4	*29042904).).

```
from vmlinux:
```

```
fffffc001666800 *a8c27bfd *d65f03c0 *a9bf7bfd *f0003d40 *910003fd *f906581f *f0003d40 *f9065c1f .{...._.{!@=.....X..@=...\.
fffffc001666820 *f0003d40 *f906681f *f0003d40 *f906641f *97b02c53 *a8c17bfd *d65f03c0 *a9bf7bfd @=...h..@=...d..S,...{...._.{..
fffffc001666840 *d0ffce41 *52800040 *910003fd *91194021 *97d720ce *a8c17bfd *d65f03c0 *a9be7bfd A...@..R....!@.....{...._.{..
fffffc001666860 *910003fd *f9000bf3 *90001793 *91248273 *91004260 *97d6b486 *91018260 *52800021 .....s.$.`B.....`!!!..R
fffffc001666880 *97d72a0d *91036260 *52800041 *97d729a6 *91072260 *97d5c114 *f9400bf3 *a8c27bfd *..`b..A..R.)..`".....@..{..
fffffc0016668a0 *d65f03c0 *90003da1 *d0ffce40 *a9bf7bfd *911c0000 *910003fd *f9427821 *97d72e86 .._..=.@....{.....!xB.....
fffffc0016668c0 *90001780 *912c8000 *97d5c107 *a8c17bfd *d65f03c0 *90003da1 *d0ffce40 *a9bf7bfd .....,.....{...._..=.@....{..
fffffc0016668e0 *911da000 *910003fd *f9427c21 *97d72e7a *90001780 *912d8000 *97d5c0fb *a8c17bfd .....!|B.z.....-.....{..
```


DDR Cache Compare

Kernel Configuration for debug spinlocks is not enabled, cannot compare the magic values!!

Checking for task list corruption.

Init Task Address = 0xffffffffc001a29d30L
Task Offset 0x398
Comm Offset 0x608

Next = 0xffffffffc0d9c90000 (init)
Next = 0xffffffffc0d9c90c00 (kthreadd)
Next = 0xffffffffc0d9c91800 (ksoftirqd/0)
Next = 0xffffffffc0d9c93000 (kworker/0:0H)
Next = 0xffffffffc0d9c93c00 (kworker/u8:0)
Next = 0xffffffffc0d9c94800 (rcu_preempt)
Next = 0xffffffffc0d9c95400 (rcu_sched)
Next = 0xffffffffc0d9c96000 (rcu_bh)
Next = 0xffffffffc0d9c96c00 (migration/0)
Next = 0xffffffffc0d9e9a400 (migration/1)
Next = 0xffffffffc0d9e9b000 (ksoftirqd/1)
Next = 0xffffffffc0d9e9c800 (kworker/1:0H)

Next = 0xffffffffc004250000 (kworker/3:3)
Next = 0xffffffffc09ee03000 (kworker/2:2)
Next = 0xffffffffc0ccfd8c00 (kworker/1:2)
Next = 0xffffffffc0343dc800 (kworker/2:1)
Next = 0xffffffffc0cbf35400 (kworker/0:1)
Next = 0xffffffffc0343dbc00 (kworker/u8:12)
Next = 0xffffffffc04fcc0000 (kworker/3:1)
Next = 0xffffffffc04fcc1800 (kworker/1:3)
Next = 0xffffffffc0cbf30000 (kworker/2:3)
Next = 0xffffffffc0cd1eec00 (kworker/u8:16)
Next = 0xffffffffc001a29d30 (swapper/0)

RESULT: No issues found in the task list

Qualcomm
2019-03-13 05:27:18 PDT
zk_sw@wingtech.com

Questions?

<https://createpoint.qti.qualcomm.com>

