

PI ELECTRONICS

PART NO. :

DESCRIPTION : AD2081N20110-2LF APPROVAL PACKAGE

DOCUMENT NO. : 102189 010101-302

Filename:

102189 010101-302-180426 (PDF)

| Action | Signatory | Date |
|--------------------|-----------|-----------------|
| Prepared By: | 袁志毅 | 180426 16:54:52 |
| Reviewed By: | 張紹武 | 180426 16:58:18 |
| | 高忠錯 | 180426 17:13:30 |
| Double Checked By: | 曹國威 | 180427 11:54:14 |

TOTAL 34 PAGES

Cover Page

This document has been digitally signed. Actual signature is not required.

PI ELECTRONICS (H.K.) Ltd.

TEL : (852) 2790-8175

FAX : (852) 2797-9176

AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

| | |
|-------------------|--------------------|
| CUSTOMER NAME | : ASUS |
| CUSTOMER PART NO. | : |
| PI MODEL NO. | : AD2081N20110-2LF |
| REV. | : 1 |
| DATE | : 26-Apr-2018 |

| | | |
|-------------------|----------------------|--------------------------------|
| APPROVED | CHECKED | DRAWN |
| Winton Lou | HerBert HBXie | Yuan Zhiyi /Chen MD |

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

Customer Part No./Model Name and PI Model List :

| PI Model No. | Customer Part No. | Customer Model Name |
|------------------|-------------------|---------------------|
| AD2081N20110-2LF | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

Table of Contents :

| | |
|---|----|
| Cover Page..... | 3 |
| Section 1 - History of Changes..... | 3 |
| Section 2 - Specification | 5 |
| 1. DESCRIPTION..... | 6 |
| 2. ELECTRICAL SPECIFICATION..... | 6 |
| 2.1. TYPE..... | 6 |
| 2.2. INPUT | 6 |
| 2.3. OUTPUT | 7 |
| 2.4. OTHERS | 7 |
| 3. RELIABILITY | 8 |
| 4. ENVIRONMENTAL..... | 8 |
| 4.1. CLIMATIC SPECIFICATIONS | 8 |
| 4.2. DYNAMIC SPECIFICATIONS | 9 |
| 5. SAFETY AND EMC | 9 |
| 5.1. DIELECTRIC WITHSTANDING VOLTAGE | 9 |
| 5.2. SAFETY STANDARD..... | 9 |
| 5.3. EMC SPECIFICATION..... | 9 |
| 6. MECHANICAL SPECIFICATIONS | 11 |
| Section 3 - Outline Drawing | 12 |
| Section 4 - DC Cable Drawing | 14 |
| Section 5 - Rating and S/N Label Drawing..... | 16 |
| Section 6 - Packaging Drawing | 20 |
| Section 7 - Bill Of Material (BOM) | 24 |
| Section 8 - Schematic..... | 26 |
| Section 9 - PCB Layout | 28 |
| Section 10 - Safety Certificates..... | 30 |

Section 1 - History of Changes

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

History of Changes :

| Date | Rev | Remarks |
|-------------|-----|----------------------|
| 26-Apr-2018 | 1 | Preliminary release. |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

Section 2 - Specification

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

1. DESCRIPTION

This is a general purpose AC/DC adaptor which converts 100Vac~240Vac to a stabilized DC voltage of 5.0V/2.0A .

2. ELECTRICAL SPECIFICATION

2.1. TYPE

- Switching regulator type.

2.2. INPUT

| | | |
|-------|-------------------------|---|
| 2.2.1 | Rated Input Voltage | : 100~240Vac, @ 50/60Hz. |
| 2.2.2 | Operating Input Voltage | : 90~264Vac, 47~ 63Hz. |
| 2.2.3 | Input Current | : < 0.3A. |
| 2.2.4 | Inrush Current | : The inrush current of the power supply shall be less than the rating of its critical components (include bridge diode, surge limiting device) for all condition of line voltage of 2.2.1. The I ² t shall less than 22% of the fuse, surge limiting device and bridge diode rating. No component damaged. |
| 2.2.5 | Standby power | : <0.075W @ 230Vac/50Hz and 115Vac/60Hz. Off Mode: P _{out} =0.25W, P _{in} <0.45W |
| 2.2.6 | Efficiency | : ≥ 79% Under the active mode and input voltage 115Vac/60Hz&230Vac/50Hz. The power supply efficiency shall be more than 77.5% measure at the normal voltage maximum load as specified with the AC input set at the nominal voltage. The 10% efficiency shall be more than 69.8% measure at 115V/60Hz and 230Vac/50Hz |

Notes :

- The average efficiency shall comply with the DOE VI / COC v5 Tier 2 request.
- The UUT shall be operated at 100% of nameplate current output for at least 30 minutes immediately prior to conducting efficiency measurements.
- The ambient temperature shall be maintained at 23°C ± 5°C throughout the test.
- (The measure point is end of DC cable , the cable impedance is 180m ohm)

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

2.3. OUTPUT

- 2.3.1 Rated Output Voltage : $V_o=5.0V_{dc}$
- 2.3.2 Output Voltage Regulation : $V_o=4.85\sim 5.25V_{@(0A-0.49A)}$ Load
 $V_o=5.0\sim 5.25V_{@(0.5A-Full)}$ Load
- 2.3.3 Output Ripple and noise : $<200mV_{p-p}$. The output Ripple & Noise voltage shall be less than 100mV at load 0.5A.
- Notes :
- Ripple voltage is measured using oscilloscope with bandwidth limited to 20MHz.
 - A 10uF electrolytic capacitor and a 0.1uF ceramic capacitor shall be connected to the connector in parallel.
- 2.3.4 Output Load Current : Rating current: 2.0A
Operating Max current: $\approx 2.0A$
Operating Min current: $\approx 0A$
Ripple current: $<100mA_{(pk-pk)}$
- 2.3.5 Overshoot/Undershoot : 10% of nominal voltage
- 2.3.6 Hold up time : $>5ms_{@Full\ load/100Vac}$
- 2.3.7 Rise time : $<40ms$.
- 2.3.8 ID Function : 1. D+ and D- short to follow BC 1.2
2. Add another ID resistor from short point (D+ & D-) to Ground
3. ID resistor is 750Kohm

2.4. OTHERS

- 2.4.1 Turn-on Delay : < 3 seconds. The input voltage measure at 100/240Vac and at maximum output load.
- 2.4.2 Over Voltage Protection : $V_o<7.5V$, the recover voltage $< 3.3V$ at auto recovery mode.
- 2.4.3 Over Current Protection : (2.1-2.45)A, Auto-recovery.
- 2.4.4 Short Circuit Protection : Shorting of output will not cause power supply to damage, or any safety hazard. Auto-recovery.
- 2.4.5 Power on/off repeat : Set the output at maximum load and switch AC ON/OFF at 264Vac/63Hz for 10000 cycles.
AC ON 4 sec and OFF 1 sec for each cycle.
No any component damage or fault condition during the test.
- 2.4.6 Dynamic Load : Under resistive load conditions, any change in output current at a rate of $1A/\mu s$,
Condition 1: $0.5A_{@5ms}, 0A_{@295ms}$
Condition 2: $2.0A_{@5ms}, 0.5A_{@25ms}$
Output voltage range: Max. 6V , Min. 4.6V
If output drop less than 4.6V, the during shall be

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

- 2.4.7 Case Temperature rise : less than 3ms @ condition 1.
: The case temperature rise shall be less 35deg C at 25deg C Ambient on bakelite (Not including the bottom surface)without airflow.
- 2.4.8 Acoustic Noise : 1.Microphone at a distance of 10cm from the surface and noise level is less than 20dB@static load (from 0A to Full Load, 0.05A pre step)& dynamic load as item 2.4.6.
2.Microphone at a distance of 3cm from the surface and noise level is less than 25dB@static load (from 0A to Full Load, 0.05A pre step)& dynamic load as item 2.4.6.
- 2.4.9 Common Mode Noise : Test Equipment and Environment : Follow EN61000-4-6
Test voltage Condition :3V
Test Frequency :150K ~ 600KHz
Specification :CMN Max.:0.8V@150K~600K

3. RELIABILITY

- 3.1 MTBF : > 150K Hours at 25 degree C.
- 3.2 Life/Power On Hours : The power supply must be designed to operate for 13,140 power on hours.
AC input voltage: 100 and 240Vrms
Ambient Temp. : 25 °C
- 3.3 Burn-in Test Condition : More than 4 hours at 40 °C, normal input voltage. AC on/off must be tested.
- 3.4 AC Plug Pull/Push Test : >30kg, the AC plug can't separated from the main body and case can't deformation.
- 3.5 DC Connector Salt Spray Test : - Follow EIA Spec.
- Salt Solution : Density 5%, PH value 6.5~7.2
- Chamber Temp. and Corrosion Time : 35 °C for 48hrs
- Without excessive corrosion or crack in appearance.

4. ENVIRONMENTAL

4.1. CLIMATIC SPECIFICATIONS

- 4.1.1 Operating Temperature : 0degC ~ 40degC
- 4.1.2 Operating Humidity : 5% ~90 % (Non-condensing)
- 4.1.3 Storage Temperature : -30degC ~80degC
- 4.1.4 Storage Humidity : 5% ~90% (Non-condensing)

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

4.2. DYNAMIC SPECIFICATIONS

- 4.2.1 Vibration Test - Non-Operating : 1.5mm, 10-50-10Hz / sine wave.
4.2.2 Pass Criterion : Normal functional test should be satisfied after the test.

5. SAFETY AND EMC

5.1. DIELECTRIC WITHSTANDING VOLTAGE

- 5.1.1 Primary to Secondary : 3.0KVac , 1 minute, 5mA for type test, 2 seconds for production.
5.1.2 Leakage Current : The total combined leakage current shall be <20uA when tested at 240Vrms, 50Hz in normal operating condition.
5.1.3 Insulation Resistance : 30Mohm check at DC 500V.

5.2. SAFETY STANDARD

| Type | Country/Region | Standard |
|------|----------------|------------------|
| CB | EU | IEC60950/EN60950 |
| BIS | IN | IS13252 |

5.3. EMC SPECIFICATION

- 5.3.1. Noise-suppressed according to EN55022 Class B and FCC 15 Class B for both Radiated and Conducted Emissions.

- 5.3.2. Immunity to Electrostatic Discharge (ESD) according to EN 61000-4-2.

| Discharge Characteristic | Test Level | Acceptance Criteria *1 |
|--------------------------|-----------------|------------------------|
| Air Discharge | ±15KV, 10 times | B |
| | ±12KV, 10 times | A |
| Contact Discharge | ±8KV, 10 times | A |

Note *1: For the test result, please refer to (5.3.8) Assessment criteria.

- 5.3.3. Immunity to Radiated Electromagnetic Field (RS) according to EN 61000-4-3.
- Test characteristic: 80 - 1000MHz, 80% AM (1kHz)

| Test Level | Acceptance Criteria |
|------------|---------------------|
| 3V/m | A |

- 5.3.4. Immunity to Electrical Fast Transients / Burst (EFT) according to EN 61000-4-4.

| Coupling | Test level | Acceptance Criteria |
|----------|------------|---------------------|
| AC-input | 1KV | A |
| AC-input | 2KV | B |

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

5.3.5. Lightning Surge capability according to EN 61000-4-5.

| Surge voltage | Acceptance Criteria |
|--------------------------------------|---------------------|
| Common mode +/-2KV 12R, 10 times | A |
| Differential mode +/-1KV 2R, 5 times | A |

5.3.6. Immunity to Conducted disturbances, induced by radio frequent fields according to EN 61000-4-6.

- Test characteristic 0.15- 80MHz, 80% AM(1kHz)

| Test level | Acceptance Criteria |
|------------|---------------------|
| 3V | A |

5.3.7. Immunity to Voltage dips, short interruptions and voltage variations.

- Test according to EN 61000-4-11.
- Test performed at Vin =120Vac/60Hz.
- Note : Test with resistive load at rated loading.

| Test Level % Vin | Voltage Dips and Short Interruptions % Vin | Duration Time of Voltage Dips (in half-sine cycles) | Acceptance Criteria |
|---------------------|--|--|---------------------|
| | | | 120Vac/60Hz |
| 0 | 100 | 1 | B |
| | | 2 | B |
| | | 5 | B |
| | | 10 | B |
| | | 25 | B |

5.3.8. Assessment criteria

| Acceptance Criteria | Performance |
|---------------------|---|
| A | Agreed operational behavior within the specified limits. |
| B | Time limited functional diminishment or malfunction during the tests is permitted. The function is self- reactivated by the unit following completion of the tests. |
| C | Malfunction is permitted. The function can be reactivated either by reconnection to the mains or by operator intervention. |

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

6. MECHANICAL SPECIFICATIONS

- | | | |
|------------|-------------------------|---|
| 6.1 | Weight | : 47.7g ±5% |
| 6.2 | Input Connector | : Refer to attached drawing |
| 6.3 | Output Cable | : Refer to attached drawing |
| 6.4 | Output Connector | : Refer to attached drawing |
| 6.5 | Drop Test | Drop 30 times(5 times on each face) on each cycles from a height of 36 inches onto a hardwood surface. There must be no function damage after testing. |

Section 3 - Outline Drawing

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

TBD

Section 4 - DC Cable Drawing

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

N/A

Section 5 - Rating and S/N Label Drawing

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

RATING LABEL DRAWING

TBD

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

2D BAR CODE LABEL DRAWING

TBD

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

LABEL LOCATION DRAWING

TBD

Section 6 - Packaging Drawing

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

OPP FILM LOCATION DRAWING

TBD

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

ASSY-CARTON

TBD

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

ASSY-PALLET

TBD

Section 7 - Bill Of Material (BOM)

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

TBD

Section 8 - Schematic

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

TBD

Section 9 - PCB Layout

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

TBD

Section 10 - Safety Certificates

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

TBD

Confidential to PIE.For ASUS Internal Reference Only.

PI ELECTRONICS (H.K.) Ltd.
AD2081N20110-2LF APPROVAL PACKAGE (Rev. 1)

*** END ***