PROJECT REPORT

Sales Tracker in Google Sheets

A lightweight spreadsheet for raw sales entry and automatic daily, weekly, and monthly summaries

TOTAL SALES	QUANTITY SOLD	TRANSACTIONS	REPORTING PERIOD
259,900	39	10	Oct 2026

1. Project Overview

The Sales Tracker is a Google Sheets workbook designed to record retail transactions in a structured table and turn those entries into useful sales summaries. The workbook separates source data from summary calculations so that day-to-day entry is easier to manage and the totals are easier to check.

Objectives

- Create a consistent structure for entering transaction dates, products, categories, quantities, and unit prices.
- Calculate each transaction value automatically using quantity multiplied by unit price.
- Summarize sales daily, weekly, and monthly with date-based formulas.
- Reduce common entry errors with validation rules and clear column labels.
- Verify summary figures against a known sample dataset.

2. Workbook Structure

Tab	Purpose	Key fields / outputs
Sales_Data	Raw transaction entry	Date, Product, Category, Quantity, Unit Price, Total Sales
Summary	Automatic rollups and KPIs	Total sales, quantity, transaction count, daily totals, weekly totals, monthly totals

3. Formulas and Logic

Purpose	Formula / approach
Transaction value	=D2*E2 in F2, filled down
Total sales (10 sample rows)	=SUM(Sales_Data!F2:F11)
Total quantity	=SUM(Sales_Data!D2:D)
Transaction count (sample)	=COUNTA(Sales_Data!B2:B11); for ongoing entry, use =COUNTA(Sales_Data!B2:B)
Daily sales	=SUMIF(Sales_Data!A:A,A10,Sales_Data!F:F)
Weekly sales	=SUMIFS(Sales_Data!F:F,Sales_Data!A:A,">="&D10,Sales_Data!A:A,"<"&D10+7)
Monthly sales	=SUMIFS(Sales_Data!F:F,Sales_Data!A:A,">="&G10,Sales_Data!A:A,"<"&EDATE(G10,1))

The weekly rollup uses Monday as the first day of the week. The monthly rollup sums dates from the first day of the selected month up to, but not including, the first day of the next month. For continued use, formulas with a bounded sample range should be expanded or changed to open-ended ranges as new rows are added.

4. Data Validation and Usability

Range	Rule	Purpose
Sales_Data!D2:D1000	Number greater than 0; reject invalid input	Prevents zero or negative quantities
Sales_Data!E2:E1000	Number greater than 0; reject invalid input	Prevents zero or negative unit prices
Sales_Data!A2:A1000	Valid date; reject invalid input	Keeps transaction dates usable in date-based summaries

- The raw entry table and the summary are on separate tabs.
- The header row is bold and frozen to keep field names visible while scrolling.
- Sales values can be formatted as Indian Rupees (₹) for readability.
- Formula cells should be protected where possible if multiple people will edit the workbook.

5. Sample Data and Verification

The workbook was tested with 10 manually entered sample retail transactions dated October 1-27, 2026. Each row calculates Total Sales as Quantity × Unit Price. The summary outputs were checked against the transaction values.

Metric	Verified result	Check
Total sales	259,900	Sum of transaction values
Total quantity sold	39	Sum of quantities
Number of transactions	10	Count of product entries
October 2026 sales	259,900	All sample transactions fall in October

Sample data is illustrative; apply the ₹ currency format in Google Sheets if needed.

6. How to Use the Tracker

- Enter one transaction per row in Sales_Data. Complete the date, product, category, quantity, and unit price.
- Ensure Total Sales contains the formula =D2*E2 and that the formula is filled down for new records.
- Review the Summary tab for daily, weekly, and monthly results.
- When adding transactions beyond row 11, extend any sample-bounded formulas or use open-ended ranges so the new entries are included.
- Periodically compare the summary with the raw entries to catch accidental edits or incomplete formulas.

7. Reflection: Interview Questions

How can a spreadsheet be designed so non-technical staff can enter data safely?

Use clear column labels, consistent number and date formats, a dedicated data-entry tab, validation rules, frozen headers, and protected formula cells. Keep summaries separate from raw entries and provide brief instructions for entering each record.

What is the risk of mixing raw data and formulas on the same tab?

Users may overwrite formulas, place new rows in the wrong area, or accidentally include calculated values in the source data. Separating data entry from summaries improves maintainability, reduces accidental changes, and makes troubleshooting easier.

8. Conclusion

The project demonstrates how a simple Google Sheets workbook can structure raw sales entries, calculate transaction values automatically, summarize results across time periods, and apply validation to improve data quality. The sample totals were verified, and the workbook can be extended for ongoing entry by ensuring formulas cover newly added rows.