## Assignment-15

Using Subqueries with DML Commands.

1) Assume there is a table called Multicust, with all of the same column definitions as Salespeople. Write a command that inserts all salespeople with more than one customer into this table.

```
KD3_86686_Vaibhav@>create table Multicust as select * from salespeople where
 snum in(select snum from orders
    -> group by snum
    -> having count(cnum) >1 );
Query OK, 2 rows affected, 1 warning (0.04 sec) Records: 2 Duplicates: 0 Warnings: 1
KD3_86686_Vaibhav@>select * from Multicust;
  Snum
          Sname
                    city
                                  Comm
                                  0.13
  1002
          Serres
                    San Jose
          Rifkin
  1007
                    Barcelona
                                  0.15
  rows in set (0.00 sec)
```

2) Write a command that deletes all customers with no current orders.

```
KD3_86686_Vaibhav@>delete from customers where cnum not in (select cnum from
orders);
Query OK, 1 row affected (0.01 sec)
KD3_86686_Vaibhav@>select * from customers;
                    Citv
 Cnum
         Cname
                                Rating
                                          Snum
         Hoffman
  2001
                     London
                                    100
                                          1001
  2002
         Giovanni
                     Rome
                                    300
                                          1003
                     San Jose
  2003
         Liu
                                    200
                                          1004
  2004
                     Berlin
         Grass
                                    300
                                          1004
  2008
                     San Jose
                                          1007
         Cisneros
                                    300
  2007
         Pereira
                     Rome
                                    200
                                          1004
 rows in set (0.00 sec)
KD3_86686_Vaibhav@>
```

3)Write a command that increases by twenty percent the commissions of all salespeople with total orders above Rs. 3,000.

```
KD3_86686_Vaibhav@>update salespeople set comm = comm + comm*0.2
    -> where snum = all(
    -> select snum from orders
    -> group by snum
    -> having sum(amt) > 3000);
Query OK, 1 row affected (0.02 sec)
Rows matched: 1 Changed: 1 Warnings: 0
KD3_86686_Vaibhav@>select * from salespeople;
  Snum | Sname
                  city
                               Comm
  1001
         Peel
                   London
                                0.12
  1002
         Serres
                   San Jose
                                0.16
         Motika
  1004
                   London
                                0.11
         Rifkin
                   Barcelona
                                0.15
  1007
                   New York
  1003
         Axelrod
                                0.10
                   San Jose
  1100
         Blanco
                               NULL
6 rows in set (0.00 sec)
KD3_86686_Vaibhav@>
```