

Q1 Write two different queries that would produce all orders taken on October 3rd or 4 th, 1990.

→ first query ==> select \* from orders where Odate in('1990-10-03','1990-10-04');

```
KD3_86704_Mayur@>select * from orders where Odate in('1990-10-03','1990-10-04');
```

Onum	Amt	Odate	Cnum	Snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3002	767.19	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002

```
7 rows in set (0.00 sec)

KD3_86704_Mayur@>
```

Second Query ==> select \* from orders where Odate between '1990-10-03' AND '1990-10-04';

```
KD3_86704_Mayur@>select * from orders where Odate between '1990-10-03' AND '1990-10-04';
```

Onum	Amt	Odate	Cnum	Snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3002	767.19	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002

```
7 rows in set (0.00 sec)

KD3_86704_Mayur@>
```

Q3 Write a query that will produce all the customers whose names begin with a letter from 'A' to 'G'.

→ select \* from customers where Cname >='A' and Cname <='H';

```
KD3_86704_Mayur@>select * from customers where Cname >='A' and Cname <='H';
```

Cnum	Cname	City	Rating	Snum
2002	Giovanni	Rome	200	1003
2004	Grass	Berlin	300	1002
2006	Celms	London	100	1001
2008	Cisneros	San Jose	300	1007

```
4 rows in set (0.00 sec)

KD3_86704_Mayur@>
```

Q4--. Write a query that selects all customers whose names begin with the letter 'C'.

→select \* from customers where Cname like 'C%';

```
KD3_86704_Mayur@>select * from customers where Cname like 'C%';
```

Cnum	Cname	City	Rating	Snum
2006	Celms	London	100	1001
2008	Cisneros	San Jose	300	1007

```
2 rows in set (0.01 sec)

KD3_86704_Mayur@>
```

Q5 Write a query that selects all orders except those with zeroes or NULLs in the amt field.

➔ select \* from orders where Amt is not null and Amt >0;

```
KD3_86704_Mayur@>select * from orders where Amt is not null and Amt >0;
```

Onum	Amt	Odate	Cnum	Snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3002	767.19	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002
3008	4723.00	1990-10-05	2006	1001
3010	1309.95	1990-10-06	2004	1002
3011	9891.88	1990-10-06	2006	1001

```
10 rows in set (0.00 sec)
```

```
KD3_86704_Mayur@>
```