

Assignment –6

Using Special Operators in Conditions.

- 1) Write two different queries that would produce all orders taken on October 3rd or 4 th, 1990.

```
KD3_86728_mayur_pawar@>select * from orders where odate = '1990-10-03' o  
r odate = '1990-10-04';
```

```
KD3_86728_mayur_pawar@>select * from orders where odate in('1990-10-03',  
'1990-10-04');
```

- 2) Write a query that selects all of the customers serviced by Peel or Motika. (Hint: the snum field relates the two tables to one another)

```
KD3_86728_mayur_pawar@>select * from customers where snum = 1001 or snum  
= 1004;
```

Cnum	Cname	City	Rating	Snum
2001	MAYUR	London	100	1001
2006	Clemens	London	100	1001
2007	Pereira	Rome	100	1004

3 rows in set (0.00 sec)

- 3) Write a query that will produce all the customers whose names begin with a letter from 'A' to 'G'.

```
KD3_86728_mayur_pawar@>select * from customers where Cname between 'A' a  
nd 'H';
```

Cnum	Cname	City	Rating	Snum
2002	Giovanni	Rome	200	1003
2004	Grass	Berlin	300	1002
2006	Clemens	London	100	1001
2008	Cisneros	San Jose	300	1007

4 rows in set (0.00 sec)

- 4) Write a query that selects all customers whose names begin with the letter 'C'.

```
KD3_86728_mayur_pawar@>
KD3_86728_mayur_pawar@>select * from customers where cname like 'C%';
```

Cnum	Cname	City	Rating	Snum
2006	Clemens	London	100	1001
2008	Cisneros	San Jose	300	1007

```
2 rows in set (0.00 sec)
```

- 5) Write a query that selects all orders except those with zeroes or NULLs in the amt field

```
KD3_86728_mayur_pawar@>select * from orders where amt != 0 or amt != null;
```

Onum	Amt	Odate	Cnum	Snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002
3008	4723.00	1990-10-05	2006	1001
3010	1309.95	1990-10-06	2004	1002
3011	9891.88	1990-10-06	2006	1001

```
10 rows in set (0.00 sec)
```