Assignment 13

1) Create a union of two queries that shows the names, cities, and ratings of all customers.

Those with rating of 200 or greater will also have the words "High Rating", while the others will have the words "Low Rating".

```
KD2-SATYAJEET-86740@>select cname, city, rating, 'High rating' as "Remark" from customers where rating >=200
    -> select cname, city, rating, 'Low rating' as "Remark" from customers where rating <200;
                        | rating | Remark
  cname
  Giovanni
                                    High rating
              San Jose
Berlin
                             200
300
                                   High rating
High rating
  Liu
  Grass
                             300
100
  Cisneros
              San Jose
                                   High rating
              London
                                   Low rating
  Hoffman
              London
  Clemens
  Pereira
              Rome
                                   Low rating
 rows in set (0.00 sec)
KD2-SATYAJEET-86740@>
```

2) Write a command that produces the name and number of each salesperson and each customer with more than one current order. Put the results in alphabetical order.

```
| KD2-SATYAJEET-86740@>select * from salespeople where snum in (SELECT snum FROM orders GROUP BY snum HAVING COUNT(snum) > 1);
| Snum | Sname | City | Comm |
| 1001 | Peel | London | 0.12 |
| 1002 | Serres | San Jose | 0.13 |
| 1007 | Rifkin | Barcelona | 0.15 |
| 1008 | Serres | San Jose | 10.15 |
| 1009 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000 | Serres | San Jose | 10.15 |
| 1000
```

3) Form a union of three queries. Have the first select the snums of all salespeople in San Jose; the second, the cnums of all customers in San Jose; and the third the onums of all orders on October 3. Retain duplicates between the last two queries but eliminate any redundancies between either of them and the first. (Note: in the sample tables as given, there would be no such redundancy. This is besides the point.)

```
KD2-SATYAJEET-86740@>select snum from salespeople where city= 'San Jose'union select cnum from customers where city= 'San Jose' union select onum from orders where odate='1190-10-03';

+-----+
| snum |
+----+
| 1002 |
| 2003 |
| 2008 |
+-----+
3 rows in set (0.02 sec)
```