



Northeastern  
University

# Lecture 6: Object Oriented Programming - 1

Prof. Chen-Hsiang (Jones) Yu, Ph.D.  
College of Engineering

Materials are edited by Prof. Jones Yu from

Liang, Y. Daniel. Introduction to Java Programming, Comprehensive Version, 12th  
edition, Pearson, 2019.

# Outline

---

- Objects and Classes
- Thinking in Objects

# Outline

---

- Objects and Classes
- Thinking in Objects

# Objects and Classes

Objects

# OO Programming Concepts

---

- Object-oriented programming (OOP) involves programming using **objects**.
- **An object** represents an entity in the real world that can be distinctly identified, such as a desk, a button, a car, etc.
- An object has **a unique identity**, **state**, and **behaviors**.

# OO Programming Concepts

---

- The *state* of an object consists of *a set of data fields* (also known as *properties*) with their current *values*.
- The *behavior* of an object is defined by *a set of methods*.

# Objects

---

- An object has both a **state** and **behavior**.
- The **state** defines the object, and the **behavior** defines what the object does.



# Classes

# Classes

---

- *Classes* are constructs (structures, blueprints) that define objects of the same type.
- A Java class uses variables to define data fields and methods to define behaviors.
- Additionally, a class provides a special type of methods, known as constructors, which are called to construct objects from the class.




image source: <https://tinyurl.com/37h6h43w>, <https://tinyurl.com/2cxc3dc8>

# Classes

---

```
class Circle {  
    /** The radius of this circle */  
    double radius = 1.0;  
  
    /** Construct a circle object */  
    Circle() {  
    }  
  
    /** Construct a circle object */  
    Circle(double newRadius) {  
        radius = newRadius;  
    }  
  
    /** Return the area of this circle */  
    double getArea() {  
        return radius * radius * 3.14159;  
    }  
}
```

← Data field





← Constructors

← Method

# UML (Unified Modeling Language) Class Diagram

---

UML Class Diagram



← UML notation for objects

# Exercise

---

- Create and define a **TV** class to have following data fields and methods:

- » data fields:

- `channel (int)`

- `volumeLevel (int)`

- `on (boolean)`

- » methods:

- `turnOn(): void`

- `turnOff(): void`

# Answer

---

```
public class TV {  
  
    int channel;  
    int volumeLevel;  
    boolean on;  
  
    TV() {  
        channel = 1;  
        volumeLevel = 1;  
        on = false;  
    }  
  
    public void turnOn() {  
        on = true;  
    }  
  
    public void turnOff() {  
        on = false;  
    }  
  
}
```

```
public class TV {  
  
    int channel = 1;  
    int volumeLevel = 1;  
    boolean on = false;  
  
    public void turnOn() {  
        on = true;  
    }  
    public void turnOff() {  
        on = false;  
    }  
  
}
```

TV.java (two possible solutions)

# Constructing Objects Using Constructors



# Constructors

---

- **Constructors** are a special kind of methods that are called to construct objects.

```
Circle() {  
    }  
}
```

```
Circle(double newRadius) {  
    radius = newRadius;  
}
```

# Constructors

---

- A constructor with no parameters is referred to as a *no-arg constructor*.
  - » Constructors must have the same name as the class itself.
  - » Constructors do not have a return type - not even void.
  - » Constructors are called using the new operator when an object is created. Constructors play the role of initializing objects.

# Creating Objects Using Constructors

---

```
new ClassName();
```

**Example:**

```
new Circle();
```

```
new Circle(5.0);
```

# Default Constructors

---

- A class *may be defined without constructors*.
- In this case, *a no-arg constructor* with an empty body is implicitly defined in the class.
- This constructor, called *a default constructor*, is provided automatically *only if no constructors are explicitly defined in the class*.

## Accessing Objects via Reference Variables

# Declaring object Reference Variables

---

- To reference an object, assign **the object** to a **reference variable**.
- To declare **a reference variable**, use the syntax:

```
ClassName objectRefVar;
```

- Example:

```
Circle myCircle;
```

# Declaring / Creating Objects in a Single Step

---

```
ClassName objectRefVar = new ClassName();
```

## ■ Example:

Assign object reference      Create an object

```
Circle myCircle = new Circle();
```

# Accessing Object's Members

---

- Referencing the object's data:

`objectRefVar.data`

*e.g.,* `myCircle.radius`

- Invoking the object's method:

`objectRefVar.methodName (arguments)`

*e.g.,* `myCircle.getArea()`



# Trace Code

---

**Circle myCircle** = new Circle(5.0);

**Circle yourCircle** = new Circle();

**yourCircle.radius** = 100;

myCircle

no value

Declare myCircle

# Trace Code

---


**Circle myCircle = new Circle(5.0);**

myCircle

no value

**Circle yourCircle = new Circle();**

**yourCircle.radius = 100;**



Create a circle


# Trace Code

---

**Circle myCircle** = **new Circle(5.0);**

**Circle yourCircle = new Circle();**

**yourCircle.radius = 100;**




# Trace Code

---

**Circle myCircle = new Circle(5.0);**

**Circle yourCircle = new Circle();**

**yourCircle.radius = 100;**



yourCircle

no value

Declare yourCircle

# Trace Code

---

**Circle myCircle = new Circle(5.0);**

**Circle yourCircle = new Circle();**

**yourCircle.radius = 100;**

myCircle

reference value

: Circle

radius: 5.0

yourCircle

no value

: Circle

radius: 1.0

Create a new  
Circle object


# Trace Code

---

**Circle myCircle = new Circle(5.0);**

**Circle yourCircle = new Circle();**

**yourCircle.radius = 100;**



# Trace Code

---

**Circle myCircle = new Circle(5.0);**

**Circle yourCircle = new Circle();**

**yourCircle.radius = 100;**

myCircle

reference value

: Circle

radius: 5.0

yourCircle

reference value

: Circle

radius: 100

Change radius in  
yourCircle

# Default Value for a Data Field

---

- The default value of a data field:
  - » null for a reference type
  - » 0 for a numeric type
  - » false for a boolean type
  - » '\u0000' (null character) for a char type
- However, Java assigns no default value to a local variable inside a method.




# Example

---

- Java assigns no default value to a local variable inside a method.

```
public class Test {  
    public static void main(String[] args) {  
        int x; // x has no default value  
        String y; // y has no default value  
        System.out.println("x is " + x);  
        System.out.println("y is " + y);  
    }  
}
```



Compile error: variable  
not initialized

# Exercise

---

- Define a `Student` class to have following data fields:  
`name` (String), `age` (int), `isScienceMajor` (boolean) and `gender` (char)
- Create an object of `Student` class type and print out the default values of its data fields

# Answer

---

```
public class Student {  
    String name;  
    int age;  
    boolean isScienceMajor;  
    char gender;  
}
```

Student.java

```
public class ClassExamples {  
    public static void main(String[] args) {  
        Student student = new Student();  
        System.out.println("name? " + student.name);  
        System.out.println("age? " + student.age);  
        System.out.println("isScienceMajor? " + student.isScienceMajor);  
        System.out.println("gender? " + student.gender);  
    }  
}
```


ClassExamples.java

```
name? null  
age? 0  
isScienceMajor? false  
gender?
```

Output


# Primitive Data Type vs. Object Types

---




## Primitive type assignment $i = j$

Before:




After:




## Object type assignment $c1 = c2$

Before:



After:



# Garbage Collections

---

- As shown in the previous figure, after the assignment statement `c1 = c2`, `c1` points to the same object referenced by `c2`.
- The object previously referenced by `c1` is no longer referenced. This object is known as garbage. Garbage is automatically collected by JVM.

# Garbage Collections

---

- TIP: If you know that an object is no longer needed, you can explicitly assign **null** to a reference variable for the object.
- The JVM will automatically collect the space if the object is not referenced by any variable.