



Northeastern
University

Lecture 10: Object Oriented Programming - 5

Prof. Chen-Hsiang (Jones) Yu, Ph.D.
College of Engineering

Materials are edited by Prof. Jones Yu from

Liang, Y. Daniel. Introduction to Java Programming, Comprehensive Version, 12th
edition, Pearson, 2019.

Outline

- Objects and Classes
- Thinking in Objects

Outline

- Objects and Classes
- Thinking in Objects

The String Class

Strings Are Immutable

- A String object is immutable; **its contents cannot be changed.**
- Does the following code change the contents of the string?

```
String s = "Java";  
  
s = "HTML";
```


- The answer is **no**. Why?

Trace Code

```
String s = "Java";
```

```
s = "HTML";
```

After executing `String s = "Java";`




Trace Code


```
String s = "Java";
```

```
s = "HTML";
```

After executing `String s = "Java";`



After executing `s = "HTML";`




Interned Strings

- Since strings are *immutable* and are frequently used, to improve efficiency and save memory, the JVM uses *a unique instance* for *string literals* with the same character sequence.
- Such an instance is called *interned*.

Example

```
String s1 = "Welcome to Java";  
String s2 = new String("Welcome to Java");  
String s3 = "Welcome to Java";  
System.out.println("s1 == s2 is " + (s1 == s2));  
System.out.println("s1 == s3 is " + (s1 == s3));
```



display

s1 == s2 is false

s1 == s3 is true

A new object is created if you use the **new** operator.


When you use **the string initializer**, no new object is created if **the interned object** is already created.

Trace Code

```
String s1 = "Welcome to Java";
```

```
String s2 = new String("Welcome to Java");
```

```
String s3 = "Welcome to Java";
```





Trace Code

```
String s1 = "Welcome to Java";
```


```
String s2 = new String("Welcome to Java");
```

```
String s3 = "Welcome to Java";
```



Trace Code

```
String s1 = "Welcome to Java";  
String s2 = new String("Welcome to Java");  
String s3 = "Welcome to Java";
```



Replacing and Splitting Strings

java.lang.String	
+replace(oldChar: char, newChar: char): String	
+replaceFirst(oldString: String, newString: String): String	
+replaceAll(oldString: String, newString: String): String	
+split(delimiter: String): String[]	

Returns a new string that replaces all matching character in this string with the new character.

Returns a new string that replaces the first matching substring in this string with the new substring.

Returns a new string that replace all matching substrings in this string with the new substring.

Returns an array of strings consisting of the substrings split by the delimiter.

Example

`"Welcome".replace('e', 'A')` // returns a new string, WAlcomA.

`"Welcome".replaceFirst("e", "AB")` // returns a new string, WABlcome.

`"Welcome".replaceAll("e", "AB")` // returns a new string, WABlcomAB.

`"Welcome".replace("el", "AB")` // returns a new string, WABcome.

Splitting a String

```
String[] tokens = "Java#HTML#Perl".split("#");  
for (int i = 0; i < tokens.length; i++)  
    System.out.print(tokens[i] + " ");
```

Output:

Java HTML Perl

Matching, Replacing and Splitting by Patterns

- You can **match**, **replace**, or **split** a string by specifying a pattern. This is an extremely useful and powerful feature, commonly known as *regular expression*.
- Regular expression is complex to beginning students. For this reason, two simple patterns are used in this section.

```
"Java".matches("Java");           //true
```

```
"Java".equals("Java");           //true
```

```
"Java is fun".matches("Java.*");   //true
```

```
"Java is cool".matches("Java.*");  //true
```


Matching, Replacing and Splitting by Patterns

- The `replaceAll`, `replaceFirst`, and `split` methods can be used with a regular expression.
- For example, the following statement returns a new string that replaces `$`, `+`, or `#` in `"a+b$#c"` by the string `NNN`.

```
String s = "a+b$#c".replaceAll("[$+#]", "NNN");  
System.out.println(s);
```

- Here the regular expression `[$+#]` specifies a pattern that matches `$`, `+`, or `#`. So, the output is `aNNNbNNNNNNNc`.

Matching, Replacing and Splitting by Patterns

- The following statement splits the string into an array of strings delimited by some punctuation marks.

```
String[] tokens = "Java,C?C#,C++".split("[.,:;?]");  
  
for (int i = 0; i < tokens.length; i++)  
    System.out.println(tokens[i]);
```

Output:

```
Java  
C  
C#  
C++
```

Convert Character and Numbers to Strings

- The String class provides several **static valueOf** methods for converting **a character**, **an array of characters**, and **numeric values** to **strings**.
- These methods have the same name **valueOf** with different argument types **char**, **char[]**, **double**, **long**, **int**, and **float**.
- For example, to convert a double value to a string, use **String.valueOf(5.44)**. The return value is string consists of characters '5', '.', '4', and '4'.

Exercise (10 mins)

- Given two strings, **write a method** to decide if one is a permutation of the other.

hello vs. elolh

Answer

```
import java.util.Scanner;

public class ClassExercise {

    public static void main(String[] args) {
        Scanner input = new Scanner(System.in);

        System.out.print("1st string: ");
        String string1 = input.next();

        System.out.print("2nd string: ");
        String string2 = input.next();

        boolean result = PermutationCheck(string1, string2);

        if(result) {
            System.out.println("Permutation: Yes");
        }else {
            System.out.println("Permutation: No");
        }

        input.close();
    }

    public static String sort(String s) {
        char[] content = s.toCharArray();
        java.util.Arrays.sort(content);
        return new String(content);
    }

    public static boolean PermutationCheck(String a, String b) {

        if(a.length() != b.length()) {
            return false;
        }

        return sort(a).equals(sort(b));
    }
}
```

The `StringBuilder` and `StringBuffer` Classes

StringBuilder and StringBuffer

- The `StringBuilder/StringBuffer` class is an alternative to the `String` class.
- In general, a `StringBuilder/StringBuffer` can be used wherever a string is used.
- However, `StringBuilder/StringBuffer` is more flexible than `String`.
- You can `add`, `insert`, or `append` new contents into a string buffer, whereas the value of a `String` object is fixed once the string is created.

StringBuilder Constructors

java.lang.StringBuilder
+StringBuilder()
+StringBuilder(capacity: int)
+StringBuilder(s: String)

Constructs an empty string builder with capacity 16.

Constructs a string builder with the specified capacity.

Constructs a string builder with the specified string.

java.lang.StringBuilder	
+append(data: char[]): StringBuilder	Appends a char array into this string builder.
+append(data: char[], offset: int, len: int): StringBuilder	Appends a subarray in data into this string builder.
+append(v: <i>aPrimitiveType</i>): StringBuilder	Appends a primitive type value as a string to this builder.
+append(s: String): StringBuilder	Appends a string to this string builder.
+delete(startIndex: int, endIndex: int): StringBuilder	Deletes characters from startIndex to endIndex.
+deleteCharAt(index: int): StringBuilder	Deletes a character at the specified index.
+insert(index: int, data: char[], offset: int, len: int): StringBuilder	Inserts a subarray of the data in the array to the builder at the specified index.
+insert(offset: int, data: char[]): StringBuilder	Inserts data into this builder at the position offset.
+insert(offset: int, b: <i>aPrimitiveType</i>): StringBuilder	Inserts a value converted to a string into this builder.
+insert(offset: int, s: String): StringBuilder	Inserts a string into this builder at the position offset.
+replace(startIndex: int, endIndex: int, s: String): StringBuilder	Replaces the characters in this builder from startIndex to endIndex with the specified string.
+reverse(): StringBuilder	Reverses the characters in the builder.
+setCharAt(index: int, ch: char): void	Sets a new character at the specified index in this builder.

Exercise

```
StringBuilder stringBuilder = new StringBuilder();
stringBuilder.append("Welcome");
stringBuilder.append(' ');
stringBuilder.append("to");
stringBuilder.append(' ');
stringBuilder.append("Java"); // "Welcome to Java"
```

```
stringBuilder.insert(11, "HTML and ") // "Welcome to HTML and Java"
stringBuilder.delete(8, 11)           // "Welcome HTML and Java"
```

```
stringBuilder.deleteCharAt(8)          // "Welcome o Java"
stringBuilder.reverse()                 // "avaJ ot emocleW"
stringBuilder.replace(11, 15, "HTML")   // "Welcome to HTML"
stringBuilder.setCharAt(0, 'w')         // "welcome to Java"
```

Exercise (10 mins)

- Given a `String[]` of words: Dog, Cat, Fish, Bird, Horse

```
String[] myWords = {"Dog", "Cat", "Fish", "Bird", "Horse"};
```

- Please write a method `makeSentence()` that takes this `String[]` as an input parameter.
- Inside the method, please use `StringBuffer` to concatenate all words as a `String` and return it back.
- Print out the concatenated string

Answer

```
public class ClassExercise {  
  
    public static void main(String[] args){  
        String[] myWords = {"Dog", "Cat", "Fish", "Bird", "Horse"};  
        System.out.println(makeSentence(myWords));  
    }  
  
    public static String makeSentence(String[] words){  
  
        //You can replace StringBuilder with StringBuffer  
        StringBuffer sentence = new StringBuffer();  
  
        for(String w: words){  
            sentence.append(w);  
        }  
  
        return sentence.toString();  
    }  
}
```

Exercise (offline)

- Implement a method to perform **basic string compression** using the counts of repeated characters.
- For example, the string **aabccccbbb** would become **a2b1c4b3**.
- If the “compressed” string would not become smaller than the original string, your method should return the original string.
- You can assume the string has only uppercase and lowercase letters (a-z).