

Objective-C Runtime / ...

Class

NSObject

The root class of most Objective-C class hierarchies, from which subclasses inherit a basic interface to the runtime system and the ability to behave as Objective-C objects.

iOS 2.0+ | iPadOS 2.0+ | Mac Catalyst 13.1+ | macOS 10.0+ | tvOS 9.0+ | visionOS 1.0+ |

watchOS 1.0+

```
class NSObject
```

Topics

Initializing a Class

```
class func initialize()
```

Initializes the class before it receives its first message.

```
class func load()
```

Invoked whenever a class or category is added to the Objective-C runtime; implement this method to perform class-specific behavior upon loading.

Creating, Copying, and Deallocating Objects

```
init()
```

Implemented by subclasses to initialize a new object (the receiver) immediately after memory for it has been allocated.

```
func copy() -> Any
```

Returns the object returned by `copy(with:)`.

```
func mutableCopy() -> Any
```

Returns the object returned by `mutableCopy(with:)` where the zone is `nil`.

Identifying Classes

```
class func superclass() -> AnyClass?
```

Returns the class object for the receiver's superclass.

```
class func isKindOfClass(of: AnyClass) -> Bool
```

Returns a Boolean value that indicates whether the receiving class is a subclass of, or identical to, a given class.