

Spark the Definitive Guide 2nd Edition

Chapter 07

Aggregations

Aggregations

Text Book



Objectives and Outcomes

- ▶ Aggregating is the act of collecting something together
 - ▶ It is the cornerstone of big data analytics
- ▶ You specify a *key* or *grouping* and an *aggregation function*
 - ▶ This function specifies how you should transform one or more columns
- ▶ Spark allows us to create the following types of groupings:
 - ▶ A “*group by*” specifies one or more keys and one or more aggregations
 - ▶ A “*window*” specifies one or more keys and one or more aggregations to transform the value columns
 - ▶ A “*grouping set*” specifies you can use aggregations at multiple levels
 - ▶ A “*rollup*” specifies one or more keys as well as one or more aggregation functions to transform the value of a column
 - ▶ A “*cube*” specifies one or more keys as well as one or more aggregations to transform the value columns

Review

- ▶ So far:
 - ▶ We learned how to build expressions using typed data
 - ▶ We learned how to use:
 - ▶ Booleans
 - ▶ Numbers
 - ▶ Strings
 - ▶ Dates and Timestamps
 - ▶ Nulls
 - ▶ Complex and user types

Basic Aggregations

- ▶ One of the simplest aggregations is `count()` which will count all rows in a `DataFrame`
 - ▶ `df.count()`
 - ▶ `.count()` is technically an action not a transformation
- ▶ Elements of an entire column can be counted as well
 - ▶ `from pyspark.sql.functions import count`
 - ▶ `df.select(count("StockCode")).show()`
 - ▶ Watch out! When counting all columns ("`*`") Spark will count nulls, even rows that are all null
 - ▶ When counting an individual column, Spark will not count nulls

countDistinct

- ▶ Sometimes total number is not relevant, only unique number is
 - ▶ There is a `.countDistinct()` function
 - ▶ `from pyspark.sql.functions import countDistinct`
 - ▶ `df.select(countDistinct("StockCode")).show()`
- ▶ There is also an `.approx_count_distinct()`
 - ▶ When working with a large dataset, time, processing power, even energy usage are a consideration
 - ▶ There are times when a degree of approximation can be used without an issue
 - ▶

```
from pyspark.sql.functions import approx_count_distinct
```
 - ▶

```
df.select(approx_count_distinct("StockCode", 0.1)).show()
```
 - ▶

```
SELECT approx_count_distinct(StockCode, 0.1) FROM dfTable
```
 - ▶ 0.1 is the estimation error margin
 - ▶ Note the results, but note the performance gain

Simple Aggregations

- ▶ You can get the first and last elements of a DataFrame by two obvious elements
 - ▶ `.first()`
 - ▶ `.last()`
- ▶ You can extract min and max values using the builtin pyspark sql functions
- ▶ You can use the `sum` method to sum the content of a column
 - ▶ There is also a `sumDistinct` function that will perform that actions as well
- ▶ There is an `avg` function to do an average of a column
 - ▶ You can combine this result with an alias to reuse the calculated value later 107
- ▶ If you are calculating Average, then you are dealing with *Variance* and *Standard Deviation*
- ▶ *Skewness* and *kurtosis* are both measurements of extreme points in your data
 - ▶ Skewness measures the asymmetry of your values around the mean
 - ▶ Kurtosis measures the tail of data

More Simple Aggregations

- ▶ Some functions compare the interactions of the values in two different columns together
 - ▶ *Covariance and Correlation*
 - ▶ `cov` and `corr`
 - ▶ Chapter 6 talked about the Pearson correlation coefficient
 - ▶ Correlation is measured on a -1 to 1 scale
 - ▶ The covariance can be taken over a population sample or the entire population of records 110

Grouping

- ▶ We have done `groupBy` on the DataFrame level aggregations
 - ▶ We can perform calculations based on *groups* in the data
 - ▶ Using our purchase data DataFrame, for example we can group on unique **invoice number** and do a `count()` of items on that invoice
 - ▶ This returns a second DataFrame that is lazily evaluated

- ▶

```
df.groupBy("InvoiceNo", "CustomerId").count().show()
```

- ▶

```
SELECT count(*) FROM dfTable GROUP BY InvoiceNo, CustomerId
```

- ▶ We can specify an arbitrary expression statement as an agg statement

- ▶ This makes it possible to say *alias* a column

- ▶

```
df.groupBy("InvoiceNo").agg(count("Quantity").alias("quantity"))
```

Grouping With Maps

- ▶ Sometimes it can be easier to specify your transformations as a series of **Maps**
 - ▶ For which the key is the column
 - ▶ The value is the aggregation function that you would like to perform



```
df.groupBy("InvoiceNo").agg(expr("avg(Quantity)"), expr()
```

Window Functions 112

- ▶ Window Functions can be used to carry out aggregations by computing on a certain *window* of data
 - ▶ This sounds very similar to a `groupBy` function, so what is the difference?
 - ▶ `groupBy` takes data and every row can only go into one grouping
 - ▶ A Window function calculates a return value for every input row of a table based on groups of rows, called a **frame**
 - ▶ Not a `DataFrame`
 - ▶ Each row can fall into one or more frame, unlike a `groupBy`

Conclusion

- ▶ Conc goes here

Questions

- ▶ Any questions?
- ▶ Read Chapter 08 & 09 and do any exercises in the book.