



SKE011-1

TREAT-WAITING CHAIR



SAIKANG/Medical

Healthier
your life

SKE011-1

FEATURES AND HIGHLIGHTS

Design: Simple overall design, ergonomically designed to prevent deformation from prolonged sitting.

Seat and backrest: Material: Backboard ≥ 23 mm; Seat board ≥ 25 mm thick high-density polyurethane (PU) (steel frame internal, steel frame standard: Q235 steel pipe) molded. The seat and backrest are designed as a whole for easy cleaning and maintenance, providing stability and aesthetics. Surface hardness: No obvious traces are left on the surface for unintentional scratching, scraping, rubbing, grinding, impact, etc. Ensure sufficient load-bearing capacity and firmness of the seat backboard while providing appropriate elasticity and maximum comfort. The polyurethane (PU) density of the seat is ≥ 380 kg/m³.

Technical parameters

Overall dimensions (3-seater)	1630×665×850mm±10
Center distance	530±10mm
Seat width	520±10mm
Seat depth	460±10mm
Seat height from the ground	430±10mm
Seat top depth	630±10mm
Seat top height from ground	850±10mm
Armrest top height from the ground	632±10mm
Weight	52.5KG/roll



Seat support frame

Each individual seat is equipped with two aluminum alloy brackets with dimensions of 300mm*35mm*119mm underneath, and comes with dedicated fixing clips, enhancing load-bearing capacity with a maximum weight of 250kg. Aluminum alloy die-casting, with a surface coated with wear-resistant electrostatic epoxy powder, corrosion-resistant and aging-resistant.



Armrest leg

Material: Made of high-quality aluminum alloy through die-casting, with a surface coated with wear-resistant electrostatic epoxy powder, the armrests are additionally installed with high-density polyurethane (PU), providing enhanced comfort and a more user-friendly experience without a cold sensation.



Crossbar

The material adopts high-strength 80mm*40mm*1.5mm cold-rolled steel pipe, offering excellent load-bearing capacity and stability. The surface is coated with wear-resistant electrostatic epoxy powder, ensuring good load-bearing performance, a stylish appearance, a smooth surface, and resistance to debris accumulation.



Backrest

The backrest is designed with wave-like water ripples to fit the body's curves and relieve overall pressure. It has good elasticity and tight material integration. Frequent use will not cause deformation, wrinkling, breakage, or fragmentation.



Seat and backrest

The seat and backrest are designed as a whole, with reasonable gap design between the seat boards, and seamless treatment between the armrests and seat boards, avoiding the risk of children's hands and feet getting stuck in the gaps between seats. The seat has no exposed screws, providing an overall aesthetic look and easy to clean.



PU

Regular color of PU color card is optional.





CONSTANT INNOVATION



Design



Research



Manufacturing



Maintenance



Service



WORLDWIDE BRANCHES

South America Branch

Saikang Medical Technology, Inc
W3400 Corrientes, Argentina
TEL: +55 (11) 2758-0438
Rua Universal, Hollywood,
São Bernardo do Campo,
Brazil
TEL: +55 (11) 2758-0438

East Africa Branch

Saikang Medical Technology Ltd
Mezzanine Floor, Taj Tower,
upper hill, nairobi, Kenya
TEL: +254714084806

South East Asia Branch

Saikang Medical Technology Ltd
Sala Thammasop Subdistrict
Thawi
Watthana District
Bangkok Thailand
TEL: +66 642741046

UK Branch

Uk Healthward International Limited
DEPT 111,
196 High Road Wood Green,
London, N22 8HH
United Kingdom
TEL: +31 (0) 2021111106

Russia Branch

LLC 'SAIKANG'
454004, Russian Federation,
Chelyabinsk,
Universitetskaya
Naberezhnaya, Russia
TEL: +7 (919)300-00-06

Mid East Branch

Saikang Medical Supplies (Mid East) LLC
Musaffah
P.O Box 53200, Abu Dhabi,
UAE
Tel: +971 585710652

SAIKANG Medical

Jiangsu Saikang Medical Equipment Co., Ltd.
STOCK CODE: 870098

📍 No. 35, Lehong Road · Zhangjiagang (Jiangsu) · China
☎ +86 18021231901 · 🕒 24/7
✉ export@saikangmedical.com
🌐 www.saikangmedical.com



Company video



General catalogue