



SK-EM001

12-INCH PATIENT MONITOR



SAIKANG Medical

Healthier
your life

SK-EM001

FEATURES AND HIGHLIGHTS

Internal structure: Adopting aluminum-magnesium alloy bracket, stable and reliable, with good shock resistance and easy to move.

Monitoring functions: 6 major monitoring functions, comprehensive detection from multiple angles: electrocardiogram monitoring, body temperature, blood pressure, blood oxygen, respiration, and heart rate.

Technical parameters

▪ Product weight	GW: 6kg, NW: 3.5kg
▪ ECG (Lead configuration)	Standard three-lead or five-lead cable
▪ ECG (Gain)	‘0.25, ‘0.5, ‘1, ‘2
▪ ECG (Heart rate range Adults)	15bpm to 300bpm
▪ ECG (Newborns/children)	15bpm to 350bpm
▪ ECG (Electrode polarization voltage range)	±300mV
▪ ECG (Baseline recovery time)	<3 seconds after defibrillation
▪ Respiration (Measurement method)	RA-LL (R-F) impedance method
▪ Respiration (Respiration rate range: Adults)	(0-120) BrPM
▪ Respiration (Children and newborns)	(0-150) BrPM
▪ Respiration (Apnea alarm)	(10-40) seconds
▪ Measurement range of blood oxygen saturation	0~100%, resolution: 1%, accuracy: 70%~100%: ±2, 0%~69%: undefined
▪ Measurement range of pulse rate	20bpm~300bpm resolution: 1bpm accuracy: ±3bpm
▪ Non-invasive blood pressure (Operating modes)	manual/automatic/continuous
▪ Non-invasive blood pressure (Measurement range)	Systolic pressure (40-270) mmHg, diastolic pressure (10-215) mmHg, mean arterial pressure (20-235) mmHg.
▪ Non-invasive blood pressure (Static pressure range)	(0-300) mmHg, static pressure accuracy: ±3 mmHg.
▪ Dual-channel temperature measurement, measurement range	(5-50)°C, resolution: 0.1°C, accuracy

Technical configuration

☒ ECG/heart rate, SPO2, NIBP, RESP, TEMP, PR
☒ Optional feature: Sidestream/mainstream EtCO2
☒ Sidestream/mainstream carbon dioxide
☒ GAS anesthesia gas module
☒ Depth of anesthesia
☒ IBP-1: Single-channel invasive blood pressure
☒ IBP-2: Dual-channel invasive blood pressure
☒ 2-TEMP dual temperature probe
☒ Thermal Recorder
☒ Wall mount
☒ Trolley
☒ CMS
☒ Wireless network
☒ Pediatric accessories
☒ Neonate accessories
☒ Veterinary version
☒ Touch Screen

Other Features

Large character interface, 336 hours of monitoring parameter trend graphs, trend table review, 1000 sets of NIBP data lists, 1800 alarm event reviews;

Respiratory oxygenation graph function, ST segment analysis, pacing analysis, drug concentration calculation function, alarm event review, and heart rate abnormality review;

Adopts Aiah™ ECG technology, which can effectively improve the anti-interference ability of ECG and ensure the accuracy of heart rate abnormality analysis;

It has automatic, manual, and continuous blood pressure measurement methods, dual pressure overpressure protection function, and whether it is for patients with high blood pressure or low blood pressure, the measurement is very accurate.

Design

The integrated structural design is streamlined in function, stable in performance, strong in anti-interference ability, and durable.



Shell material

Brand new ABS engineering plastic mold injection molding.



Screen design

12.1-inch true color TFT LCD display, with high resolution of 800×600. The operating interface is extremely simple and the data waveform is clear and visible.



Blood pressure button

Eye-catching and independent blood pressure button. Anti-slip design for easy rotation.



Handle

Fixed handle design, comfortable to hold, stable and easy to move.



Alarm system

Automatic sound and light screen triple alarm, intelligent alarm, and simple operation.



Power supply

Using high-performance power supply, even in harsh power grid environments, it can provide excellent monitoring and make monitoring information continuous and uninterrupted. It is compatible with both AC and DC power sources, and has an external plug-in lithium battery with a continuous power supply time of ≥ 3 hours.



Operating interface

1-7 channel ECG waveform synchronous display, with the ability to display 8 channels of waveforms on the same screen. The interface can be displayed in Chinese or English, with large fonts. The device can be operated using one-button shuttle or touch screen.



Patient information input function

Support wired/wireless networking function.



Interface settings

USB and network interfaces facilitate the formation of a central monitoring system and the free exchange of information.





CONSTANT INNOVATION



Design



Research



Manufacturing



Maintenance



Service



WORLDWIDE BRANCHES

South America Branch

Saikang Medical Technology, Inc
W3400 Corrientes, Argentina
TEL: +55 (11) 2758-0438
Rua Universal, Hollywood,
São Bernardo do Campo,
Brazil
TEL: +55 (11) 2758-0438

East Africa Branch

Saikang Medical Technology Ltd
Mezzanine Floor, Taj Tower,
upper hill, nairobi, Kenya
TEL: +254714084806

South East Asia Branch

Saikang Medical Technology Ltd
Sala Thammasop Subdistrict
Thawi
Watthana District
Bangkok Thailand
TEL: +66 642741046

UK Branch

Uk Healthward International Limited
DEPT 111,
196 High Road Wood Green,
London, N22 8HH
United Kingdom
TEL: +31 (0) 2021111106

Russia Branch

LLC 'SAIKANG'
454004, Russian Federation,
Chelyabinsk,
Universitetskaya Naberezhnaya,
Russia
TEL: +7 (919)300-00-06

Mid East Branch

Saikang Medical Supplies (Mid East) LLC
Musaffah
P.O Box 53200, Abu Dhabi,
UAE
Tel: +971 585710652

SAIKANG Medical

Jiangsu Saikang Medical Equipment Co., Ltd.
STOCK CODE: 870098

📍 No. 35, Lehong Road · Zhangjiagang (Jiangsu) · China

☎ +86 18021231901 · 🕒 24/7

✉ export@saikangmedical.com

🌐 www.saikangmedical.com



Company video



General catalogue