



SK-EM401

12 INCH PATIENT MONITOR



SK-EM401

FEATURES AND HIGHLIGHTS

Internal structure: It uses an aluminum-magnesium alloy stand, which is stable, reliable, has good shock resistance, and is easy to move. **Monitoring functions:** Offers 6 comprehensive monitoring functions, covering various aspects: ECG (Electrocardiogram), heart rate (HR), respiration rate (RESP), blood oxygen level (SpO2), pulse rate (PR), non-invasive blood pressure (NIBP), and body temperature (TEMP).

Technical parameters

12.1-inch non-touchscreen, 800 × 600 high resolution	
Standard parameters: SpO ₂ , ECG, PR, BP, Resp, Temp	
Standard electrocardiogram with 5-lead cable	
2000mAh built-in battery	
Available in 8 languages, including Chinese and English	
A set of adult accessories	
Product weight	NW: 2.72kg
Product size	262×336×84mm
Package size	380×350×300mm
Operating temperature	0-40 °C
Working humidity	≤ 85
ECG (Lead configuration)	6-pin, 5-lead ECG lead wires
ECG (Gain settings)	'0.25, '0.5, '1, '2, '4, automatic
ECG (Heart rate range Adults)	1.0 bpm to 300 bpm
ECG (Newborns/children)	15 bpm to 350 bpm
ECG (Electrode polarization voltage range)	±300mV
Respiration (Measurement method)	RA-LL (R-F) Impedance Method
Respiration (Respiration rate range: Adults)	(0 to 120) BrPM
Respiration (Children and newborns)	(7-120) BrPM
Respiration (Apnea alarm)	(10-40) seconds
Measurement range of blood oxygen saturation	0~100%, resolution: 1%, accuracy: 70%~100%: ±2, 0% to 69%: undefined
Measurement range of pulse rate	30 bpm to 300 bpm, with a resolution of 1 bpm and an accuracy of ±3 bpm
Non-invasive blood pressure (Operating modes)	manual/automatic/continuous
Measurement interval for automatic mode	1-480 minutes
Non-invasive blood pressure (Pulse Rate Range)	(30 - 300) bpm



- Non-invasive blood pressure (Measurement range)
Systolic Pressure: (40 to 270) mmHg; Diastolic Pressure: (10 to 215) mmHg; Mean Pressure: (20 to 235) mmHg
- Non-invasive blood pressure (Static pressure range) (0-300) mmHg
- Non-invasive blood pressure (SStatic Pressure Accuracy) ±3 mmHg
- Body Temperature Measurement Range (0 to 50)°C, Accuracy 0.1°C

Power supply

Power supply voltage	AC 100~240 V
Power frequency	50/60Hz
Maximum input power	70VA
The fuse	F2AL 250V
Working mode	continuous working
Built-in lithium battery	DC
11.1V is not less than 2000mA, working time is not less than 2 hours.	

Optional feature

- ☐ Wireless Network;
- ☐ Central Monitoring System;
- ☐ ETCO₂, Dual-Channel IBP;
- ☐ Built-in Recorder Monitor;
- ☐ Stand Cart or Wall Mount;
- ☐ NELLCOR Oxygen Saturation Module, SunTech Blood Pressure Module;
- ☐ Upgraded Independent Module Compatible for Surgery and Intensive Care Unit;

Other Features

Fanless design for a quiet, energy-efficient, and clean operation, providing comprehensive monitoring for adults, children, and newborns. Alarm event review, drug concentration calculation, and titration table functions.

Built-in recorder for one-touch data printing.

Multiple-channel synchronized ECG algorithm, supporting ST and ARR analysis functions, as well as abnormal ECG analysis.

Analog SpO₂ technology, resistant to motion interference, ambient light interference, and suitable for measurements during weak perfusion.

Non-invasive blood pressure measurement options: manual, continuous, or interval measurement, with storage capacity for up to 400 sets of blood pressure data.

Design

Integrated design, streamlined functionality, stable performance, strong anti-interference capability, and long-lasting durability.

**Shell material**

Made from new ABS engineering plastic mold injection molding, which is more corrosion-resistant.

**Screen design**

12.1-inch full-color TFT LCD display, high-definition, 170° wide viewing angle, extremely simple user interface, and clear visible data.

**Blood pressure button**

Conspicuous, independent blood pressure button for easy operation.

**Handle**

A concealed groove handle on the back, simple and stylish, comfortable to hold, stable, and easy to move.

**Alarm system**

Automatic audio, visual, and screen three-level alarm with intelligent operation for easy use.

**Power supply**

Utilizes high-performance power supply, wide voltage range from AC100V-240V, built-in rechargeable lithium battery, compatible with both AC and DC power sources, providing continuous power for over 2 hours.

**Operating interface**

Simultaneously displays ECG waveforms for channels 1 to 7, with the ability to show all 8 waveforms on the same screen, enabling cascading ECG waveform display. The interface supports both Chinese and English, featuring large font size for easy reading, and offers one-touch shuttle operation.

**Patient information input function**

Supports both wired and wireless networking capabilities.


**Interface settings**

USB and network interfaces facilitate the integration into a central monitoring system and enable the free exchange of information.





CONSTANT INNOVATION




Design



Research



Manufacturing



Maintenance



Service



WORLDWIDE BRANCHES

Portugal Showroom

Av. da Liberdade, nº 101
8150-101
São Brás de Alportel
Portugal
TEL: +351 289 090 212

Brazil Showroom

Rua Lauro Muller 116, Sala
1503 - Botafogo, Rio de
Janeiro - RJ, 22290-160
E-mail: mehecobrasil@
gmail.com

Indian Showroom

1460 M.I.E, Bahadurgarh,
Haryana-124507, INDIA
TEL: +91 96677 70747
E-mail: ind@saikangmedical.
com

China Headquarter

No.35 Lehong Road,
Zhangjiagang City,
Jiangsu Province, China.
TEL: +86 18021231901
E-mail: export@
saikangmedical.com

South East Asia Branch

**SAIKANG Medical
(Thailand) Co., Ltd.**
Ample Tower 909 Room 11/3
Debaratana Road,
Bangna Nuea, Bangkok
10260 Thailand
TEL: +66-936-569469

US Branch

**Healthward Technology,
INC**
17800 castleton st ste 180,
Los Angeles
TEL: +1 (380) 254 4913

SAIKANG Medical

Jiangsu Saikang Medical Equipment Co., Ltd.
STOCK CODE: 870098

📍 No. 35, Lehong Road · Zhangjiagang (Jiangsu) · China
☎ +86 18021231901 · 🕒 24/7
✉ export@saikangmedical.com
🌐 www.saikangmedical.com



Company video



General catalogue