



SK-EM402

12 INCH PATIENT MONITOR



SK-EM402

FEATURES AND HIGHLIGHTS

Internal structure: It uses an aluminum-magnesium alloy stand, which is stable and reliable, has good shock resistance, and is easy to move.

Monitoring functions: Offers 6 comprehensive monitoring functions, covering various aspects: ECG (Electrocardiogram), heart rate (HR), respiration rate (RESP), blood oxygen level (SpO₂), pulse rate (PR), non-invasive blood pressure (NIBP), and body temperature (TEMP).

Technical parameters

▪ 12.1-inch non-touchscreen, 800 × 600 high resolution	
▪ Standard parameters: SpO ₂ , ECG, PR, BP, Resp, Temp	
▪ Standard electrocardiogram with 5-lead cable	
▪ 2000mAh built-in battery	
▪ Available in 8 languages, including Chinese and English	
▪ A set of adult accessories	
▪ Product weight	NW: 2.79kg
▪ Product size	340*245*134 mm
▪ ECG (Lead configuration)	6-pin, 5-lead ECG lead wires
▪ ECG (Gain)	'1.25, '2.5, '5.0, '10
▪ ECG (Heart rate range Adults)	1.0 bpm to 300 bpm
▪ ECG (Newborns/children)	15 bpm to 350 bpm
▪ ECG (Electrode polarization voltage range)	±300mV
▪ Respiration (Measurement method)	RA-LL (R-F) Impedance Method
▪ Respiration (Respiration rate range: Adults)	(0 to 120) BrPM
▪ Respiration (Children and newborns)	(0-150) BrPM
▪ Respiration (Apnea alarm)	(10-40) seconds
▪ Measurement range of blood oxygen saturation	0~100%, resolution: 1%, accuracy: 70%~100%: ±2, 40% to 69%±3%
▪ Measurement range of pulse rate	30 bpm to 300 bpm, with a resolution of 1 bpm and an accuracy of ±3 bpm
▪ Non-invasive blood pressure (Operating modes)	manual/automatic/continuous
▪ Non-invasive blood pressure (Pulse Rate Range)	(40 - 240) bpm
▪ Non-invasive blood pressure (Measurement range)	Systolic pressure (40-280) mmHg, diastolic pressure (10-220) mmHg, mean arterial pressure (20-240) mmHg.
▪ Non-invasive blood pressure (Static pressure range)	(0-300) mmHg, static pressure accuracy: ±3 mmHg.
▪ Dual-channel temperature measurement, measurement range	(0-50)°C, resolution: 0.1°C, accuracy

Optional feature

☐ Touch Screen
☐ Wireless Network
☐ Central Monitoring System
☐ ETCO ₂ , Dual-Channel IBP
☐ Built-in Recorder Monitor
☐ Stand Cart or Wall Mount
☐ NELLCOR Oxygen Saturation Module, SunTech Blood Pressure Module
☐ Upgraded Independent Module Compatible for Surgery and Intensive Care Unit



Other Features


Can record and playback ECG waveforms, blood pressure data, trend waveforms, alarm events, etc;
With 400 blood pressure list, 6000 second ECG waveform review, 60 alarm event record review, 7-day trend map storage function;
Has the function of automatic analysis of abnormal ECG waveforms and ST segment analysis;
Specific data storage function when power is off;
Blood oxygen saturation detection is highly sensitive and supports weak pulse detection;
Supports three monitoring modes: diagnosis, monitoring and surgery.

Design

Integrated design, streamlined functionality, stable performance, strong anti-interference capability, and long-lasting durability.

**Shell material**

Made from new ABS engineering plastic mold injection molding, which is more corrosion-resistant.

**Screen design**

12.1-inch TFT high-brightness LCD display, black mirror display, and the data wave is clearly visible.

**Blood pressure button**

Conspicuous, independent blood pressure button for easy operation.

**Handle**

A concealed groove handle on the back, simple and stylish, comfortable to hold, stable, and easy to move.

**Alarm system**

Allows for the customization of different alarm levels with both audible and visual alerts.

**Power supply**

Utilizes high-performance power supply, wide voltage range from AC100V-240V, built-in rechargeable lithium battery, compatible with both AC and DC power sources, providing continuous power for over 2 hours.

**Operating interface**

Simultaneously displays ECG waveforms for channels 1 to 7, with the ability to show all 8 waveforms on the same screen, enabling cascading ECG waveform display. The interface supports both Chinese and English, featuring large font size for easy reading, and offers one-touch shuttle operation.

**Patient information input function**

Supports both wired and wireless networking capabilities.


**Interface settings**

USB and network interfaces facilitate the integration into a central monitoring system and enable the free exchange of information.





CONSTANT INNOVATION




Design



Research



Manufacturing



Maintenance



Service



WORLDWIDE BRANCHES

Portugal Showroom

Av. da Liberdade, nº 101
8150-101
São Brás de Alportel
Portugal
TEL: +351 289 090 212

Brazil Showroom

Rua Lauro Muller 116, Sala
1503 - Botafogo, Rio de
Janeiro - RJ, 22290-160
E-mail: mehecobrasil@
gmail.com

Indian Showroom

1460 M.I.E, Bahadurgarh,
Haryana-124507, INDIA
TEL: +91 96677 70747
E-mail: ind@saikangmedical.
com

China Headquarter

No.35 Lehong Road,
Zhangjiagang City,
Jiangsu Province, China.
TEL: +86 18021231901
E-mail: export@
saikangmedical.com

South East Asia Branch

**SAIKANG Medical
(Thailand) Co., Ltd.**
Ample Tower 909 Room 11/3
Debaratana Road,
Bangna Nuea, Bangkok
10260 Thailand
TEL: +66-936-569469

US Branch

**Healthward Technology,
INC**
17800 castleton st ste 180,
Los Angeles
TEL: +1 (380) 254 4913

SAIKANG Medical

Jiangsu Saikang Medical Equipment Co., Ltd.
STOCK CODE: 870098

📍 No. 35, Lehong Road · Zhangjiagang (Jiangsu) · China
☎ +86 18021231901 · 🕒 24/7
✉ export@saikangmedical.com
🌐 www.saikangmedical.com



Company video



General catalogue