



SK-EX122

SUCTION DEVICE



SAIKANG Medical

Healthier
your life

SK-EX122

FEATURES AND HIGHLIGHTS

Technical parameters

▪ Material:	Adopting ABS injection molding
▪ Pumping rate:	≥30L/Min
▪ Limit negative pressure value:	≥0.09MPa (680mmHg)
▪ Negative pressure adjustment range:	0.02MPa - ultimate negative pressure value
▪ Noise:	≤55dB
▪ Power Voltage:	AC110-220V ±22V
▪ Power frequency:	50-60Hz
▪ Running method:	Continuous Operation with Intermittent Loading, Short-time operation, the longest running time 30min, duration rate 50%
▪ Control Method:	Foot switch and manual switch control
▪ Suction pump:	Oil-free plunger pump
▪ Glass Liquid Storage Bottle:	2500mL × 2 pieces
▪ Casters:	50mm × 4 (two casters with brakes)

Technical configuration

☒ Suction flexible catheter: (length 2M, Φ7×13)	1 pc
☒ Foot switch	1 pc
☒ Air filter	2 pcs
☒ Fuses	2 pcs
☒ Chest suction tube	1 pc



Feature

Low noise, maintenance-free, high pumping rate, fast negative pressure rise, no oil mist pollution.

Design

Novel shape, floor type mobile medical suction device.

Structure feature

The product structure primarily consists of piston pump, vacuum gauge, negative pressure regulating valve, air filter, storage bottle, and foot pedal switch.

Working principle

Utilizing a high-efficiency piston pump, it operates without the need for oil lubrication, ensuring long-term operation and has a long service life. The structure is rational and will not generate positive pressure, absolutely guaranteeing safety.

Piston pump

Utilizing a high-efficiency piston pump, it operates without the need for oil lubrication, enabling long-term operation and has a long service life.

Shell material

Featuring an ABS injection-molded shell, it has an attractive appearance, stable and durable, and ease of cleaning.



Handle

Fixed hand handle, easy to move, save time and effort.



Vacuum gauge

Utilizing a high-efficiency plunger pump, it operates without the need for oil lubrication, enabling long-term operation and a lengthy lifespan.



Negative pressure regulating valve

Any negative pressure value can be selected within the limit range for easy operation. Negative pressure adjustment range: 0.02MPa - ultimate negative pressure value.



Air filter

Air filter reduce air pollution of the surrounding environment from dirty liquids.



Storage bottle

Large caliber, large-capacity liquid storage bottle, made of glass, easy to clean, with a sealing ring stopper, good sealing, easy to open. The bottle is equipped with an overflow protection device to prevent dirty liquid from flowing into the pump body.



Switch

Foot switch, manual switch for low voltage control, and fully sealed, safe and reliable. Foot switch sensitivity, low voltage control, 12V.




Caster

4 ϕ 50mm diameter mobile casters, 2 with lock, easy to move.





CONSTANT INNOVATION




Design



Research



Manufacturing



Maintenance



Service

WORLDWIDE BRANCHES

European Branch

Saikang Medical Portugal Office

Av. da Liberdade, nº 101
8150-101
São Brás de Alportel
Portugal
TEL: +351 289 090 212

Russian Branch

LLC 'SAIKANG'

454004, Russian Federation,
Chelyabinsk,
Universitetskaya
Naberezhnaya, Russia
TEL: +7 (919)300-00-06

South America Branch

Saikang Medical Technology, INC

Rua Lauro Muller 116, Sala
1503 - Botafogo,
Rio de Janeiro -
RJ, 22290-160
E-mail: mehecobrasil@
gmail.com

East Africa Branch

Saikang Medical Technology Ltd

Mezzanine Floor, Taj Tower,
upper hill, nairobi, Kenya
TEL: +254714084806

South East Asia Branch

SAIKANG Medical (Thailand) Co., Ltd.

Ample Tower 909 Room 11/3
Debaratana Road,
Bangna Nuea, Bangkok
10260 Thailand
TEL: +66-936-569469

US Branch

Healthward Technology, INC

17800 castleton st ste 180,
Los Angeles
TEL: +1 (603) 416-3063

SAIKANG Medical

Jiangsu Saikang Medical Equipment Co., Ltd.
STOCK CODE: 870098

📍 No. 35, Lehong Road · Zhangjiagang (Jiangsu) · China

☎ +86 18021231901 · 🕒 24/7

✉ export@saikangmedical.com

🌐 www.saikangmedical.com



Company video



General catalogue