



SK-EX124

SUCTION DEVICE



SK-EX124

FEATURES AND HIGHLIGHTS

Technical parameters

▪ Power voltage	AC110-220V±22V
▪ Material:	Adopting ABS injection molding
▪ Pumping rate:	≥18L/Min
▪ Limit negative pressure value:	≥0.08MPa (600mmHg)
▪ Noise:	≤55dB
▪ Power Voltage:	AC110-220V±22V
▪ Power frequency:	50-60Hz
▪ Running method:	Continuous Operation with Intermittent Loading, Short-time operation, the longest running time 30min, duration rate 50%
▪ Control Method:	manual switch control
▪ Suction Pump:	Oil-free plunger pump, The negative pressure pump is a unidirectional pump that does not generate positive pressure
▪ Polycarbonate liquid storage bottle:	1000mL × 1 pieces

Technical configuration

☑ Suction flexible catheter(length 2M, Φ7×13)	1 pc
☑ Air filter	2 pcs
☑ Fuses	2 pcs
☑ Suction catheter	1 pc



Feature

Low noise, maintenance-free, high pumping rate, fast negative pressure rise, no oil mist pollution.

Design

Portable medical suction device, easy to move, compact and flexible. It can be used to suction out the thick sputum and thick liquid from the pharynx of obstructed patients or pediatric patients.

Structure feature

The product structure primarily consists of piston pump, vacuum gauge, negative pressure regulating valve, air filter, storage bottle, and foot pedal switch.

Working principle

Utilizing a high-efficiency piston pump, it operates without the need for oil lubrication, ensuring long-term operation and has a long service life. The structure is rational and will not generate positive pressure, absolutely guaranteeing safety.

Piston pump

Utilizing a high-efficiency piston pump, it operates without the need for oil lubrication, enabling long-term operation and has a long service life.

Shell material

Featuring an ABS injection-molded shell, it has an attractive appearance, stable and durable, and ease of cleaning.



Handle

Fixed, portable handle for easy lifting, saving time and effort.



Vacuum gauge

Using high precision vacuum pressure gauge, direct display of negative pressure value.



Negative pressure regulating valve

Any negative pressure value can be selected within the limit range for easy operation. Negative pressure adjustment range: 0.02-0.09MPa (680mmHg).



Air filter

Air filter reduce air pollution of the surrounding environment from dirty liquids.



Storage bottle

Large caliber, large-capacity liquid storage bottle, made of glass, easy to clean, with a sealing ring stopper, good sealing, easy to open. The bottle is equipped with an overflow protection device to prevent dirty liquid from flowing into the pump body.




Switch

Manual switch for low voltage control, and fully sealed, safe and reliable.





CONSTANT INNOVATION




Design



Research



Manufacturing



Maintenance



Service

WORLDWIDE BRANCHES

European Branch

Saikang Medical Portugal Office

Av. da Liberdade, nº 101
8150-101
São Brás de Alportel
Portugal
TEL: +351 289 090 212

Russian Branch

LLC 'SAIKANG'

454004, Russian Federation,
Chelyabinsk,
Universitetskaya
Naberezhnaya, Russia
TEL: +7 (919)300-00-06

South America Branch

Saikang Medical Technology, INC

Rua Lauro Muller 116, Sala
1503 - Botafogo,
Rio de Janeiro -
RJ, 22290-160
E-mail: mehecobrasil@
gmail.com

East Africa Branch

Saikang Medical Technology Ltd

Mezzanine Floor, Taj Tower,
upper hill, nairobi, Kenya
TEL: +254714084806

South East Asia Branch

SAIKANG Medical (Thailand) Co., Ltd.

Ample Tower 909 Room 11/3
Debaratana Road,
Bangna Nuea, Bangkok
10260 Thailand
TEL: +66-936-569469

US Branch

Healthward Technology, INC

17800 castleton st ste 180,
Los Angeles
TEL: +1 (603) 416-3063

SAIKANG Medical

Jiangsu Saikang Medical Equipment Co., Ltd.
STOCK CODE: 870098

📍 No. 35, Lehong Road · Zhangjiagang (Jiangsu) · China

☎ +86 18021231901 · 🕒 24/7

✉ export@saikangmedical.com

🌐 www.saikangmedical.com



Company video



General catalogue