

Topology	Scenario	Variant	Safe Acceptance Rate (%)	Attempted MSD Violation Rate (%)	Admitted MSD Violation Rate (%)	SLA Violation Rate (%)	Average Latency (ms)
VN	uniform	full	18.5	81.5	0	0	1.5
VN	uniform	w/o GAT	17.5	82.5	0	0	3.4
VN	uniform	w/o hard masking	18	81.8	0	0	0.9
VN	uniform	with soft MSD penalty	1.3	98	33.7	0.1	2.7
VN	uniform	w/o adaptive penalty	16.6	83.4	0	0	2.3
VN	bursty	full	18.5	81.5	0	0	0.8
VN	bursty	w/o GAT	17.6	82.4	0	0	3.7
VN	bursty	w/o hard masking	15.8	84.2	0	0	0.2
VN	bursty	with soft MSD penalty	1.4	98.5	33.8	0	3
VN	bursty	w/o adaptive penalty	16.3	83.7	0	0	1
VN	heavyTail	full	18.6	81.3	0	0	1.9
VN	heavyTail	w/o GAT	17	83	0	0	3.4
VN	heavyTail	w/o hard masking	17.6	82.3	0	0	1
VN	heavyTail	with soft MSD penalty	1.3	97.8	33	0	2.2
VN	heavyTail	w/o adaptive penalty	15.6	84.4	0	0	2