

# Metric METAR for Discord

## 1. Introduction

This discord bot provides realtime meteorological aerodrome reports (METAR) and terminal aerodrome forecasts (TAF) of a requested station via a discord channel. METAR and TAF will be provided:

1. **in a more readable or even completely decoded way in which all units are stated and converted to SI.** This custom standard strives to be a more modern and better compromise between being able to quickly brief the relevant information and enhancing its readability.

### ⚠ Warning

While the code has been proven reliable over years of daily private use, **it is not certified to be used in real flight operations.** Please [open an issue on Github](#) if you find any bugs or have any suggestions.

2. in their original format which is directly forwarded from [NOAA](#)<sup>12</sup>, mainly for cross-checking

Once a station is requested, 2 things happen:

1. The current METAR and, if requested, TAF are provided. Only these reports state how long ago they have been published.
2. The station is registered as the currently subscribed station. This means as soon as this station publishes a new METAR and, if requested, a new TAF, it will be automatically provided. This is a convenience functionality and the reason why using this bot is only recommended in a designated bot channel whose name is specified in `discord_bot_channel_names.config`. Channels with the name `bots`, `botspam`, and `metar` will be recognised by default.

<sup>1</sup>METAR: <https://tgftp.nws.noaa.gov/data/observations/metar/stations/>

<sup>2</sup>TAF: <https://tgftp.nws.noaa.gov/data/forecasts/taf/stations/>

## 2. Table of Contents

1. Introduction .....	1
2. Table of Contents .....	2
3. Examples .....	3
3.1. METAR .....	3
3.2. TAF .....	3
3.3. USA .....	3
3.4. Russia .....	4
4. Core Advantages .....	5
5. Installation .....	5
5.1. by Inviting My Bot User (recommended) .....	5
5.2. by Setting Up Your Own Bot .....	5
6. Usage .....	6

## 3. Examples

### 3.1. METAR

```
EDDL 311120Z AUTO 23018KT 9999 -SHRA FEW029 FEW///TCU 12/08 Q0995 RESHRA TEMPO 23020G30KT
```

```
EDDL 2023-03-31T11:20 AUTO 230°09m/s 10km+ -SHRA FEW930m|880m FEW///TCU 12°C/08°C  
Q099,5kPa RESHRA  
TEMPO 230°10G15m/s
```

Note the following differences:

- full datetime
- wind direction, visibility, cloud altitude, temperature, and QNH all stated with their unit reducing ambiguity
- clouds given with altitude and height if they're different after rounding

### 3.2. TAF

```
TAF EDDL 311100Z 3112/0118 22015G25KT 9999 BKN030 PROB30  
TEMPO 3112/3113 24020G35KT SHRA BKN030TCU  
TEMPO 3113/0103 RA PROB40  
TEMPO 3114/3124 22020G30KT  
BECMG 0100/0103 21013KT BKN012  
TEMPO 0103/0118 4000 RADZ BKN007  
BECMG 0106/0109 28010KT
```

```
TAF EDDL 2023-03-31T11:00 31T12/04-01T18 220°08G13m/s 10km+ BKN960m|910m  
PROB0,3 TEMPO 31T12/13 240°10G18m/s SHRA BKN960m|910m|TCU  
TEMPO 31T13/04-01T03 RA  
PROB0,4 TEMPO 31T14/04-01T00 220°10G15m/s  
BECMG 04-01T00/03 210°07m/s **BKN410m|370m**  
TEMPO 04-01T03/18 **4,0km** RADZ **BKN260m|210m**  
BECMG 04-01T06/09 280°05m/s
```

Note the following differences:

- Timespans only contain the minimum amount of necessary information and are ISO8601 compliant. If only the hour changes, only that is stated in the end. If day and hour change, the day is also provided and so on.
- Information violating the customisable weather minimums are encapsulated with double asterisks \*\* to quickly draw attention at a glance. This is also true for METAR.

### 3.3. USA

```
KPHX 051151Z 12006KT 10SM FEW240 08/M08 A3010 RMK A02 SLP186 T00831078 10133 20083 53005
```

```
KPHX 2023-04-05T11:51 (420s ago) 120°03m/s 16km FEW7.700m|7.300m 08°C/-08°C A101,9kPa  
RMK A02 SLP101,86kPa 08,3°C/-07,8°C TX6h/13,3°C TN6h/08,3°C ΔPRES3h/+50Pa
```

Note the following differences:

- Altimeter settings in inHg are converted to Pa, but the letter A remains to let the reader know that this value had been converted. This should usually not be a problem though as 0,01inHg < 100Pa, meaning precision is lost and not falsely added.
- Sea level pressure (SLP) is converted from 10Pa – 90kPa V –100kPa whatever the fuck to Pa.
- Explicitly requested METAR and TAF state how long ago they have been published.
- Weather station codes in the remark section are changed to be readable and actually provide value.

### 3.4. Russia

UEEE 051230Z 30005MPS 9999 SCT030CB M15/M22 Q1009 R23L/490139 NOSIG RMK QFE748

UEEE 2023-04-05T12:30 (1,5ks ago) 300°05m/s 10km+ \*\*SCT1.000m|910m|CB\*\* -15°C/-22°C  
Q100,9kPa  
\*\*R23L/SNOW:DRY/0,51~1/1mm/MEDIUM~GOOD\*\*  
NOSIG  
RMK QFE099,7kPa

Note the following differences:

- Runway condition codes are decoded, yet remain relatively compact.
- QFE is converted from mmHg to Pa to actually provide value.

## 4. Core Advantages

- METAR and TAF encoding with consistent use of units and better readability
- better readability makes runway state decoders obsolete and unlocks the additional information of USA weather station codes
- easy access and simple usability via discord
- simple staying up-to-date with station subscription feature, just scroll down

## 5. Installation

### 5.1. by Inviting My Bot User (recommended)

This method is recommended if you just want to use the bot out of the box and set and forget it. I have it running 24/7, there should be no problems in availability. Updates are also automatically applied as soon as I deploy them on my system.

1. Invite my bot user to your server by clicking [this link](#).
2. Make sure to have a text channel named `bots`, `botspam`, or `metar` on your server. The bot will only react in these specific channels.

If you need another channel name the bot reacts to, follow the guideline in Section 5.2 to set up your own bot instance. It is recommended to only have 1 of the beforementioned channels on your server, because I have not tested what happens if there are multiple.

### 5.2. by Setting Up Your Own Bot

This method is recommended if you want to have full control about the bot's behaviour and maybe change some things for yourself here and there.

1. Download the source code or download a release.
2. In `./.env`, set `DISCORD_BOT_TOKEN`.
  1. Create a discord application [here](#).
  2. Create your bot.
  3. Add it to your server.
  4. Copy your token.

If you don't know how to do these steps, I recommend [this tutorial](#).

3. In `./.env`, optionally change `DISCORD_BOT_CHANNEL_NAME`.

## 6. Usage

Once set up, using the bot is dead-easy. Write one of the following commands into the designated bot channel:

- current METAR: {ICAO code}  
Example: EDDF
- current METAR and TAF: {ICAO code} TAF  
Example: EDDF TAF