

Functional and logic programming

- written exam -

Important:

1. Subjects are graded as follows: of - 1p; A – 1.5p; B - 2.5p; C - 2.5p; D - 2.5p.
2. Prolog problems will be resolved using SWI Prolog. The following are required: (1) explanation of the code and of the reasoning behind it; (2) recursive model that solves the problem, for all the predicates used; (3) specification of every predicate (parameters and their meaning, flow model, type of the predicate - deterministic/non-deterministic).
3. Lisp problems will be resolved using Common Lisp. The following are required: (1) explanation of the code and of the reasoning behind it; (2) recursive model that solves the problem, for each function used; (3) specification of every function (parameters and their meaning).

A. Given the following PROLOG predicate definition **f(integer, integer)**, with the flow model (i, o):

f(1, 1):-!.

f(K,X):-K1 is K-1, **f(K1,Y)**, Y>1, !, K2 is K1-1, X is K2.

f(K,X):-K1 is K-1, **f(K1,Y)**, Y>0.5, !, X is Y.

f(K,X):-K1 is K-1, **f(K1,Y)**, X is Y-1.

Rewrite the definition in order to avoid the recursive call **f(J,V)** in all clauses. Do NOT redefine the predicate. Justify your answer.

B. Given a nonlinear list of both numerical and non-numerical atoms, write a LISP program that builds a linear list composed only from those non-numerical atoms that occur an even number of times in the initial list. The result will contain each element only once, in reverse order of the initial list. **For example**, for the list (F A 2 3 (B 1 (A D 5) C C (F)) 8 11 D (A F) F), the result will be (C D F). You are NOT allowed to use predefined LISP functions *reverse* or *member*.

C. Write a PROLOG program that generates the list of all arrangements of k elements with the value of sum of all elements from each arrangement equal with a given S , from a list of integers. Write the mathematical models and flow models for the predicates used. For example, for the list $[6, 5, 3, 4]$, $k=2$ and $S=9 \Rightarrow [[6,3],[3,6],[5,4],[4,5]]$ (not necessarily in this order).

D. Given a nonlinear list, write a Lisp function to return the list with all atoms on level **k** removed. The superficial level is assumed 1. **A MAP function shall be used.**

Example for the list (a (1 (2 b)) (c (d)))

a) k=2 => (a ((2 b)) ((d))) **b)** k=1 => ((1 (2 b)) (c (d))) **c)** k=4 => the list does not change