DIGITAL SIGNAL PROCESSING: COSC390

Jordan Hanson January 10, 2019

Whittier College Department of Physics and Astronomy

UNIT 1.3 OUTLINE

Previous lectures covered:

- Complex numbers 2: The Fourier series and Fourier transform (continuous and discrete)
- Time-permitting: The Laplace transform (continuous and discrete)

This lecture will cover: (Reading: Chapter 2)

- Statistics and probability: the normal distribution and other useful distributions
- Noise: digitization and sampling
- · Noise: Spectral properties of noise, ADC and DAC

STATISTICS AND PROBABILITY: THE NOR-

MAL DISTRIBUTION

The mean, μ , and standard deviation, σ , of a data set $\{x_i\}$ are defined as

$$\mu = \frac{1}{N} \sum_{i=1}^{N} x_i \tag{1}$$

$$\sigma^2 = \frac{1}{N-1} \sum_{i=1}^{N} (x_i - \mu)^2$$
 (2)

Octave commands:

```
x = randn(100,1);
mean(x)
std(x)
```

One nice theorem: The variance is the average of the squares minus the square of the average. Let $\langle x \rangle$ represent the average of the quantity or expression x. We have

$$\sigma_{\rm X}^2 = \langle {\rm X}^2 \rangle - \langle {\rm X} \rangle^2 \tag{3}$$

Proof: observe on board.

Note: There is a distinction between the process or signal process and the the data. Just because the data has a given μ and σ does not imply that the signal process has or will continue to have the exact same values of μ and σ . The underlying process could be non-stationary.




Figure 1: Signal processes in (a) and (b) are considered non-stationary because one or both of μ and σ depend on time.

A histogram is an object that represents the frequency¹ of particular values in a signal. For example, below is a histogram of 256,000 numbers drawn from a probability distribution:




Figure 2: The histogram contains counts versus sample values.

¹Careful: the word frequency refers to the number of occurences in the data, not a sinusoidal frequency.

The following octave code should reproduce something like Fig. 2 from the textbook:

```
x = randn(256000,1)*10.0+130.0;
[b,a] = hist(x,100);
plot(a,b,'o');
```

The function randn(N,M) draws $N \times M$ numbers from a normal distribution and returns them in the size the user desires. The function hist(x,N) creates N bins and sorts the data x_i into them.

For data that is appropriately stationary, we can use histograms to estimate μ and σ faster, since we only have to loop over bins rather than every data sample. Let H_i represent the counts in a given bin, and i represent the bin sample. We have:

$$\mu = \frac{1}{N} \sum_{i=1}^{M} i H_i \tag{4}$$

$$\sigma^2 = \frac{1}{N-1} \sum_{i=1}^{M} (i - \mu)^2 H_i$$
 (5)

To obtain the mean in signal *amplitude*, you'll have to convert bin number to amplitude.

```
3.1
-0.03
1.2
0.2
-0.7
-1.45
2.2
-0.05
0.93
0.21
```

Table 1: Using Eq. 4 and 5, find estimates of μ and σ for this data.

```
x = [...];
[b,a] = hist(x,4); %(How many bins?)
```

Some vocabulary:

- normalization Total probability is 1.0. For pdf the integral from $[-\infty, \infty]$ is 1.0. For pmf the sum from $[-\infty, \infty]$ is 1.0.
- pmf Probability mass function: A normalized continuous function that gives the probability of a value, given the value.
- histogram Histograms are an attempted measurement of the pmf by breaking the data into discrete bins. Histograms can be normalized as well.
- pdf Probability density function: A normalized continuous function that gives the probability density of a value, given the value. Integrating the normalized pdf between two values gives the probability of observing data between the given values.




Figure 3: The square-wave signal spends equal time at 0.0 and 1.0, and the probability density function reflects that.




Figure 4: The triangle-wave signal spends equal time at all values between 0.0 and 1.0, and the probability density function reflects that.




Figure 5: The random noise *usually* spends time near 0.0, but rarely it fluctuates to larger values.

Normally distributed data decreases in probability at a rate that is proportional (1) to the *distance from the mean*, and that is proportional (2) to the *probability itself*.




Figure 6: Normally distributed data counts decrease as measured further from the mean for *two reasons*.

Normal Distribution PDF

Let p(x) be the PDF of normally distributed data x with mean μ . In order to obey conditions (1) and (2), the function p(x) must be described by the following differential equation, where k is some constant.

$$\frac{dp}{dx} = -k(x - \mu)p(x) \tag{6}$$

Rearranging Eq. 6, we have

$$\frac{dp}{p} = -k(x - \mu)dx \tag{7}$$

Integrating both sides gives

$$\ln(p) = -\frac{1}{2}k(x - \mu)^2 + C_0 \tag{8}$$

Exponentiating,

$$p(x) = C_1 \exp\left(-\frac{1}{2}k(x-\mu)^2\right)$$
 (9)

Ensuring that the PDF is normalized requires

$$\int_{-\infty}^{\infty} p(x)dx = 1 \tag{10}$$

But how do we integrate Eq. 9? First, a change of variables. Let $s = \sqrt{k/2}(x - \mu)$, so $ds = \sqrt{k/2}dx$. Then, we have

$$C_1 \sqrt{\frac{2}{k}} \int_{-\infty}^{\infty} \exp(-s^2) ds = 1$$
 (11)

Squaring both sides, we have

$$C_1^2 \frac{2}{k} \left(\int_{-\infty}^{\infty} \exp(-s^2) ds \right)^2 = 1$$
 (12)

Let's pretend the two factors of the integral involve different variables:

$$C_1^2 \frac{2}{k} \left(\int_{-\infty}^{\infty} \exp(-x^2) dx \right) \left(\int_{-\infty}^{\infty} \exp(-y^2) dy \right) = 1$$
 (13)

Now we have

$$C_1^2 \frac{2}{k} \int_{-\infty}^{\infty} \exp(-(x^2 + y^2)) dx dy = 1$$
 (14)

Change to polar coordinates $(x^2 + y^2 = r^2)$

$$C_1^2 \frac{2}{k} \int_0^\infty \int_0^{2\pi} r \exp(-r^2) dr d\phi = 1$$
 (15)

One more substitution: $u = r^2$, and du = 2rdr:

$$-\frac{C_1^2}{k} \int_0^\infty \int_0^{2\pi} \exp(-u) du d\phi = 1$$
 (16)

Solving for C_1 , we find

$$C_1 = \sqrt{\frac{k}{2\pi}} \tag{17}$$

Thus the pdf of normally distributed data is

$$p(x) = \sqrt{\frac{k}{2\pi}} \exp\left(-\frac{1}{2}k(x-\mu)^2\right)$$
 (18)

Let's defined $k = \frac{1}{\sigma_x^2}$ so that it's clear the exponent has the proper ratio of units:

$$p(x) = \sqrt{\frac{1}{2\pi\sigma_X^2}} \exp\left(-\frac{1}{2}\left(\frac{x-\mu}{\sigma_S}\right)^2\right)$$
 (19)

STATISTICS AND PROBABILITY: PROGRAM-

MING WITH OCTAVE

STATISTICS AND PROBABILITY: PROGRAMMING WITH OCTAVE

More on the hist function in octave:

```
pkg install -forge io
pkg install -forge statistics
pkg load statistics
pkg help histfit
histfit(randn(1000,1))
histfit(rand(1000,1))
```

Let's work out the σ of a *flat* distribution between [0,1]. What is it for a flat distribution between [-1,1]?

STATISTICS AND PROBABILITY: OTHER

USEFUL DISTRIBUTIONS

CONCLUSION

UNIT 1.3 OUTLINE

Previous lectures covered:

- Complex numbers 2: The Fourier series and Fourier transform (continuous and discrete)
- Time-permitting: The Laplace transform (continuous and discrete)

This lecture will cover: (Reading: Chapter 2)

- Statistics and probability: the normal distribution and other useful distributions
- Noise: digitization and sampling
- · Noise: Spectral properties of noise, ADC and DAC